


<b>FCC TEST REPORT</b> <b>FCC 47 CFR Part 15C</b> <b>Industry Canada RSS-210</b> <b>Intentional radiator operating within the bands</b> <b>902 – 928 MHz, 2400 – 2483.5 MHz and 5725 – 5875 MHz</b>	
<b>Report Reference No.</b> .....	G0M-1805-7424-TFC249-V01
<b>Testing Laboratory</b> .....	Eurofins Product Service GmbH
<b>Address</b> .....	Storkower Str. 38c 15526 Reichenwalde Germany
<b>Accreditation</b> .....	  A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A-2
<b>Applicant's name</b> .....	Liftup A/S
<b>Address</b> .....	Hagensvej 21 DK- 9530 Støvring DENMARK
<b>Test specification:</b>	
<b>Standard</b> .....	47 CFR Part 15C RSS-210, Issue 9, 2016-08 RSS-Gen, Issue 4, 2014-11 ANSI C63.10, 2013
<b>Test scope</b> .....	complete Radio compliance test
<b>Equipment under test (EUT):</b>	
Product description	Radio module for Liftup A/S products
Model No.	MODULE1
Additional Model(s)	None
Brand Name(s)	Liftup
Hardware version	C
Firmware / Software version	0.14
	FCC-ID: 2AK8H-MODULE1      IC: 22516-MODULE1
<b>Test result</b>	<b>Passed</b>

**Possible test case verdicts:**

- required by standard but not appl. to test object ..... : N/A
- required by standard but not tested ..... : N/T
- not required by standard for the test object ..... : N/R
- test object does meet the requirement ..... : P (Pass)
- test object does not meet the requirement ..... : F (Fail)

**Testing:**

Test Lab Temperature ..... : 20 – 23 °C

Test Lab Humidity ..... : 32 – 38 %

Date of receipt of test item ..... : 2018-07-02

Date (s) of performance of tests ..... : 2018-07-09 – 2018-07-13


Compiled by ..... : Sebastian Suckow

Tested by (+ signature) ..... : Sebastian Suckow  
(Responsible for Test)

Approved by (+ signature) ..... : Toralf Jahn  
(Deputy Head of Lab)

Date of issue ..... : 2018-08-17

Total number of pages ..... : 82

  

**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**Additional comments:**

---

## Version History

Version	Issue Date	Remarks	Revised by
01	2018-08-17	Initial Release	


## REPORT INDEX

<b>1</b>	<b>EQUIPMENT (TEST ITEM) DESCRIPTION:</b>	<b>5</b>
1.1	Photos – Equipment External	6
1.2	Photos – Equipment internal	7
1.3	Photos – Test setup	8
1.4	Supporting Equipment Used During Testing	9
1.5	Test Modes	10
1.6	Test Equipment Used During Testing	11
1.7	Sample emission level calculation	12
<b>2</b>	<b>RESULT SUMMARY</b>	<b>13</b>
<b>3</b>	<b>TEST CONDITIONS AND RESULTS</b>	<b>14</b>
3.1	Test Conditions and Results – Occupied Bandwidth	14
3.2	Test Conditions and Results – Duty Cycle	18
3.3	Test Conditions and Results – Fundamental field strength emissions	20
3.4	Test Conditions and Results – Emissions radiated outside the specified frequency band	22
3.5	Test Conditions and Results – Receiver radiated emissions	24
3.6	Test Conditions and Results – AC power line conducted emissions	26
ANNEX A	Transmitter radiated spurious emissions	29
ANNEX B	Receiver radiated spurious emissions	73



## 1 Equipment (Test item) Description:

<b>Description</b>	Radio module for Liftup A/S products	
<b>Model</b>	MODULE1	
<b>Additional Model(s)</b>	None	
<b>Brand Name(s)</b>	Liftup	
<b>Serial number</b>	None	
<b>Hardware version</b>	C	
<b>Software / Firmware version</b>	0.14	
<b>PMN</b>	MODULE1	
<b>HVIN</b>	MODULE1	
<b>FVIN</b>	N/A	
<b>HMN</b>	N/A	
<b>FCC-ID</b>	2AK8H-MODULE1	
<b>IC</b>	22516-MODULE1	
<b>Equipment type</b>	End product	
<b>Radio type</b>	Transceiver	
<b>Radio technology</b>	custom	
<b>Operating frequency range</b>	2410 - 2460 MHz	
<b>Assigned frequency band</b>	2400 - 2483.5 MHz	
<b>Frequency range</b>	$F_{\text{LOW}}$	2410 MHz
	$F_{\text{MID}}$	2435 MHz
	$F_{\text{HIGH}}$	2460 MHz
<b>Spreading</b>	None	
<b>Modulations</b>	GFSK	
<b>Number of channels</b>	3	
<b>Channel spacing</b>	25 MHz	
<b>Number of antennas</b>	1	
<b>Antenna</b>	Type	integrated
	Model	PCB
	Manufacturer	Liftup A/S
	Gain	0.72 dBi
<b>Manufacturer</b>	Liftup A/S Hagensvej 21 DK- 9530 Støvring DENMARK	
<b>Power supply</b>	$V_{\text{NOM}}$	5.6 VDC
	$V_{\text{MIN}}$	N/A
	$V_{\text{MIN}}$	N/A

## 1.1 Photos – Equipment External




## 1.2 Photos – Equipment internal





### 1.3 Photos – Test setup





#### 1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
None				
<p><b>*Note:</b> Use the following abbreviations:</p> <p>AE : Auxiliary/Associated Equipment, or</p> <p>SIM : Simulator (Not Subjected to Test)</p> <p>CABL : Connecting cables</p>				

## 1.5 Test Modes

Mode #	Description	
Transmit	General conditions:	Specially prepared test mode with 100% duty cycle.
	Radio conditions:	Mode = standalone transmit Modulation = GFSK Power level = Maximum
Receive	General conditions:	EUT powered by fully charged battery
	Radio conditions:	Mode = standalone receive Modulation = GFSK

## 1.6 Test Equipment Used During Testing

Measurement Software			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2015.2.4

Occupied Bandwidth					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSU 26	EF01003	2017-07	2018-07

Duty Cycle					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSU 26	EF01003	2017-07	2018-07

Field strength emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 1	EF00062	-	-
MXE EMI Receiver	Keysight Technologies	N9038A-526/WXP	EF01070	2017-08	2018-08
Biconical Antenna	R&S	HK 116	EF00203	2018-06	2020-06
LPD Antenna	R&S	HL 223	EF00187	2016-05	2019-05
Horn antenna	Schwarzbeck	BBHA 9120D	EF00019	2016-09	2018-09

## 1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dBμV. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dBμV/m). The FCC limits are given in units of μV/m. The following formula is used to convert the units of μV/m to dBμV/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 \cdot \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

Reading	+	AF	=	Net Reading	:	Net reading - FCC limit	=	Margin
21.5 dBμV	+	26 dB	=	47.5 dBμV/m	:	47.5 dBμV/m - 57.0 dBμV/m	=	-9.5 dB

## 2 Result Summary

FCC 47 CFR Part 15C, IC RSS-210				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
RSS-Gen 6.6	Occupied Bandwidth	RSS-Gen 6.6	N/R	Informational only
FCC 15.35(c) RSS-Gen 6.10	Duty Cycle	ANSI C63.10	N/R	Informational only
FCC 15.249(a),(c),(e) RSS-210 B.10(a)	Fundamental field strength emissions	ANSI C63.10	PASS	
FCC 15.249(a),(c),(d),(e) RSS-210 B.10(b)	Emission radiated outside the specified frequency band	ANSI C63.10	PASS	
RSS-Gen 7.1	Receiver radiated spurious emissions	ANSI C63.10	PASS	
FCC § 15.207 RSS-Gen 8.8	AC power line conducted emissions	ANSI C63.10	PASS	
Remarks:				

### 3 Test Conditions and Results

#### 3.1 Test Conditions and Results – Occupied Bandwidth


Occupied Bandwidth acc. to IC RSS-Gen			Verdict: N/R
Test according to measurement reference		Reference Method	
		RSS-Gen 6.6	
Test frequency range		Tested frequencies	
		F <sub>LOW</sub> , F <sub>MID</sub> , F <sub>HIGH</sub>	
EUT test mode		Transmit	
Limits			
None (Informational only)			
Test setup			
<div><div>Spectrum Analyzer</div><div>EUT</div></div>			
Test procedure			
<div>1. EUT set to test mode (Communication tester is used if needed)</div> <div>2. Span set to at least twice the emission spectrum</div> <div>3. Resolution bandwidth set to 1 % of span</div> <div>4. Occupied Bandwidth (99 %) measurement with spectrum analyzer built in measurement function</div>			
Test results			
Channel	Frequency [MHz]	Occupied Bandwidth [kHz]	
F <sub>LOW</sub>	2410	510	
F <sub>MID</sub>	2435	504	
F <sub>HIGH</sub>	2460	509	
Comments:			



### Occupied Bandwidth - F<sub>Low</sub>

#### Occupied Bandwidth acc. to ISED RSS-Gen 6.6

Project Number: G0M-1805-7423  
 Applicant: Liftup A/S  
 Model Description: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Sample ID: 19142  
 Operator: S. Suckow  
 Test Site: Eurofins Product Service GmbH  
 Test Date: 2018-07-09  
 Operating Conditions: Tnom/Vnom  
 Mode: TX 2410 MHz GFSK



Date: 9.JUL.2018 09:52:13


Test Report No.: G0M-1805-7424-TFC249-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

# Occupied Bandwidth - F<sub>MID</sub>

## Occupied Bandwidth acc. to ISED RSS-Gen 6.6

Project Number: G0M-1805-7423  
Applicant: Liftup A/S  
Model Description: Radio module for Liftup A/S products  
Model: MODULE1  
Test Sample ID: 19142  
Operator: S. Suckow  
Test Site: Eurofins Product Service GmbH  
Test Date: 2018-07-09  
Operating Conditions: Tnom/Vnom  
Mode: TX 2435 MHz GFSK



Date: 9.JUL.2018 09:55:30


Test Report No.: G0M-1805-7424-TFC249-V01

Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

### Occupied Bandwidth - F<sub>HIGH</sub>

#### Occupied Bandwidth acc. to ISED RSS-Gen 6.6

Project Number: G0M-1805-7423  
 Applicant: Liftup A/S  
 Model Description: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Sample ID: 19142  
 Operator: S. Suckow  
 Test Site: Eurofins Product Service GmbH  
 Test Date: 2018-07-09  
 Operating Conditions: Tnom/Vnom  
 Mode: TX 2460 MHz GFSK



Date: 9.JUL.2018 09:54:12

Test Report No.: G0M-1805-7424-TFC249-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany


### 3.2 Test Conditions and Results – Duty Cycle

Duty cycle acc. to FCC 47 CFR 15.35(c) / ISED RSS-Gen 6.10			Verdict: N/R
Test according referenced standards	Reference Method		
	FCC 15.35(c) / ISED RSS-Gen 6.10		
Test according to measurement reference	Reference Method		
	non specific		
Test frequency range	Tested frequencies		
	F <sub>HIGH</sub>		
EUT test mode	Transmit		
Limits			
None (only for peak to average correction, 20dB max)			
Test setup			
<div><div>Spectrum Analyzer</div><div>EUT</div></div>			
Test procedure			
<div>1. EUT set to test mode</div> <div>2. Center frequency is set to test frequency</div> <div>3. Span it set to zero span</div> <div>4. Resolution bandwidth is set large enough to accurately capture transmission bursts</div> <div>5. Total transmission time is measured</div>			
Test results			
Channel	Frequency [MHz]	Duty Cycle [% @ 100ms]	Duty Cycle correction [dB]
F <sub>HIGH</sub>	2460	1	40 -> 20
Comments: Duty cycle correction is used if pulsed operation is employed and field strength limits are expressed in terms of average value.			

Duty Cycle – F<sub>HIGH</sub>

## Duty Cycle

Project Number: G0M-1805-7423  
 Applicant: Liftup A/S  
 Model Description: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Sample ID: 16140  
 Reference Standards: ANSI C63.10:2013  
 Reference Method: ANSI C63.10:2013, Section 7.5  
 Operating Frequency: 2460 MHz  
 Operating Conditions: Tnom/Vnom  
 Operator: S. Suckow  
 Test Site: Eurofins Product Service GmbH  
 Test Date: 2018-07-12  
 Duty Cycle Period: 100  
 Maximum Duty Cycle: 0.01  
 Maximum Duty Cycle [%]: 1  
 Duty Cycle Correction [dB]: -40.00




Date: 12.JUL.2018 16:04:12

Test Report No.: G0M-1805-7424-TFC249-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

### 3.3 Test Conditions and Results – Fundamental field strength emissions


Field strength emissions acc. to FCC 47 CFR 15.249 / IC RSS-210				Verdict: N/R
Test according referenced standards	Reference Method			
	FCC 15.249(a),(c),(e) / IC RSS-210 B.10(a)			
Test according to measurement reference	Reference Method			
	ANSI C63.10			
Test frequency range	Tested frequencies			
	$F_{\text{LOW}}$ , $F_{\text{MID}}$ , $F_{\text{HIGH}}$			
EUT test mode	Transmit			
Limits				
Frequency range [MHz]	Detector	Limit [mV/m]	Limit [dBμV/m]	Limit Distance [m]
902 – 928	Quasi-Peak	50	94	3
2400 – 2483.5	Average	50	94	3
5725 - 5875	Average	50	94	3
FCC 15.249(e) : for frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.				
Below 1GHz a CISPR quasi-peak detector is used.				
Test setup				
				




Test procedure								
<ol style="list-style-type: none"> <li>1. EUT set to test mode</li> <li>2. Span it set according to measurement range</li> <li>3. Below 1 GHz the resolution bandwidth is set according to CISPR 16 to 120 kHz with peak/quasi-peak detector.</li> <li>4. Above 1 GHz the resolution bandwidth is set to 1 MHz with peak/average detector. Pulsed emissions are averaged over 100 ms with duty cycle correction.</li> <li>5. Markers are set to maximum emission levels</li> </ol>								
Test results pulsed emissions > 1 GHz								
Channel	Frequency [MHz]	Pol.	Peak Level [dB $\mu$ V/m]	Duty Cycle Correct. [dB]	Average Level [dB $\mu$ V/m]	Average Limit [dB $\mu$ V/m]	Limit distance [m]*	Margin [dB]
F <sub>LOW</sub>	2410	hor	86.41	20	66.41	94	3	-27.59
F <sub>LOW</sub>	2410	ver	98.07	20	78.07	94	3	-15.93
F <sub>MID</sub>	2435	hor	90.49	20	70.49	94	3	-23.51
F <sub>MID</sub>	2435	ver	96.60	20	76.60	94	3	-17.40
F <sub>HIGH</sub>	2460	hor	90.64	20	70.64	94	3	-23.36
F <sub>HIGH</sub>	2460	ver	96.32	20	76.32	94	3	-17.68
Comments: * Physical distance between EUT and measurement antenna.								

### 3.4 Test Conditions and Results – Emissions radiated outside the specified frequency band

Radiated out-of-band band emissions acc. to FCC 47 CFR 15.249 / IC RSS-210				Verdict: PASS
Test according referenced standards		Reference Method		
		FCC 15.249(a),(c),(d),(e) / IC RSS-210 B.10(b)		
Test according to measurement reference		Reference Method		
		ANSI C63.10		
Test frequency range		Tested frequencies		
		30 MHz – 10 <sup>th</sup> harmonic		
EUT test mode		Transmit		
Limits - Harmonics				
The field strength of harmonic emissions, measured at 3 m, shall not exceed 500 µV/m (54 dBµV/m).				
Limits - General				
Frequency range [MHz]	Detector	Limit [µV/m]	Limit [dBµV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
For frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.				
Except the higher order harmonics, emission radiated outside the specified frequency band shall be attenuated by at least 50 dB below the level of the fundamental or to the general field strength limits listed in 15.209 / RSS-Gen, whichever is less stringent.				

Test setup							
							
Test procedure							
<ol style="list-style-type: none"> <li>1. EUT set to test mode</li> <li>2. Span it set according to measurement range</li> <li>3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz</li> <li>4. Markers are set to maximum emission levels</li> </ol>							
Test results							
Channel	Frequency [MHz]	Emission [MHz]	Level [dB $\mu$ V/m]	Detector	Pol.	Limit [dB $\mu$ V/m]	Margin [dB]
F <sub>LOW</sub>	2410	4819	41.37	pk	hor	74.00	-32.63
F <sub>MID</sub>	2435	4867	41.52	pk	hor	74.00	-32.48
F <sub>HIGH</sub>	2460	4919	42.09	pk	hor	74.00	-31.91
Comments: * Physical distance between EUT and measurement antenna.							

### 3.5 Test Conditions and Results – Receiver radiated emissions

Receiver radiated emissions acc. to IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	RSS-Gen 7.1			
Test according to measurement reference	Reference Method			
	ANSI C63.10			
Test frequency range	Tested frequencies			
	30 MHz – 5 <sup>th</sup> Harmonic			
EUT test mode	Receive			
Limits				
Frequency range [MHz]	Detector	Limit [μV/m]	Limit [dBμV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Test setup				
				

Test procedure							
<ol style="list-style-type: none"> <li>1. EUT set to receive mode (Communication tester is used if needed)</li> <li>2. Span it set according to measurement range</li> <li>3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz</li> <li>4. Markers are set to peak emission levels</li> </ol>							
Test results							
Channel	Frequency [MHz]	Emission [MHz]	Level [dB $\mu$ V/m]	Detector	Pol.	Limit [dB $\mu$ V/m]	Margin [dB]
F <sub>MID</sub>	2435	36.0049	37.30	qpk	ver	40.00	-02.70
The stated emission level corresponds to ambient noise floor. No real spurious emission has been measured.							

### 3.6 Test Conditions and Results – AC power line conducted emissions

Power line conducted emissions acc. to FCC 47 CFR 15.207 / IC RSS-Gen				Verdict: PASS	
Test according referenced standards		Reference Method			
		ANSI C63.10			
Fully configured sample scanned over the following frequency range		Frequency range			
		0.15 MHz to 30 MHz			
Points of Application		Application Interface			
AC Mains		LISN			
EUT test mode		AC-Powerline			
Limits and results					
Frequency [MHz]	Quasi-Peak [dBµV]	Result	Average [dBµV]	Result	
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS	
0.5 to 5	56	PASS	46	PASS	
5 to 30	60	PASS	50	PASS	
Comments:					
* Limit decreases linearly with the logarithm of the frequency.					




**Conducted Emissions**
**EMI voltage test in the ac-mains according to FCC part 15B**

Project number: G0M-1805-7424

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Suckow
Test Conditions:	Tnom: 24°C, Unom: 5.6 VDC
LISN:	ESH2-Z5 N
Mode:	TX FHSS 2435 MHz GFSK
Test Date:	2018-07-16
Note:	Minus

Index 1




**Conducted Emissions**
**EMI voltage test in the ac-mains according to FCC part 15B**

Project number: G0M-1805-7424

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Suckow
Test Conditions:	Tnom: 24°C, Unom: 5.6 VDC
LISN:	ESH2-Z5 L
Mode:	TX FHSS 2435 MHz GFSK
Test Date:	2018-07-16
Note:	Plus

Index 2



Test Report No.: G0M-1805-7424-TFC249-V01

Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany


## ANNEX A Transmitter radiated spurious emissions

### Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Suckow  
 Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HK 116, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-13  
 Note:

Index 2




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Suckow  
 Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HK 116, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-13  
 Note:

Index 3




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 49




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 56






## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 17




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 22




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:


Index 18



**Spurious emissions according to FCC 15.249**

Project number: G0M-1805-7423  
 Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 23




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 19




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 24




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 39



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.819 GHz	41.37 dBµV/m	74 dBµV/m	-32.63 dB	Pass

Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

**Spurious emissions according to FCC 15.249**

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2410 MHz  
 Test Date: 2018-07-12  
 Note:

Index 31



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.819 GHz	43.18 dBµV/m	74 dBµV/m	-30.82 dB	Pass

Test Report No.: G0M-1805-7424-TFC249-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2410 MHz
Test Date:	2018-07-12
Note:	

Index 38




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2410 MHz
Test Date:	2018-07-12
Note:	

Index 30



Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Amplifier Research AT 4560 (old name) / ATH18G40 (new name),
Horizontal	
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2410 MHz
Test Date:	2018-07-12
Note:	

Index 40



Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

**Spurious emissions according to FCC 15.249**

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Amplifier Research AT 4560 (old name) / ATH18G40 (new name),
Vertical	
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2410 MHz
Test Date:	2018-07-12
Note:	

Index 41




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Suckow  
 Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HK 116, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; TX, FHSS, 2435 MHz  
 Test Date: 2018-07-13  
 Note:

Index 6




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Suckow  
 Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HK 116, Vertical  
 Measurement distance: 3 m  
 Mode: TX; TX, FHSS, 2435 MHz  
 Test Date: 2018-07-13  
 Note:

Index 7




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
EUT Name: Radio module for Liftup A/S products  
Model: MODULE1  
Test Site: Eurofins Product Service GmbH  
Operator: Sebastian Suckow  
Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
Antenna: Rohde & Schwarz HL 223, Horizontal  
Measurement distance: 3 m  
Mode: TX; FHSS GFSK 2435 MHz  
Test Date: 2018-07-12  
Note:

Index 52




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 58






## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 20




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 21




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 35



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.867 GHz	41.52 dBµV/m	74 dBµV/m	-32.48 dB	Pass

Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 32



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.867 GHz	43.09 dBµV/m	74 dBµV/m	-30.91 dB	Pass

Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 34




**Spurious emissions according to FCC 15.249**

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2435 MHz
Test Date:	2018-07-12
Note:	

Index 33




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Amplifier Research AT 4560 (old name) / ATH18G40 (new name),
Horizontal	
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2435 MHz
Test Date:	2018-07-12
Note:	

Index 44



Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Amplifier Research AT 4560 (old name) / ATH18G40 (new name),
Vertical	
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2435 MHz
Test Date:	2018-07-12
Note:	

Index 45






## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Remote Control for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Suckow  
 Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HK 116, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-13  
 Note:

Index 5




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Remote Control for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Suckow  
 Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HK 116, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-13  
 Note:

Index 4




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 50




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
EUT Name: Radio module for Liftup A/S products  
Model: MODULE1  
Test Site: Eurofins Product Service GmbH  
Operator: Sebastian Suckow  
Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
Antenna: Rohde & Schwarz HL 223, Vertical  
Measurement distance: 3 m  
Mode: TX; FHSS GFSK 2460 MHz  
Test Date: 2018-07-12  
Note:

Index 57




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 12




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
EUT Name: Radio module for Liftup A/S products  
Model: MODULE1  
Test Site: Eurofins Product Service GmbH  
Operator: Sebastian Suckow  
Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
Antenna: Schwarzbeck BBHA 9120D, Vertical  
Measurement distance: 3 m  
Mode: TX; FHSS GFSK 2460 MHz  
Test Date: 2018-07-12  
Note:


Index 27



**Spurious emissions according to FCC 15.249**

Project number: G0M-1805-7423  
 Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 16




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 26






## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:


Index 15



**Spurious emissions according to FCC 15.249**

Project number: G0M-1805-7423  
 Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 25




**Spurious emissions according to FCC 15.249**

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 36



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.919 GHz	42.09 dBµV/m	74 dBµV/m	-31.91 dB	Pass

Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 28



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.919 GHz	43.68 dBµV/m	74 dBµV/m	-30.32 dB	Pass

Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 25°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 1 m converted to 3m  
 Mode: TX; FHSS GFSK 2460 MHz  
 Test Date: 2018-07-12  
 Note:

Index 37



Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2460 MHz
Test Date:	2018-07-12
Note:	

Index 29




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Amplifier Research AT 4560 (old name) / ATH18G40 (new name),
Horizontal	
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2460 MHz
Test Date:	2018-07-12
Note:	

Index 43



Test Report No.: G0M-1805-7424-TFC249-V01


Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7423

Applicant:	Liftup A/S
EUT Name:	Radio module for Liftup A/S products
Model:	MODULE1
Test Site:	Eurofins Product Service GmbH
Operator:	Sebastian Suckow
Test Conditions:	Tnom: 25°C, Vnom: 5.6 VDC
Antenna:	Amplifier Research AT 4560 (old name) / ATH18G40 (new name),
Vertical	
Measurement distance:	1 m converted to 3m
Mode:	TX; FHSS GFSK 2460 MHz
Test Date:	2018-07-12
Note:	

Index 42






## ANNEX B Receiver radiated spurious emissions

### Spurious emissions according to RSS-Gen

Project number: G0M-1805-7424

Applicant: Liftup A/S  
EUT Name: Radio module for Liftup A/S products  
Model: MODULE1  
Test Site: Eurofins Product Service GmbH  
Operator: Mr. Suckow  
Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
Antenna: Rohde & Schwarz HK 116, Vertical  
Measurement distance: 3 m  
Mode: RX; FHSS, 2435 MHz  
Test Date: 2018-07-13  
Note:

Index 2




Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status	Angle	Height
36.0049 MHz	37.3 dBµV/m	40 dBµV/m	-2.7 dB	Pass	0 Degree	1 m

**Spurious emissions according to RSS-Gen**

Project number: G0M-1805-7424  
 Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Suckow  
 Test Conditions: Tnom: 24°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HK 116, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; FHSS, 2435 MHz  
 Test Date: 2018-07-13  
 Note:

Index 3




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; FHSS, 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 2




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: RX; FHSS, 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 1




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; FHSS, 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 3




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
EUT Name: Radio module for Liftup A/S products  
Model: MODULE1  
Test Site: Eurofins Product Service GmbH  
Operator: Sebastian Suckow  
Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
Antenna: Schwarzbeck BBHA 9120D, Vertical  
Measurement distance: 3 m  
Mode: RX; FHSS, 2435 MHz  
Test Date: 2018-07-12  
Note:

Index 6




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; FHSS, 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 4




## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 3 m  
 Mode: RX; FHSS, 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 5






## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
EUT Name: Radio module for Liftup A/S products  
Model: MODULE1  
Test Site: Eurofins Product Service GmbH  
Operator: Sebastian Suckow  
Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
Antenna: Schwarzbeck BBHA 9120D, Horizontal  
Measurement distance: 1 m converted to 3m  
Mode: RX; FHSS, 2435 MHz  
Test Date: 2018-07-12  
Note:

Index 8



## Spurious emissions according to FCC 15.249

Project number: G0M-1805-7424

Applicant: Liftup A/S  
 EUT Name: Radio module for Liftup A/S products  
 Model: MODULE1  
 Test Site: Eurofins Product Service GmbH  
 Operator: Sebastian Suckow  
 Test Conditions: Tnom: 26°C, Vnom: 5.6 VDC  
 Antenna: Schwarzbeck BBHA 9120D, Vertical  
 Measurement distance: 1 m converted to 3m  
 Mode: RX; FHSS, 2435 MHz  
 Test Date: 2018-07-12  
 Note:

Index 7

