



Date: 2019-01-23  
Report Number: 60.790.18.050.01  
Model No.: 75003PP01  
FCC ID: 2AK9F-7500

### **Radiofrequency radiation exposure evaluation**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances  $\leq 50$  mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR

>> The fundamental frequency of the EUT is 2402-2480MHz,  
the test separation distance is  $\leq 50$ mm.  
(Manufacturer specified the separation distance is: 5mm)

Step a)

>> Numeric threshold (2402MHz),  $\text{mW} / 5\text{mm} \cdot \sqrt{2.402\text{GHz}} \leq 3.0$   
Numeric threshold (2402MHz)  $\leq 9.678\text{mW}$

>> Numeric threshold (2440MHz),  $\text{mW} / 5\text{mm} \cdot \sqrt{2.441\text{GHz}} \leq 3.0$   
Numeric threshold (2440MHz)  $\leq 9.601\text{mW}$

>> Numeric threshold (2480MHz),  $\text{mW} / 5\text{mm} \cdot \sqrt{2.480\text{GHz}} \leq 3.0$   
Numeric threshold (2480MHz)  $\leq 9.525\text{mW}$

>> The power of EUT measured (2402MHz) is:  $-1.39\text{dBm} = 0.726\text{mW}$   
The power of EUT measured (2440MHz) is:  $-1.48\text{dBm} = 0.711\text{mW}$   
The power of EUT measured (2480MHz) is:  $-1.80\text{dBm} = 0.661\text{mW}$

Which is smaller than the Numeric threshold.  
Therefore, the device is exempt from stand-alone SAR test requirements.

3/F, West Wing, Phase 2, 10 Science Park West Avenue, Hong Kong Science Park, Shatin, Hong Kong