

Appendix 11. RF Exposure Requirement

1.Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency	Electric Field	Magnetic Field	Power Density	Average Time	
Range (MHz)	Strength(V/m)	Strength (A/m)	(mW/cm2)	(Minutes)	
(A) Limits for Occupational/ Control Exposures					
300-1500	-	-	F/300	6	
1500-100,000	-	-	5	6	
(B) Limits for General Population/ Uncontrolled Exposures					
300-1500	-	-	F/1500	6	
1500-100,000	-	-	1	30	

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*pi*r2)

Where

Pd = power density in mW/ cm^2 Pout = output power to antenna in mW G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/ cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 23°C and 42% RH.



3.Test Result of RF Exposure Evaluation

Frequency	RF Output Power(dBm)
2402	5.09
2441	3.51
2480	3.02
2402	2.53
2441	3.90
2480	2.55
2402	2.40
2441	4.17
2480	2.83
2402	4.03
2440	4.93
2480	3.84
	Frequency 2402 2441 2480 2402 2441 2480 2402 2441 2480 2402 2441 2480 2402 2440

Maximum RF Power=5.09dBm-2.84=2.25dBm=1.68mW

1.68/(4*3.14*400)= 0.000334

Frequency Band(MHz)	Maximum RF Power(mW)	Power Density at R = $20 \text{cm}(\text{mW}/\text{cm}^2)$
2402-2480	1.68	0.000334

Note:

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/ cm^2 .