

Annex 1: Measurement diagrams to

TEST REPORT No.: 16-1-0141801T07b-C1

According to: **FCC Regulations** Part 22, Part 24

IC-Regulations

RSS-132 Issue 3, RSS-133 Issue 6, RSS-Gen Issue 4

for

Daimler Trucks North America

ECU CTPBASEDTNA

FCC-ID: 2AKC8CTP054631 IC: 22221-CTP054631 HVIN: CTPBASEDTNA PMN: CTPBASEDTNA FVIN: 16.095.2







Table of contents

1. MEASUREMENT DIAGRAMS	3
1.1. Power Measurements and PAPR-Value	
1.2. Magnetic field emissions radiated (850 MHz transmitting mode)	10
1.3. Magnetic field emissions radiated 1900 MHz transmitting mode)	
1.4. Spurious emissions radiated (850 MHz transmitting mode)	12
1.5. Spurious emissions radiated (1900 MHz transmitting mode)	13
1.6. Radiated emissions on 850 MHz transmitting band-edge	14
1.7. Radiated emissions on 1900 MHz transmitting band-edge	16

1. Measurement diagrams

1.1. Power Measurements and PAPR-Value

1.1.1. GSM 850 (GMSK Modulation)




Complementary Cumulative Distribution Function NOF samples: 2308, Usable EW: 3.5MHz

Mean Peak Crest	Trace 32.45 32.78 0.33	dBm dBm
10 % 1 % .1 %	0.26 0.33 0.34 0.34	dB dB

Date: 21.DEC.2016 11:33:38

Diagram CCDF_128_GMSK




Complementary Cumulative Distribution Function NOF samples: 2308, Usable EW: 3.5MHz

Mean Peak Crest	32.38 32.71 0.33	dBn dBn
10 % 1 % .1 %	0.26 0.33 0.34 0.34	dB dB

Date: 21.DEC.2016 11:35:24

Diagram CCDF_192_GMSK




Mean Peak Crest	Trace 32.30 32.64 0.34	dBm dBm
10 % 1 % .1 %	0.26 0.30 0.34 0.34	dB dB

Date: 21.DEC.2016 11:37:43

Diagram CCDF_251_GMSK

1.1.2. GSM 850 (8-PSK Modulation)




Complementary Cumulative Distribution Function NOF samples: 2308, Usable EW: 3.5MHz

Trace 1
Mean 24.34 dBm
Peak 27.84 dBm
Crest 3.50 dB

10 % 2.36 dB
1 % 3.38 dB
.1 % 3.48 dB
.01 % 3.51 dB

Date: 21.DEC.2016 11:25:16

Diagram CCDF_128_8PSK




Complementary Cumulative Distribution Function NOF samples: 2308, Usable BW: 3.5MHz

Trace 1
Mean 24.24 dBm
Peak 27.77 dBm
Crest 3.53 dB

10 % 2.37 dB
1 % 3.38 dB
.1 % 3.50 dB
.01 % 3.54 dB

Date: 21.DEC.2016 11:28:01


Diagram CCDF_192_8PSK



Mean Peak Crest	Trace 24.18 27.77 3.59	dBm dBm
10 % 1 % .1 %	2.75 3.42 3.52 3.59	dB dB

Date: 21.DEC.2016 11:29:52


Diagram CCDF_251_8PSK 1.1.3. GSM 1900 (GMSK Modulation)



Mean Peak Crest	Trace 25.52 25.87 0.34	dBm dBm
10 % 1 % .1 %	0.26 0.28 0.34 0.35	dB dB

Date: 21.DEC.2016 11:44:12

Diagram CCDF_512_GMSK




Complementary Cumulative Distribution Function NOF samples: 2308, Usable EW: 3.5MHz

Mean Peak Crest	Trace 26.17 26.50 0.33	dBm dBm
10 % 1 % .1 %	0.26 0.32 0.34 0.34	dB dB

Date: 21.DEC.2016 11:46:28

Diagram CCDF_661_GMSK




Mean Peak	Trace 1 27.50 dBm 27.84 dBm		
Crest	0.34		
10 % 1 % .1 %	0.27 0.28 0.32 0.35	dB dB	

Date: 21.DEC.2016 11:47:49

Diagram CCDF_810_GMSK

1.1.4. GSM 1900 (8-PSK Modulation)




Complementary Cumulative Distribution Function NOF samples: 2308, Usable BW: 3.5MHz

Mean Peak Crest	Trace 21.83 25.23 3.40	dBm dBm
10 % 1 % .1 %	2.71 3.23 3.37 3.40	dB dB

Date: 21.DEC.2016 11:13:32


Diagram CCDF_512_8PSK



Mean Peak Crest	Trace 22.43 26.01 3.58	dBm dBm
10 % 1 % .1 %	2.67 3.38 3.50	dB dB

Date: 21.DEC.2016 11:16:48

Diagram CCDF_661_8PSK



Complementary Cumulative Distribution Function NOF samples: 2308, Usable EW: 3.5MHz

Mean Peak Crest	23.74 27.14 3.40	dBm dBm
10 % 1 % .1 %	2.57 3.25 3.38 3.40	dB dB

Date: 21.DEC.2016 11:20:28

Diagram CCDF_810_8PSK

1.2. Magnetic field emissions radiated (850 MHz transmitting mode) Diagram No. 2.01_Magnetic_GPRS850_Ch192

Date: 21.12.2016 Page 1 of 1

Test description: Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance

Version of Testsoftware: EMC32 V9.25.0

Distance correction: used accord. table, pls. see test report

Technical Data: Please see page 2 for detailed data of measurement setup Rec. antenna (pre-scan): height 1.00 m, parallel and 90° to EUT polarisation

Used filter: bypass

Test specification: FCC 15.205 § 15.209; RSS-Gen: Issue 4

Operator: AFr

Operating conditions: GPRS Ch 192 (middle)
Power during tests: 12 V DC (car battery)

EUT Information

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU CTPBASEDTNA


HW Version: 6794G05

SW Version: DAIMLER_CTP_16.095.2.

Serial Number: 2800003466

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC



1.3. Magnetic field emissions radiated 1900 MHz transmitting mode) Diagram No. 2.05_Magnetic_GSM1900_Ch661

Date: 22.12.2016 Page 1 of 1

Test description: Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance

Version of Testsoftware: EMC32 V9.25.0

Distance correction: used accord. table, pls. see test report

Technical Data: Please see page 2 for detailed data of measurement setup Rec. antenna (pre-scan): height 1.00 m, parallel and 90° to EUT polarisation

Used filter: bypass

Test specification: FCC 15.205 § 15.209; RSS-Gen: Issue 4

Operator: YSa Operating conditions: TX-on

Power during tests: 12 V DC (car battery)

EUT Information

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU CTPBASEDTNA


HW Version: 6794G05

SW Version: DAIMLER_CTP_16.095.2.

Serial Number: 2800003466

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC



1.4. Spurious emissions radiated (850 MHz transmitting mode) 8.05 RSE R Ch192 GPRS

Common Information

Test Description:

Test Site Location:

Test Site:

Radiated Emissions GSM850

CETECOM GmbH Essen

Fully Anechoic Room (FAR)

Test Standard: FCC Part22.917
Test Case: GPRS_850

Operating Mode: RSE_R_CH192_GPRS

Exclusionband: 824 - 849MHz

Environmental Conditions: Humidity: 40%rH; Temperature: 20°C

Operator: TFr

EUT Information

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU CTPBASEDTNA

.....


HW Version: 6794G05

SW Version: DAIMLER_CTP_16.095.2.

Serial Number: 2800003466

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC



1.5. Spurious emissions radiated (1900 MHz transmitting mode)

8.14_RSE_R_Ch661_GPRS

Common Information

Test Description:

Radiated Emissions GSM850

Test Site Location:

CETECOM GmbH Essen

Fully Anechoic Room (FAR)

Test Standard: FCC Part24.238

Test Case:

Operating Mode: MS allocated UL channel 512,661,810

Exclusionband: 1850 - 1910MHz

Environmental Conditions: Humidity: 40%rH; Temperature: 20°C

Operator:

EUT Information

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU cTP mid

 HW Version:
 67946794G05


 SW Version:
 16/41/01

 Serial Number:
 2820003843

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC

Full Spectrum



Final_Result

Frequency (MHz)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Pol	Azimut h (deg)	Elevatio n (deg)	Corr. (dB)
3759.864729	-	17.22	1000.0	V	11.0	0.0	-95.1
5639.794589	-	26.08	1000.0	Н	22.0	90.0	-89.7
7520.055110	-	14.07	1000.0	V	47.0	90.0	-83.4
9399.644288	-	17.24	1000.0	Н	-26.0	90.0	-82.8

1.6. Radiated emissions on 850 MHz transmitting band-edge 9.03 BE R Ch128 GPRS

Common Information

Test Description: Radiated Band Edge Compliance GSM850

Test Site Location: CETECOM GmbH Essen
Test Site: Fully Anechoic Room (FAR)

Test Standard: FCC Part 22.917

Operating Mode: MS allocated channel 128 (fc = 824.2MHz), Voice, PCL5 (+33dBm)

Exclusionband: 824 - 849MHz

Environmental Conditions: Humidity: 35%rH; Temperature: 20°C

Operator: AFr

EUT Information

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU CTPBASEDTNA


HW Version: 6794G05

SW Version: DAIMLER_CTP_16.095.2.

Serial Number: 2800003466

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC



9.04_BE_R_Ch251_GPRS

Common Information

Test Description: Radiated Band Edge Compliance GSM850

Test Site Location: CETECOM GmbH Essen
Test Site: Fully Anechoic Room (FAR)

Test Standard: FCC Part 22.917

Operating Mode: MS allocated channel 251 (fc = 848.8MHz), Voice, PCL0 (+33dBm)

Exclusionband: 824 - 849MHz
Environmental Conditions: Humidity: 35%rH; Temperature: 20°C

Operator: AFr

EUT Information

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU CTPBASEDTNA


HW Version: 6794G05

SW Version: DAIMLER_CTP_16.095.2.

Serial Number: 2800003466

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC



1.7. Radiated emissions on 1900 MHz transmitting band-edge 9.09 BE R Ch512 GPRS

Common Information

Test Description: Radiated Spurious Emissions GSM1900

Test Site Location: CETECOM GmbH Essen
Test Site: Fully Anechoic Room (FAR)

Test Standard: FCC Part 24.238
Comm. Link: GSM1900, Voice/EDGE

Operating Mode: MS allocated channel 512 (UL = 1850.2MHz),661(UL = 1880.0MHz),810 (UL =

1909.8MHz)

Exclusionband: 1850- 1910MHz

Environmental Conditions: Humidity: 40%rH; Temperature: 20°C

Operator: AFr

EUT Information

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU CTPBASEDTNA


HW Version: 6794G05

SW Version: DAIMLER_CTP_16.095.2.

Serial Number: 2800003466

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC



9.10_BE_R_Ch810_GPRS

Common Information

Test Description: Radiated Spurious Emissions GSM1900

Test Site Location: CETECOM GmbH Essen
Test Site: Fully Anechoic Room (FAR)
Test Standard: FCC Part 24.238

Test Standard: FCC Part 24.238
Comm. Link: GSM1900, Voice/EDGE

Operating Mode: MS allocated channel 512 (UL = 1850.2MHz),661(UL = 1880.0MHz),810 (UL =

1909.8MHz) 1850- 1910MHz

Environmental Conditions: Humidity: 40%rH; Temperature: 20°C

Operator: AFr

EUT Information

Exclusionband:

Manufacturer: Bosch Car Multimedia Portugal, S.A.

EuT: ECU CTPBASEDTNA

HW Version: 6794G05

SW Version: DAIMLER_CTP_16.095.2.

Serial Number: 2800003466

Connected Interfaces: USB-cable + main wiring + GSM/GNSS antenna

Power Supply: 12 V DC

