

RF Exposure Report

Report No.: SA170810E01

FCC ID: 2AKCZ-0C3

Test Model: APL43-0C3

Received Date: June 01, 2017

Test Date: Aug. 01, 2017

Issued Date: Aug. 23, 2017

Applicant: SonicWall Inc.

Address: 5455 Great America Parkway, Santa Clara, CA 95054 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA170810E01	Original release.	Aug. 23, 2017

1 Certificate of Conformity

Product: Wireless Access Point

Brand: SONICWALL

Test Model: APL43-0C3

Sample Status: ENGINEERING SAMPLE

Applicant: SonicWall Inc.

Test Date: Aug. 01, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :




Date:

Aug. 23, 2017

Claire Kuan / Specialist

Approved by :



Date:

Aug. 23, 2017

May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 50cm away from the body of the user. So, this device is classified as Mobile Device.

2.4 Classification

Internal antenna										
Type	PIFA									
Connector	IPEX									
Radio	1				2				3	4
Frequency	2.4GHz				5GHz				2.4GHz	BT-LE
Antenna	1	2	3	4	5	6	7	8	9	10
Gain (dBi)	3.15	3.52	3.39	4.57	4.92	5.87	5.47	5.95	2.91	3.13

3 Calculation Result of Maximum Conducted Power

Radio	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
1	WLAN 2412~2462 (CDD mode)	27.55	9.7	50	0.16884	1
	WLAN 2412~2462 (Beamforming mode)	24.21	9.7	50	0.07830	1
2	WLAN 5180-5240 (CDD mode)	24.20	11.58	50	0.12056	1
	WLAN 5745-5825 (CDD mode)	27.54	11.58	50	0.25966	1
	WLAN 5180-5240 (Beamforming mode)	21.37	11.58	50	0.06279	1
	WLAN 5745-5825 (Beamforming mode)	21.48	11.58	50	0.06435	1
3	WLAN 2412~2462	20.66	2.91	50	0.00724	1
4	BT-LE 2402-2480	6.04	3.13	50	0.00026	1

Note:

For radio 1

2.4GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 9.7\text{dBi}$

For radio 2

5GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.58\text{dBi}$

For radio 3

2.4GHz: Directional gain = 2.91dBi

For radio 4

BT-LE: Directional gain = 3.13dBi

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Radio 1 + Radio 2 + Radio 3 + Radio 4

= $0.16884 / 1 + 0.25966 / 1 + 0.00724 / 1 + 0.00026 / 1 = 0.43600 < 1$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---