

# FCC PART 15.247

## TEST REPORT

For

### Johnson Industries (Shanghai) CO., LTD

A1, Export Processing Zone, No. 4500 Bao Qian Rd., Jia Ding, Shanghai, China

**FCC ID: 2AKDB-WLT2564M**

<b>Report Type:</b> Original Report	<b>Product Type:</b> BT Module
<b>Test Engineer:</b> Peter Jiang	<i>Peter Jiang</i>
<b>Report Number:</b> RKS161031011-00C	
<b>Report Date:</b> 2016-11-21	
<b>Reviewed By:</b> EMC Manager	Jesse Huang <i>Jesse Huang</i>
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
EUT EXERCISE SOFTWARE .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>9</b>
<b>FCC§15.247 (i), §1.1310&amp; §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
ANTENNA CONNECTOR CONSTRUCTION .....	11
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>12</b>
APPLICABLE STANDARD .....	12
EUT SETUP.....	12
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE .....	12
CORRECTED FACTOR & MARGIN CALCULATION .....	13
TEST RESULTS SUMMARY .....	13
TEST DATA .....	14
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
EUT SETUP .....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	17
TEST PROCEDURE .....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	17
TEST RESULTS SUMMARY .....	17
TEST DATA .....	18
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>	<b>23</b>
APPLICABLE STANDARD .....	23
TEST PROCEDURE .....	23
TEST DATA .....	23
<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>26</b>

APPLICABLE STANDARD .....	26
TEST PROCEDURE .....	26
TEST DATA .....	26
<b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>28</b>
APPLICABLE STANDARD .....	28
TEST PROCEDURE .....	28
TEST DATA .....	28
<b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>	<b>30</b>
APPLICABLE STANDARD .....	30
TEST PROCEDURE .....	30
TEST DATA .....	30

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The Johnson Industries (Shanghai) CO., LTD's product, model number: WLT2564M (FCC ID: 2AKDB-WLT2564M) or the "EUT" in this report was a BT Module, which was measured approximately:35mm (L) x18 mm (W) x3mm(H). Rated input voltage: 3.3VDC.

*\*All measurement and test data in this report was gathered from production sample serial number: 20161103003.  
(Assigned by the BACL. The EUT supplied by the applicant was received on 2016-11-03)*

### Objective

This report is prepared on behalf of Johnson Industries (Shanghai) CO., LTD in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC part 15.247 DSS submission with FCC ID: 2AKDB-WLT2564M.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB558074 D01 DTS Meas Guidance v03r05.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
AC Power Lines Conducted Emissions		$\pm 3.26$ dB
RF conducted test with spectrum		$\pm 0.9$ dB
RF Output Power with Power meter		$\pm 0.5$ dB
Radiated emission	30MHz~1GHz	$\pm 5.91$ dB
	Above 1G	$\pm 4.92$ dB
Occupied Bandwidth		$\pm 0.5$ kHz
Temperature		$\pm 1.0$ °C
Humidity		$\pm 6\%$

**Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10-2013.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
...	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

RF Test Tool for PC

The worst case was performed under:  
BLE: Power level: 7

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
Johnson	Control Board	N/A	N/A

### External I/O Cable


Cable Description	Length (m)	From Port	To
USB Cable	0.3	Control Board	Notebook

## Block Diagram of Test Setup

For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance



**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-12	2017-11-11
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-12	2017-11-11
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
ETS	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Sonoma Instrument	Amplifier	330	171377	2016-10-21	2017-10-20
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-07
R&S	Auto test Software	EMC32	100361	/	/
Haojintech	Coaxial Cable	Cable-1	001	2015-12-12	2016-12-11
Haojintech	Coaxial Cable	Cable-2	002	2015-12-12	2016-12-11
Haojintech	Coaxial Cable	Cable-3	003	2015-12-12	2016-12-11
MICRO-COAX	Coaxial Cable	Cable-4	004	2015-12-12	2016-12-11
MICRO-COAX	Coaxial Cable	Cable-5	005	2015-12-12	2016-12-11
<b>RF Conducted Test</b>					
Rohde & Schwarz	OSP120 Base Unit	OSP120	101247	2016-07-04	2017-07-03
BACL	EMC32 Version	EMC 32	V 09.10.0	/	/
Rohde & Schwarz	SMBV100A Vector Signal Generator	SMBV100A	261558	2016-07-04	2017-07-03
Rohde & Schwarz	SMB 100A Signal Generator	SMB100A	110390	2016-07-04	2017-07-03
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-20
Agilent	Power Meter	N1912A	MY5000492	2016-11-18	2017-11-17
Agilent	Power Sensor	N1921A	MY54210024	2016-11-18	2017-11-17
Johnson	RF Cable	N/A	N/A	2016-11-19	2017-11-18
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2016-11-12	2017-11-11
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2016-10-10	2017-10-09
ROHDE&SCHWARZ	LISN	ENV216	3560655016	2015-11-25	2016-11-24
Rohde & Schwarz	CE Test software	EMC 32	100357	/	/
HP	Current probe	11967A	636	2016-07-04	2017-07-03
FCC	ISN	FCC-TLISN-T8-02	20376	2016-07-04	2017-07-03
MICRO-COAX	Coaxial Cable	Cable-6	006	2016-09-08	2017-09-07

## FCC§15.247 (i), §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### Calculated Data:

Mode	Frequency	Antenna Gain		Output Power		Evaluation Distance	Power Density	MPE Limit
	(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
BLE	2480	2.5	1.78	8.00	6.31	20	0.0022	1

Note: The target output power:  $6.5 \pm 1.5$  dBm, which declared by the Manufacturer.

**Result:** The device meet FCC MPE at 20 cm distance

**FCC §15.203 - ANTENNA REQUIREMENT**

---

**Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

**Antenna Connector Construction**

The EUT has a ceramic antenna arrangement for BLE, which the antenna gain is 2.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a AC 120 V/60 Hz power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

**Corrected Factor & Margin Calculation**

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

**Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Part 15.207

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$


In BACL,  $U_{(Lm)}$  is less than  $U_{\text{cispr}}$ , if  $L_m$  is less than  $L_{\text{lim}}$ , it implies that the EUT complies with the limit.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	22.8 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.1kPa

The testing was performed by Peter Jiang on 2016-11-21.

EUT operation mode: Transmitting

**AC 120V/60 Hz, Line**

Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.155000	---	32.68	9.000	L1	10.3	23.05	55.73	Compliance
0.155000	49.73	---	9.000	L1	10.3	16.00	65.73	Compliance
0.175000	---	31.23	9.000	L1	10.3	23.49	54.72	Compliance
0.175000	46.32	---	9.000	L1	10.3	18.40	64.72	Compliance
0.280000	---	20.59	9.000	L1	10.3	30.23	50.82	Compliance
0.280000	32.39	---	9.000	L1	10.3	28.43	60.82	Compliance
0.485000	---	29.24	9.000	L1	10.3	17.01	46.25	Compliance
0.485000	34.61	---	9.000	L1	10.3	21.64	56.25	Compliance
3.925000	---	21.11	9.000	L1	10.5	24.89	46.00	Compliance
3.925000	30.06	---	9.000	L1	10.5	25.94	56.00	Compliance
27.360000	---	21.82	9.000	L1	10.5	28.18	50.00	Compliance
27.360000	27.08	---	9.000	L1	10.5	32.92	60.00	Compliance

**AC 120V/60 Hz, Neutral**


Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.155000	---	34.97	9.000	N	10.3	20.76	55.73	Compliance
0.155000	53.33	---	9.000	N	10.3	12.40	65.73	Compliance
0.190000	---	33.47	9.000	N	10.3	20.57	54.04	Compliance
0.190000	48.25	---	9.000	N	10.3	15.79	64.04	Compliance
0.240000	---	25.39	9.000	N	10.3	26.71	52.10	Compliance
0.240000	39.43	---	9.000	N	10.3	22.67	62.10	Compliance
0.470000	---	25.01	9.000	N	10.3	21.50	46.51	Compliance
0.470000	34.83	---	9.000	N	10.3	21.68	56.51	Compliance
3.940000	---	20.17	9.000	N	10.5	25.83	46.00	Compliance
3.940000	31.11	---	9.000	N	10.5	24.89	56.00	Compliance
27.360000	---	23.32	9.000	N	10.5	26.68	50.00	Compliance
27.360000	28.83	---	9.000	N	10.5	31.17	60.00	Compliance

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS****Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

**EUT Setup**

**Below 1 GHz:**



**Above 1GHz:**



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.



## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP

Frequency Range	RBW	Video B/W	Duty cycle	Detector
1GHz – 25GHz	1MHz	3 MHz	Any	PK
	1MHz	10 Hz	>98%	Ave.
	1MHz	1/T	<98%	

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$


In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	24.1 °C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.2kPa

The testing was performed by Peter Jiang on 2016-11-19.

EUT operation mode: Transmitting

**30M-1GMHz**



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μV/m)	Margin (dB)
47.389500	23.25	QP	301.0	100.0	V	-14.81	8.44	40.00	31.56
57.232650	25.01	QP	274.0	100.0	V	-16.74	8.27	40.00	31.73
248.934650	41.84	QP	269.0	100.0	H	-12.13	29.71	46.00	16.29
384.828000	43.25	QP	250.0	100.0	H	-8.76	34.49	46.00	11.51
432.941050	45.04	QP	73.0	100.0	H	-7.70	37.34	46.00	8.66
746.586250	19.19	QP	57.0	100.0	V	-2.50	16.69	46.00	29.31

**1GMHz-25GHz**


Frequency	Receiver		Turntable	Rx Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/205/209	
	Reading	Detector		Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave.)	Degree	(cm)	(H/V)	(dB)	(dBμV/m)	(dB μV/m)	(dB)
Low Channel (2402 MHz)									
2402.00	103.47	PK	155	136	V	-3.04	100.43	/	/
2402.00	99.38	Ave	155	136	V	-3.04	96.34	/	/
2402.00	99.91	PK	212	149	H	-3.04	96.87	/	/
2402.00	95.88	Ave	212	149	H	-3.04	92.84	/	/
2390.00	42.31	PK	341	238	V	-3.04	39.27	74	34.73
2390.00	33.06	Ave	341	238	V	-3.04	30.02	54	23.98
2400.00	45.68	PK	23	182	V	-3.04	42.64	74	31.36
2400.00	35.13	Ave	23	182	V	-3.04	32.09	54	21.91
1598.30	33.36	PK	225	114	H	-6.11	27.25	74	46.75
1598.30	27.61	Ave	225	114	H	-6.11	21.50	54	32.50
4804.00	50.30	PK	202	140	V	7.16	57.46	74	16.54
4804.00	38.30	Ave	202	140	V	7.16	45.46	54	8.54
7206.00	42.65	PK	217	121	H	16	58.65	74	15.35
7206.00	32.45	Ave	217	121	H	16	48.45	54	5.55

Frequency	Receiver		Turntable	Rx Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/205/209	
	Reading	Detector		Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave.)	Degree	(cm)	(H/V)	(dB)	(dBμV/m)	(dB μV/m)	(dB)
Middle Channel (2440 MHz)									
2440.00	104.56	PK	53	210	V	-3.02	101.54	/	/
2440.00	99.80	Ave	53	210	V	-3.02	96.78	/	/
2440.00	98.70	PK	202	177	H	-3.02	95.68	/	/
2440.00	94.50	Ave	202	177	H	-3.02	91.48	/	/
1466.90	42.64	PK	33	146	V	-7.06	35.58	74	38.42
1466.90	31.85	Ave	33	146	V	-7.06	24.79	54	29.21
1702.40	45.81	PK	289	137	H	-5.39	40.42	74	33.58
1702.40	34.64	Ave	289	137	H	-5.39	29.25	54	24.75
4880.00	50.20	PK	190	216	V	7.28	57.48	74	16.52
4880.00	41.79	Ave	190	216	V	7.28	49.07	54	4.93
6677.00	37.65	PK	318	240	H	13.79	51.44	74	22.56
6677.00	32.66	Ave	318	240	H	13.79	46.45	54	7.55
7320.00	40.23	PK	202	137	H	16.37	56.60	74	17.40
7320.00	32.00	Ave	202	137	H	16.37	48.37	54	5.63

Frequency	Receiver		Turntable	Rx Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/205/209	
	Reading	Detector		Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave.)	Degree	(cm)	(H/V)	(dB)	(dBμV/m)	(dB μV/m)	(dB)
High Channel (2480MHz)									
2480.00	105.58	PK	304	121	V	-2.99	102.59	/	/
2480.00	100.81	Ave	304	121	V	-2.99	97.82	/	/
2480.00	101.62	PK	44	223	H	-2.99	98.63	/	/
2480.00	97.18	Ave	44	223	H	-2.99	94.19	/	/
2483.50	45.52	PK	98	236	V	-2.99	42.53	74	31.47
2483.50	32.78	Ave	98	236	V	-2.99	29.79	54	24.21
2563.00	46.91	PK	183	174	V	-2.58	44.33	74	29.67
2563.00	37.08	Ave	183	174	V	-2.58	34.50	54	19.50
4960.00	49.51	PK	234	103	H	7.40	56.91	74	17.09
4960.00	41.76	Ave	234	103	H	7.40	49.16	54	4.84
6654.10	23.11	PK	298	134	H	13.70	36.81	74	37.19
6654.10	16.31	Ave	298	134	H	13.70	30.01	54	23.99
7440.00	41.28	PK	299	213	H	16.89	58.17	74	15.83
7440.00	33.36	Ave	299	213	H	16.89	50.25	54	3.75

**Conducted Spurious Emissions at Antenna Port****Low Channel****Middle Channel**

# High Channel




**FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH****Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Peter Jiang on 2016-11-19.*


**Test Result:** Pass.

Please refer to the following tables and plots.

*EUT operation mode: Transmitting*


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	0.709	$\geq 0.5$
Middle	2440	0.709	$\geq 0.5$
High	2480	0.727	$\geq 0.5$

### Low Channel






## Middle Channel



## High Channel




## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

<b>Temperature:</b>	24.5°C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.2 kPa

The testing was performed by Peter Jiang on 2016-11-19.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Conducted Average Output Power Reading (dBm)	Corrected Factor $10\log(1/x)$ (dB)	Conducted Average Output Power (dBm)	Limit (dBm)	Result
Low	2402	5.81	5.54	0.00	5.54	30	Pass
Middle	2440	7.37	6.82	0.00	6.82	30	Pass
High	2480	7.63	7.24	0.00	7.24	30	Pass

Note: x is the duty cycle. As the follow plot:  $x=1$

Conducted Average Output Power = Reading + Corrected Factor

The reading value is reading from the test software.

Marker 1 [T1] 7.37 dBm

RBW 1 MHz RF Att 30 dB

Ref Lvl 20.5 dBm 1.623246 ms

VBW 3 MHz

SWT 30 ms

Unit dBm

0.5 dB Offset

Center 2.44 GHz 3 ms/

Date: 19.NOV.2016 16:32:45

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



**Test Data****Environmental Conditions**

<b>Temperature:</b>	24.1 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.3 kPa

*The testing was performed by Peter Jiang on 2016-11-19.*

**Test Result:** *Compliance*

Please refer to the following table and plots.

**Band Edge, Left Side****Band Edge, Right Side**

## **FCC §15.247(e) - POWER SPECTRAL DENSITY**

### **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### **Test Procedure**

According to KDB558074 D01 DTS Meas Guidance v03r05 sub-clause 10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.5 °C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.3 kPa


*The testing was performed by Peter Jiang on 2016-11-19.*

*EUT operation mode: Transmitting*


**Test Result:** Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-8.77	$\leq 8$
Middle	2440	-7.54	$\leq 8$
High	2480	-7.05	$\leq 8$


### Power Spectral Density , Low Channel



### Power Spectral Density , Middle Channel



### Power Spectral Density , High Channel



\*\*\*\*\* END OF REPORT \*\*\*\*\*