



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03  
Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20190700562E-02

**Applicant:** WIZNET CO.,LTD

**Address of Applicant:** 5F Humax Village,216 Hwangsaeul-ro,Bundang-gu,Seongnam-si,Gyeonggi-Do,Korea

**Manufacturer:** Shenzhen Yunlink Technology CO., Ltd

**Address of Manufacturer:** B3 Building, An'le Industiral Zone, Hangcheng Road, Gushu, Xixiang Town, Baoan District, Shenzhen City, Guangdong, P.R.China

**Factory:** Shenzhen Yunlink Technology CO., Ltd

**Address of Factory:** B3 Building, An'le Industiral Zone, Hangcheng Road, Gushu, Xixiang Town, Baoan District, Shenzhen City, Guangdong, P.R.China

**Equipment Under Test (EUT):**

**Product:** WiFi Module

**Model No.:** WizFi630S

**Brand Name:** Wiznet

**FCC ID:** 2AKKWWIZFI630S

**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06

**Date of Test:** 2019-06-22 to 2019-07-08

**Date of Issue:** 2019-07-08

**Test Result :** PASS\*

**Tested By:**

*Martin Lee*

(Martin Lee)

**Reviewed By:**

*Aaron Ma*

(Aaron Ma)

**Approved By:**

*Jack Ai*

( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 2 Version

### Revision History Of Report

| Report No.           | Version | Description    | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20190700562E-02 | Rev.01  | Initial report | 2019-07-08 |

### 3 Contents

|  | Page |
|--|------|
| 1 COVER PAGE.....                            | 1    |
| 2 VERSION .....                              | 2    |
| 3 CONTENTS .....                             | 3    |
| 4 RF EXPOSURE EVALUATION .....               | 4    |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT ..... | 4    |
| 4.1.1 Limits .....                           | 4    |
| 4.1.2 Test Procedure.....                    | 4    |
| 4.2 EUT RF EXPOSURE EVALUATION.....          | 5    |

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range<br>(MHz)                                       | Electric field<br>strength<br>(V/m) | Magnetic field<br>strength<br>(A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |
|--|-------------------------------------|-------------------------------------|--|-----------------------------|
| <b>(A) Limits for Occupational/Controlled Exposures</b>        |                                     |                                     |  |                             |
| 0.3–3.0 .....  | 614                                 | 1.63                                | *(100)                                 | 6                           |
| 3.0–30 .....   | 1842/f                              | 4.89/f                              | *(900/f <sup>2</sup> )                 | 6                           |
| 30–300 .....   | 61.4                                | 0.163                               | 1.0                                    | 6                           |
| 300–1500 .....   | .....                               | .....                               | f/300                                  | 6                           |
| 1500–100,000 .....   | .....                               | .....                               | 5                                      | 6                           |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                                     |                                     |  |                             |
| 0.3–1.34 .....   | 614                                 | 1.63                                | *(100)                                 | 30                          |
| 1.34–30 .....  | 824/f                               | 2.19/f                              | *(180/f <sup>2</sup> )                 | 30                          |
| 30–300 .....   | 27.5                                | 0.073                               | 0.2                                    | 30                          |
| 300–1500 .....   | .....                               | .....                               | f/1500                                 | 30                          |
| 1500–100,000 .....   | .....                               | .....                               | 1.0                                    | 30                          |

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 4.2 EUT RF Exposure Evaluation

### Calculated Result and Limit

| Mode                    | Frequency<br>(MHz) | output<br>power<br>(dBm) | output<br>power<br>(mW) | Target<br>power<br>(dBm) | Antenna gain |          | Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Limited<br>of<br>Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Test<br>Result |
|-------------------------|--------------------|--------------------------|-------------------------|--------------------------|--------------|----------|--|---|----------------|
|                         |                    |                          |                         |                          | (dBi)        | (Linear) |  |   |                |
| IEEE<br>802.11b         | 2412               | 16.01                    | 39.90                   | 16±1                     | 3.2          | 2.10     | 0.02088  | 1   | Compiles       |
|                         | 2437               | 16.05                    | 40.27                   | 16±1                     | 3.2          | 2.10     | 0.02088  | 1   | Compiles       |
|                         | 2462               | 15.41                    | 34.75                   | 15±1                     | 3.2          | 2.10     | 0.01663  | 1   | Compiles       |
| IEEE<br>802.11g         | 2412               | 11.54                    | 14.26                   | 11±1                     | 3.2          | 2.10     | 0.00660  | 1   | Compiles       |
|                         | 2437               | 11.72                    | 14.86                   | 11±1                     | 3.2          | 2.10     | 0.00660  | 1   | Compiles       |
|                         | 2462               | 11.54                    | 14.26                   | 11±1                     | 3.2          | 2.10     | 0.00660  | 1   | Compiles       |
| IEEE<br>802.11n<br>HT20 | 2412               | 8.09                     | 6.44                    | 8±1                      | 3.2          | 2.10     | 0.00332  | 1   | Compiles       |
|                         | 2437               | 8.32                     | 6.79                    | 8±1                      | 3.2          | 2.10     | 0.00332  | 1   | Compiles       |
|                         | 2462               | 8.81                     | 7.60                    | 8±1                      | 3.2          | 2.10     | 0.00332  | 1   | Compiles       |
| IEEE<br>802.11n<br>HT40 | 2422               | 5.47                     | 3.52                    | 5±1                      | 3.2          | 2.10     | 0.00166  | 1   | Compiles       |
|                         | 2437               | 5.22                     | 3.33                    | 5±1                      | 3.2          | 2.10     | 0.00166  | 1   | Compiles       |
|                         | 2452               | 5.34                     | 3.42                    | 5±1                      | 3.2          | 2.10     | 0.00166  | 1   | Compiles       |