

IC: 22302-MM002XUS Model: MM002-LS-US

RF Exposure Considerations as per RSS-102, clause 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10^{-2} $f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For the device, the parameters for consideration are as follows:

Frequency (MHz)	Maximum output power including tune-up tolerance (mW)	Minimum separation distance (cm)	Exemption Limits (W)	% of limit	Verdict
902-9028	166.0	20	1.37	12.11	Exempt from RF exposure evaluation

<u>Conclusion:</u> Therefore the device complies with Industry Canada RF radiation exposure limits for general population without RF exposure evaluation

Certified By

Laurent CHAPUS (Agent for this device)

SMEE – CE Mesures Rue de Taille ZI des Blanchisseries 38500 Voiron - France laurent.chapus@smee.fr IC Company Number: 9545A

Applicant for this device:

NEMEUS SAS
Gilles Ronco
President / CEO
36, Rue des Landelles
35510 Cessons Sevigne France
gilles.ronco@nemeus.fr
+33(0)6 51 72 32 30

TEL: 04 76 65 76 50

FAX: 04 76 66 18 30