# FCC RF EXPOSURE REPORT

Music Wave Limited

CAR AUDIO

Model Number: NA205

Additional Model:MW095CDBT

FCC ID: 2AKVT-MW-CDBT

Prepared By : Music Wave Limited
Room 07, 14/F.,Blk. B,Wing Cheung Ind. Bldg.,58-70 Kwai Cheong Road,Kwai Chung,Hong Kong,China

Prepared By :  EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City, GuangDong, China.

Tel: 86-769-83081888-808

Report Number : ESTE-R1701023
Date of Test     : December 21,2016~ January 13,2017
Date of Report : January 16,2017

# Maximum Permissible Exposure

## 1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

### (a)、Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm2) | Averaging Times｜E｜2，｜H｜2 or S (minutes) |
|---|---|---|---|---|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-10000 | | | 5 | 6 |

### (b)、Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm2) | Averaging Times｜E｜2，｜H｜2 or S (minutes) |
|---|---|---|---|---|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-10000 | | | 1.o | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

## 2、MPE Calculation Method

$E$ (V/m) = $(30*P*G)^{0.5}/d$　　　　Power Density: $Pd$ (W/m2) = $E^2/377$

$E$ = Electric Field (V/m)

$P$ = Peak RF output Power (W)

$G$ = EUT Antenna numeric gain (numeric)

$d$ = Separation distance between radiator and human body (m)

The formula can be changed to

$Pd$ = $(30*P*G) / (377*d^2)$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 3、**Calculated Result and Limit**

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) | Target power （dBm） | Antenna gain | | Power Density (S) (mW /cm2) | Limited of Power Density (S) (mW /cm2) | Test Result |
|---|---|---|---|---|---|---|---|---|---|
| | | | | | (dBi) | (Linear) | | | |
| GFSK | 2402 | 2.544 | 1.796 | 2±1 | 0 | 1 | 0.00040 | 1 | Complies |
| | 2441 | 3.033 | 2.010 | 3±1 | 0 | 1 | 0.00050 | 1 | Complies |
| | 2480 | 3.716 | 2.353 | 3±1 | 0 | 1 | 0.00050 | 1 | Complies |
| 8-DPSK | 2402 | 2.470 | 1.766 | 2±1 | 0 | 1 | 0.00040 | 1 | Complies |
| | 2441 | 2.955 | 1.975 | 2±1 | 0 | 1 | 0.00040 | 1 | Complies |
| | 2480 | 3.660 | 2.323 | 3±1 | 0 | 1 | 0.00050 | 1 | Complies |