## **FCC RF EXPOSURE REPORT**

EUT	Building Automation System					
Frequency band						
(Operating)	WLAN: 5.180GHz ~ 5.240GHz					
	☐ WLAN: 5.190GHz ~ 5.230GHz					
Doving actoriory	☐ Portable (<20cm separation)					
Device category						
	☐ Occupational/Controlled exposure (S = 5mW/cm²)					
Exposure classification	☐ General Population/Uncontrolled exposure					
	$(S=1 \text{mW/cm}^2)$					
Antenna diversity	☐Single antenna					
	☐ Tx diversity					
	Rx diversity					
Max. output power	26.98dBm (498.884mW)					
Antenna gain (Max)	a gain (Max) 2dBi(Numeric gain:1.58)					
Evaluation applied	☐ SAR Evaluation					
	N/A N/A					
Note:						
4. The manifestory and i						
• •	rer i <u>s 26.98dBm (498.884mW)</u> at <u>2422MHz</u> (with <u>numeric 1.58 antenna gain</u> .)					
DTS device is not subject to routine RF evaluation: MPF estimate is used to justify the compliance						

Report No.: DEFI1704060

- For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

Cerpass Technology Corp. Issued date : May 16, 2017

> Page No. : 1 of 2

## **TEST RESULTS**

No non-compliance noted.

## Calculation

Given

$$E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

*d* = *Distance in meters* 

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and  $d(cm) = d(m) / 100$ 

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$
 Equation 1

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW / cm^2$ 

## **Maximum Permissible Exposure**

Modulation Mode	Frequency band (MHz)	Peak output power(dBm)	Peak output power(mW)	Antenna Gain (dBi)	Antenna gain ( <i>Numeric</i> )	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
802.11b	2412-2462	19.66	92.4698174	2	1.58489319	20	0.0291644	1
802.11g	2412-2462	25.55	358.921935	2	1.58489319	20	0.11320173	1
802.11n HT20	2412-2462	26.47	443.608644	2	1.58489319	20	0.13991139	1
802.11n HT40	2422-2452	26.98	498.884487	2	1.58489319	20	0.15734505	1

Issued date : May 16, 2017

Page No. : 2 of 2

Report No.: DEFI1704060