

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Passive Coach
Model Name	PC-01
FCC ID	2AL4B-PC01

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula :

According to the report AGC09648170402FE03,
 $P_t=9.774\text{dBm}=9.49\text{mW}$

The result for RF exposure evaluation

$\text{SAR} = (9.49\text{mW} / 5\text{mm}) \cdot [\sqrt{0.9267(\text{GHz})}] = 1.83 < 3.0$ for 1-g SAR

4. CONCLUSION

The SAR evaluation is not required.