

# FCC TEST REPORT

For

Shenzhen Welldy Technology Co., Limited
Bluetooth speaker

Model No.: OZ-X7

Prepared For : Shenzhen Welldy Technology Co., Limited

Address 2F, Building 6, Sinpool Pioneer Park, Shangtang Intersection, Gongye

Road, Longhua new District, Shenzhen, China

Prepared For : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan

District, Shenzhen, Guangdong, China

Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : R0217100009W

Date of Test : Oct. 11~Nov. 22, 2017

Date of Report : Nov. 22, 2017



# **Contents**

1. General Information.	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	5
1.4. Description of Test Modes	6
1.5. List of channels	7
1.6. Description Of Test Setup	8
1.7. Test Equipment List	9
1.8. Measurement Uncertainty	10
1.9. Description of Test Facility	10
2. Summary of Test Results	11
3. Conducted Emission Test	12
3.1. Test Standard and Limit	12
3.2. Test Setup	12
3.3. Test Procedure	12
3.4. Test Data	
4. Radiation Spurious Emission and Band Edge	17
4.1. Test Standard and Limit	17
4.2. Test Setup.	17
4.3. Test Procedure	18
4.4. Test Data	19
5. Maximum Peak Output Power Test	26
5.1. Test Standard and Limit	26
5.2. Test Setup	26
5.3. Test Procedure	26
5.4. Test Data	26
6. 20DB Occupy Bandwidth Test	30
6.1. Test Standard	30
6.2. Test Setup	30
6.3. Test Procedure	30
6.4. Test Data	30
7. Carrier Frequency Separation Test	34
7.1. Test Standard and Limit	34
7.2. Test Setup	34
7.3. Test Procedure	34
7.4. Test Data	34
8. Number of Hopping Channel Test	38
8.1. Test Standard and Limit	38
8.2. Test Setup	38
8.3. Test Procedure	
8.4. Test Data	38
9. Dwell Time Test	40



9.1. Test Standard and Limit	40
9.2. Test Setup	40
9.3. Test Procedure	40
9.4. Test Data	40
10. 100kHz Bandwidth of Frequency Band Edge Requirement	44
10.1. Test Standard and Limit	44
10.2. Test Setup	44
10.3. Test Procedure	
10.4. Test Data	44
11. Antenna Requirement	49
11.1. Test Standard and Requirement.	49
11.2. Antenna Connected Construction	
APPENDIX I TEST SETUP PHOTOGRAPH	50
APPENDIX II EXTERNAL PHOTOGRAPH	52
APPENDIX III INTERNAL PHOTOGRAPH	56



# TEST REPORT

Applicant : Shenzhen Welldy Technology Co., Limited

Manufacturer : Shenzhen Welldy Technology Co., Limited

Product Name : Bluetooth speaker

Model No. : OZ-X7

Trade Mark : N/A

Rating(s) : Input DC 5V, 1A (Battery DC 3.7V, 2200mAh)

Test Standard(s) : FCC Part15 Subpart C 2016, Section 15.247

**Test Method(s)** : **ANSI C63.10: 2013** 

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test:	Oct. 11~Nov. 22, 201/
Prepared by :	Winkey Wang
	(Tested Engineer / Winkey Wang)
Reviewer:	Tangey. T.
	(Project Manager / Tangcy. T)
: Approved & Authorized Signer:	Ton Chen
_	(Manager / Tom Chen)



## 1. General Information

### 1.1. Client Information

Applicant	:	Shenzhen Welldy Technology Co., Limited		
A 11		2F, Building 6, Sinpool Pioneer Park, Shangtang Intersection, Gongye Road,		
Address	•	Longhua new District, Shenzhen, China		
Manufacturer	:	Shenzhen Welldy Technology Co., Limited		
Address		2F, Building 6, Sinpool Pioneer Park, Shangtang Intersection, Gongye Road,		
		Longhua new District, Shenzhen, China		

## 1.2. Description of Device (EUT)

Product Name	:	Bluetooth speaker			
Model No.	:	OZ-X7			
Trade Mark	:	N/A			
Test Power Supply	:	AC 120V, 60Hz for adapter/AC 2 DC 3.7V Battery inside	AC 120V, 60Hz for adapter/AC 240V, 60Hz for adapter DC 3.7V Battery inside		
Product :		Operation Frequency:	2402MHz~2480MHz		
		Transfer Rate:	1/2/3 Mbits/s		
		Number of Channel:	79 Channels		
		Modulation Type:	GFSK, π/4-DQPSK, 8-DPSK		
		Antenna Type:	PCB Antenna		
		Antenna Gain(Peak):	-0.58 dBi		

**Remark:** 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

## 1.3. Auxiliary Equipment Used During Test

Adapter	:	Manufacturer: ZTE	
		M/N: STC-A2050I1000USBA-C	
		S/N: 201202102100876	
		Input: 100-240V~50/60Hz 0.3A	
		Output: DC 5V, 1000mA	



## 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	СН39
Mode 3	CH78
Mode 4	Keeping TX mode

	For Conducted Emission
Final Test Mode	Description
Mode 4	Keeping TX mode

For Radiated Emission				
Final Test Mode	Description			
Mode 1	CH00			
Mode 2	CH39			
Mode 3	CH78			

#### Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The data rate was set in 1Mbps for radiated emission due to the highest RF output power.



## 1.5. List of channels

Channel	Freq.								
	(MHz)								
00	2402	17	2419	34	2436	51	2453	68	2470
01	2403	18	2420	35	2437	52	2454	69	2471
02	2404	19	2421	36	2438	53	2455	70	2472
03	2405	20	2422	37	2439	54	2456	71	2473
04	2406	21	2423	38	2440	55	2457	72	2474
05	2407	22	2424	39	2441	56	2458	73	2475
05	2408	23	2425	40	2442	57	2459	74	2476
07	2409	24	2426	41	2443	58	2460	75	2477
08	2410	25	2427	42	2444	59	2461	76	2478
09	2411	26	2428	43	2445	60	2462	77	2479
10	2412	27	2429	44	2446	61	2463	78	2480
11	2413	28	2430	45	2447	62	2464		
12	2414	29	2431	46	2448	63	2465		
13	2415	30	2432	47	2449	64	2466		
14	2416	31	2433	48	2450	65	2467		
15	2417	32	2434	49	2451	66	2468		
16	2418	33	2435	50	2452	67	2469		


## Note:

- 1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
- 2. EUT built-in battery-powered, fully-charged battery use of the test battery.




## 1.6. Description Of Test Setup

CE



RE





## 1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	May 27, 2017	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	May 27, 2017	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	May 27, 2017	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	May 27, 2017	1 Year
5.	Spectrum Analysis	Agilent	N9038A	MY53227295	May 27, 2017	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	May 27, 2017	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	May 27, 2017	1 Year
8.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	May 31, 2017	1 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	May 31, 2017	1 Year
10.	Loop Antenna	Schwarzbeck	HFH2-Z2	100047	Apr. 03, 2017	1 Year
11.	Horn Antenna	Schewarzbeck	BBHA9170	9170-375	May 27, 2017	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	May 27, 2017	1 Year
13.	Pre-amplifier	SKET Electronic	BK1G40G50 A	KD25352	May 27, 2017	1 Year
14.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
15.	Power Sensor	DAER	RPR3006W	15I00041SN045	May 27, 2017	1 Year
16.	Power Sensor	DAER	RPR3006W	15I00041SN046	May 27, 2017	1 Year
17.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	May 27, 2017	1 Year
18.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	May 27, 2017	1 Year
19.	Signal Generator	Agilent	E4421B	MY41000743	May 27, 2017	1 Year
20.	DC Power supply	IVYTECH	IV6003	1601D6030007	May 26, 2017	1 Year
21.	TEMP&HUMI PROGRAMMABLE CHAMBER	Sertep	ZJ-HWHS80 B	ZJ-17042804	Mar. 03, 2017	1 Year



## 1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 4.1 dB (Horizontal)
		Ur = 4.3 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4dB

## 1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

#### ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

#### **Test Location**

All Emissions tests were performed at

Shenzhen Anbotek Compliance Laboratory Limited.

at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China



# 2. Summary of Test Results

Standard Section	Test Item	Result			
15.203/15.247(c)	Antenna Requirement	PASS			
15.207	Conducted Emission	PASS			
15.205/15.209	Spurious Emission	PASS			
15.247(b)(1)	Conducted Peak Output Power	PASS			
15.247(a)(1)	20dB Occupied Bandwidth	PASS			
15.247(a)(1)	Carrier Frequencies Separation	PASS			
15.247(a)(1)	Hopping Channel Number	PASS			
15.247(a)(1)	Dwell Time	PASS			
15.247(d)	Band Edge	PASS			
Remark: "N/A" is an abbreviation for Not Applicable.					



## 3. Conducted Emission Test


#### 3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207					
	Eraguanav	Maximum RF L	ine Voltage (dBuV)			
	Frequency	Quasi-peak Level	Average Level			
Test Limit	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *			
	500kHz~5MHz	56	46			
	5MHz~30MHz	60	50			

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequency.

## 3.2. Test Setup



## 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

#### 3.4. Test Data

Please to see the following pages




Test Site: 1# Shielded Room Operating Condition: Keeping TX mode

Test Specification: AC 120V, 60Hz for adapter

Comment: Live Line

Tem.:25℃ Hum.:50%






Test Site: 1# Shielded Room Operating Condition: Keeping TX mode

Test Specification: AC 120V, 60Hz for adapter

Comment: Neutral Line

Tem.:25°C Hum.:50%






Test Site: 1# Shielded Room Operating Condition: Keeping TX mode

Test Specification: AC 240V, 60Hz for adapter

Comment: Live Line

Tem.:25℃ Hum.:50%






Test Site: 1# Shielded Room Operating Condition: Keeping TX mode

Test Specification: AC 240V, 60Hz for adapter

Comment: Neutral Line

Tem.:25°C Hum.:50%





## 4. Radiation Spurious Emission and Band Edge

### 4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205							
	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)			
	0.009MHz~0.490MHz	2400/F(kHz)	-	<u></u>	300			
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30			
	1.705MHz-30MHz	30	1	-	30			
Test Limit	30MHz~88MHz	100	40.0	Quasi-peak	3			
	88MHz~216MHz	150	43.5	Quasi-peak	3			
	216MHz~960MHz	200	46.0	Quasi-peak	3			
	960MHz~1000MHz	500	54.0	Quasi-peak	3			
	Above 1000MHz	500	54.0	Average	3			
	AUGVE TOUGHTIZ	-	74.0	Peak	3			

#### Remark:

- (1) The lower limit shall apply at the transition frequency.
- (2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

## 4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

## 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying



aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

#### 4.4. Test Data

#### **PASS**

During the test, pre-scan the GFSK,  $\pi/4$ QPSK, 8DPSK modulation, and found the GFSK modulation which is worse case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.




#### Test Results (30~1000MHz)

Job No.: 0217100009W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH

Standard: FCC PART 15C Power Source: DC 3.7V Battery inside

Test Mode: TX Mode Polarization: Horizontal






#### Test Results (30~1000MHz)

Job No.: 0217100009W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH

Standard: FCC PART 15C Power Source: DC 3.7V Battery inside

Test Mode: TX Mode Polarization: Vertical





## **Test Results (1GHz-25GHz)**

Test Mode: 0	GFSK			Test	channel: Lowe	est		
				Peak Value				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804.00	37.87	34.04	6.58	34.09	44.40	74.00	-29.60	V
7206.00	32.21	37.11	7.73	34.50	42.55	74.00	-31.45	V
9608.00	31.80	39.31	9.23	34.79	45.55	74.00	-28.45	V
12010.00	*					74.00		V
14412.00	*					74.00		V
4804.00	42.28	34.04	6.58	34.09	48.81	74.00	-25.19	Н
7206.00	34.01	37.11	7.73	34.50	44.35	74.00	-29.65	Н
9608.00	31.28	39.31	9.23	34.79	45.03	74.00	-28.97	Н
12010.00	*					74.00		Н
14412.00	*					74.00		Н
			A	verage Valu	e			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804.00	26.58	34.04	6.58	34.09	33.11	54.00	-20.89	V
7206.00	20.83	37.11	7.73	34.50	31.17	54.00	-22.83	V
9608.00	19.87	39.31	9.23	34.79	33.62	54.00	-20.38	V
12010.00	*					54.00		V
14412.00	*					54.00		V
4804.00	30.87	34.04	6.58	34.09	37.40	54.00	-16.60	Н
7206.00	23.04	37.11	7.73	34.50	33.38	54.00	-20.62	Н
9608.00	19.65	39.31	9.23	34.79	33.40	54.00	-20.60	Н
12010.00	*					54.00		Н
14412.00	*					54.00		Н



## **Test Results (1GHz-25GHz)**

Test Mode: 0	GFSK			Test	channel: Midd	le		
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4882.00	36.17	34.38	6.69	34.09	43.15	74.00	-30.85	V
7323.00	31.07	37.22	7.78	34.53	41.54	74.00	-32.46	V
9764.00	30.80	39.46	9.35	34.80	44.81	74.00	-29.19	V
12205.00	*					74.00		V
14646.00	*					74.00		V
4882.00	40.22	34.38	6.69	34.09	47.20	74.00	-26.80	Н
7323.00	32.73	37.22	7.78	34.53	43.20	74.00	-30.80	Н
9764.00	30.11	39.46	9.35	34.80	44.12	74.00	-29.88	Н
12205.00	*					74.00		Н
14646.00	*					74.00		Н
			A	verage Valu	e			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4882.00	25.20	34.38	6.69	34.09	32.18	54.00	-21.82	V
7323.00	19.89	37.22	7.78	34.53	30.36	54.00	-23.64	V
9764.00	19.04	39.46	9.35	34.80	33.05	54.00	-20.95	V
12205.00	*					54.00		V
14646.00	*					54.00		V
4882.00	29.31	34.38	6.69	34.09	36.29	54.00	-17.71	Н
7323.00	21.99	37.22	7.78	34.53	32.46	54.00	-21.54	Н
9764.00	18.68	39.46	9.35	34.80	32.69	54.00	-21.31	Н
12205.00	*					54.00		Н
14646.00	*					54.00		Н



### **Test Results (1GHz-25GHz)**

Test Mode: 0	Test channel: Highest							
	Peak Value							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	35.81	34.72	6.79	34.09	43.23	74.00	-30.77	V
7440.00	30.84	37.34	7.82	34.57	41.43	74.00	-32.57	V
9920.00	30.58	39.62	9.46	34.81	44.85	74.00	-29.15	V
12400.00	*					74.00		V
14880.00	*					74.00		V
4960.00	39.79	34.72	6.79	34.09	47.21	74.00	-26.79	Н
7440.00	32.46	37.34	7.82	34.57	43.05	74.00	-30.95	Н
9920.00	29.87	39.62	9.46	34.81	44.14	74.00	-29.86	Н
12400.00	*					74.00		Н
14880.00	*					74.00		Н
			A	verage Valu	e			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	24.95	34.72	6.79	34.09	32.37	54.00	-21.63	V
7440.00	19.72	37.34	7.82	34.57	30.31	54.00	-23.69	V
9920.00	18.89	39.62	9.46	34.81	33.16	54.00	-20.84	V
12400.00	*					54.00		V
14880.00	*					54.00		V
4960.00	29.01	34.72	6.79	34.09	36.43	54.00	-17.57	Н
7440.00	21.80	37.34	7.82	34.57	32.39	54.00	-21.61	Н
9920.00	18.50	39.62	9.46	34.81	32.77	54.00	-21.23	Н
12400.00	*					54.00		Н
14880.00	*					54.00		Н

#### Remark

- 1. During the test, pre-scan the GFSK,  $\pi/4$ QPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
- 2. Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 3. "\*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



## Radiated Band Edge:

Test Mode: 0	Test Mode: GFSK					est		
	Peak Value							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2390.00	44.49	29.15	3.41	34.01	43.04	74.00	-30.96	Н
2400.00	61.51	29.16	3.43	34.01	60.09	74.00	-13.91	Н
2390.00	45.20	29.15	3.41	34.01	43.75	74.00	-30.25	V
2400.00	63.72	29.16	3.43	34.01	62.30	74.00	-11.70	V
			A	verage Valu	e			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2390.00	34.68	29.15	3.41	34.01	33.23	54.00	-20.77	Н
2400.00	46.01	29.16	3.43	34.01	44.59	54.00	-9.41	Н
2390.00	34.74	29.15	3.41	34.01	33.29	54.00	-20.71	V
2400.00	47.81	29.16	3.43	34.01	46.39	54.00	-7.61	V

Test Mode: 0	Test Mode: GFSK					est		
				Peak Value				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2483.50	46.79	29.28	3.53	34.03	45.57	74.00	-28.43	Н
2500.00	45.65	29.30	3.56	34.03	44.48	74.00	-29.52	Н
2483.50	47.90	29.28	3.53	34.03	46.68	74.00	-27.32	V
2500.00	46.81	29.30	3.56	34.03	45.64	74.00	-28.36	V
			A	verage Value	e			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2483.50	37.53	29.28	3.53	34.03	36.31	54.00	-17.69	Н
2500.00	35.30	29.30	3.56	34.03	34.13	54.00	-19.87	Н
2483.50	38.87	29.28	3.53	34.03	37.65	54.00	-16.35	V
2500.00	35.35	29.30	3.56	34.03	34.18	54.00	-19.82	V

#### Remark:

- 1. During the test, pre-scan the GFSK,  $\pi/4$ QPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
- 2. Level = Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor



## 5. Maximum Peak Output Power Test

### 5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W or 125 mW

## 5.2. Test Setup



#### **5.3. Test Procedure**

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
- 2. Spectrum Setting:

RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

 $VBW \ge RBW$ 

Sweep = auto

Detector function = peak

Trace = max hold


#### 5.4. Test Data

Test Item	:	Max. peak output power	Test Mode :	CH Low ~ CH High
Test Voltage	:	DC 3.7V Battery inside	Temperature :	24℃
Test Result	:	PASS	Humidity :	55%RH


Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results	Modulation
2402	-7.483	30	PASS	BDR
2441	-6.977	30	PASS	BDR
2480	-6.085	30	PASS	BDR
2402	-7.712	20.96	PASS	EDR
2441	-7.239	20.96	PASS	EDR
2480	-6.378	20.96	PASS	EDR

Remark: The EDR was tested on  $(\pi/4DQPSK, 8DPSK)$  modes, only the worst data of (8DPSK) is attached in the following pages.





Test Mode: BDR---Low




Test Mode: BDR---Middle






Test Mode: BDR---High




Test Mode: EDR---Low





Test Mode: EDR---Middle



Test Mode: EDR---High




## 6. 20DB Occupy Bandwidth Test

#### 6.1. Test Standard

Test Standard	FCC Part15 C Section 15.247 (a)(1)
---------------	------------------------------------

### 6.2. Test Setup



### 6.3. Test Procedure

Using the following spectrum analyzer settings:

- 1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
- 2. Set the RBW = 30 kHz.
- 3. Set the VBW = 100 kHz.
- 4. Sweep time = auto couple.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

#### 6.4. Test Data

Test Item : 20dB BW Test Mode : CH Low ~ CH High

Test Voltage : DC 3.7V Battery inside Temperature :  $24^{\circ}$ C Test Result : PASS Humidity :  $55^{\circ}$ RH


Channel	Frequency(MHz)	20dB Down BW(kHz)	Modulation Mode
Low	2402	932.9	BDR
Middle	2441	933.5	BDR
High	2480	933.6	BDR
Low	2402	1269.0	EDR
Middle	2441	1269.0	EDR
High	2480	1266.0	EDR

Remark: The EDR was tested on  $(\pi/4DQPSK, 8DPSK)$  modes, only the worst data of (8DPSK) is attached in the following pages.






Test Mode: BDR---Low




Test Mode: BDR---Middle





Test Mode: BDR---High




Test Mode: EDR---Low





Test Mode: EDR---Middle



Test Mode: EDR---High



# 7. Carrier Frequency Separation Test

## 7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)	
Test Limit	>25KHz or >two-thirds of the 20 dB bandwidth	

### 7.2. Test Setup



## 7.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

- 1. Span= Wide enough to capture the peaks of two adjacent channels
- 2. Set the RBW = 30 kHz.
- 3. Set the VBW = 100 kHz.
- 4. Sweep time = auto couple.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

#### 7.4. Test Data

Test Item :	Frequency Separa	tion Test Mode	:	CH Low ~ CH High
Test Voltage :	DC 3.7V Battery	inside Temperature	:	24℃
Test Result :	PASS	Humidity	:	55%RH

Channel	Frequency	Separation Read	Limit	Modulation
	(MHz)	Value (kHz)	(kHz)	Mode
Low	2402	1000	932.9	BDR
Middle	2441	1000	933.5	BDR
High	2480	1000	933.6	BDR
Low	2402	1000	846.0	EDR
Middle	2441	1000	846.0	EDR
High	2480	1000	844.0	EDR

#### Remark

- 1. The limit of mode (EDR) is 2/3 of 20dB BW;
- 2. The EDR was tested on ( $\pi$ /4DQPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages.





Test Mode: BDR---Low



Test Mode: BDR---Middle





Test Mode: BDR---High



Test Mode: EDR---Low





Test Mode: EDR---Middle



Test Mode: EDR---High




# 8. Number of Hopping Channel Test

#### 8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>15 channels

## 8.2. Test Setup



## 8.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:


- 1. Span= the frequency band of operation
- 2. Set the RBW = 100kHz.
- 3. Set the VBW = 300kHz.
- 4. Sweep time = auto couple.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

#### 8.4. Test Data


Test Item : Number of Hopping Frequency Test Mode :  $CH Low \sim CH High$  Test Voltage : DC 3.7V Battery inside Temperature :  $24^{\circ}C$  Test Result : PASS Humidity :  $55^{\circ}RH$ 

Hopping Channel Frequency	Quantity of Hopping Channel	Quantity of Hopping Channel	
Range			
2402-2480MHz	79	>15	





**BDR Mode** 



EDR Mode




## 9. Dwell Time Test

#### 9.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	0.4 sec

### 9.2. Test Setup



## 9.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span= zero span, centered on a hopping channel
- 2. Set the RBW = 1 MHz.
- 3. Set the VBW = 1 MHz.
- 4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

#### 9.4. Test Data


Test Item : Time of Occupancy Test Mode : CH Low ~ CH High

Test Voltage : DC 3.7V Battery inside Temperature :  $24^{\circ}$ C Test Result : PASS Humidity :  $55^{\circ}$ RH


Package Type	Pulse width (ms)	Time slot length(ms)	Dwell time (ms)	Limit (s)	Modulation
DH1	0.368	time slot length *1600/2 /79 * 31.6	117.76	0.4	BDR
DH3	1.625	time slot length *1600/4 /79 * 31.6	260.00	0.4	BDR
DH5	2.864	time slot length *1600/6 /79 * 31.6	305.49	0.4	BDR
3DH1	0.376	time slot length *1600/2 /79 * 31.6	120.32	0.4	EDR
3DH3	1.625	time slot length *1600/4 /79 * 31.6	260.00	0.4	EDR
3DH5	2.880	time slot length *1600/6 /79 * 31.6	307.20	0.4	EDR

Remark: The EDR was tested on ( $\pi/4$ DQPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages.






Test Mode: BDR---DH1




Test Mode: BDR---DH3






Test Mode: BDR—DH5




Test Mode: EDR---3DH1





Test Mode: EDR---3DH3



Test Mode: EDR—3DH5



# 10. 100kHz Bandwidth of Frequency Band Edge Requirement

#### 10.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

## 10.2. Test Setup



#### 10.3. Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:

- 1. Set the RBW = 100kHz.
- 2. Set the VBW = 300kHz.
- 3. Sweep time = auto couple.
- 4. Detector function = peak.
- 5. Trace mode =  $\max$  hold.
- 6. Allow trace to fully stabilize.

## 10.4. Test Data


Test Item : Band edge : CH Low ~ CH High

Test Voltage : DC 3.7V Battery inside Temperature : 24°C
Test Result : PASS Humidity : 55%RH


Remark: The EDR was tested on ( $\pi$ /4DQPSK, 8DPSK) modes, only the worst data of ( $\pi$ /4DQPSK) is attached in the following pages.



### For Hopping Mode




BDR mode




EDR mode



### For Non-Hopping Mode




BDR mode -- Lowest




BDR mode -- Highest



### For Non-Hopping Mode




EDR mode -- Lowest



EDR mode -- Highest



#### Conducted Emission Method





System Display Settings

Stop 25.00 GH Sweep 2.386 s (601 pt

System Display Settings



# 11. Antenna Requirement

## 11.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

## 11.2. Antenna Connected Construction

The bluetooth antenna is PCB antenna which permanently attached, and the best case gain of the antenna is -0.58 dBi. It complies with the standard requirement.






## **APPENDIX I -- TEST SETUP PHOTOGRAPH**

Photo of Conducted Emission Measurement



Photo of Radiation Emission Test









## **APPENDIX II -- EXTERNAL PHOTOGRAPH**
























## **APPENDIX III -- INTERNAL PHOTOGRAPH**







