

[Barrier Sensor User Manual]

1. Contents

- Product specification
- Install Android App
- Product and Account registration
- Create User Name
- Moisture and TEWL Measurement
- Error measures
- Contact

2. Barrier Sensor Device Specification

Product Name	gpskin Barrier Sensor
Sensor	Moisture and Temperature/Humidity
Interface	Bluetooth 4.0(BLE)
Height	32 * 160 * 32 mm
Weight	42g(within Battery)
Power	3V lithium Coin(220mAh)
Specification	Low power 0.653milliwatt hr/cc

3. Function description



Company Confidential

FCC Information to User

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution

Modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

FCC Compliance Information : This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation