

FCC SAR Measurement and Test Report

For

SZZT ELECTRONICS CO.,LTD

SZZT Industrial Park,NO.3TongguanRoad,Guangming New District,

Shenzhen, Guangdong, China

FCC ID: 2AL7RKS8223

| | |
|--------------------------------------|--|
| FCC Rules: | FCC Part 2.1093 ANSI / IEEE C95.1 :2005 <u>ANSI / IEEE C95.3 :2002</u> |
| Product Description: | <u>Smart wireless pos</u> |
| Tested Model: | <u>KS8223</u> |
| Report No.: | <u>STR17048102H</u> |
| Tested Date: | <u>2017-05-15 to 2017-05-22</u> |
| Issued Date: | <u>2017-05-23</u> |
| Tested By: | <u>Lucy Wei / Engineer</u> <i>Lucy Wei</i> |
| Reviewed By: | <u>Silin Chen / EMC Manager</u> <i>Silin Chen</i> |
| Approved & Authorized By: | <u>Jandy So / PSQ Manager</u> <i>Jandy So</i> |
| Prepared By: | |

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. General Information | 3 |
| 1.1 Product Description for Equipment Under Test (EUT)..... | 3 |
| 1.2 Test Standards | 6 |
| 1.3 Test Methodology | 6 |
| 1.4 Test Facility | 6 |
| 2. Summary of Test Results | 7 |
| 3. Specific Absorption Rate (SAR)..... | 8 |
| 3.1 Introduction..... | 8 |
| 3.2 SAR Definition | 8 |
| 4. SAR Measurement System..... | 9 |
| 4.1 The Measurement System | 9 |
| 4.2 Probe | 9 |
| 4.3 Probe Calibration Process..... | 11 |
| 4.4 Phantom | 12 |
| 4.5 Device Holder..... | 12 |
| 4.6 Test Equipment List..... | 13 |
| 5. Tissue Simulating Liquids..... | 14 |
| 5.1 Composition of Tissue Simulating Liquid..... | 14 |
| 5.2 Tissue Dielectric Parameters for Head and Body Phantoms..... | 15 |
| 5.3 Tissue Calibration Result..... | 16 |
| 6. SAR Measurement Evaluation | 17 |
| 6.1 Purpose of System Performance Check..... | 17 |
| 6.2 System Setup | 17 |
| 6.3 Validation Results..... | 18 |
| 7. EUT Testing Position | 19 |
| 7.1 EUT Antenna Position | 19 |
| 7.2 EUT Testing Position..... | 20 |
| 8. SAR Measurement Procedures..... | 21 |
| 8.1 Measurement Procedures | 21 |
| 8.2 Spatial Peak SAR Evaluation | 21 |
| 8.3 Area & Zoom Scan Procedures..... | 22 |
| 8.4 Volume Scan Procedures..... | 22 |
| 8.5 SAR Averaged Methods | 22 |
| 8.6 Power Drift Monitoring | 22 |
| 9. SAR Test Result | 23 |
| 9.1 Conducted RF Output Power | 23 |
| 9.2 Test Results for Standalone SAR Test..... | 39 |
| 9.3 Simultaneous Multi-band Transmission SAR Analysis | 43 |
| 10. Measurement Uncertainty | 48 |
| 10.1 Uncertainty for EUT SAR Test..... | 48 |
| 10.2 Uncertainty for System Performance Check..... | 49 |
| Annex A. Plots of System Performance Check | 51 |
| Annex B. Plots of SAR Measurement | 57 |
| Annex C. EUT Photos | 86 |
| Annex D. Test Setup Photos | 89 |
| Annex E. Calibration Certificate..... | 93 |

1. General Information

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: SZZT ELECTRONICS CO.,LTD
Address of applicant: SZZT Industrial Park,NO.3TongguanRoad,Guangming New District, Shenzhen, Guangdong ,China

Manufacturer: SZZT ELECTRONICS CO.,LTD
Address of manufacturer: SZZT Industrial Park,NO.3TongguanRoad,Guangming New District, Shenzhen, Guangdong, China

| General Description of EUT | |
|--|--------------------|
| Product Name: | Smart wireless pos |
| Brand Name: | SZZT |
| Model No.: | KS8223 |
| Adding Model(s): | / |
| Hardware version: | KS8223_MB_V2.1.2 |
| Software version: | V1.0.0 |
| Rated Voltage: | DC 3.7V by battery |
| Battery Capacity: | 5000mAh |
| <i>The EUT Main board support GSM850/PCS1900,WCDMA Band 2/5, LTE Band 2/5 Smart wireless pos . The Smart wireless pos is not support GSM voice mode. It is equipped with GPRS/EDGE class 12 for GSM850 /PCS1900, GPS,WIFI, Bluetooth and NFC functions. For more information see the following datasheet</i> | |
| <i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i> | |

| Technical Characteristics of EUT | |
|----------------------------------|--|
| 2G | |
| Support Networks: | GPRS, EDGE |
| Support Band: | GSM850/PCS1900 |
| Uplink Frequency: | GPRS/EDGE 850: 824~849MHz GPRS/EDGE 1900: 1850~1910MHz |
| Downlink Frequency: | GPRS/EDGE 850: 869~894MHz GPRS/EDGE 1900: 1930~1990MHz |
| Max RF Output Power: | GSM850: 32.39dBm, GSM1900: 28.74dBm EDGE850: 24.81dBm, EDGE1900: 24.52dBm |
| Type of Modulation: | GMSK, 8PSK |
| Type of Antenna: | Integral Antenna |
| Antenna Gain: | 1.0dBi |
| GPRS/EDGE Class: | Class 12 |
| 3G | |
| Support Networks: | WCDMA, HSDPA, HSUPA |
| Support Band: | WCDMA Band 2, WCDMA Band 5 |
| Uplink Frequency: | WCDMA Band 2: 1850~1910MHz WCDMA Band 5: 824~849MHz |
| Downlink Frequency: | WCDMA Band 2: 1930~1990MHz WCDMA Band 5: 869~894MHz |
| RF Output Power: | WCDMA Band 2: 22.33dBm, WCDMA Band 5: 22.21dBm |
| Type of Modulation: | BPSK |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | 1.0dBi |
| WIFI | |
| Support Standards: | 802.11b, 802.11g, 802.11n |
| Frequency Range: | 2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40) |
| AV Output Power: | 15.0dBm (Conducted) |
| Type of Modulation: | CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM |
| Data Rate: | 1-11Mbps, 6-54Mbps, up to 150Mbps |
| Quantity of Channels: | 11/7 |
| Channel Separation: | 5MHz |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | 1.0dBi |
| Bluetooth | |
| Bluetooth Version: | V4.0 |
| Frequency Range: | 2402-2480MHz |
| AV Output Power: | 4.972dBm (Conducted) |
| Data Rate: | 1Mbps, 2Mbps, 3Mbps |

| | |
|-----------------------|--|
| Modulation: | GFSK, Pi/4 QDPSK, 8DPSK |
| Quantity of Channels: | 79/40 |
| Channel Separation: | 1MHz/2MHz |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | 1.0dBi |
| 4G | |
| Support Networks: | FDD-LTE |
| Support Band: | FDD-LTE Band 2,5 |
| Uplink Frequency: | FDD-LTE Band 2: Tx: 1850-1910MHz, FDD-LTE Band 5: Tx: 824-849MHz, |
| Downlink Frequency: | FDD-LTE Band 2: Rx: 1930-1990MHz, FDD-LTE Band 5: Rx: 869-894MHz, |
| RF Output Power: | FDD-LTE Band 2: 24.53dBm, FDD-LTE Band 5: 25.73dBm |
| Type of Modulation: | QPSK, 16QAM |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | 2.0dBi |

1.2 Test Standards

The following report is prepared on behalf of the SZTZ ELECTRONICS CO.,LTD in accordance with FCC 47 CFR Part 2.1093, ANSI/IEEE C95.1-2005, IEEE 1528-2013 and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Body SAR(5mm Gap)

| Frequency Band | Maximum SAR _{1g} (W/kg) | SAR _{1g} Limit (W/kg) |
|---------------------------|-------------------------------------|--------------------------------------|
| GSM | 1.107 | 1.6 |
| WCDMA | 0.448 | 1.6 |
| LTE | 0.795 | 1.6 |
| WLAN 2.4GHz | 0.251 | 1.6 |
| Simultaneous Transmission | 1.315 | 1.6 |

Hand SAR(0mm Gap)

| Frequency Band | Maximum SAR _{10g} (W/kg) | SAR _{10g} Limit (W/kg) |
|---------------------------|--------------------------------------|---------------------------------------|
| GSM | 2.455 | 4.0 |
| WCDMA | 0.594 | 4.0 |
| LTE | 1.021 | 4.0 |
| WLAN 2.4GHz | 0.304 | 4.0 |
| Simultaneous Transmission | 2.611 | 4.0 |

Remark:

*The highest reported SAR values for body, and Hand and simultaneous transmission conditions are **1.107W/kg**, **2.455W/kg**, and **2.611W/kg** respectively.*

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedure specified in KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02

3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.


4.2 Probe

For the measurements the Specific Dosimetric E-Field Probe SSE5 SN 09/13 EP168 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Probe Length: 330 mm
- Length of Individual Dipoles: 4.5 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter : 5 mm
- Distance between dipoles / probe extremity: 2.7mm

- Probe linearity: <0.25 dB
 - Axial Isotropy: <0.25 dB
 - Spherical Isotropy: <0.50 dB
 - Calibration range: 700 to 3000MHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528 STD, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1 annexe technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) c^{(2z/\delta)}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

I = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage $V_{lin}(N)$ is obtained from the displayed output voltage $V(N)$ using

$$V_{lin}(N)=V(N)*(1+V(N)/DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

$$SAR = C \frac{\Delta T}{\Delta t}$$

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



| System Material | Permittivity | Loss Tangent |
|-----------------|--------------|--------------|
| Delrin | 3.7 | 0.005 |


4.6 Test Equipment List

| Description | Manufacturer | Model | Serial Number | Cal. Date | Due. Date |
|----------------------|-----------------|---------------|------------------------|------------|------------|
| E-Field Probe | SATIMO | SSE5 | SN 09/13 EP168 | 2016-06-01 | 2017-05-31 |
| 835MHz Dipole | SATIMO | SID835 | SN 47/12 DIP 0G835-204 | 2017-03-16 | 2018-03-15 |
| 1900MHz Dipole | SATIMO | SID1900 | SN 47/12 DIP 1G900-207 | 2017-03-16 | 2018-03-15 |
| 2450MHz Dipole | SATIMO | SID2450 | SN 13/15 DIP 2G450-364 | 2017-03-16 | 2018-03-15 |
| Dielectric Probe Kit | SATIMO | SCLMP | SN 47/12 OCPG49 | 2017-03-16 | 2018-03-15 |
| SAM Phantom | SATIMO | SAM | SN/ 47/12 SAM95 | N/A | N/A |
| MULTIMETER | KEITHLEY | Keithley 2000 | 4006367 | 2016-06-04 | 2017-06-03 |
| Signal Generator | Rohde & Schwarz | SMR20 | 100047 | 2016-06-04 | 2017-06-03 |
| Universal Tester | Rohde & Schwarz | CMU200 | 112012 | 2016-06-04 | 2017-06-03 |
| Universal Tester | Rohde & Schwarz | CMW500 | 148650 | 2016-06-04 | 2017-06-03 |
| Network Analyzer | HP | 8753C | 2901A00831 | 2016-06-04 | 2017-06-03 |
| Directional Couplers | Agilent | 778D | 20160 | 2016-06-04 | 2017-06-03 |

5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Head SAR



Liquid Height for Body SAR

The Composition of Tissue Simulating Liquid

| Frequency (MHz) | Water (%) | Salt (%) | Sugar (%) | HEC (%) | Preventol (%) | DGBE (%) |
|--------------------|--------------|-------------|--------------|------------|------------------|-------------|
| Body | | | | | | |
| 835 | 50.8 | 0.9 | 48.1 | 0.1 | 0.1 | 0 |
| 1900 | 70.2 | 0.4 | 0 | 0 | 0 | 29.4 |
| 2450 | 68.6 | 0.1 | 0 | 0 | 0 | 31.3 |
| 2600 | 64.5 | 0.1 | 0 | 0 | 0 | 35.4 |

5.2 Tissue Dielectric Parameters for Head and Body Phantoms

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

| Target Frequency (MHz) | Head | | Body | |
|---------------------------|------------------------------|----------------------------------|------------------------------|----------------------------------|
| | Conductivity (σ) | Permittivity (ϵ_r) | Conductivity (σ) | Permittivity (ϵ_r) |
| 150 | 0.76 | 52.3 | 0.80 | 61.9 |
| 300 | 0.87 | 45.3 | 0.92 | 58.2 |
| 450 | 0.87 | 43.5 | 0.94 | 56.7 |
| 750 | 0.89 | 41.9 | 0.96 | 55.5 |
| 835 | 0.90 | 41.5 | 0.97 | 55.2 |
| 900 | 0.97 | 41.5 | 1.05 | 55.0 |
| 915 | 0.98 | 41.5 | 1.06 | 55.0 |
| 1450 | 1.20 | 40.5 | 1.30 | 54.0 |
| 1610 | 1.29 | 40.3 | 1.40 | 53.8 |
| 1800-2000 | 1.40 | 40.0 | 1.52 | 53.3 |
| 2450 | 1.80 | 39.2 | 1.95 | 52.7 |
| 3000 | 2.40 | 38.5 | 2.73 | 52.0 |
| 5800 | 5.27 | 35.3 | 6.00 | 48.2 |

5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

| Body Tissue Simulating Liquid | | | | | | | | | |
|-------------------------------|---------------|-------------------------|------------------------|--------------|-----------------------------|----------------------------|--------------|--------------|------------|
| Freq. MHz. | Temp. (°C) | Conductivity | | | Permittivity | | | Limit (%) | Date |
| | | Reading (σ) | Target (σ) | Delta (%) | Reading (ϵ_r) | Target (ϵ_r) | Delta (%) | | |
| 835 | 21.2 | 0.95 | 0.97 | -2.06 | 54.85 | 55.20 | -0.63 | ± 5 | 2017-05-15 |
| 1900 | 21.3 | 1.50 | 1.52 | -1.32 | 52.42 | 53.30 | -1.65 | ± 5 | 2017-05-15 |
| 2450 | 21.3 | 1.91 | 1.95 | -2.05 | 52.01 | 52.70 | -1.31 | ± 5 | 2017-05-15 |


6. SAR Measurement Evaluation

6.1 Purpose of System Performance Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

6.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 835 MHz and 1900 MHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom.



System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24dBm (250mW) before dipole is connected.

6.3 Validation Results


Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

| Frequency | Targeted SAR _{1g} | Measured SAR _{1g} | Normalized SAR _{1g} | Tolerance |
|-----------|----------------------------|----------------------------|------------------------------|-----------|
| MHz | (W/kg) | (W/kg) | (W/kg) | (%) |
| Body | | | | |
| 835 | 9.36 | 2.35 | 9.4 | 0.43 |
| 1900 | 39.01 | 9.78 | 39.12 | 0.28 |
| 2450 | 50.33 | 12.59 | 50.36 | 0.06 |

Please refer to Annex A for the plots of system performance check.

7. EUT Testing Position

7.1 EUT Antenna Position



7.2 EUT Testing Position

Body /Hand mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

| Body SAR tests, Test distance: 5mm | | | | | | |
|------------------------------------|-------|------|------------|-----------|----------|-------------|
| Antennas | Front | Back | Right Side | Left Side | Top Side | Bottom Side |
| WWAN | Yes | Yes | Yes | Yes | No | No |
| WLAN | Yes | Yes | Yes | No | No | No |

| Hand SAR tests, Test distance: 0mm | | | | | | |
|------------------------------------|-------|------|------------|-----------|----------|-------------|
| Antennas | Front | Back | Right Side | Left Side | Top Side | Bottom Side |
| WWAN | Yes | Yes | Yes | Yes | No | No |
| WLAN | Yes | Yes | Yes | No | No | No |

Remark:

1. Referring to 447498 D01 v06 , when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test separation distances of body and hand is 5 mm and 0mm *respectively*. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex D demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

9. SAR Test Result

9.1 Conducted RF Output Power

| GSM - Burst Average Power (dBm) | | | | | | | | |
|---------------------------------|--------|-------|-------|---------------------------|---------|-------|--------|---------------------------|
| Band | GSM850 | | | Tune-up power (dBm) | PCS1900 | | | Tune-up power (dBm) |
| Channel | 128 | 190 | 251 | | 512 | 661 | 810 | |
| Frequency (MHz) | 824.2 | 836.6 | 848.8 | | 1850.2 | 1880 | 1909.8 | |
| GSM | / | / | / | / | / | / | / | / |
| GPRS (1 slot) | 32.22 | 32.34 | 32.39 | 32.5 | 27.82 | 28.15 | 28.74 | 29.0 |
| GPRS (2 slots) | 31.96 | 32.08 | 32.19 | 32.5 | 27.52 | 27.8 | 28.39 | 29.0 |
| GPRS (3 slots) | 31.77 | 31.9 | 32 | 32.0 | 27.67 | 28.01 | 28.56 | 29.0 |
| GPRS (4 slots) | 31.67 | 31.79 | 31.74 | 32.0 | 27.41 | 27.68 | 28.22 | 28.5 |
| EDGE (1 slot) | 24.81 | 24.79 | 24.71 | 25.0 | 24.52 | 24.38 | 24.46 | 25.0 |
| EDGE (2 slots) | 24.64 | 24.66 | 24.59 | 25.0 | 24.21 | 24.14 | 24.27 | 24.5 |
| EDGE (3 slots) | 24.5 | 24.47 | 24.45 | 24.5 | 24.07 | 23.95 | 23.99 | 24.5 |
| EDGE (4 slots) | 24.36 | 24.33 | 24.27 | 24.5 | 23.89 | 23.72 | 23.81 | 24.0 |

| GSM - Source-Based Time-Average Power (dBm) | | | | | | | | |
|---|--------|-------|-------|---------------------------|---------|-------|--------|---------------------------|
| Band | GSM850 | | | Tune-up power (dBm) | PCS1900 | | | Tune-up power (dBm) |
| Channel | 128 | 190 | 251 | | 512 | 661 | 810 | |
| Frequency (MHz) | 824.2 | 836.6 | 848.8 | | 1850.2 | 1880 | 1909.8 | |
| GSM | / | / | / | / | / | / | / | / |
| GPRS (1 slot) | 23.22 | 23.34 | 23.39 | 23.5 | 18.82 | 19.15 | 19.74 | 20.0 |
| GPRS (2 slots) | 25.96 | 26.08 | 26.19 | 26.5 | 21.52 | 21.80 | 22.39 | 22.5 |
| GPRS (3 slots) | 27.52 | 27.65 | 27.75 | 28.0 | 23.42 | 23.76 | 24.31 | 24.5 |
| GPRS (4 slots) | 28.67 | 28.79 | 28.74 | 29.0 | 24.41 | 24.68 | 25.22 | 25.5 |
| EDGE (1 slot) | 15.81 | 15.79 | 15.71 | 16.0 | 15.52 | 15.38 | 15.46 | 16.0 |
| EDGE (2 slots) | 18.64 | 18.66 | 18.59 | 19.0 | 18.21 | 18.14 | 18.27 | 18.5 |
| EDGE (3 slots) | 20.25 | 20.22 | 20.20 | 20.5 | 19.82 | 19.70 | 19.74 | 20.0 |
| EDGE (4 slots) | 21.36 | 21.33 | 21.27 | 21.5 | 20.89 | 20.72 | 20.81 | 21.0 |

Note: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time-average power = Burst averaged power - Duty cycle factor in dB

Duty cycle factor = 9 dB for 1 Tx slot, 6 dB for 2 Tx slots, 4.25 dB for 3 Tx slots, 3 dB for 4 Tx slots

Remark:

1. For Body SAR testing, GPRS should be evaluated, therefore the EUT was set in GPRS (4TX slots) for GSM850 and GSM1900 due to its highest source-based time-average power.
2. Per KDB 447498 D01 v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
3. The DUT do not support DTM function.

| WCDMA - Average Power (dBm) | | | | | | | | |
|-----------------------------|---------------|--------|--------|-------------|--------------|-------|-------|-------------|
| Band | WCDMA Band II | | | | WCDMA Band V | | | |
| Channel | 9262 | 9400 | 9538 | Tune-up | 4132 | 4182 | 4233 | Tune-up |
| Frequency (MHz) | 1852.4 | 1880.0 | 1907.6 | power (dBm) | 826.4 | 836.6 | 846.6 | power (dBm) |
| RMC 12.2k | 22.33 | 21.88 | 22.08 | 22.5 | 22.11 | 22.21 | 22.02 | 22.5 |
| HSDPA Subtest-1 | 21.38 | 20.96 | 21.49 | 21.5 | 20.91 | 21.14 | 20.97 | 21.5 |
| HSDPA Subtest-2 | 21.31 | 20.95 | 21.46 | 21.5 | 20.89 | 21.12 | 20.82 | 21.5 |
| HSDPA Subtest-3 | 21.27 | 20.91 | 21.42 | 21.5 | 20.87 | 21.10 | 20.81 | 21.5 |
| HSDPA Subtest-4 | 21.19 | 20.88 | 21.39 | 21.5 | 20.82 | 21.05 | 20.79 | 21.5 |
| HSUPA Subtest-1 | 20.55 | 20.55 | 20.52 | 21.5 | 20.42 | 20.65 | 20.55 | 21.5 |
| HSUPA Subtest-2 | 20.51 | 20.49 | 20.51 | 21.5 | 20.42 | 20.59 | 20.54 | 21.5 |
| HSUPA Subtest-3 | 20.47 | 20.45 | 20.49 | 21.5 | 20.40 | 20.55 | 20.49 | 21.5 |
| HSUPA Subtest-4 | 20.44 | 20.39 | 20.48 | 21.5 | 20.39 | 20.48 | 20.45 | 21.5 |
| HSUPA Subtest-5 | 20.39 | 20.34 | 20.45 | 21.5 | 20.40 | 20.41 | 20.43 | 21.5 |

Remark:

1. For Body SAR, per KDB 941225 D01 v03, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA subset-1 output power is < 1/4 dB higher than RMC, and SAR with RMC 12.2kbps setting is $\leq 1.2\text{W/kg}$, HSDPA SAR evaluation can be excluded.

FDD-LTE Band 2:

| Channel Bandwidth: 1.4 MHz | | | | | |
|----------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 23.08 | 25.0 |
| | | 1 | 3 | 23.27 | 25.0 |
| | | 1 | 5 | 22.92 | 25.0 |
| | | 3 | 0 | 23.00 | 25.0 |
| | | 3 | 2 | 23.03 | 25.0 |
| | | 3 | 3 | 22.98 | 25.0 |
| | | 6 | 0 | 22.07 | 25.0 |
| | MCH | 1 | 0 | 23.87 | 25.0 |
| | | 1 | 3 | 23.77 | 25.0 |
| | | 1 | 5 | 23.73 | 25.0 |
| | | 3 | 0 | 22.75 | 25.0 |
| | | 3 | 2 | 22.74 | 25.0 |
| | | 3 | 3 | 22.84 | 25.0 |
| | | 6 | 0 | 22.79 | 25.0 |
| | HCH | 1 | 0 | 24.30 | 25.0 |
| | | 1 | 3 | 24.33 | 25.0 |
| | | 1 | 5 | 24.24 | 25.0 |
| | | 3 | 0 | 22.35 | 25.0 |
| | | 3 | 2 | 22.29 | 25.0 |
| | | 3 | 3 | 22.51 | 25.0 |
| | | 6 | 0 | 23.39 | 25.0 |
| 16QAM | LCH | 1 | 0 | 22.51 | 25.0 |
| | | 1 | 3 | 23.13 | 25.0 |
| | | 1 | 5 | 22.94 | 25.0 |
| | | 3 | 0 | 22.27 | 25.0 |
| | | 3 | 2 | 22.26 | 25.0 |
| | | 3 | 3 | 22.21 | 25.0 |
| | | 6 | 0 | 21.09 | 25.0 |
| | MCH | 1 | 0 | 23.33 | 25.0 |
| | | 1 | 3 | 23.38 | 25.0 |
| | | 1 | 5 | 23.37 | 25.0 |
| | | 3 | 0 | 22.71 | 25.0 |
| | | 3 | 2 | 22.74 | 25.0 |
| | | 3 | 3 | 22.61 | 25.0 |
| | | 6 | 0 | 21.73 | 25.0 |
| | HCH | 1 | 0 | 23.72 | 25.0 |

| | | | | | |
|--|--|---|---|-------|------|
| | | 1 | 3 | 23.96 | 25.0 |
| | | 1 | 5 | 23.95 | 25.0 |
| | | 3 | 0 | 22.22 | 25.0 |
| | | 3 | 2 | 22.21 | 25.0 |
| | | 3 | 3 | 22.26 | 25.0 |
| | | 6 | 0 | 22.72 | 25.0 |

| Channel Bandwidth: 3 MHz | | | | | |
|--------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 23.22 | 25.0 |
| | | 1 | 7 | 23.15 | 25.0 |
| | | 1 | 14 | 23.33 | 25.0 |
| | | 8 | 0 | 22.10 | 25.0 |
| | | 8 | 4 | 22.11 | 25.0 |
| | | 8 | 7 | 22.12 | 25.0 |
| | | 15 | 0 | 22.10 | 25.0 |
| | MCH | 1 | 0 | 23.77 | 25.0 |
| | | 1 | 7 | 23.65 | 25.0 |
| | | 1 | 14 | 24.05 | 25.0 |
| | | 8 | 0 | 22.90 | 25.0 |
| | | 8 | 4 | 22.84 | 25.0 |
| | | 8 | 7 | 22.89 | 25.0 |
| | | 15 | 0 | 22.90 | 25.0 |
| | HCH | 1 | 0 | 24.27 | 25.0 |
| | | 1 | 7 | 24.08 | 25.0 |
| | | 1 | 14 | 24.43 | 25.0 |
| | | 8 | 0 | 22.28 | 25.0 |
| | | 8 | 4 | 22.33 | 25.0 |
| | | 8 | 7 | 22.25 | 25.0 |
| | | 15 | 0 | 22.34 | 25.0 |
| 16QAM | LCH | 1 | 0 | 22.99 | 25.0 |
| | | 1 | 7 | 22.81 | 25.0 |
| | | 1 | 14 | 22.93 | 25.0 |
| | | 8 | 0 | 22.18 | 25.0 |
| | | 8 | 4 | 22.10 | 25.0 |
| | | 8 | 7 | 22.11 | 25.0 |
| | | 15 | 0 | 22.10 | 25.0 |
| | MCH | 1 | 0 | 23.63 | 25.0 |
| | | 1 | 7 | 23.60 | 25.0 |
| | | 1 | 14 | 23.74 | 25.0 |
| | | 8 | 0 | 22.01 | 25.0 |

| | | | | | |
|--|-----|----|----|-------|------|
| | | 8 | 4 | 21.97 | 25.0 |
| | | 8 | 7 | 22.00 | 25.0 |
| | | 15 | 0 | 21.84 | 25.0 |
| | HCH | 1 | 0 | 23.81 | 25.0 |
| | | 1 | 7 | 23.55 | 25.0 |
| | | 1 | 14 | 24.09 | 25.0 |
| | | 8 | 0 | 22.39 | 25.0 |
| | | 8 | 4 | 22.30 | 25.0 |
| | | 8 | 7 | 22.30 | 25.0 |
| | | 15 | 0 | 22.24 | 25.0 |

| Channel Bandwidth: 5 MHz | | | | | |
|--------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 22.93 | 25.0 |
| | | 1 | 12 | 23.22 | 25.0 |
| | | 1 | 24 | 23.24 | 25.0 |
| | | 12 | 0 | 22.21 | 25.0 |
| | | 12 | 6 | 22.09 | 25.0 |
| | | 12 | 13 | 22.31 | 25.0 |
| | | 25 | 0 | 22.20 | 25.0 |
| | MCH | 1 | 0 | 23.74 | 25.0 |
| | | 1 | 12 | 22.69 | 25.0 |
| | | 1 | 24 | 24.02 | 25.0 |
| | | 12 | 0 | 22.91 | 25.0 |
| | | 12 | 6 | 22.84 | 25.0 |
| | | 12 | 13 | 22.07 | 25.0 |
| | | 25 | 0 | 21.91 | 25.0 |
| | HCH | 1 | 0 | 24.08 | 25.0 |
| | | 1 | 12 | 24.21 | 25.0 |
| | | 1 | 24 | 24.16 | 25.0 |
| | | 12 | 0 | 22.34 | 25.0 |
| | | 12 | 6 | 22.15 | 25.0 |
| | | 12 | 13 | 22.32 | 25.0 |
| | | 25 | 0 | 22.39 | 25.0 |
| 16QAM | LCH | 1 | 0 | 22.63 | 25.0 |
| | | 1 | 12 | 22.14 | 25.0 |
| | | 1 | 24 | 22.92 | 25.0 |
| | | 12 | 0 | 21.27 | 25.0 |
| | | 12 | 6 | 21.20 | 25.0 |
| | | 12 | 13 | 21.50 | 25.0 |
| | | 25 | 0 | 21.28 | 25.0 |

| | | | | | |
|--|-----|----|----|-------|------|
| | MCH | 1 | 0 | 23.30 | 25.0 |
| | | 1 | 12 | 23.32 | 25.0 |
| | | 1 | 24 | 22.67 | 25.0 |
| | | 12 | 0 | 21.89 | 25.0 |
| | | 12 | 6 | 21.91 | 25.0 |
| | | 12 | 13 | 21.16 | 25.0 |
| | | 25 | 0 | 21.96 | 25.0 |
| | HCH | 1 | 0 | 23.22 | 25.0 |
| | | 1 | 12 | 22.82 | 25.0 |
| | | 1 | 24 | 23.06 | 25.0 |
| | | 12 | 0 | 22.31 | 25.0 |
| | | 12 | 6 | 22.28 | 25.0 |
| | | 12 | 13 | 22.48 | 25.0 |
| | | 25 | 0 | 22.65 | 25.0 |

| Channel Bandwidth: 10 MHz | | | | | |
|---------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 23.23 | 25.0 |
| | | 1 | 24 | 23.01 | 25.0 |
| | | 1 | 49 | 23.20 | 25.0 |
| | | 25 | 0 | 22.23 | 25.0 |
| | | 25 | 12 | 22.35 | 25.0 |
| | | 25 | 25 | 22.26 | 25.0 |
| | | 50 | 0 | 22.10 | 25.0 |
| | MCH | 1 | 0 | 23.80 | 25.0 |
| | | 1 | 24 | 23.69 | 25.0 |
| | | 1 | 49 | 24.07 | 25.0 |
| | | 25 | 0 | 22.91 | 25.0 |
| | | 25 | 12 | 22.82 | 25.0 |
| | | 25 | 25 | 22.10 | 25.0 |
| | | 50 | 0 | 21.94 | 25.0 |
| | HCH | 1 | 0 | 23.81 | 25.0 |
| | | 1 | 24 | 24.04 | 25.0 |
| | | 1 | 49 | 24.21 | 25.0 |
| | | 25 | 0 | 22.20 | 25.0 |
| | | 25 | 12 | 22.26 | 25.0 |
| | | 25 | 25 | 22.31 | 25.0 |
| | | 50 | 0 | 22.27 | 25.0 |
| 16QAM | LCH | 1 | 0 | 22.77 | 25.0 |
| | | 1 | 24 | 22.89 | 25.0 |
| | | 1 | 49 | 22.79 | 25.0 |

| | | | | | |
|--|-----|----|----|-------|------|
| | | 25 | 0 | 22.00 | 25.0 |
| | | 25 | 12 | 21.97 | 25.0 |
| | | 25 | 25 | 21.06 | 25.0 |
| | | 50 | 0 | 21.17 | 25.0 |
| | MCH | 1 | 0 | 22.36 | 25.0 |
| | | 1 | 24 | 22.53 | 25.0 |
| | | 1 | 49 | 23.13 | 25.0 |
| | | 25 | 0 | 21.90 | 25.0 |
| | | 25 | 12 | 21.70 | 25.0 |
| | | 25 | 25 | 21.99 | 25.0 |
| | | 50 | 0 | 21.99 | 25.0 |
| | HCH | 1 | 0 | 23.50 | 25.0 |
| | | 1 | 24 | 23.38 | 25.0 |
| | | 1 | 49 | 23.84 | 25.0 |
| | | 25 | 0 | 22.23 | 25.0 |
| | | 25 | 12 | 22.21 | 25.0 |
| | | 25 | 25 | 22.26 | 25.0 |
| | | 50 | 0 | 22.15 | 25.0 |

| Channel Bandwidth: 15 MHz | | | | | |
|---------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 22.40 | 25.0 |
| | | 1 | 37 | 22.10 | 25.0 |
| | | 1 | 74 | 22.51 | 25.0 |
| | | 37 | 0 | 21.21 | 25.0 |
| | | 37 | 18 | 21.19 | 25.0 |
| | | 37 | 38 | 21.34 | 25.0 |
| | | 75 | 0 | 21.31 | 25.0 |
| | MCH | 1 | 0 | 22.83 | 25.0 |
| | | 1 | 37 | 22.57 | 25.0 |
| | | 1 | 74 | 23.30 | 25.0 |
| | | 37 | 0 | 21.78 | 25.0 |
| | | 37 | 18 | 21.72 | 25.0 |
| | | 37 | 38 | 22.01 | 25.0 |
| | | 75 | 0 | 21.82 | 25.0 |
| | HCH | 1 | 0 | 23.71 | 25.0 |
| | | 1 | 37 | 24.14 | 25.0 |
| | | 1 | 74 | 24.03 | 25.0 |
| | | 37 | 0 | 22.89 | 25.0 |
| | | 37 | 18 | 22.13 | 25.0 |
| | | 37 | 38 | 22.29 | 25.0 |

| | | | | | |
|-------|-----|----|----|-------|------|
| | | 75 | 0 | 22.03 | 25.0 |
| 16QAM | LCH | 1 | 0 | 21.47 | 25.0 |
| | | 1 | 37 | 21.49 | 25.0 |
| | | 1 | 74 | 22.16 | 25.0 |
| | | 37 | 0 | 21.26 | 25.0 |
| | | 37 | 18 | 21.21 | 25.0 |
| | | 37 | 38 | 21.20 | 25.0 |
| | | 75 | 0 | 21.18 | 25.0 |
| | MCH | 1 | 0 | 22.22 | 25.0 |
| | | 1 | 37 | 22.00 | 25.0 |
| | | 1 | 74 | 23.21 | 25.0 |
| | | 37 | 0 | 21.70 | 25.0 |
| | | 37 | 18 | 21.62 | 25.0 |
| | | 37 | 38 | 21.86 | 25.0 |
| | | 75 | 0 | 21.80 | 25.0 |
| | HCH | 1 | 0 | 23.58 | 25.0 |
| | | 1 | 37 | 23.87 | 25.0 |
| | | 1 | 74 | 24.21 | 25.0 |
| | | 37 | 0 | 21.98 | 25.0 |
| | | 37 | 18 | 21.94 | 25.0 |
| | | 37 | 38 | 22.12 | 25.0 |
| | | 75 | 0 | 21.99 | 25.0 |

| Channel Bandwidth: 20 MHz | | | | | |
|---------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 22.49 | 25.0 |
| | | 1 | 49 | 22.33 | 25.0 |
| | | 1 | 99 | 22.82 | 25.0 |
| | | 50 | 0 | 21.28 | 25.0 |
| | | 50 | 25 | 21.32 | 25.0 |
| | | 50 | 50 | 21.44 | 25.0 |
| | | 100 | 0 | 21.29 | 25.0 |
| | MCH | 1 | 0 | 22.81 | 25.0 |
| | | 1 | 49 | 22.97 | 25.0 |
| | | 1 | 99 | 23.54 | 25.0 |
| | | 50 | 0 | 21.71 | 25.0 |
| | | 50 | 25 | 21.79 | 25.0 |
| | | 50 | 50 | 22.05 | 25.0 |
| | | 100 | 0 | 21.87 | 25.0 |
| | HCH | 1 | 0 | 23.54 | 25.0 |
| | | 1 | 49 | 23.97 | 25.0 |

| | | | | | |
|-------|-----|-----|----|-------|------|
| | | 1 | 99 | 24.53 | 25.0 |
| | | 50 | 0 | 22.74 | 25.0 |
| | | 50 | 25 | 23.01 | 25.0 |
| | | 50 | 50 | 23.29 | 25.0 |
| | | 100 | 0 | 22.98 | 25.0 |
| 16QAM | LCH | 1 | 0 | 21.10 | 25.0 |
| | | 1 | 49 | 21.85 | 25.0 |
| | | 1 | 99 | 21.91 | 25.0 |
| | | 50 | 0 | 21.15 | 25.0 |
| | | 50 | 25 | 21.23 | 25.0 |
| | | 50 | 50 | 21.42 | 25.0 |
| | | 100 | 0 | 21.30 | 25.0 |
| | MCH | 1 | 0 | 22.14 | 25.0 |
| | | 1 | 49 | 21.50 | 25.0 |
| | | 1 | 99 | 22.05 | 25.0 |
| | | 50 | 0 | 21.75 | 25.0 |
| | | 50 | 25 | 21.77 | 25.0 |
| | | 50 | 50 | 21.94 | 25.0 |
| | | 100 | 0 | 21.81 | 25.0 |
| | HCH | 1 | 0 | 22.59 | 25.0 |
| | | 1 | 49 | 22.95 | 25.0 |
| | | 1 | 99 | 23.79 | 25.0 |
| | | 50 | 0 | 21.62 | 25.0 |
| | | 50 | 25 | 21.97 | 25.0 |
| | | 50 | 50 | 22.33 | 25.0 |
| | | 100 | 0 | 21.93 | 25.0 |

FDD-LTE Band 5:

| Channel Bandwidth: 1.4 MHz | | | | | |
|----------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 24.46 | 26.0 |
| | | 1 | 3 | 24.85 | 26.0 |
| | | 1 | 5 | 24.76 | 26.0 |
| | | 3 | 0 | 24.48 | 26.0 |
| | | 3 | 2 | 24.73 | 26.0 |
| | | 3 | 3 | 24.70 | 26.0 |
| | | 6 | 0 | 23.58 | 26.0 |
| | MCH | 1 | 0 | 24.88 | 26.0 |
| | | 1 | 3 | 24.71 | 26.0 |
| | | 1 | 5 | 24.70 | 26.0 |
| | | 3 | 0 | 24.83 | 26.0 |
| | | 3 | 2 | 24.82 | 26.0 |
| | | 3 | 3 | 24.86 | 26.0 |
| | | 6 | 0 | 24.19 | 26.0 |
| | HCH | 1 | 0 | 25.50 | 26.0 |
| | | 1 | 3 | 25.35 | 26.0 |
| | | 1 | 5 | 25.37 | 26.0 |
| | | 3 | 0 | 24.49 | 26.0 |
| | | 3 | 2 | 24.38 | 26.0 |
| | | 3 | 3 | 24.34 | 26.0 |
| | | 6 | 0 | 23.45 | 26.0 |
| 16QAM | LCH | 1 | 0 | 24.58 | 26.0 |
| | | 1 | 3 | 24.63 | 26.0 |
| | | 1 | 5 | 24.50 | 26.0 |
| | | 3 | 0 | 23.96 | 26.0 |
| | | 3 | 2 | 23.97 | 26.0 |
| | | 3 | 3 | 23.95 | 26.0 |
| | | 6 | 0 | 22.46 | 26.0 |
| | MCH | 1 | 0 | 24.44 | 26.0 |
| | | 1 | 3 | 24.37 | 26.0 |
| | | 1 | 5 | 24.42 | 26.0 |
| | | 3 | 0 | 23.98 | 26.0 |
| | | 3 | 2 | 24.00 | 26.0 |
| | | 3 | 3 | 23.97 | 26.0 |
| | | 6 | 0 | 22.85 | 26.0 |
| | HCH | 1 | 0 | 25.24 | 26.0 |

| | | | | | |
|--|--|---|---|-------|------|
| | | 1 | 3 | 25.37 | 26.0 |
| | | 1 | 5 | 25.20 | 26.0 |
| | | 3 | 0 | 24.78 | 26.0 |
| | | 3 | 2 | 24.64 | 26.0 |
| | | 3 | 3 | 24.71 | 26.0 |
| | | 6 | 0 | 23.67 | 26.0 |

| Channel Bandwidth: 3 MHz | | | | | |
|--------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 24.53 | 26.0 |
| | | 1 | 7 | 24.60 | 26.0 |
| | | 1 | 14 | 25.03 | 26.0 |
| | | 8 | 0 | 23.83 | 26.0 |
| | | 8 | 4 | 23.85 | 26.0 |
| | | 8 | 7 | 23.91 | 26.0 |
| | | 15 | 0 | 23.80 | 26.0 |
| | MCH | 1 | 0 | 25.13 | 26.0 |
| | | 1 | 7 | 24.79 | 26.0 |
| | | 1 | 14 | 24.86 | 26.0 |
| | | 8 | 0 | 24.11 | 26.0 |
| | | 8 | 4 | 23.87 | 26.0 |
| | | 8 | 7 | 24.00 | 26.0 |
| | | 15 | 0 | 24.03 | 26.0 |
| | HCH | 1 | 0 | 25.46 | 26.0 |
| | | 1 | 7 | 25.37 | 26.0 |
| | | 1 | 14 | 25.16 | 26.0 |
| | | 8 | 0 | 24.53 | 26.0 |
| | | 8 | 4 | 24.50 | 26.0 |
| | | 8 | 7 | 24.34 | 26.0 |
| | | 15 | 0 | 24.44 | 26.0 |
| 16QAM | LCH | 1 | 0 | 24.55 | 26.0 |
| | | 1 | 7 | 24.41 | 26.0 |
| | | 1 | 14 | 24.64 | 26.0 |
| | | 8 | 0 | 22.94 | 26.0 |
| | | 8 | 4 | 22.91 | 26.0 |
| | | 8 | 7 | 22.93 | 26.0 |
| | | 15 | 0 | 22.74 | 26.0 |
| | MCH | 1 | 0 | 24.99 | 26.0 |
| | | 1 | 7 | 24.34 | 26.0 |
| | | 1 | 14 | 24.25 | 26.0 |
| | | 8 | 0 | 23.20 | 26.0 |

| | | | | | |
|--|-----|----|----|-------|------|
| | | 8 | 4 | 22.96 | 26.0 |
| | | 8 | 7 | 22.90 | 26.0 |
| | | 15 | 0 | 22.94 | 26.0 |
| | HCH | 1 | 0 | 25.15 | 26.0 |
| | | 1 | 7 | 25.30 | 26.0 |
| | | 1 | 14 | 25.05 | 26.0 |
| | | 8 | 0 | 23.95 | 26.0 |
| | | 8 | 4 | 23.96 | 26.0 |
| | | 8 | 7 | 23.83 | 26.0 |
| | | 15 | 0 | 23.34 | 26.0 |

| Channel Bandwidth: 5 MHz | | | | | |
|--------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 24.64 | 26.0 |
| | | 1 | 12 | 24.60 | 26.0 |
| | | 1 | 24 | 25.08 | 26.0 |
| | | 12 | 0 | 23.77 | 26.0 |
| | | 12 | 6 | 23.80 | 26.0 |
| | | 12 | 13 | 24.10 | 26.0 |
| | | 25 | 0 | 23.77 | 26.0 |
| | MCH | 1 | 0 | 24.96 | 26.0 |
| | | 1 | 12 | 24.61 | 26.0 |
| | | 1 | 24 | 24.72 | 26.0 |
| | | 12 | 0 | 24.04 | 26.0 |
| | | 12 | 6 | 23.92 | 26.0 |
| | | 12 | 13 | 24.04 | 26.0 |
| | | 25 | 0 | 23.96 | 26.0 |
| | HCH | 1 | 0 | 25.30 | 26.0 |
| | | 1 | 12 | 25.72 | 26.0 |
| | | 1 | 24 | 25.38 | 26.0 |
| | | 12 | 0 | 24.43 | 26.0 |
| | | 12 | 6 | 24.56 | 26.0 |
| | | 12 | 13 | 24.57 | 26.0 |
| | | 25 | 0 | 24.44 | 26.0 |
| 16QAM | LCH | 1 | 0 | 24.10 | 26.0 |
| | | 1 | 12 | 24.20 | 26.0 |
| | | 1 | 24 | 24.74 | 26.0 |
| | | 12 | 0 | 22.67 | 26.0 |
| | | 12 | 6 | 22.61 | 26.0 |
| | | 12 | 13 | 23.14 | 26.0 |
| | | 25 | 0 | 22.82 | 26.0 |

| | | | | | |
|--|-----|----|----|-------|------|
| | MCH | 1 | 0 | 24.53 | 26.0 |
| | | 1 | 12 | 24.09 | 26.0 |
| | | 1 | 24 | 23.98 | 26.0 |
| | | 12 | 0 | 23.31 | 26.0 |
| | | 12 | 6 | 23.06 | 26.0 |
| | | 12 | 13 | 22.96 | 26.0 |
| | | 25 | 0 | 23.09 | 26.0 |
| | HCH | 1 | 0 | 24.93 | 26.0 |
| | | 1 | 12 | 25.15 | 26.0 |
| | | 1 | 24 | 24.87 | 26.0 |
| | | 12 | 0 | 23.52 | 26.0 |
| | | 12 | 6 | 23.73 | 26.0 |
| | | 12 | 13 | 23.71 | 26.0 |
| | | 25 | 0 | 23.53 | 26.0 |

| Channel Bandwidth: 10 MHz | | | | | |
|---------------------------|---------|------------------|--------|---------------------|---------------------|
| Modulation | Channel | RB Configuration | | Average Power [dBm] | Tune-up power (dBm) |
| | | Size | Offset | | |
| QPSK | LCH | 1 | 0 | 24.62 | 26.0 |
| | | 1 | 24 | 25.11 | 26.0 |
| | | 1 | 49 | 25.14 | 26.0 |
| | | 25 | 0 | 23.84 | 26.0 |
| | | 25 | 12 | 24.12 | 26.0 |
| | | 25 | 25 | 24.24 | 26.0 |
| | | 50 | 0 | 23.94 | 26.0 |
| | MCH | 1 | 0 | 24.86 | 26.0 |
| | | 1 | 24 | 24.52 | 26.0 |
| | | 1 | 49 | 25.05 | 26.0 |
| | | 25 | 0 | 24.22 | 26.0 |
| | | 25 | 12 | 23.94 | 26.0 |
| | | 25 | 25 | 24.04 | 26.0 |
| | | 50 | 0 | 24.11 | 26.0 |
| | HCH | 1 | 0 | 25.12 | 26.0 |
| | | 1 | 24 | 25.73 | 26.0 |
| | | 1 | 49 | 25.73 | 26.0 |
| | | 25 | 0 | 24.25 | 26.0 |
| | | 25 | 12 | 24.66 | 26.0 |
| | | 25 | 25 | 24.97 | 26.0 |
| | | 50 | 0 | 24.52 | 26.0 |
| 16QAM | LCH | 1 | 0 | 24.06 | 26.0 |
| | | 1 | 24 | 24.96 | 26.0 |
| | | 1 | 49 | 25.10 | 26.0 |

| | | | | | |
|--|-----|----|----|-------|------|
| | | 25 | 0 | 22.75 | 26.0 |
| | | 25 | 12 | 22.93 | 26.0 |
| | | 25 | 25 | 23.11 | 26.0 |
| | | 50 | 0 | 22.96 | 26.0 |
| | MCH | 1 | 0 | 24.92 | 26.0 |
| | | 1 | 24 | 24.23 | 26.0 |
| | | 1 | 49 | 24.27 | 26.0 |
| | | 25 | 0 | 23.17 | 26.0 |
| | | 25 | 12 | 22.85 | 26.0 |
| | | 25 | 25 | 22.90 | 26.0 |
| | | 50 | 0 | 23.17 | 26.0 |
| | HCH | 1 | 0 | 24.51 | 26.0 |
| | | 1 | 24 | 25.70 | 26.0 |
| | | 1 | 49 | 25.64 | 26.0 |
| | | 25 | 0 | 23.10 | 26.0 |
| | | 25 | 12 | 23.51 | 26.0 |
| | | 25 | 25 | 23.61 | 26.0 |
| | | 50 | 0 | 23.38 | 26.0 |

Remark:

1. Per KDB941225 D05 v02r05, Start with the largest channel bandwidth then measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle, and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.
2. Per KDB941225 D05 v02r05, The procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.
3. Per KDB941225 D05 v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations, and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB941225 D05 v02r05, For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in 5.2.1, 5.2.2, and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

| WLAN - Maximum Average Power | | | | |
|------------------------------|-----------|---------|-----------------|---------------------|
| Test Mode | Data Rate | Channel | Frequency (MHz) | Average Power (dBm) |
| 802.11b | 11Mbps | CH 01 | 2412 | 11.49 |
| | | CH 06 | 2437 | 15.0 |
| | | CH 11 | 2462 | 11.12 |
| 802.11g | 54Mbps | CH 01 | 2412 | 11.66 |
| | | CH 06 | 2437 | 14.76 |
| | | CH 11 | 2462 | 11.19 |
| 802.11n (20MHz) | MCS7 | CH 01 | 2412 | 11.26 |
| | | CH 06 | 2437 | 14.96 |
| | | CH 11 | 2462 | 11.44 |
| 802.11n (40MHz) | MCS7 | CH 03 | 2422 | 9.53 |
| | | CH 06 | 2437 | 9.95 |
| | | CH 09 | 2452 | 10.8 |

Remark:

1. Per KDB 248227 D01 v02r02, For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions.
2. Per KDB 248227 D01 v02r02, For 802.11b DSSS SAR measurements ,when the reported SAR of the highest measured maximum output power channel (see 3.1) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration. When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.
- 3 .For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.

| Bluetooth - Maximum Average Power | | |
|-----------------------------------|-----------|--------------------|
| Test Mode | Data Rate | Average Power(dBm) |
| GFSK | 1Mbps | 4.24 |
| Pi/4 QDPSK | 2Mbps | 4.654 |
| 8DPSK | 3Mbps | 4.972 |

| Bluetooth - Maximum Average Power | | | | |
|-----------------------------------|-----------|---------|-----------------|---------------------|
| Test Mode | Data Rate | Channel | Frequency (MHz) | Average Power (dBm) |
| BLE | 1Mbps | CH 00 | 2402 | 0.288 |
| | | CH 19 | 2440 | 1.018 |
| | | CH 39 | 2480 | -2.742 |

Remark:

Bluetooth maximum output power is 4.972dBm, and Tune-Up output power is 5.0dBm. Per KDB 447498 D01 V06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

| Tune-Up Power (dBm) | Max. Power (mW) | Distance (mm) | Frequency (GHz) | Result | Limit |
|---------------------|-----------------|---------------|-----------------|--------|-------|
| 5.0 | 3.16 | 5 | 2.441 | 0.99 | 3 |

The exclusion thresholds is $0.99 < 3$, therefore, the RF exposure evaluation is not required.

9.2 Test Results for Standalone SAR Test

Body SAR

| GSM850 – Body SAR Test (Gap: 5mm) | | | | | | | | | |
|-----------------------------------|----------|--------------------|-----------|-------|--------------------|-------------------|----------------|--------------|---------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR1g (W/kg) | Scaled SAR1g (W/kg) |
| | | | CH. | MHz | | | | | |
| 1. | GPRS_4TX | Back Side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.3366 | 0.3533 |
| 2. | GPRS_4TX | Front Side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.5791 | 0.6078 |
| 3. | GPRS_4TX | Right side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.1392 | 0.1461 |
| 4. | GPRS_4TX | Left side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.6541 | 0.6865 |

| GSM1900 – Body SAR Test(Gap: 5mm) | | | | | | | | | |
|-----------------------------------|----------|--------------------|-----------|--------|--------------------|-------------------|----------------|--------------|---------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR1g (W/kg) | Scaled SAR1g (W/kg) |
| | | | CH. | MHz | | | | | |
| 5. | GPRS_4TX | Back Side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 1.0377 | 1.1068 |
| 6. | GPRS_4TX | Back Side | 512 | 1850.2 | 27.41 | 28.5 | 1.2853 | 0.8294 | 1.0660 |
| 7. | GPRS_4TX | Back Side | 661 | 1880.0 | 27.68 | 28.5 | 1.2078 | 0.8954 | 1.0815 |
| 8. | GPRS_4TX | Front Side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 0.1203 | 0.1283 |
| 9. | GPRS_4TX | Right side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 0.0474 | 0.0506 |
| 10. | GPRS_4TX | Left side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 0.4301 | 0.4587 |

| WCDMA Band 2 – Body SAR Test (Gap: 5mm) | | | | | | | | | |
|---|-----------|--------------------|-----------|--------|--------------------|-------------------|----------------|--------------|---------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR1g (W/kg) | Scaled SAR1g (W/kg) |
| | | | CH. | MHz | | | | | |
| 11. | RMC 12.2k | Back Side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.4307 | 0.4479 |
| 12. | RMC 12.2k | Front Side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.0686 | 0.0713 |
| 13. | RMC 12.2k | Right side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.0509 | 0.0529 |
| 14. | RMC 12.2k | Left side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.2223 | 0.2312 |

| WCDMA Band V – Body SAR Test (Gap: 5mm) | | | | | | | | | |
|---|-----------|--------------------|-----------|-------|--------------------|-------------------|----------------|--------------|---------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR1g (W/kg) | Scaled SAR1g (W/kg) |
| | | | CH. | MHz | | | | | |
| 15. | RMC 12.2k | Back Side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.1261 | 0.1348 |
| 16. | RMC 12.2k | Front Side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.1026 | 0.1097 |
| 17. | RMC 12.2k | Right side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.0062 | 0.0066 |
| 18. | RMC 12.2k | Left side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.2643 | 0.2826 |

| LTE Band 2–Body SAR Test(Gap: 5mm) | | | | | | | | |
|------------------------------------|---------------------------|--------------------|-----------|--------------------|-------------------|----------------|--------------|---------------------|
| Plot No. | Mode | Test Position Body | Frequency | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR1g (W/kg) | Scaled SAR1g (W/kg) |
| | Modulation, Bandwidth, RB | | MHz | | | | | |
| 19. | RMC QPSK 20MHz 1RB | Back Side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.7133 | 0.7948 |
| 20. | RMC QPSK 20MHz 1RB | Front Side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.0485 | 0.0540 |
| 21. | RMC QPSK 20MHz 1RB | Right side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.0723 | 0.0806 |
| 22. | RMC QPSK 20MHz 1RB | Left side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.0717 | 0.0799 |
| 23. | RMC QPSK 20MHz 50%RB | Back Side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.6546 | 0.6870 |
| 24. | RMC QPSK 20MHz 50%RB | Front Side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.0234 | 0.0246 |
| 25. | RMC QPSK 20MHz 50%RB | Right side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.0755 | 0.0792 |
| 26. | RMC QPSK 20MHz 50%RB | Left side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.0425 | 0.0446 |

| LTE Band 5–Body SAR Test (Gap: 5mm) | | | | | | | | |
|-------------------------------------|---------------------------|--------------------|-----------|--------------------|-------------------|----------------|--------------|---------------------|
| Plot No. | Mode | Test Position Body | Frequency | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR1g (W/kg) | Scaled SAR1g (W/kg) |
| | Modulation, Bandwidth, RB | | MHz | | | | | |
| 27. | RMC QPSK 10MHz 1RB | Back Side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.5600 | 0.5959 |
| 28. | RMC QPSK 10MHz 1RB | Front Side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.0444 | 0.0472 |
| 29. | RMC QPSK 10MHz 1RB | Right side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.0382 | 0.0407 |
| 30. | RMC QPSK 10MHz 1RB | Left side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.0304 | 0.0323 |
| 31. | RMC QPSK 10MHz 50%RB | Back Side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.4829 | 0.4862 |
| 32. | RMC QPSK 10MHz 50%RB | Front Side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.0333 | 0.0335 |
| 33. | RMC QPSK 10MHz 50%RB | Right side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.0213 | 0.0214 |
| 34. | RMC QPSK 10MHz 50%RB | Left side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.0103 | 0.0104 |

| WLAN 2.4GHz –Body SAR Test (Gap: 5mm) | | | | | | | | | |
|---------------------------------------|---------|--------------------|-----------|------|--------------------|-------------------|----------------|--------------|---------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR1g (W/kg) | Scaled SAR1g (W/kg) |
| | | | CH. | MHz | | | | | |
| 35. | 802.11b | Back Side | 06 | 2437 | 15.0 | 15.5 | 1.1220 | 0.1855 | 0.2081 |
| 36. | 802.11b | Front Side | 06 | 2437 | 15.0 | 15.5 | 1.1220 | 0.1290 | 0.1447 |
| 37. | 802.11b | Right side | 06 | 2437 | 15.0 | 15.5 | 1.1220 | 0.2239 | 0.2512 |

Remark: Per KDB 447498 D01 v06 , if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Hand SAR

| GSM850 – Body SAR Test(Gap: 0mm) | | | | | | | | | |
|----------------------------------|----------|--------------------|-----------|-------|--------------------|-------------------|----------------|----------------|-----------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR10 g (W/kg) | Scaled SAR10 g (W/kg) |
| | | | CH. | MHz | | | | | |
| 38. | GPRS_4TX | Back Side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.8652 | 0.9081 |
| 39. | GPRS_4TX | Front Side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.7075 | 0.7426 |
| 40. | GPRS_4TX | Right side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.3454 | 0.3625 |
| 41. | GPRS_4TX | Left side | 190 | 836.6 | 31.79 | 32.0 | 1.0495 | 0.8797 | 0.9233 |

| GSM1900 – Body SAR Test(Gap: 0mm) | | | | | | | | | |
|-----------------------------------|----------|--------------------|-----------|--------|--------------------|-------------------|----------------|----------------|-----------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR10 g (W/kg) | Scaled SAR10 g (W/kg) |
| | | | CH. | MHz | | | | | |
| 42. | GPRS_4TX | Back Side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 2.3014 | 2.4547 |
| 43. | GPRS_4TX | Back Side | 512 | 1850.2 | 27.41 | 28.5 | 1.2853 | 1.8525 | 2.3810 |
| 44. | GPRS_4TX | Back Side | 661 | 1880.0 | 27.68 | 28.5 | 1.2078 | 1.9783 | 2.3894 |
| 45. | GPRS_4TX | Front Side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 0.1776 | 0.1894 |
| 46. | GPRS_4TX | Right side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 0.0394 | 0.0420 |
| 47. | GPRS_4TX | Left side | 810 | 1909.8 | 28.22 | 28.5 | 1.0666 | 1.1566 | 1.2336 |

| WCDMA Band 2 – Body SAR Test (Gap: 0mm) | | | | | | | | | |
|---|-----------|--------------------|-----------|--------|--------------------|-------------------|----------------|----------------|-----------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR10 g (W/kg) | Scaled SAR10 g (W/kg) |
| | | | CH. | MHz | | | | | |
| 48. | RMC 12.2k | Back Side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.5708 | 0.5936 |
| 49. | RMC 12.2k | Front Side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.0444 | 0.0462 |
| 50. | RMC 12.2k | Right side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.0339 | 0.0353 |
| 51. | RMC 12.2k | Left side | 9262 | 1852.4 | 22.33 | 22.5 | 1.0399 | 0.2116 | 0.2200 |

| WCDMA Band V – Body SAR Test (Gap: 0mm) | | | | | | | | | |
|---|-----------|--------------------|-----------|-------|--------------------|-------------------|----------------|----------------|-----------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR10 g (W/kg) | Scaled SAR10 g (W/kg) |
| | | | CH. | MHz | | | | | |
| 52. | RMC 12.2k | Back Side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.1420 | 0.1518 |
| 53. | RMC 12.2k | Front Side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.1565 | 0.1673 |

| | | | | | | | | | |
|-----|-----------|------------|------|-------|-------|------|--------|--------|--------|
| 54. | RMC 12.2k | Right side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.0042 | 0.0045 |
| 55. | RMC 12.2k | Left side | 4183 | 836.6 | 22.21 | 22.5 | 1.0691 | 0.3084 | 0.3297 |

| LTE Band 2–Body SAR Test(Gap: 0mm) | | | | | | | | | |
|------------------------------------|---------------------------|--------------------|-----------|--------------------|-------------------|----------------|----------------|-----------------------|--|
| Plot No. | Mode | Test Position Body | Frequency | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR10 g (W/kg) | Scaled SAR10 g (W/kg) | |
| | Modulation, Bandwidth, RB | | MHz | | | | | | |
| 56. | RMC QPSK 20MHz 1RB | Back Side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.9165 | 1.0213 | |
| 57. | RMC QPSK 20MHz 1RB | Front Side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.0375 | 0.0418 | |
| 58. | RMC QPSK 20MHz 1RB | Right side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.0892 | 0.0994 | |
| 59. | RMC QPSK 20MHz 1RB | Left side | 1900.0 | 24.53 | 25.0 | 1.1143 | 0.1237 | 0.1378 | |
| 60. | RMC QPSK 20MHz 50%RB | Back Side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.7555 | 0.7929 | |
| 61. | RMC QPSK 20MHz 50%RB | Front Side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.0322 | 0.0338 | |
| 62. | RMC QPSK 20MHz 50%RB | Right side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.0644 | 0.0676 | |
| 63. | RMC QPSK 20MHz 50%RB | Left side | 1900.0 | 23.29 | 23.5 | 1.0495 | 0.1021 | 0.1072 | |

| LTE Band 5–Body SAR Test (Gap: 0mm) | | | | | | | | | |
|-------------------------------------|---------------------------|--------------------|-----------|--------------------|-------------------|----------------|----------------|-----------------------|--|
| Plot No. | Mode | Test Position Body | Frequency | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR10 g (W/kg) | Scaled SAR10 g (W/kg) | |
| | Modulation, Bandwidth, RB | | MHz | | | | | | |
| 64. | RMC QPSK 10MHz 1RB | Back Side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.8025 | 0.8540 | |
| 65. | RMC QPSK 10MHz 1RB | Front Side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.0753 | 0.0801 | |
| 66. | RMC QPSK 10MHz 1RB | Right side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.0410 | 0.0436 | |
| 67. | RMC QPSK 10MHz 1RB | Left side | 844.0 | 25.73 | 26.0 | 1.0641 | 0.0327 | 0.0348 | |
| 68. | RMC QPSK 10MHz 50%RB | Back Side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.6387 | 0.6431 | |
| 69. | RMC QPSK 10MHz 50%RB | Front Side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.0472 | 0.0475 | |
| 70. | RMC QPSK 10MHz 50%RB | Right side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.0322 | 0.0324 | |
| 71. | RMC QPSK 10MHz 50%RB | Left side | 844.0 | 24.97 | 25.0 | 1.0069 | 0.0280 | 0.0282 | |

| WLAN 2.4GHz –Body SAR Test (Gap: 0mm) | | | | | | | | | |
|---------------------------------------|---------|--------------------|-----------|------|--------------------|-------------------|----------------|----------------|-----------------------|
| Plot No. | Mode | Test Position Body | Frequency | | Output Power (dBm) | Rated Limit (dBm) | Scaling Factor | SAR10 g (W/kg) | Scaled SAR10 g (W/kg) |
| | | | CH. | MHz | | | | | |
| 72. | 802.11b | Back Side | 06 | 2437 | 15.0 | 15.5 | 1.1220 | 0.1394 | 0.1564 |
| 73. | 802.11b | Front Side | 06 | 2437 | 15.0 | 15.5 | 1.1220 | 0.0568 | 0.0637 |
| 74. | 802.11b | Right side | 06 | 2437 | 15.0 | 15.5 | 1.1220 | 0.2707 | 0.3037 |

Remark: Per KDB 447498 D01 v06 , if the highest output channel SAR for each exposure position ≤ 2.0 W/kg other channels SAR tests are not necessary.

9.3 Simultaneous Multi-band Transmission SAR Analysis

List of Mode for Simultaneous Multi-band Transmission

| No. | Configurations | Hand SAR | Body SAR |
|-----|--|----------|----------|
| 1 | GPRS/ EDGE(Data) + WLAN(2.4G)(Data) | Yes | Yes |
| 2 | WCDMA(Data)/HSDPA(Data)/ HSUPA(Data)+WLAN(2.4G)(Data) | Yes | Yes |
| 3 | LTE(Data) + WLAN(2.4G)(Data) | Yes | Yes |
| 4 | GPRS/ EDGE(Data) + Bluetooth(Data) | Yes | Yes |
| 5 | WCDMA(Data)/HSDPA(Data)/ HSUPA(Data) + Bluetooth(Data) | Yes | Yes |
| 6 | LTE(Data) + Bluetooth(Data) | Yes | Yes |

Remark:

1. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. According to the KDB 447498 D01v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]- $\sqrt{f(\text{GHz})/x}$ W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v06 as below:

Bluetooth:

| Tune-Up Power (dBm) | Max. Power (mW) | Distance (mm) | Frequency (GHz) | X | SAR(1g) 5mm | SAR(10g) 5mm |
|---------------------|-----------------|---------------|-----------------|-----------|-------------|--------------|
| 5.0 | 3.16 | 5 | 2.441 | 7.5/18.75 | 0.1317 | 0.0527 |

3. The maximum SAR summation is calculated based on the same configuration and test position.

Body SAR

WWAN and WLAN

| Position | WWAN | | WLAN | Summed SAR (W/kg) |
|-------------|--------------|----------------------|----------------------|----------------------|
| | Band | Scaled SAR (W/kg) | Scaled SAR (W/kg) | |
| Back | GSM850 | 0.3533 | 0.2081 | 0.5614 |
| Front | GSM850 | 0.6078 | 0.1447 | 0.7525 |
| Top side | GSM850 | -- | -- | -- |
| Bottom side | GSM850 | -- | -- | -- |
| Right side | GSM850 | 0.1461 | 0.2512 | 0.3973 |
| Left side | GSM850 | 0.6865 | -- | 0.6865 |
| Back | GSM1900 | 1.1068 | 0.2081 | 1.3149 |
| Front | GSM1900 | 0.1283 | 0.1447 | 0.273 |
| Top side | GSM1900 | -- | -- | -- |
| Bottom side | GSM1900 | -- | -- | -- |
| Right side | GSM1900 | 0.0506 | 0.2512 | 0.3018 |
| Left side | GSM1900 | 0.4587 | -- | 0.4587 |
| Back | WCDMA Band 2 | 0.4479 | 0.2081 | 0.656 |
| Front | WCDMA Band 2 | 0.0713 | 0.1447 | 0.216 |
| Top side | WCDMA Band 2 | -- | -- | -- |
| Bottom side | WCDMA Band 2 | -- | -- | -- |
| Right side | WCDMA Band 2 | 0.0529 | 0.2512 | 0.3041 |
| Left side | WCDMA Band 2 | 0.2312 | -- | 0.2312 |
| Back | WCDMA Band 5 | 0.1348 | 0.2081 | 0.3429 |
| Front | WCDMA Band 5 | 0.1097 | 0.1447 | 0.2544 |
| Top side | WCDMA Band 5 | -- | -- | -- |
| Bottom side | WCDMA Band 5 | -- | -- | -- |
| Right side | WCDMA Band 5 | 0.0066 | 0.2512 | 0.2578 |
| Left side | WCDMA Band 5 | 0.2826 | -- | 0.2826 |
| Back | LTE Band 2 | 0.7948 | 0.2081 | 1.0029 |
| Front | LTE Band 2 | 0.0540 | 0.1447 | 0.1987 |
| Top side | LTE Band 2 | -- | -- | -- |
| Bottom side | LTE Band 2 | -- | -- | -- |
| Right side | LTE Band 2 | 0.0806 | 0.2512 | 0.3318 |
| Left side | LTE Band 2 | 0.0799 | -- | 0.0799 |
| Back | LTE Band 5 | 0.5959 | 0.2081 | 0.804 |
| Front | LTE Band 5 | 0.0472 | 0.1447 | 0.1919 |
| Top side | LTE Band 5 | -- | -- | -- |
| Bottom side | LTE Band 5 | -- | -- | -- |
| Right side | LTE Band 5 | 0.0407 | 0.2512 | 0.2919 |
| Left side | LTE Band 5 | 0.0323 | -- | 0.0323 |

WWAN and Bluetooth

| | WWAN | | Bluetooth | Summed SAR (W/kg) |
|-----------------|--------------|------------------------------|------------------------------|------------------------------|
| Position | Band | Scaled SAR (W/kg) | Scaled SAR (W/kg) | |
| Back | GSM850 | 0.3533 | 0.1317 | 0.485 |
| Front | GSM850 | 0.6078 | 0.1317 | 0.7395 |
| Top side | GSM850 | -- | -- | -- |
| Bottom side | GSM850 | -- | -- | -- |
| Right side | GSM850 | 0.1461 | 0.1317 | 0.2778 |
| Left side | GSM850 | 0.6865 | -- | 0.6865 |
| Back | GSM1900 | 1.1068 | 0.1317 | 1.2385 |
| Front | GSM1900 | 0.1283 | 0.1317 | 0.26 |
| Top side | GSM1900 | -- | -- | -- |
| Bottom side | GSM1900 | -- | -- | -- |
| Right side | GSM1900 | 0.0506 | 0.1317 | 0.1823 |
| Left side | GSM1900 | 0.4587 | -- | 0.4587 |
| Back | WCDMA Band 2 | 0.4479 | 0.1317 | 0.5796 |
| Front | WCDMA Band 2 | 0.0713 | 0.1317 | 0.203 |
| Top side | WCDMA Band 2 | -- | -- | -- |
| Bottom side | WCDMA Band 2 | -- | -- | -- |
| Right side | WCDMA Band 2 | 0.0529 | 0.1317 | 0.1846 |
| Left side | WCDMA Band 2 | 0.2312 | -- | 0.2312 |
| Back | WCDMA Band 5 | 0.1348 | 0.1317 | 0.2665 |
| Front | WCDMA Band 5 | 0.1097 | 0.1317 | 0.2414 |
| Top side | WCDMA Band 5 | -- | -- | -- |
| Bottom side | WCDMA Band 5 | -- | -- | -- |
| Right side | WCDMA Band 5 | 0.0066 | 0.1317 | 0.1383 |
| Left side | WCDMA Band 5 | 0.2826 | -- | 0.2826 |
| Back | LTE Band 2 | 0.7948 | 0.1317 | 0.9265 |
| Front | LTE Band 2 | 0.0540 | 0.1317 | 0.1857 |
| Top side | LTE Band 2 | -- | -- | -- |
| Bottom side | LTE Band 2 | -- | -- | -- |
| Right side | LTE Band 2 | 0.0806 | 0.1317 | 0.2123 |
| Left side | LTE Band 2 | 0.0799 | -- | 0.0799 |
| Back | LTE Band 5 | 0.5959 | 0.1317 | 0.7276 |
| Front | LTE Band 5 | 0.0472 | 0.1317 | 0.1789 |
| Top side | LTE Band 5 | -- | -- | -- |
| Bottom side | LTE Band 5 | -- | -- | -- |
| Right side | LTE Band 5 | 0.0407 | 0.1317 | 0.1724 |
| Left side | LTE Band 5 | 0.0323 | -- | 0.0323 |

Hand SAR

WWAN and WLAN

| Position | WWAN | | WLAN | Summed SAR (W/kg) |
|-------------|--------------|----------------------|----------------------|----------------------|
| | Band | Scaled SAR (W/kg) | Scaled SAR (W/kg) | |
| Back | GSM850 | 0.9081 | 0.1564 | 1.0645 |
| Front | GSM850 | 0.7426 | 0.0637 | 0.8063 |
| Top side | GSM850 | -- | -- | -- |
| Bottom side | GSM850 | -- | -- | -- |
| Right side | GSM850 | 0.3625 | 0.3037 | 0.6662 |
| Left side | GSM850 | 0.9233 | -- | 0.9233 |
| Back | GSM1900 | 2.4547 | 0.1564 | 2.6111 |
| Front | GSM1900 | 0.1894 | 0.0637 | 0.2531 |
| Top side | GSM1900 | -- | -- | -- |
| Bottom side | GSM1900 | -- | -- | -- |
| Right side | GSM1900 | 0.0420 | 0.3037 | 0.3457 |
| Left side | GSM1900 | 1.2336 | -- | 1.2336 |
| Back | WCDMA Band 2 | 0.5936 | 0.1564 | 0.75 |
| Front | WCDMA Band 2 | 0.0462 | 0.0637 | 0.1099 |
| Top side | WCDMA Band 2 | -- | -- | -- |
| Bottom side | WCDMA Band 2 | -- | -- | -- |
| Right side | WCDMA Band 2 | 0.0353 | 0.3037 | 0.339 |
| Left side | WCDMA Band 2 | 0.2200 | -- | 0.2200 |
| Back | WCDMA Band 5 | 0.1518 | 0.1564 | 0.3082 |
| Front | WCDMA Band 5 | 0.1673 | 0.0637 | 0.231 |
| Top side | WCDMA Band 5 | -- | -- | -- |
| Bottom side | WCDMA Band 5 | -- | -- | -- |
| Right side | WCDMA Band 5 | 0.0045 | 0.3037 | 0.3082 |
| Left side | WCDMA Band 5 | 0.3297 | -- | 0.3297 |
| Back | LTE Band 2 | 1.0213 | 0.1564 | 1.1777 |
| Front | LTE Band 2 | 0.0418 | 0.0637 | 0.1055 |
| Top side | LTE Band 2 | -- | -- | -- |
| Bottom side | LTE Band 2 | -- | -- | -- |
| Right side | LTE Band 2 | 0.0994 | 0.3037 | 0.4031 |
| Left side | LTE Band 2 | 0.1378 | -- | 0.1378 |
| Back | LTE Band 5 | 0.8540 | 0.1564 | 1.0104 |
| Front | LTE Band 5 | 0.0801 | 0.0637 | 0.1438 |
| Top side | LTE Band 5 | -- | -- | -- |
| Bottom side | LTE Band 5 | -- | -- | -- |
| Right side | LTE Band 5 | 0.0436 | 0.3037 | 0.3473 |
| Left side | LTE Band 5 | 0.0348 | -- | 0.0348 |

WWAN and Bluetooth

| | WWAN | | Bluetooth | Summed SAR (W/kg) |
|-------------|--------------|----------------------|----------------------|----------------------|
| Position | Band | Scaled SAR (W/kg) | Scaled SAR (W/kg) | |
| Back | GSM850 | 0.9081 | 0.0527 | 0.9608 |
| Front | GSM850 | 0.7426 | 0.0527 | 0.7953 |
| Top side | GSM850 | -- | -- | -- |
| Bottom side | GSM850 | -- | -- | -- |
| Right side | GSM850 | 0.3625 | 0.0527 | 0.4152 |
| Left side | GSM850 | 0.9233 | -- | 0.9233 |
| Back | GSM1900 | 2.4547 | 0.0527 | 2.5074 |
| Front | GSM1900 | 0.1894 | 0.0527 | 0.2421 |
| Top side | GSM1900 | -- | -- | -- |
| Bottom side | GSM1900 | -- | -- | -- |
| Right side | GSM1900 | 0.0420 | 0.0527 | 0.0947 |
| Left side | GSM1900 | 1.2336 | -- | 1.2336 |
| Back | WCDMA Band 2 | 0.5936 | 0.0527 | 0.6463 |
| Front | WCDMA Band 2 | 0.0462 | 0.0527 | 0.0989 |
| Top side | WCDMA Band 2 | -- | -- | -- |
| Bottom side | WCDMA Band 2 | -- | -- | -- |
| Right side | WCDMA Band 2 | 0.0353 | 0.0527 | 0.088 |
| Left side | WCDMA Band 2 | 0.2200 | -- | 0.2200 |
| Back | WCDMA Band 5 | 0.1518 | 0.0527 | 0.2045 |
| Front | WCDMA Band 5 | 0.1673 | 0.0527 | 0.22 |
| Top side | WCDMA Band 5 | -- | -- | -- |
| Bottom side | WCDMA Band 5 | -- | -- | -- |
| Right side | WCDMA Band 5 | 0.0045 | 0.0527 | 0.0572 |
| Left side | WCDMA Band 5 | 0.3297 | -- | 0.3297 |
| Back | LTE Band 2 | 1.0213 | 0.0527 | 1.074 |
| Front | LTE Band 2 | 0.0418 | 0.0527 | 0.0945 |
| Top side | LTE Band 2 | -- | -- | -- |
| Bottom side | LTE Band 2 | -- | -- | -- |
| Right side | LTE Band 2 | 0.0994 | 0.0527 | 0.1521 |
| Left side | LTE Band 2 | 0.1378 | -- | 0.1378 |
| Back | LTE Band 5 | 0.8540 | 0.0527 | 0.9067 |
| Front | LTE Band 5 | 0.0801 | 0.0527 | 0.1328 |
| Top side | LTE Band 5 | -- | -- | -- |
| Bottom side | LTE Band 5 | -- | -- | -- |
| Right side | LTE Band 5 | 0.0436 | 0.0527 | 0.0963 |
| Left side | LTE Band 5 | 0.0348 | -- | 0.0348 |

10. Measurement Uncertainty

10.1 Uncertainty for EUT SAR Test

| a | b | c | d | e= f(d,k) | f | g | h= c*f/e | i= c*g/e | k |
|---|-------|---------------|----------------|------------|------------------|------------------|-----------------|------------------|----------|
| Uncertainty Component | Sec. | Tol (+- %) | Prob. Dist. | Div. | Ci (1g) | Ci (10g) | 1g Ui (+- %) | 10g Ui (+- %) | Vi |
| Measurement System | | | | | | | | | |
| Probe calibration | E.2.1 | 7.0 | N | 1 | 1 | 1 | 7.00 | 7.00 | ∞ |
| Axial Isotropy | E.2.2 | 2.5 | R | $\sqrt{3}$ | $(1_{Cp})^{1/2}$ | $(1_{Cp})^{1/2}$ | 1.02 | 1.02 | ∞ |
| Hemispherical Isotropy | E.2.2 | 4.0 | R | $\sqrt{3}$ | $(Cp)^{1/2}$ | $(Cp)^{1/2}$ | 1.63 | 1.63 | ∞ |
| Boundary effect | E.2.3 | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | ∞ |
| Linearity | E.2.4 | 5.0 | R | $\sqrt{3}$ | 1 | 1 | 2.89 | 2.89 | ∞ |
| System detection limits | E.2.5 | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | ∞ |
| Readout Electronics | E.2.6 | 0.02 | N | 1 | 1 | 1 | 0.02 | 0.02 | ∞ |
| Reponse Time | E.2.7 | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ∞ |
| Integration Time | E.2.8 | 2.0 | R | $\sqrt{3}$ | 1 | 1 | 1.15 | 1.15 | ∞ |
| RF ambient Conditions – Noise | E.6.1 | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ∞ |
| RF ambient Conditions - Reflections | E.6.1 | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ∞ |
| Probe positioner Mechanical Tolerance | E.6.2 | 2.0 | R | $\sqrt{3}$ | 1 | 1 | 1.15 | 1.15 | ∞ |
| Probe positioning with respect to Phantom Shell | E.6.3 | 0.05 | R | $\sqrt{3}$ | 1 | 1 | 0.03 | 0.03 | ∞ |
| Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation | E.5 | 5.0 | R | $\sqrt{3}$ | 1 | 1 | 2.89 | 2.89 | ∞ |
| Test Sample Related | | | | | | | | | |
| Test sample positioning | E.4.2 | 0.03 | N | 1 | 1 | 1 | 0.03 | 0.03 | N-1 |
| Device Holder Uncertainty | E.4.1 | 5.00 | N | 1 | 1 | 1 | 5.00 | 5.00 | |
| Output power Variation - SAR drift measurement | E.2.9 | 12.02 | R | $\sqrt{3}$ | 1 | 1 | 6.94 | 6.94 | ∞ |
| SAR scaling | E6.5 | 0.0 | R | $\sqrt{3}$ | 1 | 1 | 0.0 | 0.0 | ∞ |
| Phantom and Tissue Parameters | | | | | | | | | |
| Phantom Uncertainty (Shape and thickness tolerances) | E.3.1 | 0.05 | R | $\sqrt{3}$ | 1 | 1 | 0.03 | 0.03 | ∞ |
| Uncertainty in SAR correction for deviations in permittivity and conductivity | E3.2 | 1.9 | R | $\sqrt{3}$ | 1 | 0.84 | 1.10 | 0.90 | ∞ |
| Liquid conductivity - deviation | E.3.2 | 5.00 | R | $\sqrt{3}$ | 0.64 | 0.43 | 1.85 | 1.24 | ∞ |

| | | | | | | | | | | |
|---|-------|-------|-----|------------|------|------|-------|-------|----------|--|
| from target value | | | | | | | | | | |
| Liquid conductivity measurement uncertainty - | E.3.3 | 5.00 | N | 1 | 0.64 | 0.43 | 3.20 | 2.15 | ∞ | |
| Liquid permittivity - deviation from target value | E.3.2 | 0.37 | R | $\sqrt{3}$ | 0.6 | 0.49 | 0.13 | 0.10 | ∞ | |
| Liquid permittivity measurement uncertainty - | E.3.3 | 10.00 | N | 1 | 0.6 | 0.49 | 6.00 | 4.90 | ∞ | |
| Combined Standard Uncertainty | | | RSS | | | | 12.98 | 12.53 | | |
| Expanded Uncertainty (95% Confidence interval) | | | K=2 | | | | 25.32 | 24.43 | | |

10.2 Uncertainty for System Performance Check

| a | b | c | d | e= f(d,k) | f | g | h= c*f/e | i= c*g/e | k |
|--|-------|-------------|-------------|------------|-----------------|-----------------|---------------|----------------|----------|
| Uncertainty Component | Sec. | Tol (+ - %) | Prob. Dist. | Div. | Ci (1g) | Ci (10g) | 1g Ui (+ - %) | 10g Ui (+ - %) | Vi |
| Measurement System | | | | | | | | | |
| Probe calibration | E.2.1 | 7.0 | N | 1 | 1 | 1 | 7.00 | 7.00 | ∞ |
| Axial Isotropy | E.2.2 | 2.5 | R | $\sqrt{3}$ | $(1_Cp)^{1/2}$ | $(1_Cp)^{1/2}$ | 1.02 | 1.02 | ∞ |
| Hemispherical Isotropy | E.2.2 | 4.0 | R | $\sqrt{3}$ | $(Cp)^{1/2}$ | $(Cp)^{1/2}$ | 1.63 | 1.63 | ∞ |
| Boundary effect | E.2.3 | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | ∞ |
| Linearity | E.2.4 | 5.0 | R | $\sqrt{3}$ | 1 | 1 | 2.89 | 2.89 | ∞ |
| System detection limits | E.2.5 | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | ∞ |
| Modulation response | E.2.5 | 0 | R | $\sqrt{3}$ | 0 | 0 | 0.0 | 0.0 | ∞ |
| Readout Electronics | E.2.6 | 0.02 | N | 1 | 1 | 1 | 0.02 | 0.02 | ∞ |
| Reponse Time | E.2.7 | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ∞ |
| Integration Time | E.2.8 | 2.0 | R | $\sqrt{3}$ | 1 | 1 | 1.15 | 1.15 | ∞ |
| RF ambient Conditions – Noise | E.6.1 | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ∞ |
| RF ambient Conditions - Reflections | E.6.1 | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ∞ |
| Probe positioner Mechanical Tolerance | E.6.2 | 2.0 | R | $\sqrt{3}$ | 1 | 1 | 1.15 | 1.15 | ∞ |
| Probe positioning with respect to Phantom Shell | E.6.3 | 0.05 | R | $\sqrt{3}$ | 1 | 1 | 0.03 | 0.03 | ∞ |
| Extrapolation, interpolation and integration Algorithms for Max. | E.5.2 | 5.0 | R | $\sqrt{3}$ | 1 | 1 | 2.89 | 2.89 | ∞ |

| | | | | | | | | | |
|---|---------|-------|-----|------------|------|------|-------|-------|----------|
| SAR Evaluation | | | | | | | | | |
| Dipole | | | | | | | | | |
| Dipole axis to liquid Distance | 8,E.4.2 | 1.00 | N | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | N-1 |
| Input power and SAR drift measurement | 8,6.6.2 | 12.02 | R | $\sqrt{3}$ | 1 | 1 | 6.94 | 6.94 | ∞ |
| Deviation of experimental dipole from numerical dipole | E.6.4 | 5.5 | R | $\sqrt{3}$ | 1 | 1 | 3.20 | 3.20 | ∞ |
| Phantom and Tissue Parameters | | | | | | | | | |
| Phantom Uncertainty (Shape and thickness tolerances) | E.3.1 | 0.05 | R | $\sqrt{3}$ | 1 | 1 | 0.03 | 0.03 | ∞ |
| Uncertainty in SAR correction for deviations in permittivity and conductivity | E.3.2 | 2.0 | R | $\sqrt{3}$ | 1 | 0.84 | 1.10 | 1.10 | ∞ |
| Liquid conductivity - deviation from target value | E.3.2 | 5.00 | R | $\sqrt{3}$ | 0.64 | 0.43 | 1.85 | 1.24 | |
| Liquid conductivity - measurement uncertainty | E.3.3 | 5.00 | N | 1 | 0.64 | 0.43 | 3.20 | 2.15 | |
| Liquid permittivity - deviation from target value | E.3.2 | 0.37 | R | $\sqrt{3}$ | 0.6 | 0.49 | 0.13 | 0.10 | |
| Liquid permittivity - measurement uncertainty | E.3.3 | 10.00 | N | 1 | 0.6 | 0.49 | 6.00 | 4.90 | M |
| Combined Standard Uncertainty | | | RSS | | | | 12.00 | 11.50 | |
| Expanded Uncertainty (95% Confidence interval) | | | K=2 | | | | 23.39 | 22.43 | |

Annex A. Plots of System Performance Check

MEASUREMENT 1

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|------------------|
| Area Scan | dx=8mm dy=8mm |
| Phantom | Validation plane |
| Device Position | Dipole |
| Band | CW835 |
| Signal | Duty Cycle 1:1 |

B. SAR Measurement Results

| | |
|-----------------------------------|------------|
| Frequency (MHz) | 835.000000 |
| Relative Permittivity (real part) | 54.851214 |
| Conductivity (S/m) | 0.951454 |
| Power Variation (%) | 0.901472 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |






Maximum location: X=0.00, Y=0.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 1.438956 |
| SAR 1g (W/Kg) | 2.354211 |

Z Axis Scan

| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 | 24.00 | 29.00 |
|------------|--------|--------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.0000 | 2.5789 | 1.1300 | 0.8795 | 0.5940 | 0.5011 | 0.5100 |



| 3D screen shot | Hot spot position |
|---|--|
|  |  |

MEASUREMENT 2

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|------------------|
| Area Scan | dx=8mm dy=8mm |
| Phantom | Validation plane |
| Device Position | Dipole |
| Band | CW1900 |
| Signal | Duty Cycle 1:1 |

B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 1900.000000 |
| Relative Permittivity (real part) | 52.420415 |
| Conductivity (S/m) | 1.501966 |
| Power Variation (%) | 0.541872 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |






Maximum location: X=0.00, Y=0.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 5.134651 |
| SAR 1g (W/Kg) | 9.781550 |

Z Axis Scan

| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 | 24.00 | 29.00 |
|------------|--------|---------|---------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.0000 | 10.2031 | 6.43001 | 4.9011 | 4.5325 | 3.1201 | 2.5024 |



| 3D screen shot | Hot spot position |
|---|--|
|  |  |

MEASUREMENT 3

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|------------------|
| Area Scan | dx=8mm dy=8mm |
| Phantom | Validation plane |
| Device Position | Dipole |
| Band | CW2450 |
| Signal | Duty Cycle 1:1 |

B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 2450.000000 |
| Relative Permittivity (real part) | 52.010212 |
| Conductivity (S/m) | 1.910255 |
| Power Variation (%) | 1.369745 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.2 |






Maximum location: X=0.00, Y=0.00

| | |
|----------------|-----------|
| SAR 10g (W/Kg) | 6.119522 |
| SAR 1g (W/Kg) | 12.592360 |

Z Axis Scan

| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 | 24.00 | 29.00 |
|------------|--------|---------|---------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.0000 | 13.3911 | 11.7951 | 9.2945 | 8.5400 | 6.3712 | 4.6225 |



| 3D screen shot | Hot spot position |
|---|--|
|  |  |

Annex B. Plots of SAR Measurement

Body mode Exposure Conditions:

| <u>TYPE</u> | <u>BAND</u> | <u>PARAMETERS</u> |
|---|----------------|--|
| Tablet | GPRS850_4TX | Measurement 4: Flat Plane with Left device position on Middle Channel in GPRS mode |
| Tablet | GPRS1900_4TX | Measurement 5: Flat Plane with Back device position on High Channel in GPRS mode |
| Tablet | WCDMA1900_RMC | Measurement 11: Flat Plane with Back side device position on Low Channel in WCDMA mode |
| Tablet | WCDMA850_RMC | Measurement 18: Flat Plane with Left device position on Middle Channel in WCDMA mode |
| Tablet | LTE Band 2_RMC | Measurement 19: Flat Plane with Back device position on High Channel in LTE mode |
| Tablet | LTE Band 5_RMC | Measurement 27: Flat Plane with Back device position on High Channel in LTE mode |
| Tablet | WiFi_802.11b | Measurement 37: Flat Plane with Right side device position on Middle Channel in 802.11b mode |
| Remark: SAR plot is showed the highest measured SAR in each exposure configuration, wireless mode and frequency band combination. | | |

Hand exposure Conditions:

| <u>TYPE</u> | <u>BAND</u> | <u>PARAMETERS</u> |
|---|----------------|--|
| Tablet | GPRS850_4TX | Measurement 41: Flat Plane with Left device position on Middle Channel in GPRS mode |
| Tablet | GPRS1900_4TX | Measurement 42: Flat Plane with Back device position on High Channel in GPRS mode |
| Tablet | WCDMA1900_RMC | Measurement 48: Flat Plane with Back side device position on Low Channel in WCDMA mode |
| Tablet | WCDMA850_RMC | Measurement 55: Flat Plane with Left device position on Middle Channel in WCDMA mode |
| Tablet | LTE Band 2_RMC | Measurement 56: Flat Plane with Back device position on High Channel in LTE mode |
| Tablet | LTE Band 5_RMC | Measurement 64: Flat Plane with Back device position on High Channel in LTE mode |
| Tablet | WiFi_802.11b | Measurement 74: Flat Plane with Right side device position on Middle Channel in 802.11b mode |
| Remark: SAR plot is showed the highest measured SAR in each exposure configuration, wireless mode and frequency band combination. | | |

MEASUREMENT 4

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat plane |
| Device Position | Left |
| Band | GPRS850_4TX |
| Channels | Middle |
| Signal | Duty Cycle: 1:2 |



B. SAR Measurement Results

| | |
|-----------------------------------|------------|
| Frequency (MHz) | 836.600000 |
| Relative Permittivity (real part) | 54.851214 |
| Conductivity (S/m) | 0.951454 |
| Power Variation (%) | 0.901472 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=24.00, Y=-17.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.425806 |
| SAR 1g (W/Kg) | 0.654051 |



MEASUREMENT 5

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat plane |
| Device Position | Back |
| Band | GPRS1900_4TX |
| Channels | High |
| Signal | Duty Cycle: 1:2 |



B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 1909.800000 |
| Relative Permittivity (real part) | 52.420415 |
| Conductivity (S/m) | 1.501966 |
| Power Variation (%) | 2.483762 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=-7.00, Y=-7.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.529841 |
| SAR 1g (W/Kg) | 1.037659 |



MEASUREMENT 11

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Back |
| Band | WCDMA1900_RMC |
| Channels | Low |
| Signal | Duty Cycle 1:1 |

B. SAR Measurement Results


| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 1852.400000 |
| Relative Permittivity (real part) | 52.420415 |
| Conductivity (S/m) | 1.501966 |
| Power Variation (%) | 1.847552 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |





Maximum location: X=0.00, Y=-1.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.232113 |
| SAR 1g (W/Kg) | 0.430717 |

| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
| SAR (W/Kg) | 0.0000 | 0.4644 | 0.2502 | 0.1353 | 0.0770 |



| 3D screen shot | Hot spot position |
|---|---|
|  |  |

MEASUREMENT 18

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Left |
| Band | WCDMA850_RMC |
| Channels | Middle |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|------------|
| Frequency (MHz) | 836.600000 |
| Relative Permittivity (real part) | 54.851214 |
| Conductivity (S/m) | 0.951454 |
| Power Variation (%) | 0.754261 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=25.00, Y=-18.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.174224 |
| SAR 1g (W/Kg) | 0.264269 |



MEASUREMENT 19

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Back |
| Band | LTE Band 2_RMC |
| Channels | QPSK, 20MHz, 1RB, High |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 1900.000000 |
| Relative Permittivity (real part) | 52.420415 |
| Conductivity (S/m) | 1.501966 |
| Power Variation (%) | 1.523573 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=1.00, Y=-1.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.406556 |
| SAR 1g (W/Kg) | 0.713320 |



MEASUREMENT 27

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Back |
| Band | LTE Band 5_RMC |
| Channels | QPSK, 10MHz, 1RB, High |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|------------|
| Frequency (MHz) | 844.000000 |
| Relative Permittivity (real part) | 54.851214 |
| Conductivity (S/m) | 0.951454 |
| Power Variation (%) | 1.523573 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=-3.00, Y=-3.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.383055 |
| SAR 1g (W/Kg) | 0.560037 |



MEASUREMENT 37

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Right |
| Band | WiFi_802.11b |
| Channels | Middle |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 2437.000000 |
| Relative Permittivity (real part) | 52.010212 |
| Conductivity (S/m) | 1.910255 |
| Power Variation (%) | 0.462345 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.2 |



Maximum location: X=6.00, Y=2.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.108961 |
| SAR 1g (W/Kg) | 0.223929 |



MEASUREMENT 41

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat plane |
| Device Position | Left |
| Band | GPRS850_4TX |
| Channels | Middle |
| Signal | Duty Cycle: 1:2 |



B. SAR Measurement Results

| | |
|-----------------------------------|------------|
| Frequency (MHz) | 836.600000 |
| Relative Permittivity (real part) | 54.851214 |
| Conductivity (S/m) | 0.951454 |
| Power Variation (%) | 0.748393 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=31.00, Y=-31.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.879690 |
| SAR 1g (W/Kg) | 1.477145 |



MEASUREMENT 42

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat plane |
| Device Position | Back |
| Band | GPRS1900_4TX |
| Channels | High |
| Signal | Duty Cycle: 1:2 |



B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 1909.800000 |
| Relative Permittivity (real part) | 52.420415 |
| Conductivity (S/m) | 1.501966 |
| Power Variation (%) | 1.048393 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=1.00, Y=-7.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 2.301412 |
| SAR 1g (W/Kg) | 5.385323 |



MEASUREMENT 48

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Back |
| Band | WCDMA1900_RMC |
| Channels | Low |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 1852.400000 |
| Relative Permittivity (real part) | 52.420415 |
| Conductivity (S/m) | 1.501966 |
| Power Variation (%) | 1.546637 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=0.00, Y=-6.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.570831 |
| SAR 1g (W/Kg) | 1.270153 |



MEASUREMENT 55

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Left |
| Band | WCDMA850_RMC |
| Channels | Middle |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|------------|
| Frequency (MHz) | 836.600000 |
| Relative Permittivity (real part) | 54.851214 |
| Conductivity (S/m) | 0.951454 |
| Power Variation (%) | 0.983832 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=31.00, Y=-20.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.308424 |
| SAR 1g (W/Kg) | 0.478701 |



MEASUREMENT 56

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Back |
| Band | LTE Band 2_RMC |
| Channels | QPSK, 20MHz, 1RB, High |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 1900.000000 |
| Relative Permittivity (real part) | 52.420415 |
| Conductivity (S/m) | 1.501966 |
| Power Variation (%) | 1.393909 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=0.00, Y=0.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.916516 |
| SAR 1g (W/Kg) | 1.909501 |



MEASUREMENT 64

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13 Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Back |
| Band | LTE Band 5_RMC |
| Channels | QPSK, 10MHz, 1RB, High |
| Signal | Duty Cycle 1:1 |



B. SAR Measurement Results

| | |
|-----------------------------------|------------|
| Frequency (MHz) | 844.000000 |
| Relative Permittivity (real part) | 54.851214 |
| Conductivity (S/m) | 0.951454 |
| Power Variation (%) | 1.291911 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.3 |



Maximum location: X=-8.00, Y=-8.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.802490 |
| SAR 1g (W/Kg) | 1.240834 |



MEASUREMENT 74

Type: Phone measurement (Complete)

Date of measurement: 05/15/2017

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/01/2016

A. Experimental conditions

| | |
|-----------------|-------------------------------|
| Area Scan | sam_direct_droit2_surf8mm.txt |
| Phantom | Flat Plane |
| Device Position | Right |
| Band | WiFi_802.11b |
| Channels | Middle |
| Signal | Duty Cycle 1:1 |

B. SAR Measurement Results


| | |
|-----------------------------------|-------------|
| Frequency (MHz) | 2437.000000 |
| Relative Permittivity (real part) | 52.010212 |
| Conductivity (S/m) | 1.910255 |
| Power Variation (%) | 0.498890 |
| Ambient Temperature | 21.1 |
| Liquid Temperature | 21.2 |





Maximum location: X=13.00, Y=3.00

| | |
|----------------|----------|
| SAR 10g (W/Kg) | 0.270743 |
| SAR 1g (W/Kg) | 0.579573 |

| | | | | | |
|------------|--------|--------|--------|--------|--------|
| Z (mm) | 0.00 | 4.00 | 9.00 | 14.00 | 19.00 |
| SAR (W/Kg) | 0.0000 | 0.6367 | 0.2926 | 0.1309 | 0.0622 |



| | |
|---|---|
| 3D screen shot | Hot spot position |
|  |  |

Annex C. EUT Photos



EUT View Front




EUT View Back




Antenna View





GPS Antenna



NFC Antenna

Annex D. Test Setup Photos

Body mode Exposure Conditions

Body Front



Body Back



Body Right



Body Left



Hand exposure Conditions

Body Front



Body Back



Body Right**Body Left**

Annex E. Calibration Certificate

Please refer to the Exhibit for the Calibration Certificate

******* END OF REPORT *******