

Produkte Products

Prüfbericht - Nr.: 50105948 001 Seite 38 von 43 Page 38 of 43 Test Report No.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: Passed

Test standard FCC KDB Publication 447498 D01

RSS-102 issue 5, Table 4

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied

Maximum Exposure:

Power to Antenna (mW)	30.06 mW
Power to Antenna (dBm)	14.8 dBm
Antenna Gain	18 dBi
Power+Ant Gain	1896.7 mW
Distance	20 cm
S=	0.377 mW/cm^2

Limit FCC: 1.0 mW/cm² Limit Canada: 1.0 mW/cm²

FCC:

 0.3-1.34 MHz
 (100) mW/cr

 1.34-30 MHz
 (180/f²) mW/cm²

 30-300 MHz
 0.2 mW/cm²
(100) mW/cm² (180/f²) mW/cm² 300-1500 MHz f/1500 mW/cm² 1500-100,000 MHz 1.0 mW/cm²

Canada:

(0.8944/f^{0.5}) mW/cm² 6-15 GHz 1.0 mW/cm² 15-150 GHz 1.0 mW/cm²