

Produkte

Products

Seite 29 von 34 Prüfbericht - Nr.: 50097691 001 Page 29 of 34 Test Report No.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: Passed

Test standard FCC KDB Publication 447498 D01

RSS-102 issue 5, Table 4

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied

Maximum Exposure:

Power to Antenna (mW)	18.66 mW
Power to Antenna (dBm)	12.7 dBm
Antenna Gain	18 dBi
Power+Ant Gain	1177.4 mW
Distance	20 cm
S=	0.234 mW/cm^2

Limit FCC: 1.0 mW/cm² Limit Canada: 1.0 mW/cm²

FCC:

0.3-1.34 MHz (100) mW/cm² 1.34-30 MHz (180/f²) mW/cm² 30-300 MHz 0.2 mW/cm² 300-1500 MHz f/1500 mW/cm² 1500-100,000 MHz 1.0 mW/cm²

Canada:

 Canada.

 10-20 MHz
 0.2 mW/cm²

 20-48 MHz
 (0.8944/f^{0.5}) mW/cm²

 48-300 MHz
 0.129 mW/cm²

 300-6000 MHz
 (0.002619*f^{0.6834}) mW/cm²

 1.0 mW/cm²

6-15 GHz 15-150 GHz 1.0 mW/cm²