

Report No.: SHEM191001833602

Page: 1 of 7

## 1 Cover Page

## RF Exposure Evaluation Report

Application No.:SHEM1910018336CRFCC ID:2AL8S-0235C3MR

**Applicant:** ZHEJIANG UNIVIEW TECHNOLOGIES CO., LTD.

Address of Applicant: 8 JIANGLING RD BINJIANG DISTRICT HANGZHOU, ZHEJIANG 310051,

P.R. China

Manufacturer: ZHEJIANG UNIVIEW TECHNOLOGIES CO., LTD.

Address of Manufacturer: 8 JIANGLING RD BINJIANG DISTRICT HANGZHOU, ZHEJIANG 310051,

P.R. China

**Factory:** Zhejiang Uniview Systems Technology Co., Ltd.

Address of Factory:

No. 1277 South Qingfeng South Road, Tongxiang City, Jiaxing City

3110420, P.R. China

**Equipment Under Test (EUT):** 

EUT Name: IP Camera Model No.: URDB1

FCC Rules 47 CFR §2.1091

Standard(s): KDB447498 D01 General RF Exposure Guidance v06

**Date of Receipt:** 2019-10-29

**Date of Test:** 2019-11-04 to 2019-11-06

**Date of Issue:** 2019-11-15

Test Result: Pass\*

rlan 2han

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



pprovals in writing.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

| NC.588 West Jindu Road, Songjiang District, Shanghai, China 201612 t(86-21) 61915666 f(86-21) 61915667 www.s.gsgroup.com.cn
| 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 esg.s.china@sgs.com

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM191001833602

Page: 2 of 7

| Revision Record                 |          |            |   |  |  |  |  |
|---------------------------------|----------|------------|---|--|--|--|--|
| Version Description Date Remark |          |            |   |  |  |  |  |
| 00                              | Original | 2019-11-15 | / |  |  |  |  |
|                                 |          |            |   |  |  |  |  |

| Authorized for issue by: |                               |  |
|--------------------------|-------------------------------|--|
|                          | Vincent Zhu                   |  |
|                          | Vincent Zhu /Project Engineer |  |
|                          | Parlam Zhan                   |  |
|                          | Parlam Zhan /Reviewer         |  |



Report No.: SHEM191001833602

Page: 3 of 7

### 2 Contents

|   |     |   | Page         |
|---|-----|---|--------------|
| 1 | COV | /ER PAGE                                      | 1            |
| 2 | CON | NTENTS  | 3            |
| 3 | GEN | NERAL INFORMATION                             | 4            |
| 3 | 3.1 | GENERAL DESCRIPTION OF E.U.T.                 | 2            |
| 3 | 3.2 | TEST LOCATION                                 | 5            |
| 3 | 3.3 | TEST FACILITY                                 | 5            |
| 4 | TES | ST STANDARDS AND LIMITS                       | <del>(</del> |
| 4 | 4.1 | FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS: | <i>6</i>     |
| 5 | MEA | ASUREMENT AND CALCULATION                     | <del>(</del> |
| Ę | 5.1 | MAXIMUM TRANSMIT POWER                        | e            |
| 5 | 5.2 | MPE CALCULATION                               | 7            |



Report No.: SHEM191001833602

Page: 4 of 7

## 3 General Information

## 3.1 General Description of E.U.T.

| Power supply:       | AC 16~24V,50/60Hz 1A or DC 12V 1A by adapter |
|---------------------|--|
| Test voltage:       | AC 120V 60Hz                                 |
| Channel Spacing     | 5MHz   |
| Modulation Type     | 802.11b: DSSS (CCK, DQPSK, DBPSK)            |
|                     | 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)   |
| Number of Channels  | 802.11b/g/n(HT20):11                         |
|                     | 802.11n(HT40):7                              |
| Operation Frequency | 802.11b/g/n(HT20): 2412MHz to 2462MHz        |
|                     | 802.11n(HT40): 2422MHz to 2452MHz            |

### The EUT contains two type antenna:

#### Antenna list

|                   | Model No:        | Antenna Type | Antenna Gain |  |  |  |
|-------------------|------------------|--------------|--------------|--|--|--|
| Type 1(Antenna 1) | UB01C100F3D903AR | PCB Antenna  | 3dBi         |  |  |  |
| Type 2(Antenna 2) | RF11C02678S      | FPC Antenna  | 2dBi         |  |  |  |



Report No.: SHEM191001833602

Page: 5 of 7

#### 3.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

#### 3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### • NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

#### FCC –Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

#### • Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB Identifier: CN0020.

#### VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM191001833602

Page: 6 of 7

### 4 Test Standards and Limits

### 4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

| Frequency     | Power density(mW/cm²) | Averaging time(minutes) |  |
|---------------|-----------------------|-------------------------|--|
| 300MHz~1.5GHz | f/1500                | 30                      |  |
| 1.5GHz~100GHz | 1.0                   | 30                      |  |

### 5 Measurement and Calculation

### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM191001833601

| Test<br>Mode | Test<br>Channel | Ant  | Power<br>[dBm] | Power<br>[mW] |
|--------------|-----------------|------|----------------|---------------|
| 11B          | 2412            | Ant1 | 8.43           | 6.97          |
| 11B          | 2442            | Ant1 | 8.38           | 6.89          |
| 11B          | 2472            | Ant1 | 7.90           | 6.17          |
| 11G          | 2412            | Ant1 | 9.38           | 8.67          |
| 11G          | 2442            | Ant1 | 9.35           | 8.61          |
| 11G          | 2472            | Ant1 | 8.92           | 7.80          |
| 11N20SISO    | 2412            | Ant1 | 8.81           | 7.60          |
| 11N20SISO    | 2442            | Ant1 | 8.46           | 7.01          |
| 11N20SISO    | 2472            | Ant1 | 8.03           | 6.35          |
| 11N40SISO    | 2422            | Ant1 | 8.02           | 6.34          |
| 11N40SISO    | 2437            | Ant1 | 7.73           | 5.93          |
| 11N40SISO    | 2452            | Ant1 | 8.19           | 6.59          |



Report No.: SHEM191001833602

Page: 7 of 7

### 5.2 MPE Calculation

For FCC:

According to the formula  $S=P/4\pi R^2$ , we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- MPE limit = 1mW/cm²

The max antenna gain is type 1:

The max. antenna gain is 3 dBi

| Max.<br>Conducted<br>Power<br>P(mW) | Gain in Linear<br>Scale<br>G | Operation<br>Distance<br>R(cm) | Power<br>Density<br>(mW/cm <sup>2</sup> ) | Limit<br>(mW/cm <sup>2</sup> ) | Result |
|-------------------------------------|------------------------------|--------------------------------|---|--------------------------------|--------|
| 8.67                                | 1.995                        | 20                             | 0.00344                                   | 1                              | Pass   |

So the device is exclusion from SAR test.

-- End of the Report--