



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03  
Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20200200095E-02  
**Applicant:** Shenzhen Anboqi Technology Co.,Ltd  
**Address of Applicant:** 3F, Building B, No.1, Road 1, Shangxue Technology Park, Bantian Town, Longgang District, Shenzhen, Guangdong province, 518129, China.  
**Equipment Under Test (EUT):**  
**Product:** WIFI IP CCTV CAMERA  
**Model No.:** ABQ-510, ABQ-510B, ABQ-530A, ABQ-5200, ABQ-XXXX, ABQ-XXXXY(X stand 0-9, Y stand for A-Z)  
**Test Model No.:** ABQ-510  
**Brand Name:** Anboqi  
**FCC ID:** 2AL9C-ABQ510  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2020-02-28  
**Date of Test:** 2020-02-28 to 2020-03-05  
**Date of Issue:** 2020-03-05  
**Test Result :** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

Tom Chen

(Tom chen)

**Reviewed By:**

Aaron Ma

(Aaron Ma)

**Approved By:**

Jack Ai

(Jack Ai)



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200200095E-02	Rev.01	Initial report	2020-03-05

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION .....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	6
4.1.1 Limits .....	6
4.1.2 Test Procedure.....	6
4.1.3 EUT RF Exposure.....	7

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen Anboqi Technology Co.,Ltd
Address of Applicant:	3F, Building B, No.1, Road 1, Shangxue Technology Park, Bantian Town, Longgang District, Shenzhen, Guangdong province,518129, China.
Manufacturer:	Shenzhen Anboqi Technology Co.,Ltd
Address of Manufacturer:	3F, Building B, No.1, Road 1, Shangxue Technology Park, Bantian Town, Longgang District, Shenzhen, Guangdong province,518129, China.

#### 3.2 General Description of EUT

Product Name:	WIFI IP CCTV CAMERA
Model No.:	ABQ-510, ABQ-510B, ABQ-530A, ABQ-5200, ABQ-XXXX, ABQ-XXXXY(X stand 0-9 ,Y stand for A-Z)
Test Model No.:	ABQ-510
Trade Mark:	Anboqi
Hardware version:	IPC-RM-BLK520FX0-2145H-S V1.02
Software version:	General_IPC_XM510_RA50X10-C-S_WIFIXM712.712.Nat.dss_V5.00.R02.20190430
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Product Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	RF test (manufacturer declare )
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	AC/DC Adapter Model: BY-C1-5015 Input: 100-240~50-60Hz 0.3A Output: 5V 1.5A

Note:

Model No.: ABQ-510, ABQ-510B, ABQ-530A, ABQ-5200, ABQ-XXXX, ABQ-XXXXY(X stand 0-9 ,Y stand for A-Z)

Only the model ABQ-510 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 4.1.3 EUT RF Exposure

#### 1) For WIFI

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

#### Measurement Data

IEEE for 802.11b mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	13.08	12.5±1	13.5	22.387
Middle(2437MHz)	13.68	13.0±1	14.0	25.119
Highest(2462MHz)	14	13.5±1	14.5	28.184
IEEE for 802.11g mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	12.02	11.5±1	12.5	17.783
Middle(2437MHz)	12.26	11.5±1	12.5	17.783
Highest(2462MHz)	13.01	12.5±1	13.5	22.387
IEEE for 802.11n(HT20) mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	11.34	10.5±1	11.5	14.125
Middle(2437MHz)	11.67	11.0±1	12.0	15.849
Highest(2462MHz)	12.33	11.5±1	12.5	17.783
IEEE for 802.11n(HT40) mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2422MHz)	11.01	10.5±1	11.5	14.125
Middle(2437MHz)	12.09	11.5±1	12.5	17.783
Highest(2452MHz)	11.95	11.5±1	12.5	17.783

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
28.184	0	0.0056	1.0	PASS

Note: 1) Refer to report No. CQASZ20200200095E-01 for EUT test Max Conducted average Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (28.184 * 1) / (4 * 3.1416 * 20^2) = 0.0056$