

FCC ID: 2ALC5-KNX-IREC2

5 TEST CONDITIONS AND RESULTS


5.1 AC power line conducted emissions

For test instruments and accessories used see section 6 Part A 4.

5.1.1 Description of the test location

Test location: Shielded Room S2

5.1.2 Photo documentation of the test set-up




5.2 UWB Bandwidth

For test instruments and accessories used see section 6 Part **MB**.

5.2.1 Description of the test location

Test location: Shielded room 6

5.2.2 Photo documentation of the test set-up



5.2.3 Applicable standard

According to FCC Part 15, Section 15.517(b):

The UWB bandwidth of a UWB system operating under the provisions of this section must be contained between 3100 MHz and 10,600 MHz.

According to FCC Part 15, Section 15.503(d):

Ultra-wideband (UWB) transmitter. An intentional radiator that, at any point in time, has a fractional bandwidth equal to or greater than 0.20 or has a UWB bandwidth equal to or greater than 500 MHz, regardless of the fractional bandwidth.

FCC ID: 2ALC5-KNX-IREC2**5.3 Radiated Emissions 9 kHz to 40 GHz**


For test instruments and accessories used see section 6 Part **SER 2**, **SER3**.

5.3.1 Description of the test location

Test location: OATS 1
Test location: Anechoic chamber 1

5.3.2 Photo documentation of the test set-up

FCC ID: 2ALC5-KNX-IREC2



5.3.3 Applicable standard

According to FCC Part 15, Section 15.517(c):

The radiated emissions at or below 960 MHz from a device operating under the provisions of this section shall not exceed the emission levels in §15.209. The radiated emissions above 960 MHz from a device operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of 1 MHz.

5.3.4 Analyser settings


9 kHz – 150 kHz	RBW: 200 Hz			
150 kHz - 30 MHz	RBW: 9 kHz			
30 MHz – 960 MHz	RBW: 120 kHz	Detector: QP		
960 MHz – 40 GHz	RBW: 1 MHz	VBW: 3 MHz	Detector: RMS	Sweeptime: 1ms per MHz

FCC ID: 2ALC5-KNX-IREC2**5.4 Radiated Emissions at 1164-1240 MHz and 1559-1610 MHz**

For test instruments and accessories used see section 6 Part **SER 3**.

5.4.1 Description of the test location

Test location: Anechoic chamber 1

5.4.2 Photo documentation of the test set-up**5.4.3 Applicable standard**

According to FCC Part 15, Section 15.517(d):

In addition to the radiated emission limits specified in the table in paragraph (c) of this section, UWB transmitters operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of no less than 1 kHz.

5.4.4 Analyser settings

RBW: 1 kHz,

VBW: 3 kHz,

Detector: RMS,


Sweep time: 1 ms/1kHz,

FCC ID: 2ALC5-KNX-IREC2**5.5 Peak Power radiated**

For test instruments and accessories used see section 6 Part **CPR 3**

5.5.1 Description of the test location

Test location: Anechoic chamber 1

5.5.2 Photo documentation of the test set-up**5.5.3 Applicable standard**

According to FCC Part 15, Section 15.517(e):

There is a limit on the peak level of the emissions contained within a 50 MHz bandwidth centered on the frequency at which the highest radiated emission occurs, f_m . That limit is 0 dBm EIRP. It is acceptable to employ a different resolution bandwidth, and a correspondingly different peak emission limit, following the procedures described in §15.521.

5.5.4 Analyser settings

RBW: 50 MHz, VBW: 80 MHz, Detector: Peak, Trace Mode: Max hold