

## Maximum Permissible Exposure(MPE) Report

### 1. Applicable Standard

FCC Part §1.1310

### 2. Requirements

Limits For Maximum Permissible Exposure (MPE)				
Frequency range (MHz)	Electric field strength(V/m)	Magnetic field Strength(A/m)	Power density (mw/cm <sup>2</sup> )	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.0173	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

### 3. MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = Power density (In appropriate units, e.g., mW/cm<sup>2</sup>)

P = Power input to the antenna ( In appropriate units, e.g., mW)

G = Power gain og the antenna in the direction of interest relative to an isotropic radiator, the power gain factor,

Is normally numeric gain

R =Distance tp the center of radiation of the antenna(In appropriate units, e.g., cm

#### 4. Test Result

Operation Bands	Frequency(MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL698-716	706.75	19.69	3.5	41.59	8	6.31
DL728-746	740.85	11.67	1.2	11.14	6	3.98

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm <sup>2</sup> )	MPE limit (mW/cm <sup>2</sup> )
UL698-716	46.88	6.31	20	0.0589	0.471
DL728-746	7.21	3.98	20	0.0057	0.494

**Results: PASS**