FCC TEST REPORT

FCC ID: 2ALIP-M905

On Behalf of

Max-Future Electronics Co.,Limited

SUNRISE WAKE-UP LAMP BLUETOOTH SPEAKER

Model No.: M905, X-612

Prepared for	:	Max-Future Electronics Co.,Limited
Address	:	5/F, Building B, No. 537, Gushu 1st Road, Xi'xiang Street, Bao'an District, Shenzhen City, Guangdong, China

Prepared By	:	Shenzhen Alpha Product Testing Co., Ltd.
Address	:	Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

Report Number	:	T1881873 07
Date of Receipt	:	December 05, 2018
Date of Test	:	December 05, 2018-December 13, 2018
Date of Report	:	December 13, 2018
Version Number	:	REV0

TABLE OF CONTENTS

<u>Description</u>   <u>Page</u>

TEST REPORT DECLARATION

Applicant : Max-Future Electronics Co.,Limited

Address : 5/F, Building B, No. 537, Gushu 1st Road, Xi'xiang Street, Bao'an District, Shenzhen City, Guangdong, China

Manufacturer : Max-Future Electronics Co.,Limited

Address : 5/F, Building B, No. 537, Gushu 1st Road, Xi'xiang Street, Bao'an District, Shenzhen City, Guangdong, China

EUT Description : SUNRISE WAKE-UP LAMP BLUETOOTH SPEAKER

    (A)   Model No. : M905, X-612

    (B)   Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247: 2017,
ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature)..............:   Reak Yang
Project Engineer

Approved by (name + signature)…......:   Simple Guan
Project Manager

Date of issue…… …………………..:   December 13, 2018

Revision History

Revision	Issue Date	Revisions	Revised By
00	December 13, 2018	Initial released Issue	Simple Guan

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	P
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	:	SUNRISE WAKE-UP LAMP BLUETOOTH SPEAKER
Trademark	:	N/A
Model Number	:	M905, X-612
DIFF.	:	There is no difference between all the models, except the model number, this report performs the model SUNRISE WAKE-UP LAMP BLUETOOTH SPEAKER.
Test Voltage	:	DC 3.7V by battery, DC 5V from USB
BT		
Radio Technology	:	Bluetooth V4.2
Operation frequency	:	2402-2480MHz
Channel No.	:	79 Channels
Modulation type	:	GFSK, π /4 DQPSK, 8- DPSK
Antenna Type	:	PCB Antenna, 1.2dBi(Max.)
FM(RX)		
Radio Technology	:	FM
Operation frequency	:	87-108MHz
Modulation type	:	FM
Antenna Type	:	Internal Antenna
Software version	:	V1.0
Hardware version	:	V5.0

## 2.2. Accessories of Device (EUT)

Accessories1   :   /
Manufacturer   :   /
Model   :   /
Ratings   :   /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or DOC
1.	Notebook	ACER	ZQT	N/A	DOC

2.4. Block Diagram of connection between EUT and simulators

2.5. Test Mode Description

Tested mode, channel, and data rate information		
Mode	**Channel**	**Frequency (MHz)**
GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
π /4 DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
8- DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480

Note: All tests are performed with the product fully charged.

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	27℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
Registration Number: 293961

July 25, 2017 Certificated by IC
Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.16dB(Polarize: H)
	4.13dB(Polarize: V)
Uncertainty for radio frequency	$5.4 \times 10\text{-}8$
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2℃
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

| Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGREN	N/A	SEL0017	2018.09.21	1Year
Spectrum analyzer	Agilent	E4407B	MY46185649	2018.09.21	1Year
Receiver	R&S	ESCI	1166.5950K03-1011	2018.09.21	1Year
Receiver	R&S	ESCI	101202	2018.09.21	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2018.04.13	2Year
Horn Antenna	EMCO	3115	640201028-06	2018.04.13	2Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2018.04.13	2Year
Cable	Resenberger	N/A	No.1	2018.09.21	1Year
Cable	SCHWARZBECK	N/A	No.2	2018.09.21	1Year
Cable	SCHWARZBECK	N/A	No.3	2018.09.21	1Year
Pre-amplifier	Schwarzbeck	BBV9743	9743-019	2018.09.21	1Year
Pre-amplifier	R&S	AFS33-18002650-30-8P-44	SEL0080	2018.09.21	1Year
Temperature controller	Terchy	MHQ	120	2018.09.21	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2018.09.21	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2018.09.21	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2018.09.21	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA 9170294	2018.04.13	2 Year
Power Meter	Anritsu	ML2487A	6K00001491	2018.09.21	1 Year

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit

Please refer section15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

3.3. Test Setup

EUT → Power Meter

3.4. Test Result

Mode	Freq (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Result
GFSK	2402	0.343	1.082	30	Pass
	2441	-0.968	0.800	30	Pass
	2480	-1.476	0.712	30	Pass
π /4 DQPSK	2402	2.104	1.623	21	Pass
	2441	0.883	1.225	21	Pass
	2480	0.055	1.013	21	Pass
8- DPSK	2402	2.539	1.794	21	Pass
	2441	1.358	1.367	21	Pass
	2480	0.506	1.124	21	Pass
Conclusion: PASS					

4. BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

Mode	Freq (MHz)	20dB Bandwidth (KHz)	Conclusion
GFSK	2402	886.9	PASS
	2441	885.1	PASS
	2480	888.5	PASS
π /4 DQPSK	2402	1310.0	PASS
	2441	1311.0	PASS
	2480	1310.0	PASS
8- DPSK	2402	1247.0	PASS
	2441	1228.0	PASS
	2480	1244.0	PASS

Orginal Test data For 20dB bandwidth

| GFSK mode	π /4 DQPSK
Lowest channel	Lowest channel
Middle channel	Middle channel
Highest channel	Highest channel

8- DPSK	

Lowest channel

Middle channel

Highest channel

:

5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 20kHz RBW and 62kHz VBW.

5.3. Test Result

Mode/Channel	Channel separation (MHz)	20dB Bandwidth (KHz)	Limit (KHz)	Conclusion
GFSK	1.008	888.5	888.5	PASS
π /4 DQPSK	1.002	1311.0	874.00	PASS
8- DPSK	1.002	1247.0	831.33	PASS

Orginal test data for channel separation

GFSK

π /4 DQPSK

8- DPSK

6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result

Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
π /4 DQPSK	79	>15	PASS
8- DPSK	79	>15	PASS

Original test data for hopping channel number

GFSK

π /4 DQPSK

8- DPSK

7. DWELL TIME

7.1. Test limit

Please refer section15.247
According to §l5.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

PASS.

Detailed information please see the following page.

Mode	Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (ms)	Limit (ms)	Conclusion
GFSK	DH1	2441	0.379	121.280	400	PASS
	DH3	2441	1.637	261.920		PASS
	DH5	2441	2.890	308.267		PASS
π /4 DQPSK	DH1	2441	0.394	126.080	400	PASS
	DH3	2441	1.646	263.360		PASS
	DH5	2441	2.894	308.693		PASS
8- DPSK	DH1	2441	0.398	127.360	400	PASS
	DH3	2441	1.646	263.360		PASS
	DH5	2441	2.899	309.227		PASS

Note: 1 A period time = 0.4 (s) * 79 = 31.6(s)

    2 DH1 time slot = Pulse Duration * (1600/(2*79)) * A period time/1000

      DH3 time slot = Pulse Duration * (1600/(4*79)) * A period time/1000

      DH5 time slot = Pulse Duration * (1600/(6*79)) * A period time/1000

Dwell time

GFSK	π/4-DQPSK

Channel 39 / 2441 MHz - DH1

Channel 39 / 2441 MHz - 2DH1

Channel 39 / 2441 MHz – DH3

Channel 39 / 2441 MHz - 2DH3

Channel 39 / 2441 MHz – DH5

Channel 39 / 2441 MHz - 2DH5

Dwell time
8DPSK

Channel 39 / 2441 MHz - 3DH1

2 Channel 39 / 2441 MHz - 3DH3

Channel 39 / 2441 MHz – 3DH5

8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

8.2. Block Diagram of Test setup

8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz

8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz

8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz

Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

(2) Setup EUT and simulator as shown in section 1.4 and 6.1

(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.

(a) Change work frequency or channel of device if practicable.

(b) Change modulation type of device if practicable.

(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions

(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated

(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on Radiated Emission test.

(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result

We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency..
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS
Vertical:

File :M905   Data :#9   Date: 2018/12/6   Time: 21:56:22

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	67.2022	21.57	11.49	33.06	40.00	-6.94	QP			
2		122.4040	19.23	12.75	31.98	43.50	-11.52	peak			
3		151.5972	20.95	14.56	35.51	43.50	-7.99	peak			
4		197.2001	22.90	10.50	33.40	43.50	-10.10	peak			
5		280.0237	20.88	12.97	33.85	46.00	-12.15	peak			
6		490.7447	17.87	17.39	35.26	46.00	-10.74	peak			

Note:1. *:Maximum data; x:Over limit; !:over margin.
2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

File :M905   Data :#10   Date: 2018/12/6   Time: 21:57:31

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	67.2022	22.14	11.49	33.63	40.00	-6.37	QP			
2		159.2251	14.09	14.58	28.67	43.50	-14.83	peak			
3		210.0482	24.48	10.69	35.17	43.50	-8.33	peak			
4		283.9791	25.28	13.03	38.31	46.00	-7.69	peak			
5		607.7867	13.60	19.67	33.27	46.00	-12.73	peak			
6		942.1305	14.92	23.18	38.10	46.00	-7.90	peak			

Note:1. *:Maximum data; x:Over limit; !:over margin.
2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Remark: All modes have been tested, and only worst data of 8-DPSK mode, Channel 2402MHz (DC 3.7V) was listed in this report.

From 1G-25GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.98	V	33.95	10.18	34.26	54.85	74	19.15	PK
4804	35.47	V	33.95	10.18	34.26	45.34	54	8.66	AV
7206	/								
9608	/								
4824	46.53	H	33.95	10.18	34.26	56.40	74	17.60	PK
4824	34.85	H	33.95	10.18	34.26	44.72	54	9.28	AV
7206									
9608									
Test Mode: GFSK TX Mid									
4882	43.80	V	33.93	10.2	34.29	53.64	74	20.36	PK
4882	35.78	V	33.93	10.2	34.29	45.62	54	8.38	AV
7323	/								
9764	/								
4882	43.33	H	33.93	10.2	34.29	53.17	74	20.83	PK
4882	35.42	H	33.93	10.2	34.29	45.26	54	8.74	AV
7323									
9764									
Test Mode: GFSK TX High									
4960	43.51	V	33.98	10.22	34.25	53.46	74	20.54	PK
4960	33.46	V	33.98	10.22	34.25	43.41	54	10.59	AV
7440	/								
9920	/								
4960	45.58	H	33.98	10.22	34.25	55.53	74	18.47	PK
4960	34.44	H	33.98	10.22	34.25	44.39	54	9.61	AV
7440	/								
9920	/								

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

From 1G-25GHz

Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Test Mode: π /4 DQPSK TX Low									
4804	44.54	V	33.95	10.18	34.26	54.41	74	19.59	PK
4804	34.89	V	33.95	10.18	34.26	44.76	54	9.24	AV
7206	/		/						
9608	/		/						
4824	45.22	H	33.95	10.18	34.26	55.09	74	18.91	PK
4824	35.15	H	33.95	10.18	34.26	45.02	54	8.98	AV
7206									
9608									
Test Mode: π /4 DQPSK TX Mid									
4882	45.84	V	33.93	10.2	34.29	55.68	74	18.32	PK
4882	33.35	V	33.93	10.2	34.29	43.19	54	10.81	AV
7323	/								
9764	/								
4882	45.80	H	33.93	10.2	34.29	55.64	74	18.36	PK
4882	35.91	H	33.93	10.2	34.29	45.75	54	8.25	AV
7323									
9764									
Test Mode: π /4 DQPSK TX High									
4960	44.34	V	33.98	10.22	34.25	54.29	74	19.71	PK
4960	33.81	V	33.98	10.22	34.25	43.76	54	10.24	AV
7440	/								
9920	/								
4960	45.39	H	33.98	10.22	34.25	55.34	74	18.66	PK
4960	33.44	H	33.98	10.22	34.25	43.39	54	10.61	AV
7440	/								
9920	/								

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

From 1G-25GHz

Test Mode: 8- DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.46	V	33.95	10.18	34.26	54.33	74	19.67	PK
4804	34.48	V	33.95	10.18	34.26	44.35	54	9.65	AV
7206	/		/						
9608	/		/						
4824	43.01	H	33.95	10.18	34.26	52.88	74	21.12	PK
4824	34.95	H	33.95	10.18	34.26	44.82	54	9.18	AV
7206									
9608									
Test Mode: 8- DQPSK TX Mid									
4882	42.31	V	33.93	10.2	34.29	52.15	74	21.85	PK
4882	34.36	V	33.93	10.2	34.29	44.20	54	9.80	AV
7323	/								
9764	/								
4882	44.74	H	33.93	10.2	34.29	54.58	74	19.42	PK
4882	35.38	H	33.93	10.2	34.29	45.22	54	8.78	AV
7323									
9764									
Test Mode: 8- DQPSK TX High									
4960	45.40	V	33.98	10.22	34.25	55.35	74	18.65	PK
4960	33.83	V	33.98	10.22	34.25	43.78	54	10.22	AV
7440	/								
9920	/								
4960	45.49	H	33.98	10.22	34.25	55.44	74	18.56	PK
4960	34.98	H	33.98	10.22	34.25	44.93	54	9.07	AV
7440	/								
9920	/								

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

9. BAND EDGE COMPLIANCE

9.1. Block Diagram of Test Setup

9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3. Test Procedure

All restriction band and non- restriction band have been tested，only worse case is reported.

9.4. Test Result


PASS. (See below detailed test data)

Radiated Method:

Polarization:　　　Vertical　　　　　　　　Test Mode:　　　　GFSK-Low

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	47.08	-3.40	43.68	74.00	-30.32	peak			
2	*	2402.180	100.08	-3.41	96.67	74.00	22.67	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	48.72	-3.40	45.32	74.00	-28.68	peak			
2	*	2420.000	98.56	-3.41	95.15	74.00	21.15	peak			

hopping-on

Polarization: Horizontal: Test Mode: GFSK-Low

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	45.82	-3.40	42.42	74.00	-31.58	peak			
2	*	2402.070	101.26	-3.41	97.85	74.00	23.85	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	46.40	-3.40	43.00	74.00	-31.00	peak			
2	*	2409.220	101.79	-3.40	98.39	74.00	24.39	peak			

hopping-on

Polarization: Vertical   Test Mode: GFSK-High

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.200	105.85	-3.38	102.47	74.00	28.47	peak			
2		2483.500	66.71	-3.38	63.33	74.00	-10.67	peak			
3		2483.500	43.01	-3.38	39.63	54.00	-14.37	AVG			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2466.100	102.74	-3.39	99.35	74.00	25.35	peak			
2		2483.500	48.75	-3.38	45.37	74.00	-28.63	peak			

hopping-on

Polarization: Horizontal   Test Mode: GFSK-High

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.300	107.51	-3.38	104.13	74.00	30.13	peak			
2		2483.500	63.07	-3.38	59.69	74.00	-14.31	peak			
3		2483.500	43.63	-3.38	40.25	54.00	-13.75	AVG			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2469.300	102.02	-3.39	98.63	74.00	24.63	peak			
2		2483.500	49.89	-3.38	46.51	74.00	-27.49	peak			

hopping-on

Polarization: Vertical   Test Mode: π /4 DQPSK-Low

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2402.180	97.28	-3.41	93.87	74.00	19.87	peak			
2		2390.000	48.63	-3.40	45.23	74.00	-28.77	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	47.10	-3.40	43.70	74.00	-30.30	peak			
2	*	2411.200	101.78	-3.40	98.38	74.00	24.38	peak			

hopping-on

Polarization: Horizontal   Test Mode: π /4 DQPSK-Low

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2401.960	98.35	-3.41	94.94	74.00	20.94	peak			
2		2390.000	46.02	-3.40	42.62	74.00	-31.38	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	45.52	-3.40	42.12	74.00	-31.88	peak			
2	*	2412.520	98.31	-3.41	94.90	74.00	20.90	peak			

hopping-on

Polarization: Vertical   Test Mode: π /4 DQPSK-High

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.100	96.86	-3.38	93.48	74.00	19.48	peak			
2		2483.500	58.72	-3.38	55.34	74.00	-18.66	peak			
3		2483.500	42.01	-3.38	38.63	54.00	-15.37	AVG			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2469.300	98.86	-3.39	95.47	74.00	21.47	peak			
2		2483.500	48.72	-3.38	45.34	74.00	-28.66	peak			

hopping-on

Polarization: Horizontal   Test Mode: π /4 DQPSK-High

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2479.900	103.07	-3.38	99.69	74.00	25.69	peak			
2		2483.500	56.90	-3.38	53.52	74.00	-20.48	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2479.900	100.14	-3.38	96.76	74.00	22.76	peak			
2		2483.500	52.41	-3.38	49.03	74.00	-24.97	peak			

hopping-on

Polarization: Vertical   Test Mode: 8DPSK-Low

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2402.180	98.77	-3.41	95.36	74.00	21.36	peak			
2		2390.000	47.50	-3.40	44.10	74.00	-29.90	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	48.87	-3.40	45.47	74.00	-28.53	peak			
2	*	2419.120	99.15	-3.41	95.74	74.00	21.74	peak			

hopping-on

Polarization: Horizontal   Test Mode: 8DPSK-Low

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2402.180	99.58	-3.41	96.17	74.00	22.17	peak			
2		2390.000	44.92	-3.40	41.52	74.00	-32.48	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	45.85	-3.40	42.45	74.00	-31.55	peak			
2	*	2416.920	99.33	-3.41	95.92	74.00	21.92	peak			

hopping-on

Polarization: Vertical   Test Mode: 8DPSK-High

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.200	99.19	-3.38	95.81	74.00	21.81	peak			
2		2483.500	51.75	-3.38	48.37	74.00	-25.63	peak			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2455.800	98.89	-3.39	95.50	74.00	21.50	peak			
2		2483.500	49.10	-3.38	45.72	74.00	-28.28	peak			

hopping-on

Polarization: Horizontal   Test Mode: 8DPSK-High

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.200	103.18	-3.38	99.80	74.00	25.80	peak			
2		2483.500	62.22	-3.38	58.84	74.00	-15.16	peak			
3		2483.500	43.39	-3.38	40.01	54.00	-13.99	AVG			

hopping-off

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2468.800	101.56	-3.39	98.17	74.00	24.17	peak			
2		2483.500	46.16	-3.38	42.78	74.00	-31.22	peak			

hopping-on

Note: 1. *:Maximum data; x:Over limit; !:over margin.

    2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Conducted Method

**GFSK Mode:**

Test channel:	Lowest channel

No-hopping mode

Hopping mode

Test channel:	Highest channel

No-hopping mode

Hopping mode

Pi/4QPSK Mode:

Test channel:	Lowest channel

No-hopping mode	Hopping mode

Test channel:	Highest channel

No-hopping mode	Hopping mode

8DPSK Mode:

Test channel:	Lowest channel
No-hopping mode	Hopping mode

Test channel:	Highest channel
No-hopping mode	Hopping mode

10. POWER LINE CONDUCTED EMISSIONS

10.1. Block Diagram of Test Setup

☒ :50Ω Terminator

10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

(1) The EUT was placed on a non-metallic table, 80cm above the ground plane.

(2) Setup the EUT and simulator as shown in 10.1

(3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on conducted Emission test.

(4) The bandwidth of test receiver is set at 10KHz.

(5) The frequency range from 150 KHz to 30MHz is checked.

10.4. Test Result

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit

Line:

Conducted Emission Measurement

File :M905   Data :#4   Date: 2018-12-7   Time: 1:13:26

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	42.79	9.66	52.45	66.00	-13.55	QP	
2		0.1500	19.60	9.66	29.26	56.00	-26.74	AVG	
3		0.2640	38.45	9.69	48.14	61.30	-13.16	peak	
4	*	0.4470	34.14	9.71	43.85	56.93	-13.08	peak	
5		1.2479	29.88	9.79	39.67	56.00	-16.33	peak	
6		4.8600	25.65	10.15	35.80	56.00	-20.20	peak	
7		25.1939	25.66	10.77	36.43	60.00	-23.57	peak	

*:Maximum data   x:Over limit   !:over margin

Note: Measurement=Reading Level+Correc Factor.   Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Neutral:

File :M905   Data :#3   Date: 2018-12-7   Time: 1:11:06

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1590	46.55	9.66	56.21	65.52	-9.31	QP	
2		0.1590	23.60	9.66	33.26	55.52	-22.26	AVG	
3		0.2129	43.35	9.68	53.03	63.09	-10.06	peak	
4		0.4859	28.01	9.71	37.72	56.24	-18.52	peak	
5		0.7920	24.03	9.74	33.77	56.00	-22.23	peak	
6		0.9929	27.05	9.77	36.82	56.00	-19.18	peak	
7		5.5529	25.27	10.20	35.47	60.00	-24.53	peak	

*:Maximum data   x:Over limit   !:over margin

Note: Measurement=Reading Level+Correc Factor.   Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Remark: All modes have been tested, and only worst data of 8-DPSK mode, Channel 2402MHz (AC 120V/ 60Hz) was listed in this report.

# 11. ANTENNA REQUIREMENTS

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The EUT antenna is PCB Antenna. It complies with the standard requirement.

12. TEST SETUP PHOTO

12.1. Photos of Radiated emission

12.2.Photos of Conducted Emission test

13. PHOTOS OF EUT

---------THE END OF REPORT-------