



SAR exemption evaluation

Applicant Beijing AIQI Technology Co., Ltd.
FCC ID 2ALJ6-ZNM01
Product Mi Mini Robot Builder
Brand Mi
Model ZNM01IQI
Report No. RXA1709-0328SAR
Issue Date December 5, 2017

Approved by: Jiangpeng Lan

Reviewed by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Conducted Power

Network Standards	Carrier frequency (MHz)	Average Output Power (dBm)	Conclusion
Bluetooth (Low Energy)	2402	-3.13	PASS
	2440	-3.54	PASS
	2480	-4.58	PASS

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Bluetooth	Distance (mm)	MAX Power (dBm)	Frequency (MHz)	Ratio	Evaluation
Head	5	-3.13	2402	0.151	No
Body-worn	10	-3.13	2402	0.075	No