

RF TEST REPORT



Report No.: 17070023-FCC-R1

Supersede Report No.: N/A

Applicant	Anda Technologies S.A.C	
Product Name	Anda Watch	
Model No.	W010R1	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2016 ;FCC Part 24(E):2016; FCC Part 27:2016; ANSI/TIA-603-D: 2010	
Test Date	January 13 to February 05, 2017	
Issue Date	February 06, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 RF EXPOSURE (SAR)	10
6.2 RF OUTPUT POWER	11
6.3 PEAK-AVERAGE RATIO	24
6.4 OCCUPIED BANDWIDTH	29
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	44
6.6 SPURIOUS RADIATED EMISSIONS	60
6.7 BAND EDGE	67
6.8 FREQUENCY STABILITY	81
ANNEX A. TEST INSTRUMENT	86
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	88
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	99
ANNEX C.II. EUT OPERATING CONKITIONS	101
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	102
ANNEX E. DECLARATION OF SIMILARITY	103

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070023-FCC-R1	NONE	Original	February 06, 2017

2. Customer information

Applicant Name	Anda Technologies S.A.C
Applicant Add	Avenida Santa Cruz No. 888, Piso 4, Miraflores, Lima, Peru
Manufacturer	Borqs Beijing Ltd.
Manufacturer Add	Tower A, Building B23, Universal Business Park, No. 10 Jiuxianqiao Road, Chaoyang District Beijing, 100015 China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Anda Watch
Main Model:	W010R1
Serial Model:	N/A
Date EUT received:	January 12, 2017
Test Date(s):	January 13 to February 05, 2017
Equipment Category :	PCE
Antenna Gain:	GSM850: -5.00dBi PCS1900: 1.4dBi UMTS-FDD Band V: -5.00dBi UMTS-FDD Band IV: 0.84dBi UMTS-FDD Band II: 1.4dBi LTE Band II: 1.41dBi LTE Band IV: 0.84dBi WIFI: -1.5dBi Bluetooth/BLE: -1.5dBi GPS: 0.48dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK, 8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK GPS: BPSK

	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
	PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
	UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
	UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;
	RX : 2112.4 ~ 2152.6 MHz
RF Operating Frequency (ies):	UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
	RX: 1932.4 ~ 1987.6 MHz
	LTE Band II TX: 1850.7 ~ 1909.3MHz; RX : 1930.7 ~ 1989.3 MHz
	LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7~ 2154.3 MHz
	WIFI: 802.11b/g/n(20M): 2412-2462 MHz
	Bluetooth& BLE: 2402-2480 MHz
	GPS: 1575.42 MHz
	GSM Voce:GSM850:32.5 dBm
	PCS1900: 30.91 dBm
Maximum Conducted AV Power to Antenna:	GPRS:GSM850: 32.47 dBm
	PCS1900: 30.9 dBm
	EGPRS(MCS1):GSM850: 32.45 dBm
	PCS1900: 30.65 dBm
	EGPRS(MCS5):GSM850: 26.15 dBm
	PCS1900: 25.95 dBm
	RMC:UMTS-FDD Band V: 19.87 dBm
	UMTS-FDD Band II: 20.69 dBm
	UMTS-FDD Band IV: 20.75 dBm
	HSDPA:UMTS-FDD Band V: 19.15 dBm
ERP/EIRP:	UMTS-FDD Band II: 19.96 dBm
	UMTS-FDD Band IV: 19.99 dBm
	HSUPA:UMTS-FDD Band V: 19.16 dBm
	UMTS-FDD Band II: 19.99 dBm
	UMTS-FDD Band IV: 19.95 dBm
	GSM Voce:GSM850: 25.35 dBm / ERP
	PCS1900: 32.31 dBm / EIRP
	GPRS:GSM850: 25.32 dBm / ERP
	PCS1900: 32.30dBm / EIRP
	EGPRS(MCS5):GSM850:19.00 dBm / ERP

PCS1900: 27.35 dBm / EIRP

RMC:UMTS-FDD Band V: 14.33 dBm / ERP

UMTS-FDD Band II: 24.70 dBm / EIRP

UMTS-FDD Band IV: 23.87 dBm / EIRP

HSUPA:UMTS-FDD Band V: 13.74 dBm / ERP

UMTS-FDD Band II: 23.78 dBm / EIRP

UMTS-FDD Band IV: 23.02 dBm / EIRP

HSDPA:UMTS-FDD Band V: 13.73 dBm / ERP

UMTS-FDD Band II: 23.78 dBm / EIRP

UMTS-FDD Band IV: 23.04 dBm / EIRP

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band V: 102CH

UMTS-FDD Band IV: 202CH

Number of Channels:

UMTS-FDD Band II: 277CH

WIFI :802.11b/g/n(20M): 11CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Port:

Data and charging Port

Adapter:

Model: ASUC37a-050100

Input Power:

Input: AC100-240V~50/60Hz,0.3A

Output: DC 5.0V,1.0A

Battery:

Spec: 4.35V,400mAh

Trade Name :

Anda Watch

GPRS/EGPRS Multi-slot class

8/10/12

FCC ID:

2ALJB-W010R1

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass

The EUT is a portable device, thus requires SAR evaluation;


Please refer to RF Exposure Evaluation Report: 17070023-FCC-R1

6.2 RF Output Power

Temperature	23 °C
Relative Humidity	51%
Atmospheric Pressure	1018mbar
Test date :	January 18/19/20, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>
§27.50 (c)	c)	EIRP: 30dBm	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station EUT</p>
------------	---

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental
----------------	---

	<p>frequency was investigated.</p> <ul style="list-style-type: none"> - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.45	32.5	32.49	32.5±1	30.82	30.73	30.91	31±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	32.44	32.47	32.45	32±1	30.81	30.72	30.9	31±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	29.16	29.17	29.22	29±1	28.09	28.35	28.24	28±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	25.28	25.37	25.52	25.5±1	24.63	24.48	24.37	24.5±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	32.43	32.45	32.44	32.5±1	30.65	30.58	30.5	31±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	29.13	29.15	29.13	29±1	27.98	28.2	28.05	28±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	25.2	25.34	25.36	25.5±1	24.48	24.34	24.2	24.5±1
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	26.15	26.13	26.08	26±1	25.95	25.82	25.68	25.5±1
EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	22.89	22.87	22.85	22.5±1	22.59	22.47	22.39	22.5±1
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	19.54	19.45	19.5	19.5±1	19.2	18.85	18.72	19±1

Test Report	17070023-FCC-R1
Page	14 of 103

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	19.87	20±1
	4175	835	19.71	20±1
	4233	846.6	19.63	20±1
HSDPA Subtest1	4132	826.4	19.06	19±1
	4175	835	19.07	19±1
	4233	846.6	19.05	19±1
HSDPA Subtest2	4132	826.4	19.13	19±1
	4175	835	19.1	19±1
	4233	846.6	19.15	19±1
HSDPA Subtest3	4132	826.4	19.02	19±1
	4175	835	19.07	19±1
	4233	846.6	19.09	19±1
HSDPA Subtest4	4132	826.4	19.11	19±1
	4175	835	19.15	19±1
	4233	846.6	19.09	19±1
HSUPA Subtest1	4132	826.4	19.07	19±1
	4175	835	19.1	19±1
	4233	846.6	19.16	19±1
HSUPA Subtest2	4132	826.4	19.13	19±1
	4175	835	19.05	19±1
	4233	846.6	19.09	19±1
HSUPA Subtest3	4132	826.4	19.13	19±1
	4175	835	19.09	19±1
	4233	846.6	19.15	19±1
HSUPA Subtest4	4132	826.4	19.11	19±1
	4175	835	19.08	19±1
	4233	846.6	19.15	19±1
HSUPA Subtest5	4132	826.4	19.08	19±1
	4175	835	19.11	19±1
	4233	846.6	19.1	19±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	20.69	20.5±1
	9400	1880	20.43	20.5±1
	9538	1907.6	20.41	20.5±1
HSDPA Subtest1	9262	1852.4	19.85	20±1
	9400	1880	19.83	20±1
	9538	1907.6	19.88	20±1
HSDPA Subtest2	9262	1852.4	19.96	20±1
	9400	1880	19.92	20±1
	9538	1907.6	19.95	20±1
HSDPA Subtest3	9262	1852.4	19.73	20±1
	9400	1880	19.74	20±1
	9538	1907.6	19.77	20±1
HSDPA Subtest4	9262	1852.4	19.82	20±1
	9400	1880	19.84	20±1
	9538	1907.6	19.81	20±1
HSUPA Subtest1	9262	1852.4	19.65	20±1
	9400	1880	19.63	20±1
	9538	1907.6	19.67	20±1
HSUPA Subtest2	9262	1852.4	19.83	20±1
	9400	1880	19.86	20±1
	9538	1907.6	19.89	20±1
HSUPA Subtest3	9262	1852.4	19.99	20±1
	9400	1880	19.96	20±1
	9538	1907.6	19.92	20±1
HSUPA Subtest4	9262	1852.4	19.62	20±1
	9400	1880	19.61	20±1
	9538	1907.6	19.69	20±1
HSUPA Subtest5	9262	1852.4	19.64	20±1
	9400	1880	19.65	20±1
	9538	1907.6	19.67	20±1

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	1313	1712.6	20.75	20.5±1
	1413	1732.6	20.49	20.5±1
	1512	1752.4	20.63	20.5±1
HSDPA Subtest1	1313	1712.6	19.73	20±1
	1413	1732.6	19.75	20±1
	1512	1752.4	19.79	20±1
HSDPA Subtest2	1313	1712.6	19.74	20±1
	1413	1732.6	19.77	20±1
	1512	1752.4	19.76	20±1
HSDPA Subtest3	1313	1712.6	19.93	20±1
	1413	1732.6	19.99	20±1
	1512	1752.4	19.92	20±1
HSDPA Subtest4	1313	1712.6	19.73	20±1
	1413	1732.6	19.75	20±1
	1512	1752.4	19.74	20±1
HSUPA Subtest1	1313	1712.6	19.83	20±1
	1413	1732.6	19.85	20±1
	1512	1752.4	19.9	20±1
HSUPA Subtest2	1313	1712.6	19.72	20±1
	1413	1732.6	19.75	20±1
	1512	1752.4	19.79	20±1
HSUPA Subtest3	1313	1712.6	19.93	20±1
	1413	1732.6	19.95	20±1
	1512	1752.4	19.94	20±1
HSUPA Subtest4	1313	1712.6	19.82	20±1
	1413	1732.6	19.89	20±1
	1512	1752.4	19.81	20±1
HSUPA Subtest5	1313	1712.6	19.81	20±1
	1413	1732.6	19.83	20±1
	1512	1752.4	19.82	20±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	19.03	V	6.8	0.53	25.30	38.45
824.2	17.7	H	6.8	0.53	23.97	38.45
836.6	19.08	V	6.8	0.53	25.35	38.45
836.6	17.95	H	6.8	0.53	24.22	38.45
848.8	18.97	V	6.9	0.53	25.34	38.45
848.8	17.79	H	6.9	0.53	24.16	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	25.19	V	7.88	0.85	32.22	33
1850.2	24.11	H	7.88	0.85	31.14	33
1880	25.1	V	7.88	0.85	32.13	33
1880	23.92	H	7.88	0.85	30.95	33
1909.8	25.3	V	7.86	0.85	32.31	33
1909.8	24.15	H	7.86	0.85	31.16	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	19.02	V	6.8	0.53	25.29	38.45
824.2	17.76	H	6.8	0.53	24.03	38.45
836.6	19.05	V	6.8	0.53	25.32	38.45
836.6	17.88	H	6.8	0.53	24.15	38.45
848.8	18.93	V	6.9	0.53	25.30	38.45
848.8	17.74	H	6.9	0.53	24.11	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	25.18	V	7.88	0.85	32.21	33
1850.2	25.04	H	7.88	0.85	32.07	33
1880	25.09	V	7.88	0.85	32.12	33
1880	24.86	H	7.88	0.85	31.89	33
1909.8	25.29	V	7.86	0.85	32.30	33
1909.8	25.17	H	7.86	0.85	32.18	33

EGPRS (MCS5):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	12.73	V	6.8	0.53	19.00	38.45
824.2	11.64	H	6.8	0.53	17.91	38.45
836.6	12.71	V	6.8	0.53	18.98	38.45
836.6	11.19	H	6.8	0.53	17.46	38.45
848.8	12.56	V	6.9	0.53	18.93	38.45
848.8	11.16	H	6.9	0.53	17.53	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	20.32	V	7.88	0.85	27.35	33
1850.2	19.13	H	7.88	0.85	26.16	33
1880	20.19	V	7.88	0.85	27.22	33
1880	18.96	H	7.88	0.85	25.99	33
1909.8	20.07	V	7.86	0.85	27.08	33
1909.8	18.92	H	7.86	0.85	25.93	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	8.06	V	6.8	0.53	14.33	38.45
826.4	6.94	H	6.8	0.53	13.21	38.45
835	8.03	V	6.8	0.53	14.30	38.45
835	6.88	H	6.8	0.53	13.15	38.45
846.6	7.79	V	6.9	0.53	14.16	38.45
846.6	6.71	H	6.9	0.53	13.08	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	17.52	V	7.88	0.85	24.55	33
1852.4	16.34	H	7.88	0.85	23.37	33
1880	17.51	V	7.88	0.85	24.54	33
1880	16.29	H	7.88	0.85	23.32	33
1907.6	17.69	V	7.86	0.85	24.70	33
1907.6	16.58	H	7.86	0.85	23.59	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	16.86	V	7.76	0.82	23.80	30
1712.4	15.78	H	7.76	0.82	22.72	30
1740	16.67	V	7.76	0.82	23.61	30
1740	15.64	H	7.76	0.82	22.58	30
1752.6	16.95	V	7.74	0.82	23.87	30
1752.6	15.77	H	7.74	0.82	22.69	30

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	7.43	V	6.8	0.53	13.70	38.45
826.4	6.36	H	6.8	0.53	12.63	38.45
835	7.44	V	6.8	0.53	13.71	38.45
835	6.32	H	6.8	0.53	12.59	38.45
846.6	7.36	V	6.9	0.53	13.73	38.45
846.6	6.29	H	6.9	0.53	12.66	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	16.73	V	7.88	0.85	23.76	33
1852.4	15.54	H	7.88	0.85	22.57	33
1880	16.69	V	7.88	0.85	23.72	33
1880	15.48	H	7.88	0.85	22.51	33
1907.6	16.77	V	7.86	0.85	23.78	33
1907.6	15.61	H	7.86	0.85	22.62	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	16.05	V	7.76	0.82	22.99	30
1712.4	14.91	H	7.76	0.82	21.85	30
1740	16.07	V	7.76	0.82	23.01	30
1740	14.99	H	7.76	0.82	21.93	30
1752.6	16.12	V	7.74	0.82	23.04	30
1752.6	15.05	H	7.74	0.82	21.97	30

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	7.47	V	6.8	0.53	13.74	38.45
826.4	6.29	H	6.8	0.53	12.56	38.45
835	7.41	V	6.8	0.53	13.68	38.45
835	6.24	H	6.8	0.53	12.51	38.45
846.6	7.33	V	6.9	0.53	13.70	38.45
846.6	6.18	H	6.9	0.53	12.55	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	16.72	V	7.88	0.85	23.75	33
1852.4	15.61	H	7.88	0.85	22.64	33
1880	16.75	V	7.88	0.85	23.78	33
1880	15.68	H	7.88	0.85	22.71	33
1907.6	16.74	V	7.86	0.85	23.75	33
1907.6	15.62	H	7.86	0.85	22.63	33


EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	16.03	V	7.76	0.82	22.97	30
1712.4	14.94	H	7.76	0.82	21.88	30
1740	16.06	V	7.76	0.82	23.00	30
1740	15	H	7.76	0.82	21.94	30
1752.6	16.1	V	7.74	0.82	23.02	30
1752.6	14.98	H	7.74	0.82	21.90	30

6.3 Peak-Average Ratio

Temperature	23 °C
Relative Humidity	51%
Atmospheric Pressure	1018mbar
Test date :	January 18, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Base Station Spectrum Analyzer EUT</p>		
Test Procedure	<p>According with KDB 971168 v02r02</p> <p>5.7.2 Alternate procedure for PAPR</p> <p>5.1.2 Peak power measurements with a peak power meter</p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p>5.2.3 Average power measurement with average power meter</p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output</p>		

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.15	30.82	0.33
1880	31.1	30.73	0.37
1909.8	31.24	30.91	0.33

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.22	30.81	0.41
1880	31.19	30.72	0.47
1909.8	31.27	30.9	0.37

EGPRS (MSC5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	26.35	25.95	0.4
1880	26.31	25.82	0.49
1909.8	26.33	25.68	0.65

RMC : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	21.1	20.69	0.41
1880	20.69	20.43	0.26
1907.6	20.88	20.41	0.47

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	21.33	20.75	0.58
1732.6	20.83	20.49	0.34
1752.4	20.92	20.63	0.29

HSUPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	20.04	19.65	0.39
1880	20.08	19.63	0.45
1907.6	20.11	19.67	0.44

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	20.13	19.83	0.3
1732.6	20.18	19.85	0.33
1752.4	20.12	19.9	0.22

HSDPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	20.18	19.85	0.33
1880	20.2	19.83	0.37
1907.6	20.19	19.88	0.31


UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	20.35	19.73	0.62
1732.6	20.29	19.75	0.54
1752.4	20.27	19.79	0.48

6.4 Occupied Bandwidth

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	January 19, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.2096	317.464
190	836.6	246.1474	318.157
251	848.8	244.6274	316.216

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.1912	318.643
661	1880.0	246.3498	325.646
810	1909.8	246.6157	319.320

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	242.1026	316.071
190	836.6	245.0671	320.429
251	848.8	243.0301	316.098

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	243.5906	319.179
661	1880.0	247.6735	317.221
810	1909.8	241.9342	317.949

EGPRS (MCS 5):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	243.0015	315.779
190	836.6	240.9988	314.354
251	848.8	242.8601	316.452

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.4847	332.267
661	1880.0	242.9163	316.594
810	1909.8	247.3667	318.453

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1359	4.735
4175	835.0	4.1370	4.717
4233	846.6	4.1348	4.743

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1474	4.794
9400	1880.0	4.1386	4.752
9538	1907.6	4.1435	4.755

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1512	4.750
1413	1733	4.1424	4.782
1512	1752	4.1521	4.783

HSUPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1293	4.750
4175	835.0	4.1553	4.764
4233	846.6	4.1331	4.709

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1528	4.781
9400	1880.0	4.1494	4.755
9538	1907.6	4.1399	4.742

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1497	4.784
1413	1733	4.1473	4.756
1512	1752	4.1625	4.772

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1334	4.761
4175	835.0	4.1182	4.735
4233	846.6	4.1361	4.734

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1436	4.774
9400	1880.0	4.1414	4.735
9538	1907.6	4.1308	4.786

UMTS-FDD Band IV (Part 27)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1604	4.781
1413	1733	4.1310	4.730
1512	1752	4.1417	4.773

Test Plots


GMS Voice:




GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz





PCS 1900 BW - High CH 1910MHz


EGPRS:




RMC:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.6 MHz




Band II BW - Low CH 1853MHz




Band II BW - Mid CH 1880MHz


Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz


HSUPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.4 MHz




Band II BW - Low CH 1852.4MHz




Band II BW - Mid CH 1880MHz


Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz

HSDPA:






Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	January 20, 2017
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

GPRS:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2

PCS Band (Part24E) result




EGPRS (MCS 5):

Cellular Band (Part 22H) result




PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

UMTS-FDD Band IV (Part 27)




HSUPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

UMTS-FDD Band IV (Part 27)




HSDPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)



UMTS-FDD Band IV (Part 27)




6.6 Spurious Radiated Emissions

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	January 19/20, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---

Test Report	17070023-FCC-R1
Page	61 of 103

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-44.87	V	7.95	0.78	-37.7	-13	-24.7
1648.4	-45.16	H	7.95	0.78	-37.99	-13	-24.99
327.9	-51.37	V	6.4	0.26	-45.23	-13	-32.23
604.1	-51.25	H	6.8	0.37	-44.82	-13	-31.82

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-44.79	V	7.95	0.78	-37.62	-13	-24.62
1673.2	-45.03	H	7.95	0.78	-37.86	-13	-24.86
327.7	-51.46	V	6.4	0.26	-45.32	-13	-32.32
604.5	-51.38	H	6.8	0.37	-44.95	-13	-31.95

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-44.82	V	7.95	0.78	-37.65	-13	-24.65
1697.6	-45.11	H	7.95	0.78	-37.94	-13	-24.94
327.3	-51.67	V	6.4	0.26	-45.53	-13	-32.53
604.8	-51.53	H	6.8	0.37	-45.1	-13	-32.1

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-47.66	V	10.25	2.73	-40.14	-13	-27.14
3700.4	-48.73	H	10.25	2.73	-41.21	-13	-28.21
326.9	-52.19	V	6.4	0.26	-46.05	-13	-33.05
602.6	-52.54	H	6.8	0.37	-46.11	-13	-33.11

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-47.73	V	10.25	2.73	-40.21	-13	-27.21
3760	-48.85	H	10.25	2.73	-41.33	-13	-28.33
326.5	-52.06	V	6.4	0.26	-45.92	-13	-32.92
602.8	-52.41	H	6.8	0.37	-45.98	-13	-32.98

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-47.69	V	10.36	2.73	-40.06	-13	-27.06
3819.6	-48.56	H	10.36	2.73	-40.93	-13	-27.93
326.7	-52.21	V	6.4	0.26	-46.07	-13	-33.07
602.4	-51.33	H	6.8	0.37	-44.9	-13	-31.9

Note:

1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-47.58	V	7.95	0.78	-40.41	-13	-27.41
1652.8	-46.62	H	7.95	0.78	-39.45	-13	-26.45
327.6	-53.48	V	6.4	0.26	-47.34	-13	-34.34
606.5	-53.95	H	6.8	0.37	-47.52	-13	-34.52

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-47.61	V	7.95	0.78	-40.44	-13	-27.44
1670	-46.57	H	7.95	0.78	-39.4	-13	-26.4
327.2	-53.39	V	6.4	0.26	-47.25	-13	-34.25
606.3	-53.85	H	6.8	0.37	-47.42	-13	-34.42

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-47.56	V	7.95	0.78	-40.39	-13	-27.39
1693.2	-46.55	H	7.95	0.78	-39.38	-13	-26.38
327.7	-53.41	V	6.4	0.26	-47.27	-13	-34.27
606.5	-53.88	H	6.8	0.37	-47.45	-13	-34.45

Note:

1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-48.67	V	10.25	2.73	-41.15	-13	-28.15
3704.8	-48.73	H	10.25	2.73	-41.21	-13	-28.21
328.7	-52.19	V	6.4	0.26	-46.05	-13	-33.05
607.5	-52.26	H	6.8	0.37	-45.83	-13	-32.83

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.71	V	10.25	2.73	-41.19	-13	-28.19
3760	-48.69	H	10.25	2.73	-41.17	-13	-28.17
328.9	-52.24	V	6.4	0.26	-46.1	-13	-33.1
607.2	-52.37	H	6.8	0.37	-45.94	-13	-32.94

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.63	V	10.36	2.73	-41	-13	-28
3815.2	-48.59	H	10.36	2.73	-40.96	-13	-27.96
328.3	-52.3	V	6.4	0.26	-46.16	-13	-33.16
607.4	-52.33	H	6.8	0.37	-45.9	-13	-32.9

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

UMTS-FDD Band IV (Part 27)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-46.68	V	10.07	2.52	-39.13	-13	-26.13
3424.8	-48.97	H	10.07	2.52	-41.42	-13	-28.42
321.1	-56.64	V	6.4	0.26	-50.5	-13	-37.5
736.5	-51.86	H	7.1	0.42	-45.18	-13	-32.18

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-47.02	V	10.09	2.52	-39.45	-13	-26.45
3480	-46.99	H	10.09	2.52	-39.42	-13	-26.42
321.6	-56.82	V	6.4	0.26	-50.68	-13	-37.68
736.9	-52.34	H	7.1	0.42	-45.66	-13	-32.66

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-46.83	V	10.09	2.52	-39.26	-13	-26.26
3505.2	-46.74	H	10.09	2.52	-39.17	-13	-26.17
322.2	-56.81	V	6.4	0.26	-50.67	-13	-37.67
737.4	-52.27	H	7.1	0.42	-45.59	-13	-32.59

Note:

1, The testing has been conformed to $10 \times 1752.6 \text{ MHz} = 17.526 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases.

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

6.7 Band Edge

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	January 20, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup	 <p>The diagram shows a Base Station (green box) and a Spectrum Analyzer (green box) connected to an EUT (blue box) via a power divider (black box). The Base Station and Spectrum Analyzer are connected to the power divider, which then splits the signal to the EUT.</p>		
Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9825	-16.99	-13
849.0150	-17.23	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-15.27	-13
1910.0200	-15.19	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9750	-16.49	-13
849.0125	-14.49	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9825	-15.40	-13
1910.0175	-17.64	-13

EGPRS (MCS5):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-15.00	-13
849.0250	-16.70	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.44	-13
1910.0200	-15.55	-13

RCM:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-22.93	-13
849.025	-22.26	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.725	-18.84	-13
1910.250	-19.27	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.750	-21.34	-13
1755.200	-20.13	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-22.16	-13
849.025	-22.33	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.700	-19.92	-13
1910.225	-20.60	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.675	-21.64	-13
1755.325	-19.79	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-22.05	-13
849.025	-22.29	-13

UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.725	-19.54	-13
1910.275	-21.76	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.750	-19.63	-13
1755.175	-18.36	-13


GSM Voice:

Test Plots




GPRS:

Test Plots




EGPRS (MCS5):

Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.15/3)=4.0+0.2=4.2dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.16/3)=4.0+0.2=4.2dB



PCS Band - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(3.32/3)=4.5+0.3=4.8dB



PCS Band - High Channel


Note: Offset=Cable loss (4.5) + 10log
(3.18)=4.5+0.3=4.8dB

RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.35/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.43/30)=4.0+2.0=6.0dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.94/30)=4.5+2.0=6.5 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.55/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.5/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.0) + 10log
(47.83/30)=4.5+2.0=6.5 dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.5/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.09/30)=4.0+2.0=6.0 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.81/30)=4.5+2.0=6.5 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.42/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.84/30)=4.5+2.0=6.5dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(47.72/30)=4.5+2.0=6.5 dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.61/30)=4.0+2.0=6.0dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.34/30)=4.0+2.0=6.0 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.74/30)=4.5+2.0=6.5dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.86/30)=4.5+2.0=6.5dB



UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.81/30)=4.5+2.0=6.5dB





UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.73/30)=4.5+2.0=6.5 dB

6.8 Frequency Stability

Temperature	23 °C
Relative Humidity	51%
Atmospheric Pressure	1018mbar
Test date :	January 18, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup	 <p style="text-align: center;">Base Station Thermal Chamber</p>																																		

Procedure	<p>A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage.</p> <p>Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0227	2.5
0		15	0.0179	2.5
10		12	0.0143	2.5
20		17	0.0203	2.5
30		13	0.0155	2.5
40		15	0.0179	2.5
50		21	0.0251	2.5
55		20	0.0239	2.5
25	4.2	18	0.0215	2.5
	3.5	19	0.0227	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	13	0.0069	2.5
0		14	0.0074	2.5
10		16	0.0085	2.5
20		15	0.0080	2.5
30		16	0.0085	2.5
40		14	0.0074	2.5
50		14	0.0074	2.5
55		15	0.0080	2.5
25	4.2	16	0.0085	2.5
	3.5	20	0.0106	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	11	0.0132	2.5
0		10	0.0120	2.5
10		12	0.0144	2.5
20		13	0.0156	2.5
30		15	0.0180	2.5
40		10	0.0120	2.5
50		19	0.0228	2.5
55		14	0.0168	2.5
25	4.2	16	0.0192	2.5
	3.5	15	0.0180	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	14	0.0074	2.5
0		16	0.0085	2.5
10		17	0.0090	2.5
20		9	0.0048	2.5
30		10	0.0053	2.5
40		12	0.0064	2.5
50		11	0.0059	2.5
55		12	0.0064	2.5
25	4.2	14	0.0074	2.5
	3.5	16	0.0085	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0192	2.5
0		15	0.0180	2.5
10		13	0.0156	2.5
20		16	0.0192	2.5
30		16	0.0192	2.5
40		11	0.0132	2.5
50		13	0.0156	2.5
55		11	0.0132	2.5
25	4.2	8	0.0096	2.5
	3.5	14	0.0168	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/15/2016	09/14/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/08/2016	10/07/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/09/2016	03/08/2017	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>

Test Report	17070023-FCC-R1
Page	87 of 103

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Front View




EUT - Front View




EUT - Rear View




EUT - Top View



EUT - Bottom View



EUT - Left View




EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Mainboard with Shielding – Rear View



Mainboard without Shielding - Rear View



LCD – Front View



LCD – Rear View




GSM/PCS/UMTS-FDD Antenna View




WIFI/BT/BLE/GPS - Antenna View



Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Posh Mobile Limited	Adapter	ASUC37a-050100	F0521DH2

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	K0526DL2

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A