


# FCC Radio Test Report

## FCC ID: 2ALMN-A01R


This report concerns (check one): ☒ Original Grant ☐ Class I Change ☐ Class II Change

Project No. : 1803047  
Equipment : Bbtalkin Advance  
Test Model : A-01R  
Series Model : N/A  
Applicant : IHR FAC INC.  
Address : 2F, NO.455, Sec. 2, Zhongqing Rd., Beitun Dist.,  
Taichung City 406, Taiwan (R.O.C)

Date of Receipt : Mar. 16, 2018  
Date of Test : Mar. 16, 2018 ~ Jul. 13, 2018  
Issued Date : Jul. 16, 2018  
Tested by : BTL Inc.

Testing Engineer :   
(Kehji Lin)

Technical Manager :   
(James Chiu)

Authorized Signatory :   
(Andy Chiu)

# B T L I N C .

No.18, Ln. 171, Sec. 2, Jiuzong Rd.,  
Neihu Dist., Taipei City, Taiwan (R.O.C.)  
TEL:+886-2-2657-3299 FAX: +886-2-2657-3331



### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements in all the possible configurations as representative of its intended use.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
<b>1 . CERTIFICATION</b>	<b>7</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>8</b>
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
<b>3 . GENERAL INFORMATION</b>	<b>11</b>
3.1 GENERAL DESCRIPTION OF EUT	11
3.2 DESCRIPTION OF TEST MODES	13
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	13
3.4 DUTY CYCLE	14
3.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	15
3.6 DESCRIPTION OF SUPPORT UNITS	15
<b>4 . EMC EMISSION TEST</b>	<b>16</b>
4.1 CONDUCTED EMISSION MEASUREMENT	16
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	16
4.1.2 TEST PROCEDURE	16
4.1.3 DEVIATION FROM TEST STANDARD	16
4.1.4 TEST SETUP	17
4.1.5 EUT OPERATING CONDITIONS	17
4.1.6 EUT TEST CONDITIONS	17
4.1.7 TEST RESULTS	17
4.2 RADIATED EMISSION MEASUREMENT	18
4.2.1 RADIATED EMISSION LIMITS	18
4.2.2 TEST PROCEDURE	19
4.2.3 DEVIATION FROM TEST STANDARD	19
4.2.4 TEST SETUP	20
4.2.5 EUT OPERATING CONDITIONS	21
4.2.6 EUT TEST CONDITIONS	21
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	21
4.2.7 TEST RESULTS (30MHZ TO 1000 MHZ)	21
4.2.7 TEST RESULTS (ABOVE 1000 MHZ)	21
<b>5 . NUMBER OF HOPPING CHANNEL</b>	<b>22</b>
5.1 APPLIED PROCEDURES	22
5.1.1 TEST PROCEDURE	22
5.1.2 DEVIATION FROM STANDARD	22
5.1.3 TEST SETUP	22
5.1.4 EUT OPERATION CONDITIONS	22
5.1.5 EUT TEST CONDITIONS	22

Table of Contents	Page
5.1.6 TEST RESULTS	22
<b>6 . AVERAGE TIME OF OCCUPANCY</b>	<b>23</b>
6.1 APPLIED PROCEDURES / LIMIT	23
6.1.1 TEST PROCEDURE	23
6.1.2 DEVIATION FROM STANDARD	23
6.1.3 TEST SETUP	23
6.1.4 EUT OPERATION CONDITIONS	24
6.1.5 EUT TEST CONDITIONS	24
6.1.6 TEST RESULTS	24
<b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>25</b>
7.1 APPLIED PROCEDURES / LIMIT	25
7.1.1 TEST PROCEDURE	25
7.1.2 DEVIATION FROM STANDARD	25
7.1.3 TEST SETUP	25
7.1.4 EUT TEST CONDITIONS	25
7.1.5 TEST RESULTS	25
<b>8 . BANDWIDTH TEST</b>	<b>26</b>
8.1 APPLIED PROCEDURES	26
8.1.1 TEST PROCEDURE	26
8.1.2 DEVIATION FROM STANDARD	26
8.1.3 TEST SETUP	26
8.1.4 EUT OPERATION CONDITIONS	26
8.1.5 EUT TEST CONDITIONS	26
8.1.6 TEST RESULTS	26
<b>9 . PEAK OUTPUT POWER TEST</b>	<b>27</b>
9.1 APPLIED PROCEDURES / LIMIT	27
9.1.1 TEST PROCEDURE	27
9.1.2 DEVIATION FROM STANDARD	27
9.1.3 TEST SETUP	27
9.1.4 EUT OPERATION CONDITIONS	27
9.1.5 EUT TEST CONDITIONS	27
9.1.6 TEST RESULTS	27
<b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>28</b>
10.1 APPLIED PROCEDURES / LIMIT	28
10.1.1 TEST PROCEDURE	28
10.1.2 DEVIATION FROM STANDARD	28
10.1.3 TEST SETUP	28
10.1.4 EUT OPERATION CONDITIONS	28
10.1.5 EUT TEST CONDITIONS	28
10.1.6 TEST RESULTS	28

<b>Table of Contents</b>	<b>Page</b>
<b>11 . MEASUREMENT INSTRUMENTS LIST</b>	<b>29</b>
<b>12 . EUT TEST PHOTO</b>	<b>31</b>
<b>APPENDIX A - CONDUCTED EMISSION</b>	<b>35</b>
<b>APPENDIX B - RADIATED EMISSION (9KHZ-30MHZ)</b>	<b>38</b>
<b>APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>43</b>
<b>APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>46</b>
<b>APPENDIX E - NUMBER OF HOPPING CHANNEL</b>	<b>71</b>
<b>APPENDIX F - AVERAGE TIME OF OCCUPANCY</b>	<b>73</b>
<b>APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>76</b>
<b>APPENDIX H - BANDWIDTH</b>	<b>79</b>
<b>APPENDIX I - PEAK OUTPUT POWER</b>	<b>82</b>
<b>APPENDIX J - ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>85</b>

## REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1803047	Original Issue.	Jul. 16, 2018

## 1. CERTIFICATION

Equipment : Bbtalkin Advance  
Brand Name : Bb TALKIN'  
Test Model : A-01R  
Series Model : N/A  
Applicant : IHR FAC INC.  
Manufacturer : SHIN PUU TECHNOLOGY CO., LTD.  
Address : No. 47, Neihsi Rd., Lu Chu Dist., Taoyuan City 338, Taiwan (R.O.C)  
Date of Test : Mar. 16, 2018 ~ Jul. 13, 2018  
Test Sample : Engineering Sample  
Standard(s) : FCC Part15, Subpart C (15.247)/ ANSI C63.10-2013

The above equipment has been tested and found in compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1803047) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

**Test results included in this report is only for the Bluetooth EDR part.**

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15, Subpart C (15.247)			
Standard(s) Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	Hopping Channel Separation	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247 (b)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205	Restricted Bands	PASS	
15.203	Antenna Requirement	PASS	

Note:

(1) "N/A" denotes test is not applicable in this test report



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

### Conducted emission Test:

**C05:** (FCC RN:674415; FCC DN:TW0659)

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

### Radiated emission Test (Below 1 GHz):

**CB15:** (FCC RN:674415; FCC DN:TW0659; ISED Assigned Code:20088-5)

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

### Radiated emission Test (Above 1 GHz):

**CB15:** (FCC RN:674415; FCC DN:TW0659; ISED Assigned Code:20088-5)

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2  $U_{\text{CISPR}}$  requirement.

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

### A. Conducted emission test:

Test Site	Method	Measurement Frequency Range	U,(dB)
C05	CISPR	150 kHz ~ 30MHz	2.68

### B. Radiated emission test:

Test Site	Method	Measurement Frequency Range	U,(dB)
CB15 (3m)	CISPR	9kHz ~ 150kHz	2.82
		150kHz ~ 30MHz	2.58

Test Site	Method	Measurement Frequency Range	Ant.	U,(dB)
CB15 (3m)	CISPR	30MHz ~ 200MHz	V	4.20
		30MHz ~ 200MHz	H	3.64
		200MHz ~ 1,000MHz	V	4.56
		200MHz ~ 1,000MHz	H	3.90

Test Site	Method	Measurement Frequency Range	Ant.	U,(dB)
CB15 (3m)	CISPR	1GHz ~ 6GHz	V	4.46
		1GHz ~ 6GHz	H	4.40
		6GHz ~ 18GHz	V	3.88
		6GHz ~ 18GHz	H	4.00

Test Site	Method	Measurement Frequency Range	U,(dB)
CB15 (1m)	CISPR	18 ~ 26.5 GHz	4.62
		26.5 ~ 40 GHz	5.12

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our  $U_{lab}$  values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called  $U_{CISPR}$ , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz: 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz: 5.2 dB

It can be seen that our  $U_{lab}$  values are smaller than  $U_{CISPR}$ .

Note: unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Bbtalkin Advance
Brand Name	Bb TALKIN'
Test Model	A-01R
Series Model	N/A
Model Difference	N/A
Power Source	#1 Supplied from USB port. #2 Supplied from battery.
Power Rating	#1 DC 5V #2 DC 3.7V
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	1/2/3Mbps
Output Power Max.	1 Mbps: 13.24dBm 3 Mbps: 11.74dBm

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

## 2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

## 3. Table for Filed Antenna

Ant.	Brand	Test Model	Antenna Type	Connector	Gain (dBi)
1	Master Wave	907X00544X0	Copper Antenna	I-PEX	3.64

### 3.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Following mode(s) as (were) found to be the worst case(s) and selected for the final test.

Test Items	Test mode	Channel	Note
Conducted Emission	8-DPSK	78	-
Radiated Spurious Emission (BELOW 1GHz)	8-DPSK	78	-
Radiated Spurious Emission (ABOVE 1GHz)	GFSK/8-DPSK	00/39/78	-
Number of Hopping Frequency	GFSK/8-DPSK	00~78	-
Average Time of Occupancy	GFSK/8-DPSK	00/39/78	-
Hopping Channel Separation	GFSK/8-DPSK	00/39/78	-
Bandwidth	GFSK/8-DPSK	00/39/78	-
Peak Output Power	GFSK/8-DPSK	00/39/78	-
Antenna conducted Spurious Emission	GFSK/8-DPSK	00/39/78	-

**Note:**

- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.


### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software Version	Blue Test3 2.6.2		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	44/4	44/4	44/4
Parameters(3Mbps)	44/4	44/4	44/4

### 3.4 DUTY CYCLE


If duty cycle is  $\geq 98\%$ , duty factor is not required.  
If duty cycle is  $< 98\%$ , duty factor shall be considered.



#### Note:

For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1/3 MHz and the video bandwidth is 3 kHz (Duty cycle  $< 98\%$ ).

### 3.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



### 3.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
A	NB	HP	TPN-I119	N/A	5CG7032BNS

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.0m	USB Cable

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.50	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)  
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation



#### 4.1.4 TEST SETUP



#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 45%

Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Please refer to the Appendix A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### 4.2.2 TEST PROCEDURE


- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.2.3 DEVIATION FROM TEST STANDARD


No deviation

#### 4.2.4 TEST SETUP


##### (A) Radiated Emission Test Set-Up Frequency Below 1 GHz



##### (B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 23°C

Relative Humidity: 70%

Test Voltage: AC 120V/60Hz

#### 4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.2.7 TEST RESULTS (30MHZ TO 1000 MHZ)

Please refer to the Appendix C.

#### 4.2.7 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Appendix D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.1.5 EUT TEST CONDITIONS

Test Voltage: AC 120V/60Hz

#### 5.1.6 TEST RESULTS

Please refer to the Appendix E

## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
- DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
- DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### **6.1.5 EUT TEST CONDITIONS**

Test Voltage: AC 120V/60Hz

#### **6.1.6 TEST RESULTS**

Please refer to the Appendix F



## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- The EUT must have its hopping function enabled
- Span = wide enough to capture the peaks of two adjacent channels
  - Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span
  - Video (or Average) Bandwidth (VBW)  $\geq$  RBW
  - Sweep = Auto
  - Detector function = Peak
  - Trace = Max Hold

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT TEST CONDITIONS

Test Voltage: AC 120V/60Hz

#### 7.1.5 TEST RESULTS

Please refer to the Appendix G

## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 8.1.5 EUT TEST CONDITIONS

Test Voltage: AC 120V/60Hz

#### 8.1.6 TEST RESULTS

Please refer to the Appendix H

## 9. PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	1 Watt or 30dBm ( hopping channel >75) 0.125Watt or 21dBm (hopping channel <75)	2400-2483.5	PASS


#### 9.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

#### 9.1.2 DEVIATION FROM STANDARD

No deviation.

#### 9.1.3 TEST SETUP



#### 9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 9.1.5 EUT TEST CONDITIONS

Test Voltage: AC 120V/60Hz

#### 9.1.6 TEST RESULTS

Please refer to the Appendix I

## 10. ANTENNA CONDUCTED SPURIOUS EMISSION

### 10.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

#### 10.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.
- Offset=antenna gain+cable loss

#### 10.1.2 DEVIATION FROM STANDARD

No deviation.

#### 10.1.3 TEST SETUP



#### 10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 10.1.5 EUT TEST CONDITIONS

Test Voltage: AC 120V/60Hz

#### 10.1.6 TEST RESULTS

Please refer to the Appendix J

## 11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TWO-LINE V-NETWORK	R&S	ENV216	101050	Mar. 08, 2019
2	Test Cable	EMCI	EMCCFD300-BM-BMR-6000	170715	Aug. 08, 2018
3	EMI Test Receiver	R&S	ESR7	101433	Dec. 10, 2018
4	Measurement Software	EZ	EZ EMC (Version NB-03A)	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Preamplifier	EMCI	012645B	980267	Feb. 27, 2019
2	Preamplifier	EMCI	EMC02325	980217	Dec. 27, 2019
3	Preamplifier	EMCI	EMC2654045	980030	Feb. 13, 2019
4	Test Cable	EMCI	EMC104-SM-S M-8000	8m	Jan. 03, 2019
5	Test Cable	EMCI	EMC104-SM-S M-800	150207	Jan. 03, 2019
6	Test Cable	EMCI	EEMC104-SM-S M-3000	151205	Jan. 03, 2019
7	MXE EMI Receiver	Agilent	N9038A	MY55420127	Jan. 08, 2019
8	Signal Analyzer	Agilent	N9010A	MY52220990	Feb. 21, 2019
9	Loop Ant	EMCI	LPA600	274	May 03, 2019
10	Horn Ant	SCHWARZBECK	BBHA 9120D	9120D-1342	Feb. 27, 2019
11	Horn Ant	Schwarzbeck	BBHA 9170	187	Dec. 05, 2018
12	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-548	Jan. 15, 2019
13	5dB Attenuator	EMCI	EMCI-N-6-05	AT-N0623	Jan. 15, 2019

Number of Hopping Channel					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 24, 2019

Average Time of Occupancy					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 24, 2019

Hopping Channel Separation Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 24, 2019

Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 24, 2019

Peak Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2495A	1128008	Aug. 16, 2018
2	Power Sensor	Anritsu	MA2411B	1126001	Aug. 16, 2018


Antenna Conducted Spurious Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	R&S/FSP30	100854	May 24, 2019

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
All calibration period of equipment list is one year.

## APPENDIX A - CONDUCTED EMISSION

Test Mode:	TX Mode 2480MHz _CH78_3Mbps
------------	-----------------------------

### Line




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1	*	0.1815	48.30	9.63	57.93	64.42	-6.49	QP	
2		0.1815	28.80	9.63	38.43	54.42	-15.99	AVG	
3		0.3100	36.10	9.65	45.75	59.97	-14.22	QP	
4		0.3100	19.50	9.65	29.15	49.97	-20.82	AVG	
5		0.6066	30.50	9.66	40.16	56.00	-15.84	QP	
6		0.6066	15.60	9.66	25.26	46.00	-20.74	AVG	
7		1.8758	26.50	9.69	36.19	56.00	-19.81	QP	
8		1.8758	17.50	9.69	27.19	46.00	-18.81	AVG	
9		4.1753	25.60	9.74	35.34	56.00	-20.66	QP	
10		4.1753	19.60	9.74	29.34	46.00	-16.66	AVG	
11		22.9875	25.60	9.96	35.56	60.00	-24.44	QP	
12		22.9875	19.10	9.96	29.06	50.00	-20.94	AVG	



Test Mode: TX Mode 2480MHz \_CH78\_3Mbps

### Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1860	47.90	9.61	57.51	64.21	-6.70	QP	
2		0.1860	31.40	9.61	41.01	54.21	-13.20	AVG	
3		0.4087	31.70	9.65	41.35	57.67	-16.32	QP	
4		0.4087	16.20	9.65	25.85	47.67	-21.82	AVG	
5		1.2120	26.80	9.66	36.46	56.00	-19.54	QP	
6		1.2120	15.30	9.66	24.96	46.00	-21.04	AVG	
7		4.3507	25.00	9.73	34.73	56.00	-21.27	QP	
8		4.3507	19.30	9.73	29.03	46.00	-16.97	AVG	
9		12.3516	24.30	9.93	34.23	60.00	-25.77	QP	
10		12.3516	23.40	9.93	33.33	50.00	-16.67	AVG	
11		18.8790	26.10	9.98	36.08	60.00	-23.92	QP	
12		18.8790	18.80	9.98	28.78	50.00	-21.22	AVG	

## APPENDIX B - RADIATED EMISSION (9KHZ-30MHZ)

Test Mode:	TX Mode 2480MHz _CH78_3Mbps
------------	-----------------------------

Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1	*	0.0670	38.04	12.69	50.73	111.08	-60.35	peak

Test Mode: TX Mode 2480MHz \_CH78\_3Mbps


Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.1500	47.93	12.03	59.96	104.08	-44.12	peak	
2	*	1.3440	27.36	11.85	39.21	65.04	-25.83	peak	
3		3.5825	18.91	11.19	30.10	69.54	-39.44	peak	
4		6.1497	15.55	11.38	26.93	69.54	-42.61	peak	
5		8.6272	12.90	11.33	24.23	69.54	-45.31	peak	
6		11.7911	12.65	11.25	23.90	69.54	-45.64	peak	

Test Mode:	TX Mode 2480MHz _CH78_3Mbps
------------	-----------------------------


Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1	*	0.0580	39.60	12.86	52.46	112.34	-59.88	peak

Test Mode: TX Mode 2480MHz \_CH78\_3Mbps

Ant 0°




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.3291	40.93	11.80	52.73	97.26	-44.53	peak	
2	*	1.5530	25.58	11.75	37.33	63.78	-26.45	peak	
3		2.6274	21.29	11.27	32.56	69.54	-36.98	peak	
4		4.3290	18.38	11.30	29.68	69.54	-39.86	peak	
5		6.1497	15.55	11.38	26.93	69.54	-42.61	peak	
6		8.6272	12.90	11.33	24.23	69.54	-45.31	peak	

## APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX Mode 2480MHz \_CH78\_3Mbps

## Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		36.7900	32.66	-9.16	23.50	40.00	-16.50	peak	
2		130.8800	33.38	-10.06	23.32	43.50	-20.18	peak	
3		252.1300	37.03	-9.28	27.75	46.00	-18.25	peak	
4		359.8000	32.70	-6.20	26.50	46.00	-19.50	peak	
5		455.8300	32.74	-3.95	28.79	46.00	-17.21	peak	
6	*	558.6500	32.59	-1.94	30.65	46.00	-15.35	peak	



Test Mode: TX Mode 2480MHz \_CH78\_3Mbps

### Horizontal




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	71.7100	36.80	-11.29	25.51	40.00	-14.49	peak	
2	188.1100	40.23	-10.88	29.35	43.50	-14.15	peak	
3 *	259.8900	45.64	-8.96	36.68	46.00	-9.32	peak	
4	359.8000	35.96	-6.20	29.76	46.00	-16.24	peak	
5	455.8300	34.11	-3.95	30.16	46.00	-15.84	peak	
6	639.1600	30.67	-0.16	30.51	46.00	-15.49	peak	

## APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2384.566	15.48	31.05	46.53	74.00	-27.47	peak	
2		2384.566	2.85	31.05	33.90	54.00	-20.10	AVG	
3	X	2402.000	66.41	31.11	97.52	74.00	23.52	peak	No Limit
4	*	2402.000	66.01	31.11	97.12	54.00	43.12	AVG	No Limit

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	61.10	-10.41	50.69	74.00	-23.31	peak	
2	*	4804.000	56.25	-10.41	45.84	54.00	-8.16	AVG	

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


**Orthogonal Axis: X**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2377.039	15.94	31.02	46.96	74.00	-27.04	peak	
2		2377.039	3.19	31.02	34.21	54.00	-19.79	AVG	
3	*	2402.000	67.26	31.11	98.37	54.00	44.37	AVG	No Limit
4	X	2402.200	67.66	31.11	98.77	74.00	24.77	peak	No Limit

Test Mode	TX Mode 2402MHz _CH00_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	62.08	-10.41	51.67	74.00	-22.33	peak	
2	*	4804.000	57.86	-10.41	47.45	54.00	-6.55	AVG	

Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2441.000	71.91	31.25	103.16	74.00	29.16	peak	No Limit
2	*	2441.000	71.48	31.25	102.73	54.00	48.73	AVG	No Limit

Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------

### Orthogonal Axis: X




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	61.77	-11.28	50.49	74.00	-23.51	peak	
2	*	4882.000	57.05	-11.28	45.77	54.00	-8.23	AVG	



Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


**Orthogonal Axis: X**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2441.000	77.26	31.25	108.51	74.00	34.51	peak	No Limit
2	*	2441.000	76.81	31.25	108.06	54.00	54.06	AVG	No Limit

Test Mode	TX Mode 2441MHz _CH39_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	66.31	-11.28	55.03	74.00	-18.97	peak	
2	*	4882.000	63.23	-11.28	51.95	54.00	-2.05	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	71.93	31.39	103.32	74.00	29.32	peak	
2	*	2480.000	71.58	31.39	102.97	54.00	48.97	AVG	
3		2483.500	18.89	31.41	50.30	74.00	-23.70	peak	
4		2483.500	7.37	31.41	38.78	54.00	-15.22	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


### Orthogonal Axis: X



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	57.58	-11.15	46.43	74.00	-27.57	peak	
2	*	4960.000	50.04	-11.15	38.89	54.00	-15.11	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


**Orthogonal Axis: X**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	73.95	31.39	105.34	74.00	31.34	peak	
2	*	2480.000	73.59	31.39	104.98	54.00	50.98	AVG	
3		2483.500	26.70	31.41	58.11	74.00	-15.89	peak	
4		2483.500	13.76	31.41	45.17	54.00	-8.83	AVG	

Test Mode	TX Mode 2480MHz _CH78_1Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	4960.000	59.31	-11.15	48.16	54.00	-5.84	AVG	
2		4959.660	63.40	-11.15	52.25	74.00	-21.75	peak	

Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2389.896	17.41	31.06	48.47	74.00	-25.53	peak	
2		2389.896	3.89	31.06	34.95	54.00	-19.05	AVG	
3	X	2402.000	77.68	31.11	108.79	74.00	34.79	peak	
4	*	2402.000	72.29	31.11	103.40	54.00	49.40	AVG	

Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------

### Orthogonal Axis: X




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	65.74	-11.40	54.34	74.00	-19.66	peak	
2	*	4804.000	58.05	-11.40	46.65	54.00	-7.35	AVG	



Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2377.312	17.84	31.02	48.86	74.00	-25.14	peak	
2		2377.312	5.71	31.02	36.73	54.00	-17.27	AVG	
3	X	2402.000	81.18	31.11	112.29	74.00	38.29	peak	
4	*	2402.000	75.89	31.11	107.00	54.00	53.00	AVG	

Test Mode	TX Mode 2402MHz _CH00_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	68.57	-11.40	57.17	74.00	-16.83	peak	
2	*	4804.000	61.08	-11.40	49.68	54.00	-4.32	AVG	

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2441.000	78.57	31.25	109.82	74.00	35.82	peak	
2	*	2441.000	73.33	31.25	104.58	54.00	50.58	AVG	

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	67.25	-11.28	55.97	74.00	-18.03	peak	
2	*	4882.000	60.00	-11.28	48.72	54.00	-5.28	AVG	

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


**Orthogonal Axis: X**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2441.000	82.40	31.25	113.65	74.00	39.65	peak	
2	*	2441.000	77.21	31.25	108.46	54.00	54.46	AVG	

Test Mode	TX Mode 2441MHz _CH39_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------


### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	68.58	-11.28	57.30	74.00	-16.70	peak	
2	*	4882.000	61.29	-11.28	50.01	54.00	-3.99	AVG	

Test Mode	TX Mode 2480MHz _CH78_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------


**Orthogonal Axis: X**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	69.35	31.39	100.74	74.00	26.74	peak	
2	*	2480.000	64.88	31.39	96.27	54.00	42.27	AVG	
3		2483.500	21.56	31.41	52.97	74.00	-21.03	peak	
4		2483.500	6.64	31.41	38.05	54.00	-15.95	AVG	

Test Mode	TX Mode 2480MHz _CH78_3Mbps	Polarization	Vertical
-----------	-----------------------------	--------------	----------

### Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	58.08	-11.15	46.93	74.00	-27.07	peak	
2	*	4960.000	47.28	-11.15	36.13	54.00	-17.87	AVG	




Test Mode TX Mode 2480MHz \_CH78\_3Mbps

Polarization

Horizontal


Orthogonal Axis: X



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	75.31	31.39	106.70	74.00	32.70	peak	
2	*	2480.000	70.85	31.39	102.24	54.00	48.24	AVG	
3		2483.500	29.98	31.41	61.39	74.00	-12.61	peak	
4		2483.500	16.46	31.41	47.87	54.00	-6.13	AVG	

Test Mode	TX Mode 2480MHz _CH78_3Mbps	Polarization	Horizontal
-----------	-----------------------------	--------------	------------

### Orthogonal Axis: X




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	58.95	-11.15	47.80	74.00	-26.20	peak	
2	*	4960.000	48.87	-11.15	37.72	54.00	-16.28	AVG	

## APPENDIX E - NUMBER OF HOPPING CHANNEL

## Test Mode Hopping Mode\_1Mbps


Number of Hopping Channel 79



Date: 18.APR.2018 11:14:34

## Test Mode Hopping Mode\_3Mbps

Number of Hopping Channel 79




Date: 18.APR.2018 11:55:24

## APPENDIX F - AVERAGE TIME OF OCCUPANCY


Test Mode : TX Mode\_1Mbps

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	2.9200	0.3115	0.4000	Pass
DH3	2402	1.6600	0.2656	0.4000	Pass
DH1	2402	0.3950	0.1264	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.6600	0.2656	0.4000	Pass
DH1	2441	0.3900	0.1248	0.4000	Pass
DH5	2480	2.9200	0.3115	0.4000	Pass
DH3	2480	1.6400	0.2624	0.4000	Pass
DH1	2480	0.3950	0.1264	0.4000	Pass



Test Mode : TX Mode\_3Mbps

Data Packet	Frequency	Pulse Duration(ms)	Dwell Time(s)	Limits(s)	Test Result
DH5	2402	2.9200	0.3115	0.4000	Pass
DH3	2402	1.6400	0.2624	0.4000	Pass
DH1	2402	0.3950	0.1264	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.6600	0.2656	0.4000	Pass
DH1	2441	0.4050	0.1296	0.4000	Pass
DH5	2480	2.9200	0.3115	0.4000	Pass
DH3	2480	1.6400	0.2624	0.4000	Pass
DH1	2480	0.4050	0.1296	0.4000	Pass




## APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT




Test Mode :	Hopping on _1Mbps
-------------	-------------------

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.011	0.627	Pass
2441	1.002	0.625	Pass
2480	0.983	0.627	Pass



Test Mode :	Hopping on _3Mbps
-------------	-------------------


Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	0.998	0.837	Pass
2441	1.009	0.853	Pass
2480	0.993	0.831	Pass



## APPENDIX H - BANDWIDTH


Test Mode :	TX Mode _1Mbps
-------------	----------------

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	0.940	0.876	Pass
2441	0.938	0.848	Pass
2480	0.940	0.856	Pass



Test Mode :	TX Mode _3Mbps
-------------	----------------


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.256	1.156	Pass
2441	1.280	1.164	Pass
2480	1.247	1.156	Pass



## APPENDIX I - PEAK OUTPUT POWER


Test Mode :	TX Mode _1Mbps
-------------	----------------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	12.16	0.0164	21.00	0.125	Pass
2441	12.92	0.0196	21.00	0.125	Pass
2480	13.24	0.0211	21.00	0.125	Pass



Test Mode :	TX Mode _3Mbps
-------------	----------------


Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	10.38	0.0109	21.00	0.125	Pass
2441	11.53	0.0142	21.00	0.125	Pass
2480	11.74	0.0149	21.00	0.125	Pass






## APPENDIX J - ANTENNA CONDUCTED SPURIOUS EMISSION


# Test Mode : TX Mode \_1Mbps




## 2402 MHz – 10 Harmonics



Date: 18.APR.2018 10:32:07




Date: 18.APR.2018 10:32:14




Date: 18.APR.2018 10:32:21


## 2441 MHz – 10 Harmonics



Date: 18.APR.2018 10:56:48




Date: 18.APR.2018 10:56:55




Date: 18.APR.2018 10:57:02


## 2480 MHz – 10 Harmonics



Date: 18.APR.2018 10:59:16




Date: 18.APR.2018 10:59:23



Date: 18.APR.2018 10:59:30


# Test Mode : TX Mode \_3Mbps

## 2402 MHz\_Lower




Date: 18.APR.2018 11:40:07

## 2480 MHz\_Upper




Date: 18.APR.2018 11:43:05

## 2402 MHz\_Hopping on mode (Lower)




Date: 18.APR.2018 11:56:15

## 2480 MHz\_Hopping on mode (Upper)




Date: 18.APR.2018 11:56:40


## 2402 MHz – 10 Harmonics



Date: 18.APR.2018 11:40:54




Date: 18.APR.2018 11:41:01




Date: 18.APR.2018 11:41:07


## 2441 MHz – 10 Harmonics



Date: 18.APR.2018 11:41:43




Date: 18.APR.2018 11:41:50




Date: 18.APR.2018 11:41:57


## 2480 MHz – 10 Harmonics



Date: 18.APR.2018 11:43:52



Date: 18.APR.2018 11:43:58



Date: 18.APR.2018 11:44:05