Test Plot 1#: GSM 850_Head Left Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; ε_r = 42.188; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.177 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.600 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.189 W/kg
SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.116 W/kg
Maximum value of SAR (measured) = 0.177 W/kg

0 dB = 0.177 W/kg = -7.52 dBW/kg

Test Plot 2#: GSM 850_Head Left Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; $ε_r$ = 42.188; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0774 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.994 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.0830 W/kg
SAR(1 g) = 0.067 W/kg; SAR(10 g) = 0.053 W/kg
Maximum value of SAR (measured) = 0.0773 W/kg

0 dB = 0.0773 W/kg = -11.12 dBW/kg

Test Plot 3#: GSM 850_Head Right Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; ε_r = 42.188; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.125 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.142 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.135 W/kg
SAR(1 g) = 0.110 W/kg; SAR(10 g) = 0.087 W/kg
Maximum value of SAR (measured) = 0.126 W/kg

0 dB = 0.126 W/kg = -9.00 dBW/kg

Test Plot 4#: GSM 850_Head Right Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; ε_r = 42.188; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0886 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.512 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.0920 W/kg
SAR(1 g) = 0.076 W/kg; SAR(10 g) = 0.060 W/kg
Maximum value of SAR (measured) = 0.0873 W/kg

0 dB = 0.0873 W/kg = -10.59 dBW/kg

Test Plot 5#: GSM 850_Body Worn Back_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε_r = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.626 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.74 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.731 W/kg
SAR(1 g) = 0.411 W/kg; SAR(10 g) = 0.251 W/kg
Maximum value of SAR (measured) = 0.603 W/kg

0 dB = 0.603 W/kg = -2.20 dBW/kg

Test Plot 6#: GSM 850_Body Back_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 836.6 MHz;Duty Cycle: 1:4
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε_r = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.791 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.25 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.910 W/kg
SAR(1 g) = 0.517 W/kg; SAR(10 g) = 0.322 W/kg
Maximum value of SAR (measured) = 0.731 W/kg

0 dB = 0.731 W/kg = -1.36 dBW/kg

Test Plot 7#: GSM 850_Body Left_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 836.6 MHz;Duty Cycle: 1:4
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε_r = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.382 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 16.53 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.436 W/kg
SAR(1 g) = 0.298 W/kg; SAR(10 g) = 0.211 W/kg
Maximum value of SAR (measured) = 0.389 W/kg

0 dB = 0.389 W/kg = -4.10 dBW/kg

Test Plot 8#: GSM 850_Body Right_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 836.6 MHz;Duty Cycle: 1:4
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε_r = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.207 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.01 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.224 W/kg
SAR(1 g) = 0.158 W/kg; SAR(10 g) = 0.114 W/kg
Maximum value of SAR (measured) = 0.201 W/kg

0 dB = 0.201 W/kg = -6.97 dBW/kg

Test Plot 9#: GSM 850_Body Bottom_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 836.6 MHz;Duty Cycle: 1:4
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε_r = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.354 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.20 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.457 W/kg
SAR(1 g) = 0.230 W/kg; SAR(10 g) = 0.133 W/kg
Maximum value of SAR (measured) = 0.366 W/kg

0 dB = 0.366 W/kg = -4.37 dBW/kg

Test Plot 10#: GSM 1900_Head Left Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; ε_r = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.219 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.490 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.318 W/kg
SAR(1 g) = 0.192 W/kg; SAR(10 g) = 0.116 W/kg
Maximum value of SAR (measured) = 0.283 W/kg

0 dB = 0.283 W/kg = -5.48 dBW/kg

Test Plot 11#: GSM 1900_Head Left Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; ε_r = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.123 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.701 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 0.155 W/kg
SAR(1 g) = 0.087 W/kg; SAR(10 g) = 0.051 W/kg
Maximum value of SAR (measured) = 0.122 W/kg

0 dB = 0.122 W/kg = -9.14 dBW/kg

Test Plot 12#: GSM 1900_Head Right Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; ε_r = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.302 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.973 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 0.362 W/kg
SAR(1 g) = 0.237 W/kg; SAR(10 g) = 0.152 W/kg
Maximum value of SAR (measured) = 0.319 W/kg

0 dB = 0.319 W/kg = -4.96 dBW/kg

Test Plot 13#: GSM 1900_Head Right Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; ε_r = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.234 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.532 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.245 W/kg
SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.096 W/kg
Maximum value of SAR (measured) = 0.213 W/kg

0 dB = 0.213 W/kg = -6.72 dBW/kg

Test Plot 14#: GSM 1900_Body Worn Back_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; ε_r = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.699 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.517 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.864 W/kg
SAR(1 g) = 0.440 W/kg; SAR(10 g) = 0.237 W/kg
Maximum value of SAR (measured) = 0.682 W/kg

0 dB = 0.682 W/kg = -1.66 dBW/kg

Test Plot 15#: GSM 1900_Body Back_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 1880 MHz;Duty Cycle: 1:4
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; ε_r = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.13 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.87 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.33 W/kg
SAR(1 g) = 0.669 W/kg; SAR(10 g) = 0.356 W/kg
Maximum value of SAR (measured) = 1.07 W/kg

0 dB = 1.07 W/kg = 0.29 dBW/kg

Test Plot 16#: GSM 1900_Body Left_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 1880 MHz;Duty Cycle: 1:4
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; $ε_r$ = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.223 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.582 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.271 W/kg
SAR(1 g) = 0.150 W/kg; SAR(10 g) = 0.086 W/kg
Maximum value of SAR (measured) = 0.227 W/kg

0 dB = 0.227 W/kg = -6.44 dBW/kg

Test Plot 17#: GSM 1900_Body Right_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 1880 MHz;Duty Cycle: 1:4
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; ε_r = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.418 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.00 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.489 W/kg
SAR(1 g) = 0.282 W/kg; SAR(10 g) = 0.165 W/kg
Maximum value of SAR (measured) = 0.415 W/kg

0 dB = 0.415 W/kg = -3.82 dBW/kg

Test Plot 18#: GSM 1900_Body Bottom_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic GPRS-2 slots; Frequency: 1880 MHz;Duty Cycle: 1:4
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; ε_r = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.882 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.62 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 1.08 W/kg
SAR(1 g) = 0.563 W/kg; SAR(10 g) = 0.279 W/kg
Maximum value of SAR (measured) = 0.877 W/kg

0 dB = 0.877 W/kg = -0.57 dBW/kg

Test Plot 19#: WCDMA Band 2_Head Left Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; ε_r = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.419 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.291 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 0.442 W/kg
SAR(1 g) = 0.301 W/kg; SAR(10 g) = 0.204 W/kg
Maximum value of SAR (measured) = 0.392 W/kg

0 dB = 0.392 W/kg = -4.07 dBW/kg

Test Plot 20#: WCDMA Band 2_Head Left Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; $ε_r$ = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.268 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.18 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.320 W/kg
SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.100 W/kg
Maximum value of SAR (measured) = 0.268 W/kg

0 dB = 0.268 W/kg = -5.72 dBW/kg

Test Plot 21#: WCDMA Band 2_Head Right Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; ε_r = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.744 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.657 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.872 W/kg
SAR(1 g) = 0.534 W/kg; SAR(10 g) = 0.327 W/kg
Maximum value of SAR (measured) = 0.747 W/kg

0 dB = 0.747 W/kg = -1.27 dBW/kg

Test Plot 22#: WCDMA Band 2_Head Right Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.382 S/m; $ε_r$ = 40.581; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.48, 8.48, 8.48); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.256 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.46 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.274 W/kg
SAR(1 g) = 0.172 W/kg; SAR(10 g) = 0.104 W/kg
Maximum value of SAR (measured) = 0.233 W/kg

0 dB = 0.233 W/kg = -6.33 dBW/kg

Test Plot 23#: WCDMA Band 2_Body Back_Low

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1852.4 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1852.4 MHz; σ = 1.476 S/m; ε_r = 54.595; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.28 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.07 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 1.55 W/kg
SAR(1 g) = 0.796 W/kg; SAR(10 g) = 0.426 W/kg
Maximum value of SAR (measured) = 1.21 W/kg

0 dB = 1.21 W/kg = 0.83 dBW/kg

Test Plot 24#: WCDMA Band 2_Body Back_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; ε_r = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.39 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.92 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 1.68 W/kg
SAR(1 g) = 0.859 W/kg; SAR(10 g) = 0.462 W/kg
Maximum value of SAR (measured) = 1.31 W/kg

0 dB = 1.31 W/kg = 1.17 dBW/kg

Test Plot 25#: WCDMA Band 2_Body Back_High

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1907.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1907.6 MHz; σ = 1.495 S/m; $ε_r$ = 54.642; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.16 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.94 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 1.41 W/kg
SAR(1 g) = 0.715 W/kg; SAR(10 g) = 0.386 W/kg
Maximum value of SAR (measured) = 1.10 W/kg

0 dB = 1.10 W/kg = 0.41 dBW/kg

Test Plot 26#: WCDMA Band 2_Body Left_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; ε_r = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.437 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.12 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.539 W/kg
SAR(1 g) = 0.297 W/kg; SAR(10 g) = 0.166 W/kg
Maximum value of SAR (measured) = 0.453 W/kg

0 dB = 0.453 W/kg = -3.44 dBW/kg

Test Plot 27#: WCDMA Band 2_Body Right_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; ε_r = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.837 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.84 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.964 W/kg
SAR(1 g) = 0.544 W/kg; SAR(10 g) = 0.307 W/kg
Maximum value of SAR (measured) = 0.806 W/kg

0 dB = 0.806 W/kg = -0.94 dBW/kg

Test Plot 28#: WCDMA Band 2_Body Bottom_Low

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1852.4 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1852.4 MHz; σ = 1.476 S/m; ε_r = 54.595; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.35 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.03 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 1.80 W/kg
SAR(1 g) = 0.935 W/kg; SAR(10 g) = 0.462 W/kg
Maximum value of SAR (measured) = 1.48 W/kg

0 dB = 1.48 W/kg = 1.70 dBW/kg

Test Plot 29#: WCDMA Band 2_Body Bottom_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.486 S/m; $ε_r$ = 54.612; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.55 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.33 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 2.05 W/kg
SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.516 W/kg
Maximum value of SAR (measured) = 1.68 W/kg

0 dB = 1.68 W/kg = 2.25 dBW/kg

Test Plot 30#: WCDMA Band 2_Body Bottom_High

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 1907.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1907.6 MHz; σ = 1.495 S/m; ε_r = 54.642; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.95, 7.95, 7.95); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.39 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.18 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.86 W/kg
SAR(1 g) = 0.958 W/kg; SAR(10 g) = 0.469 W/kg
Maximum value of SAR (measured) = 1.52 W/kg

0 dB = 1.52 W/kg = 1.82 dBW/kg

Test Plot 31#: WCDMA Band 5_Head Left Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; ε_r = 42.188; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.174 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.746 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 0.179 W/kg
SAR(1 g) = 0.144 W/kg; SAR(10 g) = 0.113 W/kg
Maximum value of SAR (measured) = 0.166 W/kg

0 dB = 0.166 W/kg = -7.80 dBW/kg

Test Plot 32#: WCDMA Band 5_Head Left Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; ε_r = 42.188; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0648 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.495 V/m; Power Drift = 0.20 dB
Peak SAR (extrapolated) = 0.0680 W/kg
SAR(1 g) = 0.056 W/kg; SAR(10 g) = 0.045 W/kg
Maximum value of SAR (measured) = 0.0645 W/kg

0 dB = 0.0645 W/kg = -11.90 dBW/kg

Test Plot 33#: WCDMA Band 5_Head Right Cheek_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; ε_r = 42.188; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.131 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.777 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.144 W/kg
SAR(1 g) = 0.121 W/kg; SAR(10 g) = 0.098 W/kg
Maximum value of SAR (measured) = 0.137 W/kg

0 dB = 0.137 W/kg = -8.63 dBW/kg

Test Plot 34#: WCDMA Band 5_Head Right Tilt_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.889 S/m; ε_r = 42.188; ρ = 1000 kg/m³ ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.22, 10.22, 10.22); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0725 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.473 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.0760 W/kg
SAR(1 g) = 0.064 W/kg; SAR(10 g) = 0.052 W/kg
Maximum value of SAR (measured) = 0.0727 W/kg

0 dB = 0.0727 W/kg = -11.38 dBW/kg

Test Plot 35#: WCDMA Band 5_Body Back_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; $ε_r$ = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.639 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.20 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.751 W/kg
SAR(1 g) = 0.426 W/kg; SAR(10 g) = 0.267 W/kg
Maximum value of SAR (measured) = 0.582 W/kg

0 dB = 0.582 W/kg = -2.35 dBW/kg

Test Plot 36#: WCDMA Band 5_Body Left_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε_r = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.320 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.10 V/m; Power Drift = -0.19 dB
Peak SAR (extrapolated) = 0.362 W/kg
SAR(1 g) = 0.252 W/kg; SAR(10 g) = 0.179 W/kg
Maximum value of SAR (measured) = 0.324 W/kg

0 dB = 0.324 W/kg = -4.89 dBW/kg

Test Plot 37#: WCDMA Band 5_Body Right_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε$_r$ = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.186 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.55 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.205 W/kg
SAR(1 g) = 0.144 W/kg; SAR(10 g) = 0.104 W/kg
Maximum value of SAR (measured) = 0.183 W/kg

0 dB = 0.183 W/kg = -7.38 dBW/kg

Test Plot 38#: WCDMA Band 5_Body Bottom_Middle

DUT: 3G Smart Phone; Type: COVET; Serial: 17080400721

Communication System: Generic WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.965 S/m; ε_r = 56.587; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.85, 9.85, 9.85); Calibrated: 2016/11/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772;Calibrated: 2016/10/25
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.287 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.72 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 0.362 W/kg
SAR(1 g) = 0.185 W/kg; SAR(10 g) = 0.108 W/kg
Maximum value of SAR (measured) = 0.290 W/kg

0 dB = 0.290 W/kg = -5.38 dBW/kg