



# **RADIO TEST REPORT**

## **FCC ID: 2ALR4-WRTNODE7**

**Product:** MT7697module  
**Trade Mark:** N/A  
**Model No.:** wrtnode^7  
**Serial Model:** N/A  
**Report No.:** NTEK-2017NT04102559F1  
**Issue Date:** 18 Apr. 2017

### **Prepared for**

Beijing wanglianzhiyuan Tech Inc  
37-01 Zhonghaiwaerdenghu, 18 Dingsi Rd, Changping Dist, Beijing, China

### **Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China  
Tel.: +86-755-6115 6588  
Fax.: +86-755-6115 6599  
Website: <http://www.ntek.org.cn>

## TABLE OF CONTENTS

<b>1</b>	<b>TEST RESULT CERTIFICATION .....</b>	<b>3</b>
<b>2</b>	<b>SUMMARY OF TEST RESULTS.....</b>	<b>4</b>
<b>3</b>	<b>FACILITIES AND ACCREDITATIONS .....</b>	<b>5</b>
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS .....	5
3.3	MEASUREMENT UNCERTAINTY .....	5
<b>4</b>	<b>GENERAL DESCRIPTION OF EUT .....</b>	<b>6</b>
<b>5</b>	<b>DESCRIPTION OF TEST MODES .....</b>	<b>9</b>
<b>6</b>	<b>SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>10</b>
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	10
6.2	SUPPORT EQUIPMENT.....	11
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	12
<b>7</b>	<b>TEST REQUIREMENTS .....</b>	<b>14</b>
7.1	CONDUCTED EMISSIONS TEST .....	14
7.2	RADIATED SPURIOUS EMISSION .....	19
7.3	NUMBER OF HOPPING CHANNEL.....	33
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT .....	35
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	39
7.6	20DB BANDWIDTH TEST .....	43
7.7	PEAK OUTPUT POWER .....	47
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	51
7.9	SPURIOUS RF CONDUCTED EMISSION.....	55
7.10	ANTENNA APPLICATION .....	59

## 1 TEST RESULT CERTIFICATION

Applicant's name .....	Beijing wanglianzhiyuan Tech Inc
Address .....	37-01 Zhonghaiwaerdenghu, 18 Dingsi Rd, Changping Dist, Beijing, China
Manufacturer's Name .....	Beijing wanglianzhiyuan Tech Inc
Address .....	37-01 Zhonghaiwaerdenghu, 18 Dingsi Rd, Changping Dist, Beijing, China
Product description	
Product name .....	MT7697module
Model and/or type reference .....	wrtnode^7
Serial Model .....	N/A

Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J:2016 FCC 47 CFR Part 15, Subpart C:2016 KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013	Complied


This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 10 Apr. 2017 ~ 18 Apr. 2017

Testing Engineer :   
(Eileen Liu)

Technical Manager :   
(Jason Chen)

Authorized Signatory :   
(Sam Chen)

## 2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

**Remark:**

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

### 3 FACILITIES AND ACCREDITATIONS

#### 3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at  
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen  
518126 P.R. China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

#### 3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: Accredited by CNAS, 2014.09.04

The Laboratory has been assessed and proved to be in compliance with  
CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)

The Certificate Registration Number is L5516.

Accredited by FCC, September 6, 2013

The Certificate Registration Number is 238937.

Accredited by Industry Canada, August 29, 2012

The Certificate Registration Number is 9270A-1.

Name of Firm

: Shenzhen NTEK Testing Technology Co., Ltd.

Site Location

: 1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

#### 3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(>6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^{\circ}\text{C}$
8	Humidity	$\pm 2\%$

#### 4 GENERAL DESCRIPTION OF EUT


Product Feature and Specification	
Equipment	MT7697module
Trade Mark	N/A
FCC ID	2ALR4-WRTNODE7
Model No.	wrtnode^7
Serial Model	N/A
Model Difference	N/A
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Bluetooth Version	BT V4.0(EDR+BLE)
Number of Channels	79 Channels
Antenna Type	The EUT has two types of antenna(Note2): Antenna 1 is FPCB Antenna Antenna 2 is Ceramic Antenna
Antenna Gain	Antenna 1:4.5 dBi; Antenna 2: 0.5 dBi
Rating(s)	DC 3.3V
Power supply	<input type="checkbox"/> DC supply:
	<input type="checkbox"/> Adapter supply:
HW Version	V1.8
SW Version	V4.2.0

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Note2:

This is FPCB antenna(ANT 1)

This is Ceramic antenna(ANT 2)



### Revision History

Report No.	Version	Description	Issued Date
NTEK-2017NT04102559F1	Rev.01	Initial issue of report	Apr 18, 2017



## 5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for  $\pi/4$ -DQPSK modulation; 3Mbps for 8DPSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
...	...
39	2441
40	2442
...	...
77	2479
78	2480

Note:  $f_c = 2402\text{MHz} + k \times 1\text{MHz}$   $k=0$  to 78

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission	
Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases	
Final Test Mode	Description
Mode 1	normal link mode
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.


For Conducted Test Cases	
Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)
Mode 5	Hopping mode

Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.


## 6 SETUP OF EQUIPMENT UNDER TEST

### 6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1	MT7697module	N/A	wrtnode^7	2ALR4-WRTNODE7	EUT
E-2	Notebook	Lenovo	ThinkPad Edge E430	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.2m
C-2	RF Cable	NO	NO	0.5m

### Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

### 6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

#### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2016.07.06	2017.07.05	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2016.11.19	2017.11.18	1 year
3	Test Receiver	R&S	ESPI	101318	2016.06.07	2017.06.06	1 year
4	Bilog Antenna	TESEQ	CBL6111D	31216	2016.07.06	2017.07.05	1 year
5	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.06.07	2017.06.06	1 year
7	Horn Antenna	EM	EM-AH-1018 0	2011071402	2016.07.06	2017.07.05	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2016.07.06	2017.07.05	1 year
9	Pre-Amplifier	EMC	EMC051835 SE	980246	2016.08.09	2017.08.09	1 year
10	Loop Antenna	ARA	PLA-1030/B	1029	2016.06.08	2017.06.07	1 year
11	Test Cable (9KHz-30MHz)	N/A	R-04	N/A	2016.06.06	2017.06.05	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-01	N/A	2016.07.06	2017.07.05	1 year
13	Test Cable (1-18GHz)	N/A	R-02	N/A	2016.07.06	2017.07.05	1 year
14	High Test Cable(18G-40 GHz)	N/A	R-03	N/A	2016.06.06	2017.06.05	1 year
15	temporary antenna connector  (Note)	NTS	R001	N/A	N/A	N/A	N/A

#### Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test  
And this temporary antenna connector is listed within the instrument list

#### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2016.06.06	2017.06.05	1 year
2	LISN	R&S	ENV216	101313	2016.08.24	2017.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2016.08.24	2017.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.07	2017.06.06	1 year
7	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2016.06.08	2017.06.07	1 year
8	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2016.06.08	2017.06.07	1 year
9	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2016.06.08	2017.06.07	1 year

Note: Each piece of equipment is scheduled for calibration once a year.

## 7 TEST REQUIREMENTS

### 7.1 CONDUCTED EMISSIONS TEST

#### 7.1.1 Applicable Standard


According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

#### 7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. \*Decreases with the logarithm of the frequency  
2. The lower limit shall apply at the transition frequencies  
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 7.1.3 Test Configuration



#### 7.1.4 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 7.1.5 Test Results

Pass


### 7.1.6 Test Results

EUT:	MT7697module	Model Name :	wrtnode^7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1700	26.53	10.13	36.66	64.96	-28.30	QP
0.1700	7.15	10.13	17.28	54.96	-37.68	AVG
0.5299	24.75	10.17	34.92	56.00	-21.08	QP
0.5299	11.56	10.17	21.73	46.00	-24.27	AVG
0.5939	24.91	10.19	35.10	56.00	-20.90	QP
0.5939	13.81	10.19	24.00	46.00	-22.00	AVG
0.8619	22.67	10.24	32.91	56.00	-23.09	QP
0.8619	10.92	10.24	21.16	46.00	-24.84	AVG
4.1258	22.61	10.22	32.83	56.00	-23.17	QP
4.1258	8.53	10.22	18.75	46.00	-27.25	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	MT7697module	Model Name :	wrtnode^7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1539	28.46	10.14	38.60	65.78	-27.18	QP
0.1539	10.40	10.14	20.54	55.78	-35.24	AVG
0.5140	24.46	10.16	34.62	56.00	-21.38	QP
0.5140	13.26	10.16	23.42	46.00	-22.58	AVG
0.5820	27.01	10.19	37.20	56.00	-18.80	QP
0.5820	15.34	10.19	25.53	46.00	-20.47	AVG
0.8620	25.88	10.24	36.12	56.00	-19.88	QP
0.8620	14.26	10.24	24.50	46.00	-21.50	AVG
5.3899	23.14	10.23	33.37	60.00	-26.63	QP
5.3899	8.65	10.23	18.88	50.00	-31.12	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.






EUT:	MT7697module	Model Name :	wrtnode^7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2179	27.22	10.13	37.35	62.89	-25.54	QP
0.2179	12.01	10.13	22.14	52.89	-30.75	AVG
0.4460	26.72	10.15	36.87	56.95	-20.08	QP
0.4460	12.58	10.15	22.73	46.95	-24.22	AVG
0.6139	29.53	10.17	39.70	56.00	-16.30	QP
0.6139	15.08	10.17	25.25	46.00	-20.75	AVG
0.9939	25.88	10.20	36.08	56.00	-19.92	QP
0.9939	14.38	10.20	24.58	46.00	-21.42	AVG
2.3060	24.26	10.18	34.44	56.00	-21.56	QP
2.3060	12.40	10.18	22.58	46.00	-23.42	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	MT7697module	Model Name :	wrtnode^7
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1900	25.29	10.12	35.41	64.03	-28.62	QP
0.1900	8.46	10.12	18.58	54.03	-35.45	AVG
0.4339	23.11	10.17	33.28	57.18	-23.90	QP
0.4339	13.05	10.17	23.22	47.18	-23.96	AVG
0.5299	26.94	10.17	37.11	56.00	-18.89	QP
0.5299	15.38	10.17	25.55	46.00	-20.45	AVG
0.5979	25.25	10.19	35.44	56.00	-20.56	QP
0.5979	16.80	10.19	26.99	46.00	-19.01	AVG
0.9220	24.45	10.24	34.69	56.00	-21.31	QP
0.9220	12.58	10.24	22.82	46.00	-23.18	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



## 7.2 RADIATED SPURIOUS EMISSION

### 7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

### 7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

### 7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

### 7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



### 7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where  $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$ . , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

## 7.2.6 Test Results

### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	MT7697module	Model No.:	wtrnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $20 \log(\text{Specific distance} / \text{test distance})$  ( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission below 1GHz (30MHz to 1GHz)

All the modulation modes have been tested, and the worst result was report as below:


EUT:	MT7697module	Model Name :	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Normal Link- FPCB Antenna
Test Voltage :	DC 5V from Adapter AC 120V/60Hz		

Note:The EUT has two Antennas, This Antenna is FPCB Antenna

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	31.3992	5.56	19.13	24.69	40.00	-15.31	QP
V	66.2660	20.06	6.60	26.66	40.00	-13.34	QP
V	162.6106	24.49	12.01	36.50	43.50	-7.00	QP
V	171.9944	22.44	11.56	34.00	43.50	-9.50	QP
V	247.6819	20.70	14.83	35.53	46.00	-10.47	QP
V	261.9753	17.31	15.75	33.06	46.00	-12.94	QP

**Remark:**


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	30.5304	6.06	19.59	25.65	40.00	-14.35	QP
H	114.9167	11.35	13.22	24.57	43.50	-18.93	QP
H	157.0072	15.37	12.44	27.81	43.50	-15.69	QP
H	260.1444	20.45	15.78	36.23	46.00	-9.77	QP
H	372.0045	15.03	18.88	33.91	46.00	-12.09	QP
H	768.7481	10.28	27.80	38.08	46.00	-7.92	QP

**Remark:**

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit






EUT:	MT7697module	Model Name :	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1- Ceramic Antenna
Test Voltage :	DC 5V from Adapter AC 120V/60Hz		

Note:The EUT has two Antennas, This Antenna is Ceramic Antenna

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	69.3568	18.54	7.27	25.81	40.00	-14.19	QP
V	96.4361	14.61	11.58	26.19	43.50	-17.31	QP
V	163.1818	22.46	11.98	34.44	43.50	-9.06	QP
V	171.9944	22.44	11.56	34.00	43.50	-9.50	QP
V	261.9753	14.81	15.75	30.56	46.00	-15.44	QP
V	348.0274	10.41	17.75	28.16	46.00	-17.84	QP

#### Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	138.8735	9.71	12.96	22.67	43.50	-20.83	QP
H	157.0073	14.87	12.44	27.31	43.50	-16.19	QP
H	235.8163	19.31	12.77	32.08	46.00	-13.92	QP
H	268.4852	18.80	15.65	34.45	46.00	-11.55	QP
H	372.0045	16.03	18.88	34.91	46.00	-11.09	QP
H	768.7481	11.78	27.80	39.58	46.00	-6.42	QP

**Remark:**

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



# ■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	MT7697module	Model No.:	wtrnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4- FPCB Antenna	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(GFSK)--Above 1G									
4804.225	64.41	5.21	35.59	44.30	60.91	74.00	-13.09	Pk	Vertical
4804.225	42.23	5.21	35.59	44.30	38.73	54.00	-15.27	AV	Vertical
7206.369	63.65	6.48	36.27	44.60	61.80	74.00	-12.20	Pk	Vertical
7206.369	42.29	6.48	36.27	44.60	40.44	54.00	-13.56	AV	Vertical
4804.201	63.74	5.21	35.55	44.30	60.20	74.00	-13.80	Pk	Horizontal
4804.201	45.44	5.21	35.55	44.30	41.90	54.00	-12.10	AV	Horizontal
7206.417	65.58	6.48	36.27	44.52	63.81	74.00	-10.19	Pk	Horizontal
7206.417	45.16	6.48	36.27	44.52	43.39	54.00	-10.61	AV	Horizontal
Mid Channel (2441 MHz)(GFSK)--Above 1G									
4882.368	62.23	5.21	35.66	44.20	58.90	74.00	-15.10	Pk	Vertical
4882.368	46.59	5.21	35.66	44.20	43.26	54.00	-10.74	AV	Vertical
7323.264	65.57	7.10	36.50	44.43	64.74	74.00	-9.26	Pk	Vertical
7323.264	43.21	7.10	36.50	44.43	42.38	54.00	-11.62	AV	Vertical
4882.226	65.59	5.21	35.66	44.20	62.26	74.00	-11.74	Pk	Horizontal
4882.226	42.25	5.21	35.66	44.20	38.92	54.00	-15.08	AV	Horizontal
7323.191	63.25	7.10	36.50	44.43	62.42	74.00	-11.58	Pk	Horizontal
7323.191	42.11	7.10	36.50	44.43	41.28	54.00	-12.72	AV	Horizontal
High Channel (2480 MHz)(GFSK)-- Above 1G									
4960.292	65.54	5.21	35.52	44.21	62.06	74.00	-11.94	Pk	Vertical
4960.292	46.63	5.21	35.52	44.21	43.15	54.00	-10.85	AV	Vertical
7440.133	65.59	7.10	36.53	44.60	64.62	74.00	-9.38	Pk	Vertical
7440.133	43.32	7.10	36.53	44.60	42.35	54.00	-11.65	AV	Vertical
4960.249	65.58	5.21	35.52	44.21	62.10	74.00	-11.90	Pk	Horizontal
4960.249	42.02	5.21	35.52	44.21	38.54	54.00	-15.46	AV	Horizontal
7440.193	62.35	7.10	36.53	44.60	61.38	74.00	-12.62	Pk	Horizontal
7440.193	43.33	7.10	36.53	44.60	42.36	54.00	-11.64	AV	Horizontal

- Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).  
(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor  
(3)All other emissions more than 20dB below the limit.  
(4) The EUT has two Antennas, This Antenna is FPCB Antenna

### ■ Spurious Emission in Band edge

EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4/ Mode5- FPCB Antenna	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor dB/m	Preamplifier Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps(GFSK)- Non-hopping									
2310.00	58.95	2.97	27.80	43.80	45.92	74	-28.08	Pk	Horizontal
2310.00	43.32	2.97	27.80	43.80	30.29	54	-23.71	AV	Horizontal
2310.00	65.59	2.97	27.80	43.80	52.56	74	-21.44	Pk	Vertical
2310.00	42.14	2.97	27.80	43.80	29.11	54	-24.89	AV	Vertical
2390.00	60.67	3.14	27.21	43.80	47.22	74	-26.78	Pk	Vertical
2390.00	41.11	3.14	27.21	43.80	27.66	54	-26.34	AV	Vertical
2390.00	63.36	3.14	27.21	43.80	49.91	74	-24.09	Pk	Horizontal
2390.00	41.19	3.14	27.21	43.80	27.74	54	-26.26	AV	Horizontal
2483.50	59.67	3.58	27.70	44.00	46.95	74	-27.05	Pk	Vertical
2483.50	41.36	3.58	27.70	44.00	28.64	54	-25.36	AV	Vertical
2483.50	59.52	3.58	27.70	44.00	46.80	74	-27.2	Pk	Horizontal
2483.50	44.64	3.58	27.70	44.00	31.92	54	-22.08	AV	Horizontal
1Mbps (GFSK)- hopping									
2310.00	60.52	2.97	27.80	43.80	47.49	74	-26.51	Pk	Horizontal
2310.00	41.78	2.97	27.80	43.80	28.75	54	-25.25	AV	Horizontal
2310.00	62.35	2.97	27.80	43.80	49.32	74	-24.68	Pk	Vertical
2310.00	41.13	2.97	27.80	43.80	28.10	54	-25.9	AV	Vertical
2390.00	62.59	3.14	27.21	43.80	49.14	74	-24.86	Pk	Vertical
2390.00	41.15	3.14	27.21	43.80	27.70	54	-26.3	AV	Vertical
2390.00	62.37	3.14	27.21	43.80	48.92	74	-25.08	Pk	Horizontal
2390.00	41.18	3.14	27.21	43.80	27.73	54	-26.27	AV	Horizontal
2483.50	62.59	3.58	27.70	44.00	49.87	74	-24.13	Pk	Vertical
2483.50	42.32	3.58	27.70	44.00	29.60	54	-24.4	AV	Vertical
2483.50	60.59	3.58	27.70	44.00	47.87	74	-26.13	Pk	Horizontal
2483.50	42.21	3.58	27.70	44.00	29.49	54	-24.51	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.  
(2) The EUT has two Antennas, This Antenna is FPCB Antenna

■ Spurious Emission in Restricted Band 3260MHz-18000MHz

EUT:	MT7697module	Model No.:	wtrnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4- FPCB Antenna	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Reading Level	Cable Loss	Antenna	Preamp Factor	Emission Level	Limits	Margin	Detect or	Comment
(MHz)	(dBμV)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	62.35	4.04	29.57	44.70	51.26	74	-22.74	Pk	Vertical
3260	41.12	4.04	29.57	44.70	30.03	54	-23.97	AV	Vertical
3260	62.52	4.04	29.57	44.70	51.43	74	-22.57	Pk	Horizontal
3260	50.95	4.04	29.57	44.70	39.86	54	-14.14	AV	Horizontal
3332	63.34	4.26	29.87	44.40	53.07	74	-20.93	Pk	Vertical
3332	48.74	4.26	29.87	44.40	38.47	54	-15.53	AV	Vertical
3332	62.59	4.26	29.87	44.40	52.32	74	-21.68	Pk	Horizontal
3332	42.23	4.26	29.87	44.40	31.96	54	-22.04	AV	Horizontal
17797	41.17	10.99	43.95	43.50	52.61	74	-21.39	Pk	Vertical
17797	26.69	10.99	43.95	43.50	38.13	54	-15.87	AV	Vertical
17788	41.17	11.81	43.69	44.60	52.07	74	-21.93	Pk	Horizontal
17788	28.95	11.81	43.69	44.60	39.85	54	-14.15	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.  
(2) The EUT has two Antennas, This Antenna is FPCB Antenna

# ■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4- Ceramic Antenna	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(GFSK)--Above 1G									
4804.15	66.52	5.21	35.59	44.30	63.02	74.00	-10.98	Pk	Vertical
4804.15	41.18	5.21	35.59	44.30	37.68	54.00	-16.32	AV	Vertical
7206.21	62.64	6.48	36.27	44.60	60.79	74.00	-13.21	Pk	Vertical
7206.21	41.98	6.48	36.27	44.60	40.13	54.00	-13.87	AV	Vertical
4804.14	63.34	5.21	35.55	44.30	59.80	74.00	-14.20	Pk	Horizontal
4804.14	46.47	5.21	35.55	44.30	42.93	54.00	-11.07	AV	Horizontal
7206.25	65.58	6.48	36.27	44.52	63.81	74.00	-10.19	Pk	Horizontal
7206.25	46.69	6.48	36.27	44.52	44.92	54.00	-9.08	AV	Horizontal
Mid Channel (2441 MHz)(GFSK)--Above 1G									
4882.21	63.34	5.21	35.66	44.20	60.01	74.00	-13.99	Pk	Vertical
4882.21	45.58	5.21	35.66	44.20	42.25	54.00	-11.75	AV	Vertical
7323.26	66.67	7.10	36.50	44.43	65.84	74.00	-8.16	Pk	Vertical
7323.26	42.19	7.10	36.50	44.43	41.36	54.00	-12.64	AV	Vertical
4882.25	66.65	5.21	35.66	44.20	63.32	74.00	-10.68	Pk	Horizontal
4882.25	43.34	5.21	35.66	44.20	40.01	54.00	-13.99	AV	Horizontal
7323.04	64.44	7.10	36.50	44.43	63.61	74.00	-10.39	Pk	Horizontal
7323.04	43.96	7.10	36.50	44.43	43.13	54.00	-10.87	AV	Horizontal
High Channel (2480 MHz)(GFSK)-- Above 1G									
4960.16	66.56	5.21	35.52	44.21	63.08	74.00	-10.92	Pk	Vertical
4960.16	45.54	5.21	35.52	44.21	42.06	54.00	-11.94	AV	Vertical
7440.26	66.69	7.10	36.53	44.60	65.72	74.00	-8.28	Pk	Vertical
7440.26	42.21	7.10	36.53	44.60	41.24	54.00	-12.76	AV	Vertical
4960.27	66.69	5.21	35.52	44.21	63.21	74.00	-10.79	Pk	Horizontal
4960.27	43.38	5.21	35.52	44.21	39.90	54.00	-14.10	AV	Horizontal
7440.15	63.39	7.10	36.53	44.60	62.42	74.00	-11.58	Pk	Horizontal
7440.15	42.57	7.10	36.53	44.60	41.60	54.00	-12.40	AV	Horizontal

- Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).  
(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor  
(3)All other emissions more than 20dB below the limit.  
(4) The EUT has two Antennas, This Antenna is Ceramic Antenna

# ■ Spurious Emission in Band edge

EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4/ Mode5- Ceramic Antenna	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps(GFSK)- Non-hopping									
2310.00	59.85	2.97	27.80	43.80	46.82	74	-27.18	Pk	Horizontal
2310.00	42.23	2.97	27.80	43.80	29.20	54	-24.8	AV	Horizontal
2310.00	66.67	2.97	27.80	43.80	53.64	74	-20.36	Pk	Vertical
2310.00	43.14	2.97	27.80	43.80	30.11	54	-23.89	AV	Vertical
2390.00	59.86	3.14	27.21	43.80	46.41	74	-27.59	Pk	Vertical
2390.00	42.25	3.14	27.21	43.80	28.80	54	-25.2	AV	Vertical
2390.00	62.85	3.14	27.21	43.80	49.40	74	-24.6	Pk	Horizontal
2390.00	42.74	3.14	27.21	43.80	29.29	54	-24.71	AV	Horizontal
2483.50	60.53	3.58	27.70	44.00	47.81	74	-26.19	Pk	Vertical
2483.50	42.22	3.58	27.70	44.00	29.50	54	-24.5	AV	Vertical
2483.50	60.69	3.58	27.70	44.00	47.97	74	-26.03	Pk	Horizontal
2483.50	45.58	3.58	27.70	44.00	32.86	54	-21.14	AV	Horizontal
1Mbps (GFSK)- hopping									
2310.00	59.53	2.97	27.80	43.80	46.50	74	-27.5	Pk	Horizontal
2310.00	42.26	2.97	27.80	43.80	29.23	54	-24.77	AV	Horizontal
2310.00	61.17	2.97	27.80	43.80	48.14	74	-25.86	Pk	Vertical
2310.00	42.75	2.97	27.80	43.80	29.72	54	-24.28	AV	Vertical
2390.00	63.96	3.14	27.21	43.80	50.51	74	-23.49	Pk	Vertical
2390.00	42.26	3.14	27.21	43.80	28.81	54	-25.19	AV	Vertical
2390.00	61.01	3.14	27.21	43.80	47.56	74	-26.44	Pk	Horizontal
2390.00	42.24	3.14	27.21	43.80	28.79	54	-25.21	AV	Horizontal
2483.50	62.33	3.58	27.70	44.00	49.61	74	-24.39	Pk	Vertical
2483.50	42.35	3.58	27.70	44.00	29.63	54	-24.37	AV	Vertical
2483.50	59.85	3.58	27.70	44.00	47.13	74	-26.87	Pk	Horizontal
2483.50	41.13	3.58	27.70	44.00	28.41	54	-25.59	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.  
(2) The EUT has two Antennas, This Antenna is Ceramic Antenna

■ Spurious Emission in Restricted Band 3260MMHz-18000MHz

EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4- Ceramic Antenna	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Reading Level	Cable Loss	Antenna	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	61.23	4.04	29.57	44.70	50.14	74	-23.86	Pk	Vertical
3260	42.21	4.04	29.57	44.70	31.12	54	-22.88	AV	Vertical
3260	61.59	4.04	29.57	44.70	50.50	74	-23.50	Pk	Horizontal
3260	49.85	4.04	29.57	44.70	38.76	54	-15.24	AV	Horizontal
3332	62.34	4.26	29.87	44.40	52.07	74	-21.93	Pk	Vertical
3332	48.74	4.26	29.87	44.40	38.47	54	-15.53	AV	Vertical
3332	63.34	4.26	29.87	44.40	53.07	74	-20.93	Pk	Horizontal
3332	44.56	4.26	29.87	44.40	34.29	54	-19.71	AV	Horizontal
17797	41.13	10.99	43.95	43.50	52.57	74	-21.43	Pk	Vertical
17797	27.56	10.99	43.95	43.50	39.00	54	-15.00	AV	Vertical
17788	42.26	11.81	43.69	44.60	53.16	74	-20.84	Pk	Horizontal
17788	29.86	11.81	43.69	44.60	40.76	54	-13.24	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.  
(2) The EUT has two Antennas, This Antenna is Ceramic Antenna



### 7.3 NUMBER OF HOPPING CHANNEL

#### 7.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and ANSI C63.10-2013

#### 7.3.2 Conformance Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

#### 7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.3.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak


Trace = max hold

#### 7.3.6 Test Results

EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 5(1Mbps)	Test By:	Eileen Liu

Number of Hopping (Channel)	Adaptive Frequency hopping (Channel)	limit	Verdict
79	20	$\geq 15$	Pass

### Number of Hopping Channel Plot



## **7.4 HOPPING CHANNEL SEPARATION MEASUREMENT**

### **7.4.1 Applicable Standard**

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

### **7.4.2 Conformance Limit**

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### **7.4.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.4.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.4.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Measurement Bandwidth or Channel Separation

RBW  $\geq$  30KHz

VBW  $\geq$  3\*RBW

Sweep = auto

Detector function = peak

Trace = max hold


#### 7.4.6 Test Results

EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu


Modulation Mode	Channel Number	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)		Verdict
GFSK	0	2402	1	>748.667	2/3 of 20dB BW	PASS
	39	2441	1	>736.000	2/3 of 20dB BW	PASS
	78	2480	1	>746.000	2/3 of 20dB BW	PASS
$\pi/4$ -DQPSK	0	2402	1	>886.667	2/3 of 20dB BW	PASS
	39	2441	1	>889.333	2/3 of 20dB BW	PASS
	78	2480	1	>891.333	2/3 of 20dB BW	PASS
8DPSK	0	2402	1	>895.333	2/3 of 20dB BW	PASS
	39	2441	1	>894.667	2/3 of 20dB BW	PASS
	78	2480	1	>890.000	2/3 of 20dB BW	PASS

### Test Plot


(1Mbps) Channel Separation plot on channel 00-01




(2Mbps) Channel Separation plot on channel 00-01




(1Mbps) Channel Separation plot on channel 39-40




(2Mbps) Channel Separation plot on channel 39-40



(1Mbps) Channel Separation plot on channel 77-78




(2Mbps) Channel Separation plot on channel 77-78




### Test Plot


(3Mbps) Channel Separation plot on channel 00-01



(3Mbps) Channel Separation plot on channel 39-40



(3Mbps) Channel Separation plot on channel 77-78



## **7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)**

### **7.5.1 Applicable Standard**

According to FCC Part 15.247(a)(1)(iii) and ANSI C63.10-2013

### **7.5.2 Conformance Limit**

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

### **7.5.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.5.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.5.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.4

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW  $\geq$  1MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Measure the maximum time duration of one single pulse.

Set the EUT for DH5, DH3 and DH1 packet transmitting.

Measure the maximum time duration of one single pulse.

### 7.5.6 Test Results

EUT:	MT7697module	Model No.:	wtrnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Modulation Mode	Channel Number	Packet type	Mode	Hops Over Occupanc	Pulse width	dwell time (ms)	Limit	Verdict
				(ms)	(ms)		(ms)	
GFSK	39	DH1	Normal	320	0.416	133.120	<400	PASS
	39		AFH	160	0.416	66.560	<400	PASS
	39	DH3	Normal	160	1.675	268.000	<400	PASS
	39		AFH	80	1.675	134.000	<400	PASS
	39	DH5	Normal	106.67	2.96	315.743	<400	PASS
	39		AFH	53.33	2.96	157.857	<400	PASS
$\pi/4$ -DQPSK	39	2DH1	Normal	320	0.416	133.120	<400	PASS
	39		AFH	160	0.416	66.560	<400	PASS
	39	2DH3	Normal	160	1.675	268.000	<400	PASS
	39		AFH	80	1.675	134.000	<400	PASS
	39	2DH5	Normal	106.67	2.907	310.090	<400	PASS
	39		AFH	53.33	2.907	155.030	<400	PASS
8DPSK	39	3DH1	Normal	320	0.416	133.120	<400	PASS
	39		AFH	160	0.416	66.560	<400	PASS
	39	3DH3	Normal	160	1.667	266.720	<400	PASS
	39		AFH	80	1.667	133.360	<400	PASS
	39	3DH5	Normal	106.67	2.933	312.863	<400	PASS
	39		AFH	53.33	2.933	156.417	<400	PASS

Note:

A Period Time = (channel number)\*0.4

DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)

DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)

DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)


For Example:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time




### Test Plot


Package Transfer Time Plot CH39-DH1




Package Transfer Time Plot CH39-2DH1




Package Transfer Time Plot CH39-DH3




Package Transfer Time Plot CH39-2DH3



Package Transfer Time Plot CH39-DH5




Package Transfer Time Plot CH39-2DH5




## Test Plot


Package Transfer Time Plot CH39-3DH1



Package Transfer Time Plot CH39-3DH3



Package Transfer Time Plot CH39-3DH5



## **7.6 20DB BANDWIDTH TEST**

### **7.6.1 Applicable Standard**

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

### **7.6.2 Conformance Limit**

No limit requirement.

### **7.6.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.6.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.6.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

## 7.6.6 Test Results


EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Test Channel	Frequency	Measured Bandwidth(KHz)	Limit	Verdict
	(MHz)		(kHz)	
1Mbps				
0	2402	1123	N/A	PASS
39	2441	1104	N/A	PASS
78	2480	1119	N/A	PASS
2Mbps				
0	2402	1330	N/A	PASS
39	2441	1334	N/A	PASS
78	2480	1337	N/A	PASS
3Mbps				
0	2402	1343	N/A	PASS
39	2441	1342	N/A	PASS
78	2480	1335	N/A	PASS


Note: N/A (Not Applicable)

### Test Plot


20dB Bandwidth plot on channel 00 (1Mbps)




20dB Bandwidth plot on channel 00 (2Mbps)




20dB Bandwidth plot on channel 39 (1Mbps)




20dB Bandwidth plot on channel 39 (2Mbps)



20dB Bandwidth plot on channel 78 (1Mbps)




20dB Bandwidth plot on channel 78 (2Mbps)




## Test Plot


### 20dB Bandwidth plot on channel 00 (3Mbps)



### 20dB Bandwidth plot on channel 39 (3Mbps)



### 20dB Bandwidth plot on channel 78 (3Mbps)



## **7.7 PEAK OUTPUT POWER**

### **7.7.1 Applicable Standard**

According to FCC Part 15.247(b)(1) and ANSI C63.10-2013

### **7.7.2 Conformance Limit**

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

### **7.7.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.7.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.7.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.5.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  the 20 dB bandwidth of the emission being measured

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 7.7.6 Test Results


EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Test Channel	Frequency	Power Setting	Peak Output Power	LIMIT	Verdict
	(MHz)		(dBm)	(dBm)	
1Mbps					
0	2402	Default	3.15	20.97	PASS
39	2441	Default	4.63	20.97	PASS
78	2480	Default	4.82	20.97	PASS
2Mbps					
0	2402	Default	2.66	20.97	PASS
39	2441	Default	4.13	20.97	PASS
78	2480	Default	4.3	20.97	PASS
3Mbps					
0	2402	Default	3	20.97	PASS
39	2441	Default	4.5	20.97	PASS
78	2480	Default	4.68	20.97	PASS




### Test Plot


Peak output Power plot on channel 00 (1Mbps)




Peak output Power plot on channel 00 (2Mbps)




Peak output Power plot on channel 39 (1Mbps)




Peak output Power plot on channel 39 (2Mbps)



Peak output Power plot on channel 78 (1Mbps)




Peak output Power plot on channel 78 (2Mbps)




## Test Plot


Peak output Power plot on channel 00 (3Mbps)



Peak output Power plot on channel 39 (3Mbps)



Peak output Power plot on channel 78 (3Mbps)



## **7.8 CONDUCTED BAND EDGE MEASUREMENT**

### **7.8.1 Applicable Standard**

According to FCC Part 15.247(d) and ANSI C63.10-2013

### **7.8.2 Conformance Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **7.8.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.8.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.8.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.6.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.


## 7.8.6 Test Results

EUT:	MT7697module	Model No.:	wrtnode^7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2 /Mode4/ Mode 5	Test By:	Eileen Liu


Note: Hopping enabled and disabled have evaluated,and the worstest data was reported

### Test Plot


BDR mode (GFSK): Band Edge-Low Channel




BDR mode (GFSK): Band Edge-High Channel



BDR mode (GFSK): Band Edge-Low Channel  
(Hopping Mode)




BDR mode (GFSK): Band Edge-High Channel  
(Hopping Mode)




### Test Plot

BDR mode ( $\pi/4$ -DQPSK): Band Edge-Low

Channel




BDR mode ( $\pi/4$ -DQPSK): Band Edge-High Channel




BDR mode ( $\pi/4$ -DQPSK): Band Edge-Low

Channel (Hopping Mode)




BDR mode ( $\pi/4$ -DQPSK): Band Edge-High Channel

(Hopping Mode)






### Test Plot

BDR mode (8DPSK): Band Edge-Low Channel



BDR mode (8DPSK): Band Edge-High Channel


BDR mode (8DPSK): Band Edge-Low Channel  
(Hopping Mode)

BDR mode (8DPSK): Band Edge-High Channel  
(Hopping Mode)


## **7.9 SPURIOUS RF CONDUCTED EMISSION**

### **7.9.1 Applicable Standard**

According to RSS-247 5.5 & RSS-Gen 6.13.

### **7.9.2 Conformance Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required..

### **7.9.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.9.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.9.5 Test Procedure**

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in RSS-247 5.5 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength , and mwasure frequency range from 9KHz to 26.5GHz.


### **7.9.6 Test Results**

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.


The worst mode is GFSK mode, and the report only show the worst mode data.

### Test Plot(GFSK)


GFSK on channel 00




GFSK on channel 00



GFSK on channel 00




GFSK on channel 00






### Test Plot


GFSK on channel 39




GFSK on channel 39



GFSK on channel 39




GFSK on channel 39




### Test Plot


GFSK on channel 78




GFSK on channel 78



GFSK on channel 78



GFSK on channel 78



## **7.10 ANTENNA APPLICATION**

### **7.10.1 Antenna Requirement**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **7.10.2 Result**

The EUT antenna is permanent attached Ceramic antenna(Gain:0.5dBi). It comply with the standard requirement.

END OF REPORT