TEST REPORT

Reference No. : WTS18S04108508-1W

FCC ID..... : 2ALR9-KDL-BT1809

Applicant: SHENZHEN G-KINDLY ELECTRONIC CO., LTD

Address 4F, No.8 Fifth Road, Loucun First Industry Zone, GongMing Town,

GuangMing New District, Shenzhen, China

Manufacturer: SHENZHEN G-KINDLY ELECTRONIC CO., LTD

Address 4F, No.8 Fifth Road, Loucun First Industry Zone, GongMing Town,

GuangMing New District, Shenzhen, China

Product : WIRELESS SPEAKER

Model(s)...... : BB1656, KDL-BT1809, BB1657, BT1809, BIG-9928

Brand Name. billboard

Standards : FCC CFR47 Part 15 Section 15.247:2017

Date of Receipt sample : 2018-04-17

Date of Test : 2018-04-17 to 2018-04-25

Date of Issue : 2018-04-25

Test Result : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Test site/Test location:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,

Guangdong, China Tel:+86-755-83551033 Fax:+86-755-83552400

Tested by:

Approved by:

TREPHIIO Zhong / Manager

Robin Zhou / Test Engineer

20bin.2hou

Reference No.: WTS18S04108508-1W Page 2 of 58

1 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

Reference No.: WTS18S04108508-1W Page 3 of 58

1.1 Test Facility

A. Accreditations for Conformity Assessment (International)

Country/Region	Accreditation Body	Scope	Note
USA		FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe	A2LA	EMCD\RED	-
Taiwan	(Certificate No.: 4243.01)	NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		WPC	_
Thailand	International Services	NTC	-
Singapore		IDA	-

Note:

- 1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.
- 2. IC Canada Registration No.: 7760A

B.TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of	Notify body number
TUV Rheinland	
Intertek	
TUV SUD	Optional.
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

2 Contents

		Page
	COVER PAGE	1
1	LABORATORIES INTRODUCTION	
	1.1 TEST FACILITY	3
2	CONTENTS	4
3	REVISION HISTORY	
4	GENERAL INFORMATION	
	4.1 GENERAL DESCRIPTION OF E.U.T	
	4.2 DETAILS OF E.U.T	8
	4.3 CHANNEL LIST	
_	4.4 TEST MODE	
5	EQUIPMENT USED DURING TEST	
	5.1 EQUIPMENTS LIST	
	5.3 SUBCONTRACTED	
6	TEST SUMMARY	11
7	CONDUCTED EMISSION	
	7.1 E.U.T. OPERATION	12
	7.2 EUT SETUP	
	7.3 MEASUREMENT DESCRIPTION	
8	RADIATED EMISSIONS	
Ü	8.1 EUT OPERATION	
	8.2 TEST SETUP	
	8.3 SPECTRUM ANALYZER SETUP	
	8.4 TEST PROCEDURE	
	8.6 SUMMARY OF TEST RESULTS	
9	BAND EDGE MEASUREMENT	
	9.1 Test Procedure	
	9.2 TEST SETUP	
10	9.3 TEST RESULT: BANDWIDTH MEASUREMENT.	
10	10.1 Test Procedure:	
	10.2 TEST ROCEBORE	
	10.3 TEST RESULT:	
11	MAXIMUM PEAK OUTPUT POWER	
	11.1 Test Procedure:	
	11.2 TEST SETUP	
12	HOPPING CHANNEL SEPARATION	
12		
	12.1 TEST PROCEDURE: 12.2 TEST SETUP	
	12.3 TEST RESULT:	

Reference No.: WTS18S04108508-1W Page 5 of 58

13	NUMB	ER OF HOPPING FREQUENCY	47
	13.1	TEST PROCEDURE:	
	13.2	TEST SETUP	47
	13.3	TEST RESULT:	
14	DWEL	L TIME	50
	14.1	Test Procedure:	50
	14.2	TEST SETUP	
	14.3	TEST RESULT:	
15	ANTE	NNA REQUIREMENT	57
16	FCC IE	D: 2ALR9-KDL-BT1809 RF EXPOSURE REPORT	58
17	РНОТ	OGRAPHS – MODEL BB1656 TEST SETUP PHOTOS	58
18	РНОТ	OGRAPHS - CONSTRUCTIONAL DETAILS	
	18.1	MODEL BB1656- EXTERNAL PHOTOS	58
	18.2	MODEL BB1656 - INTERNAL PHOTOS	58

Reference No.: WTS18S04108508-1W Page 6 of 58

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS18S04108508-1W	2018-04-17	2018-04-17 to 2018-04-25	2018-04-25	original	-	Valid

Reference No.: WTS18S04108508-1W Page 7 of 58

4 General Information

4.1 General Description of E.U.T

Product : WIRELESS SPEAKER

Model(s) : BB1656, KDL-BT1809, BB1657, BT1809, BIG-9928

Model difference : All the models are same in all respects, Only the model names and

appearance color are different. The model BB1656 is the tested

sample.

Operation Frequency: 2402-2480MHz, 79(EDR) Channels in total

Antenna installation : PCB Printed Antenna

Antenna Gain : 0dBi

Type of Modulation : GFSK, π/4DQPSK, 8DPSK

Frequency hopping systems (FHS):

This transmitter device is frequency hopping device, and complies with FCC Part15.247 Requirements.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. The average time of occupancy on any channel is less than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels (79 channels) employed.

All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an Bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for FCC Part15.247.

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 19, 56, 40, 18, 50, 09, 02, 23, 32, 41, 33, 31, 65, 73, 53, 69, 06, 22, 67, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 17, 60, 63, 54, 03, 00, 59, 64, 75, 35, 66, 43, 15, 45, 39, 77, 55, 71, 47, 61, 27, 30, 48, 72, 01, 14, 07, 25, 34, 12, 28, 44, 51, 16, 49, 74, 11, 05, 13, 37, 62 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

Reference No.: WTS18S04108508-1W Page 8 of 58

4.2 Details of E.U.T

Ratings INPUT: DC 5V, 2.0A by AC/DC ADAPTER

(AC/DC ADAPTER Input: 100-240V~50/60Hz, 0.5A,

Model: TAP12-050S200U1)

4.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test mode	Low channel	Middle channel	High channel
Transmitting	2402MHz	2441MHz	2480MHz

Note: The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The product was full-charged when was testing.

Reference No.: WTS18S04108508-1W Page 9 of 58

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions							
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date	
1.	EMI Test Receiver	R&S	ESCI	100947	2017-09-12	2018-09-11	
2.	LISN	R&S	ENV216	101215	2017-09-12	2018-09-11	
3.	Cable	Тор	TYPE16(3.5M)	-	2017-09-12	2018-09-11	
3m Ser	mi-anechoic Chamber	for Radiation Emis	sions				
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date	
1	Spectrum Analyzer	R&S	FSP30	100091	2017-04-29	2018-04-28	
2	Broad-band Horn Antenna(1-18GHz)	SCHWARZBECK	BBHA 9120 D	667	2017-04-29	2018-04-28	
3	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2017-04-29	2018-04-28	
4	Coaxial Cable (above 1GHz)	Тор	1GHz-18GHz	EW02014-7	2017-04-29	2018-04-28	
5	Spectrum Analyzer	R&S	FSP40	100501	2017-10-20	2018-10-19	
6	Broad-band Horn Antenna(18-40GHz)	SCHWARZBECK	BBHA 9170	BBHA917065 1	2017-10-25	2018-10-24	
7	Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	100472	2017-10-25	2018-10-24	
8	Cable	Тор	18-40GHz	-	2017-10-25	2018-10-24	
3m Ser	mi-anechoic Chamber	for Radiation Emis	sions				
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date	
1	Test Receiver	R&S	ESCI	101296	2017-04-29	2018-04-28	
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2017-04-29	2018-04-28	
3	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2017-04-29	2018-04-28	
4	Amplifier	ANRITSU	MH648A	M43381	2017-04-29	2018-04-28	

Reference No.: WTS18S04108508-1W Page 10 of 58

5	Cable	HUBER+SUHNER	CBL2	525178	2017-04-29	2018-04-28
6	Coaxial Cable (below 1GHz)	Тор	TYPE16 (13M)	-	2017-09-12	2018-09-11
RF Co	nducted Testing					
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	R&S	FSL6	100959	2017-09-12	2018-09-11
2	Coaxial Cable	Тор	10Hz-30GHz	-	2017-09-12	2018-09-11
3	Antenna Connector*	Realacc	45RSm	-	2017-09-12	2018-09-11
4	DC Block	Gwave	GDCB-3G-N- SMA	140307001	2017-09-12	2018-09-11
"*": The	e temporary antenna co	nnector is soldered of	n the PCB board	d in order to per	form conducted	tests and this

[&]quot;*": The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5.2 Measurement Uncertainty

Parameter	Uncertainty		
Radio Frequency	± 1 x 10 ⁻⁶		
RF Power	± 1.0 dB		
RF Power Density	± 2.2 dB		
	± 5.03 dB (30M~1000MHz)		
Radiated Spurious Emissions test	± 5.47 dB (1000M~25000MHz)		
Conducted Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)		
Confidence interval: 95%. Confidence factor:k=2			

5.3 Subcontracted

Whether parts	of tests for the product have been subcontracted to other labs:
☐ Yes	⊠ No

If Yes, list the related test items and lab information:

Test Lab: N/A Lab address: N/A Test items: N/A Reference No.: WTS18S04108508-1W Page 11 of 58

6 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	Pass
	15.205(a)	
Radiated Spurious Emissions	15.209	Pass
	15.247(d)	
Dand adea	15.247(d)	Dane
Band edge	15.205(a)	Pass
Bandwidth	15.247(a)(1)	Pass
Maximum Peak Output Power	15.247(b)(1)	Pass
Frequency Separation	15.247(a)(1)	Pass
Number of Hopping Frequency	15.247(a)(1)(iii)	Pass
Dwell time	15.247(a)(1)(iii)	Pass
RF exposure	1.1307(b)(1)	Pass
Antenna Requirement	15.203	Pass
RF Exposure	1.1307(b)(1)	Pass
Note: Pass=Compliance; NC=Not Co	ompliance; NT=Not Tested; N/A=No	ot Applicable.

Reference No.: WTS18S04108508-1W Page 12 of 58

7 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Class/Severity: Class B

Limit:

Frequency (MHz)	Conducted Limit (dBµV)					
Frequency (MHZ)	Qsi-peak	Average				
0.15 to 0.5	66 to 56*	56 to 46*				
0.5 to 5.0	56	46				
5.0 to 30	60	50				
*Decreases with the logarithm of the frequency.						

7.1 E.U.T. Operation

Operating Environment:

Temperature: 22.8 °C
Humidity: 52.6 % RH
Atmospheric Pressure: 101.2kPa


Test Voltage: AC 120V, 60Hz

EUT Operation:

The test was performed in Transmitting mode, the worst test data (GFSK modulation Low channel) were shown in the report.

7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



Reference No.: WTS18S04108508-1W Page 13 of 58


7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


7.4 Conducted Emission Test Result

Remark: only the worst data (GFSK modulation Low channel mode) were reported

Live line:



Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	36.12	10.06	46.18	65.99	-19.81	QP	
2	0.1500	20.50	10.06	30.56	55.99	-25.43	AVG	
3	0.1860	29.88	9.89	39.77	64.21	-24.44	QP	
4	0.1860	14.48	9.89	24.37	54.21	-29.84	AVG	
5	0.3020	25.00	9.98	34.98	60.19	-25.21	QP	
6	0.3020	14.08	9.98	24.06	50.19	-26.13	AVG	
7	0.7060	26.95	10.11	37.06	56.00	-18.94	QP	
8	0.7060	19.16	10.11	29.27	46.00	-16.73	AVG	
9	1.6420	21.86	10.16	32.02	56.00	-23.98	QP	
10	1.6420	14.37	10.16	24.53	46.00	-21.47	AVG	
11	13.3900	30.12	10.38	40.50	60.00	-19.50	QP	
12	13.3900	22.94	10.38	33.32	50.00	-16.68	AVG	

Reference No.: WTS18S04108508-1W Page 15 of 58

8 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS
Measurement Distance: 3m

Limit:

F	Field Strei	ngth	Field Strength Limit at 3m Measurement Dist			
Frequency (MHz)	uV/m	Distance (m)	uV/m	dBuV/m		
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log ^{(2400/F(kHz))} + 80		
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log ^{(24000/F(kHz))} + 40		
1.705 ~ 30	30	30	100 * 30	20log ⁽³⁰⁾ + 40		
30 ~ 88	100	3	100	20log ⁽¹⁰⁰⁾		
88 ~ 216	150	3	150	20log ⁽¹⁵⁰⁾		
216 ~ 960	200	3	200	20log ⁽²⁰⁰⁾		
Above 960	500	3	500	20log ⁽⁵⁰⁰⁾		

8.1 EUT Operation

Operating Environment:

Temperature: 23.5 °C
Humidity: 52.1 % RH
Atmospheric Pressure: 101.2kPa

Test Voltage: DC 3.7V

EUT Operation:


The test was performed in Transmitting mode, the worst test data (GFSK modulation) were shown in the report.

Reference No.: WTS18S04108508-1W Page 16 of 58


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10: 2013.

The test setup for emission measurement below 30MHz.




The test setup for emission measurement from 30 MHz to 1 GHz.



Reference No.: WTS18S04108508-1W Page 17 of 58

The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz		
	Sweep Speed	. Auto
	IF Bandwidth	.10kHz
	Video Bandwidth	.10kHz
	Resolution Bandwidth	.10kHz
30MHz ~ 1GH:	z	
	Sweep Speed	. Auto
	Detector	.PK
	Resolution Bandwidth	.100kHz
	Video Bandwidth	.300kHz
Above 1GHz		
	Sweep Speed	. Auto
	Detector	.PK
	Resolution Bandwidth	.1MHz
	Video Bandwidth	.3MHz
	Detector	.Ave.
	Resolution Bandwidth	.1MHz
	1 (CCC) Guiori Bariattiau III.	
	Video Bandwidth	

Reference No.: WTS18S04108508-1W Page 18 of 58

8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.

- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7. The radiation measurements are tested under 3-axes(X, Y, Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
- 8. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain
The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. - Limit

Reference No.: WTS18S04108508-1W Page 19 of 58

8.6 Summary of Test Results

Test Frequency: 9 kHz ~ 30 MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

Only the worst case GFSK mode were record in the report.

Pe	Desciver.		Turn	RX Antenna				FCC Part 15.247/209/205	
Frequency	Receiver Reading	Detector	table Angle	Height	Polar	Corrected Factor	Corrected Amplitude	Limit	Margin
(MHz)	(dBµV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
			GFSK Lo	ow Chanr	nel 2402	MHz			
80.41	55.92	QP	323	1.6	Н	-19.79	36.13	40.00	-3.87
80.41	54.67	QP	26	1.9	V	-19.79	34.88	40.00	-5.12
4804.00	56.17	PK	189	1.5	V	-1.06	55.11	74.00	-18.89
4804.00	43.29	Ave	189	1.5	V	-1.06	42.23	54.00	-11.77
7206.00	54.06	PK	278	1.5	Н	1.33	55.39	74.00	-18.61
7206.00	44.18	Ave	278	1.5	Н	1.33	45.51	54.00	-8.49
2322.16	45.82	PK	69	1.0	V	-13.19	32.63	74.00	-41.37
2322.16	37.33	Ave	69	1.0	V	-13.19	24.14	54.00	-29.86
2352.73	44.64	PK	338	1.8	Н	-13.14	31.50	74.00	-42.50
2352.73	37.26	Ave	338	1.8	Н	-13.14	24.12	54.00	-29.88
2484.73	44.12	PK	343	1.5	V	-13.08	31.04	74.00	-42.96
2484.73	36.38	Ave	343	1.5	V	-13.08	23.30	54.00	-30.70

Reference No.: WTS18S04108508-1W Page 20 of 58

Receiver	Receiver	eceiver	Turn table	RX Antenna		Corrected		FCC Part 15.247/209/205	
Frequency	Reading	Detector	Angle	Height	Polar	Factor	Corrected Amplitude	Limit	Margin
(MHz)	(dBµV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
			GFSK Mid	ddle Char	nnel 244	1MHz			
80.41	56.23	QP	205	1.3	Н	-19.79	36.44	40.00	-3.56
80.41	53.33	QP	232	1.5	V	-19.79	33.54	40.00	-6.46
4882.00	57.12	PK	3	1.6	V	-0.62	56.50	74.00	-17.50
4882.00	42.94	Ave	3	1.6	V	-0.62	42.32	54.00	-11.68
7323.00	53.34	PK	3	1.4	Н	2.21	55.55	74.00	-18.45
7323.00	42.68	Ave	3	1.4	Н	2.21	44.89	54.00	-9.11
2314.03	46.62	PK	188	1.8	V	-13.19	33.43	74.00	-40.57
2314.03	39.26	Ave	188	1.8	V	-13.19	26.07	54.00	-27.93
2383.86	42.69	PK	75	1.4	Н	-13.14	29.55	74.00	-44.45
2383.86	37.80	Ave	75	1.4	Н	-13.14	24.66	54.00	-29.34
2484.42	44.16	PK	213	1.3	V	-13.08	31.08	74.00	-42.92
2484.42	37.32	Ave	213	1.3	V	-13.08	24.24	54.00	-29.76

Reference No.: WTS18S04108508-1W Page 21 of 58

Eroguanav Re	Receiver	Detector	Turn	RX Antenna		Corrected		FCC Part 15.247/209/205	
Frequency	Reading	Detector	table Angle	Height	Polar	Factor	Corrected Amplitude	Limit	Margin
(MHz)	(dBµV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
	GFSK High Channel 2480MHz								
80.41	55.31	QP	61	1.4	Н	-19.79	35.52	40.00	-4.48
80.41	53.77	QP	53	1.5	V	-19.79	33.98	40.00	-6.02
4960.00	56.79	PK	309	1.8	V	-0.24	56.55	74.00	-17.45
4960.00	41.92	Ave	309	1.8	V	-0.24	41.68	54.00	-12.32
7440.00	54.28	PK	307	1.2	Н	2.84	57.12	74.00	-16.88
7440.00	42.57	Ave	307	1.2	Н	2.84	45.41	54.00	-8.59
2325.49	46.88	PK	122	1.5	V	-13.19	33.69	74.00	-40.31
2325.49	39.16	Ave	122	1.5	V	-13.19	25.97	54.00	-28.03
2364.33	43.43	PK	337	1.2	Н	-13.14	30.29	74.00	-43.71
2364.33	38.07	Ave	337	1.2	Н	-13.14	24.93	54.00	-29.07
2493.28	42.42	PK	344	1.8	V	-13.08	29.34	74.00	-44.66
2493.28	37.80	Ave	344	1.8	V	-13.08	24.72	54.00	-29.28

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

Reference No.: WTS18S04108508-1W Page 22 of 58

9 Band Edge Measurement

Test Requirement: Section 15.247(d) In addition, radiated emissions which fall in the

restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see

Section 15.205(c)).

Test Method: ANSI C63.10

Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the


frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting

9.1 Test Procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
 Detector function = peak, Trace = max hold


9.2 Test Setup





Reference No.: WTS18S04108508-1W Page 23 of 58


9.3 Test Result:


Test plots
































Reference No.: WTS18S04108508-1W Page 29 of 58

10 Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247


Test Method: C63.10: 2013

Test Mode: Test in fixing operating frequency at low, Middle, high channel.

10.1 Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz

10.2 Test Setup




10.3 Test Result:


Modulation	Test Channel	20 dB Bandwidth	99% Bandwidth
GFSK	Low	1.042MHz	0.982MHz
GFSK	Middle	1.042MHz	0.982MHz
GFSK	High	1.042MHz	0.976MHz
π /4 DQPSK	Low	1.126MHz	1.180MHz
π 4 DQPSK	Middle	1.126MHz	1.162MHz
π /4 DQPSK	High	1.126MHz	1.150MHz
8DPSK	Low	1.048MHz	1.150MHz
8DPSK	Middle	1.048MHz	1.138MHz
8DPSK	High	1.048MHz	1.126MHz


Reference No.: WTS18S04108508-1W Page 30 of 58


Test result plot as follows:


Modulation: GFSK Low Channel



















Modulation: 8DPSK







Reference No.: WTS18S04108508-1W Page 35 of 58

11 Maximum Peak Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: C63.10:2013

Test Limit: Regulation 15.247 (b)(1), For frequency hopping systems

operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band:

0.125 watts.

Refer to the result "Number of Hopping Frequency" of this


document. The 1watts (30 dBm) limit applies.

Test mode: Test in fixing frequency transmitting mode.

11.1 Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 3 MHz. VBW =3 MHz. Sweep = auto; Detector Function = Peak.
- 3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

11.2 Test Setup




11.3 Test Result:

Tool	Dete	Pea			
Test Mode	Data Rate	Low Channel	Middle Channel	High Channel	Limit (dBm)
GFSK	1Mbps	5.63	4.33	3.28	20.97
π /4 DQPSK	2Mbps	6.76	5.68	4.46	20.97
8DPSK	3Mbps	6.72	5.78	4.65	20.97


Reference No.: WTS18S04108508-1W Page 36 of 58


Test result plot as follows:

Modulation: GFSK
Low Channel




Middle Channel







Modulation: π /4 DQPSK Low Channel Low Channel




Reference No.: WTS18S04108508-1W Page 38 of 58

Middle Channel







Modulation: 8DPSK Low Channel
Low Channel



Middle Channel





Reference No.: WTS18S04108508-1W Page 41 of 58

12 Hopping Channel Separation

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: C63.10:2013

Test Limit: Regulation 15.247(a)(1) Frequency hopping systems shall have

hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the

systems operate with an output power no greater than 1W.


Test Mode: Test in hopping transmitting operating mode.

12.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

- 2. Set the spectrum analyzer: RBW = 30KHz. VBW = 100KHz, Span = 3MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

12.2 Test Setup




Reference No.: WTS18S04108508-1W Page 42 of 58


12.3 Test Result:


Test result plot as follows:


Modulation	Test Channel	Separation (MHz)	Result
GFSK	Low	1 MHz	PASS
GFSK	Middle	1 MHz	PASS
GFSK	High	1 MHz	PASS
π/4 DQPSK	Low	1 MHz	PASS
π/4 DQPSK	Middle	1 MHz	PASS
π/4 DQPSK	High	1 MHz	PASS
8DPSK	Low	1 MHz	PASS
8DPSK	Middle	1 MHz	PASS
8DPSK	High	1 MHz	PASS


Test plots **GFSK Low Channel (** Offs 0.50 dB * RBW 30 kHz * Att 25 dB * VBW 100 kHz D1[1] -0.11 dB Batt Ref 15.50 dBm SWT 5ms 1.000000000 MHz 3.61 dBm 2.401967100 GHz M1[1] 10 dBm M1 1Pk Max 0 dBm--10 dBm -20 dBm -30 dBm الريالا -50 dBm -60 dBm -70 dBm -80 dBm CF 2.4025 GHz Span 3.0 MHz




















Reference No.: WTS18S04108508-1W Page 47 of 58

13 Number of Hopping Frequency

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: C63.10:2013

Test Limit: Regulation 15.247 (a)(1)(iii) Frequency hopping systems in the

2400-2483.5 MHz band shall use at least 15 channels.


Test Mode: Test in hopping transmitting operating mode.

13.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

- 2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;


13.2 Test Setup




Reference No.: WTS18S04108508-1W Page 48 of 58


13.3 Test Result:

Total Channels are 79 Channels.





Reference No.: WTS18S04108508-1W Page 49 of 58



Reference No.: WTS18S04108508-1W Page 50 of 58

14 Dwell Time

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: C63.10:2013

Test Limit: Regulation 15.247(a)(1)(iii) Frequency hopping systems in

the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are


used.

Test Mode: Test in hopping transmitting operating mode.

14.1 Test Procedure:

- 1.Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2.Set spectrum analyzer span = 0. centred on a hopping channel;
- 3.Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel.
- 4.Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

14.2 Test Setup



14.3 Test Result:

Dwell time = Pulse wide x (Hopping rate / Number of channels) x Period The test period: T = 0.4(s) * 79 = 31.6(s)

DH5 Packet permit maximum 1600 / 79 / 6 hops per second in each channel (5 time slots RX, 1 time

slot TX). DH3 Packet permit maximum 1600 / 79 / 4 hops per second in each channel (3 time slots RX, 1 time

DH3 Packet permit maximum 1600 / 79 / 4 hops per second in each channel (3 time slots RX, 1 time slot TX).

DH1 Packet permit maximum 1600 / 79 / 2 hops per second in each channel (1 time slot RX, 1 time slot TX).

Reference No.: WTS18S04108508-1W Page 51 of 58

So, the Dwell Time can be calculated as follows:

Data Packet	Dwell Time(s)		
DH5	1600/79/6*31.6*(MkrDelta)/1000		
DH3	1600/79/4*31.6*(MkrDelta)/1000		
DH1	1600/79/2*31.6*(MkrDelta)/1000		
Remark	Mkr Delta is single pulse time.		


Modulation	Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
GFSK	DH5	Low	3.000	0.320	0.4
		middle	3.000	0.320	0.4
		High	3.000	0.320	0.4
π /4 DQPSK	DH5	Low	3.000	0.320	0.4
		middle	3.000	0.320	0.4
		High	3.000	0.320	0.4
8DPSK	DH5	Low	3.000	0.320	0.4
		middle	3.000	0.320	0.4
		High	3.000	0.320	0.4

Reference No.: WTS18S04108508-1W Page 52 of 58


Modulation: GFSK

Data Packet:

DH5.Low channel




Data Packet: DH5.Middle channel



Reference No.: WTS18S04108508-1W Page 53 of 58


Data Packet: DH5, High channel




Modulation: π /4 DQPSK

Data Packet:


2DH5 Low channel




Data Packet: 2DH5.Middle channel




Data Packet: 2DH5, High channel



Modulation: 8DPSK
Data Packet:
3DH5.Low channel




Data Packet: 3DH5.Middle channel



Reference No.: WTS18S04108508-1W Page 56 of 58

Data Packet: 3DH5, High channel



Reference No.: WTS18S04108508-1W Page 57 of 58


15 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT has a PCB Printed Antenna for Bluetooth Antenna, meets the requirements of FCC 15.203.



Reference No.: WTS18S04108508-1W Page 58 of 58

16 FCC ID: 2ALR9-KDL-BT1809 RF Exposure Report

Note: Please refer to RF Exposure Report: WTS18S04108508-2W.

17 Photographs – Model BB1656 Test Setup Photos

Note: Please refer to Photos: WTS18S04108508-3W.

18 Photographs - Constructional Details

18.1 Model BB1656- External Photos

Note: Please refer to Photos: WTS18S04108508-3W.

18.2 Model BB1656 - Internal Photos

Note: Please refer to Photos: WTS18S04108508-3W.

====End of Report=====