

8. RADIO FREQUENCY EXPOSURE

8.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (S) (mW/cm ²)
0.3–1.34	*(100)
1.34–30	*(180/f ²)
30–300	0.2
300–1500	f/1500
1500–100,000	1.0

F = frequency in MHz

* = Plane-wave equivalent power density

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

1. Manufacturer declared that the maximum antenna gain is 3.0dBi(Max.) for WIFI.
2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
3. Only record worst case data.

8.2 Test Results

Test	Channel	ANT Power (dBm)	ANT Max. Tune Up Power (dBm)	ANT Max. Tune Up Power (mW)	ANT MPE (mW/cm ²)	Limit (mW/cm ²)
IEEE 802.11b	1	17.69	17.0±1.0	63.0957	0.0251	1.0
	6	17.45	17.0±1.0	63.0957	0.0251	1.0
	11	17.53	17.0±1.0	63.0957	0.0251	1.0
IEEE 802.11g	1	15.17	15.0±1.0	39.8107	0.0158	1.0
	6	15.22	15.0±1.0	39.8107	0.0158	1.0
	11	15.33	15.0±1.0	39.8107	0.0158	1.0
IEEE 802.11n20	1	15.47	15.0±1.0	39.8107	0.0158	1.0
	6	15.58	15.0±1.0	39.8107	0.0158	1.0
	11	15.24	15.0±1.0	39.8107	0.0158	1.0

Note: The estimation distance is 20cm

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.