



FCC PART 15.247 TEST REPORT

For

Onclick Global Corporation

No.2 LN-334 FUXING RD. KEELUNG CITY, TAIWAN

FCC ID: 2ALS9CRMP3003

Report Type: Original Report	Product Name: Mobile Phone
Test Engineer: Kevin Hu	<i>Kevin Hu</i>
Report Number: RDG170706001B	
Report Date: 2017-08-02	
Reviewed By: Henry Ding EMC Leader	<i>Henry Ding</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65525123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
EXTERNAL CABLE	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	8
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	10
EUT SETUP	10
EMI TEST RECEIVER SETUP	10
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST EQUIPMENT LIST AND DETAILS	11
TEST DATA	11
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	15
TEST EQUIPMENT LIST AND DETAILS	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST DATA	16
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	20
APPLICABLE STANDARD	20
TEST EQUIPMENT LIST AND DETAILS	20
TEST PROCEDURE	20
TEST DATA	20
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS	26
TEST DATA	26
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	32

APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS	32
TEST DATA.....	32
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST EQUIPMENT LIST AND DETAILS	36
TEST DATA.....	36
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST EQUIPMENT LIST AND DETAILS	52
TEST DATA.....	52
FCC §15.247(d) - BAND EDGES TESTING	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST EQUIPMENT LIST AND DETAILS	58
TEST DATA.....	59

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Onclick Global Corporation**'s product, model number: **CR-MP3003 (FCC ID: 2ALS9CRMP3003)** (the "EUT") in this report was a **Mobile Phone**, which was measured approximately: 10.5 cm (L) × 4.5 cm (W) × 1.3 cm (H), rated input voltage: DC3.7V from battery or DC5.0V from adapter.

Adapter information:

Model: CR-MP3003

Input: AC 100-240V 50/60Hz 500mAh

Output: DC5.0V 300mAh

**All measurement and test data in this report was gathered from final production sample, serial number: 170706001 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-07-06, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Onclick Global Corporation** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ALS9CRMP3003.

FCC Part 22H, 24E PCE submissions with FCC ID: 2ALS9CRMP3003.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All of the measurements detailed in this Test Report were performed by Bay Area Compliance Laboratories Corp. (Chengdu).

The Bay Area Compliance Laboratories Corp. Chengdu's measurement Uncertainties (calculated for a k=2 Coverage Factor corresponding to approximately 95% Coverage) were as follows:

-For all of the AC Line Conducted Emissions Tests reported herein: ± 3.17 dB.

-For of all of the Direct Antenna Conducted Emissions Tests reported herein: ± 0.56 dB.

-For of all of the direct Radiated Emissions Tests reported herein are:

30 MHz to 200 MHz: ± 4.7 dB;

200 MHz to 1 GHz: ± 6.0 dB;

1 GHz to 6 GHz: ± 5.13 dB; and,

6 GHz to 40 GHz: ± 5.47 dB.

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The engineering mode configured the maximum power as default setting.


Equipment Modifications

No modification was made to the EUT.

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Adapter Cable	No	No	0.8	Adapter	EUT
Earphone Cable	No	No	1.2	EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 5.2dBm (3.31 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 3.31/5 \cdot (\sqrt{2.480}) = 1.0 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT, and the antenna gain is -3.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	DE14781	2016-10-31	2017-10-30
Unknown	Conducted Cable	Unknown	NO.5	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data


Environmental Conditions

Temperature:	32.6°C
Relative Humidity:	37.7 %
ATM Pressure:	100.1 kPa

The testing was performed by Kevin Hu on 2017-07-27.

Test Mode: Operating


AC120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.419276	44.4	9.000	L1	19.8	13.0	57.4	Compliance
0.503608	48.4	9.000	L1	19.8	7.6	56.0	Compliance
0.670921	43.3	9.000	L1	19.8	12.7	56.0	Compliance
0.838622	44.1	9.000	L1	19.8	11.9	56.0	Compliance
1.453260	42.8	9.000	L1	19.8	13.2	56.0	Compliance
3.173039	40.3	9.000	L1	19.9	15.7	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.393383	27.9	9.000	L1	19.8	19.9	47.8	Compliance
0.499611	31.6	9.000	L1	19.8	14.4	46.0	Compliance
0.692650	25.8	9.000	L1	19.8	20.2	46.0	Compliance
0.838622	28.3	9.000	L1	19.8	17.7	46.0	Compliance
0.945093	26.4	9.000	L1	19.8	19.6	46.0	Compliance
1.441726	26.0	9.000	L1	19.8	20.0	46.0	Compliance

AC120V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.384091	36.0	9.000	N	19.6	22.1	58.1	Compliance
0.483938	42.4	9.000	N	19.6	13.9	56.3	Compliance
0.590613	35.3	9.000	N	19.5	20.7	56.0	Compliance
0.805868	37.1	9.000	N	19.5	18.9	56.0	Compliance
1.488418	36.4	9.000	N	19.6	19.6	56.0	Compliance
2.147382	33.8	9.000	N	19.6	22.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.384091	22.1	9.000	N	19.6	25.9	48.0	Compliance
0.487810	26.4	9.000	N	19.6	19.8	46.2	Compliance
0.698191	20.3	9.000	N	19.5	25.7	46.0	Compliance
0.908180	21.9	9.000	N	19.5	24.1	46.0	Compliance
1.500325	19.7	9.000	N	19.6	26.3	46.0	Compliance
2.096658	17.7	9.000	N	19.6	28.3	46.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2017-06-16	2020-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2017-05-20	2018-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	966-1	2015-04-24	2018-04-23
Unknown	RF Cable (below 1GHz)	Unknown	NO.1	2016-11-10	2017-11-09
Unknown	RF Cable (below 1GHz)	Unknown	NO.4	2016-11-10	2017-11-09
Unknown	RF Cable (above 1GHz)	Unknown	NO.2	2016-11-10	2017-11-09

*** Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions

Temperature:	32.6 °C
Relative Humidity:	37.7%
ATM Pressure:	100.1 kPa

** The testing was performed by Kevin Hu on 2017-07-27.*

Test Mode: Transmitting

30MHz-25GHz

BDR Mode (GFSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	60.21	PK	H	28.10	3.11	0.00	91.42	N/A	N/A
2402	50.23	AV	H	28.10	3.11	0.00	81.44	N/A	N/A
2402	58.49	PK	V	28.10	3.11	0.00	89.70	N/A	N/A
2402	48.18	AV	V	28.10	3.11	0.00	79.39	N/A	N/A
2390	26.06	PK	H	28.08	3.10	0.00	57.24	74.00	16.76
2390	13.29	AV	H	28.08	3.10	0.00	44.47	54.00	9.53
4804	54.44	PK	H	32.91	4.30	35.48	56.17	74.00	17.83
4804	37.15	AV	H	32.91	4.30	35.48	38.88	54.00	15.12
7206	55.92	PK	H	35.74	5.45	35.97	61.14	74.00	12.86
7206	43.84	AV	H	35.74	5.45	35.97	49.06	54.00	4.94
9608	48.65	PK	H	37.94	6.26	36.26	56.59	74.00	17.41
9608	33.57	AV	H	37.94	6.26	36.26	41.51	54.00	12.49
5395	46.45	PK	H	33.93	4.54	35.80	49.12	74.00	24.88
5395	32.37	AV	H	33.93	4.54	35.80	35.04	54.00	18.96
226.66	41.7	QP	H	11.80	1.11	27.61	27.00	46.00	19.00
859.59	42.6	QP	H	22.32	2.32	28.30	38.94	46.00	7.06
Middle Channel: 2441 MHz									
2441	60.11	PK	H	28.18	3.11	0.00	91.40	N/A	N/A
2441	50.19	AV	H	28.18	3.11	0.00	81.48	N/A	N/A
2441	58.48	PK	V	28.18	3.11	0.00	89.77	N/A	N/A
2441	48.69	AV	V	28.18	3.11	0.00	79.98	N/A	N/A
4882	50.74	PK	H	33.06	4.40	35.54	52.66	74.00	21.34
4882	35.01	AV	H	33.06	4.40	35.54	36.93	54.00	17.07
7323	55.81	PK	H	36.04	5.53	35.98	61.40	74.00	12.60
7323	43.69	AV	H	36.04	5.53	35.98	49.28	54.00	4.72
9764	48.52	PK	H	38.01	6.34	36.29	56.58	74.00	17.42
9764	33.61	AV	H	38.01	6.34	36.29	41.67	54.00	12.33
2950	45.76	PK	H	29.92	3.43	35.33	43.78	74.00	30.22
2950	29.15	AV	V	24.10	3.39	26.46	30.18	54.00	23.82
226.66	41.97	QP	H	11.80	1.11	27.61	27.27	46.00	18.73
859.59	42.74	QP	H	22.32	2.32	28.30	39.08	46.00	6.92
High Channel: 2480 MHz									
2480	60.53	PK	H	28.26	3.10	0.00	91.89	N/A	N/A
2480	50.48	AV	H	28.26	3.10	0.00	81.84	N/A	N/A
2480	59.28	PK	V	28.26	3.10	0.00	90.64	N/A	N/A
2480	48.93	AV	V	28.26	3.10	0.00	80.29	N/A	N/A
2483.5	25.27	PK	H	28.27	3.10	0.00	56.64	74.00	17.36
2483.5	13.94	AV	H	28.27	3.10	0.00	45.31	54.00	8.69
4960	48.11	PK	H	33.22	4.42	35.60	50.15	74.00	23.85
4960	33.07	AV	H	33.22	4.42	35.60	35.11	54.00	18.89
7440	55.37	PK	H	36.34	5.60	35.99	61.32	74.00	12.68
7440	43.26	AV	H	36.34	5.60	35.99	49.21	54.00	4.79
9920	49.68	PK	H	38.07	6.42	36.32	57.85	74.00	16.15
9920	34.16	AV	H	38.07	6.42	36.32	42.33	54.00	11.67
2950	45.62	PK	H	29.92	3.43	35.33	43.64	74.00	30.36
2950	32.11	AV	H	29.92	3.43	35.33	30.13	54.00	23.87
226.66	42.81	QP	H	11.80	1.11	27.61	28.11	46.00	17.89
859.59	43.16	QP	H	22.32	2.32	28.30	39.50	46.00	6.50

2EDR Mode ($\pi/4$ -DQPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	60.53	PK	H	28.10	3.11	0.00	91.74	N/A	N/A
2402	49.25	AV	H	28.10	3.11	0.00	80.46	N/A	N/A
2402	58.46	PK	V	28.10	3.11	0.00	89.67	N/A	N/A
2402	48.37	AV	V	28.10	3.11	0.00	79.58	N/A	N/A
2390	24.23	PK	V	28.08	3.10	0.00	55.41	74.00	18.59
2390	13.27	AV	V	28.08	3.10	0.00	44.45	54.00	9.55
4804	58.78	PK	H	32.91	4.30	35.48	60.51	74.00	13.49
4804	38.86	AV	H	32.91	4.30	35.48	40.59	54.00	13.41
7206	54.36	PK	H	35.74	5.45	35.97	59.58	74.00	14.42
7206	42.16	AV	H	35.74	5.45	35.97	47.38	54.00	6.62
9608	48.67	PK	H	37.94	6.26	36.26	56.61	74.00	17.39
9608	33.54	AV	H	37.94	6.26	36.26	41.48	54.00	12.52
6390	46.75	PK	H	34.22	5.14	35.76	50.35	74.00	23.65
6390	32.16	AV	H	34.22	5.14	35.76	35.76	54.00	18.24
226.66	42.34	QP	H	11.80	1.11	27.61	27.64	46.00	18.36
859.59	43.6	QP	H	22.32	2.32	28.30	39.94	46.00	6.06
Middle Channel: 2441 MHz									
2441	60.14	PK	H	28.18	3.11	0.00	91.43	N/A	N/A
2441	49.37	AV	H	28.18	3.11	0.00	80.66	N/A	N/A
2441	58.65	PK	V	28.18	3.11	0.00	89.94	N/A	N/A
2441	48.52	AV	V	28.18	3.11	0.00	79.81	N/A	N/A
4882	53.25	PK	H	33.06	4.40	35.54	55.17	74.00	18.83
4882	34.01	AV	H	33.06	4.40	35.54	35.93	54.00	18.07
7323	54.67	PK	H	36.04	5.53	35.98	60.26	74.00	13.74
7323	42.53	AV	H	36.04	5.53	35.98	48.12	54.00	5.88
9764	48.52	PK	H	38.01	6.34	36.29	56.58	74.00	17.42
9764	33.28	AV	H	38.01	6.34	36.29	41.34	54.00	12.66
5685	46.75	PK	H	34.17	4.63	35.85	49.70	74.00	24.30
5685	32.37	AV	H	34.17	4.63	35.85	35.32	54.00	18.68
226.66	41.87	QP	H	11.80	1.11	27.61	27.17	46.00	18.83
859.59	44.04	QP	H	22.32	2.32	28.30	40.38	46.00	5.62
High Channel: 2480 MHz									
2480	60.67	PK	H	28.26	3.10	0.00	92.03	N/A	N/A
2480	49.62	AV	H	28.26	3.10	0.00	80.98	N/A	N/A
2480	58.79	PK	V	28.26	3.10	0.00	90.15	N/A	N/A
2480	48.75	AV	V	28.26	3.10	0.00	80.11	N/A	N/A
2483.5	31.86	PK	V	28.27	3.10	0.00	63.23	74.00	10.77
2483.5	13.83	AV	V	28.27	3.10	0.00	45.20	54.00	8.80
4960	49.56	PK	H	33.22	4.42	35.60	51.60	74.00	22.40
4960	33.59	AV	H	33.22	4.42	35.60	35.63	54.00	18.37
7440	53.49	PK	H	36.34	5.60	35.99	59.44	74.00	14.56
7440	41.26	AV	H	36.34	5.60	35.99	47.21	54.00	6.79
9920	48.62	PK	H	38.07	6.42	36.32	56.79	74.00	17.21
9920	33.39	AV	H	38.07	6.42	36.32	41.56	54.00	12.44
6155	45.83	PK	H	34.27	4.86	35.82	49.14	74.00	24.86
6155	32.16	AV	H	34.27	4.86	35.82	35.47	54.00	18.53
226.66	41.8	QP	H	11.80	1.11	27.61	27.10	46.00	18.90
859.59	42.2	QP	H	22.32	2.32	28.30	38.54	46.00	7.46

3EDR Mode (8-DPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	60.67	PK	H	28.10	3.11	0.00	91.88	N/A	N/A
2402	49.85	AV	H	28.10	3.11	0.00	81.06	N/A	N/A
2402	58.46	PK	V	28.10	3.11	0.00	89.67	N/A	N/A
2402	48.47	AV	V	28.10	3.11	0.00	79.68	N/A	N/A
2390	24.34	PK	V	28.08	3.10	0.00	55.52	74.00	18.48
2390	13.25	AV	V	28.08	3.10	0.00	44.43	54.00	9.57
4804	57.52	PK	H	32.91	4.30	35.48	59.25	74.00	14.75
4804	38.01	AV	H	32.91	4.30	35.48	39.74	54.00	14.26
7206	56.74	PK	H	35.74	5.45	35.97	61.96	74.00	12.04
7206	44.36	AV	H	35.74	5.45	35.97	49.58	54.00	4.42
9608	49.56	PK	H	37.94	6.26	36.26	57.50	74.00	16.50
9608	34.28	AV	H	37.94	6.26	36.26	42.22	54.00	11.78
2390	46.54	PK	H	28.08	3.10	35.50	42.22	74.00	31.78
2390	32.21	AV	H	28.08	3.10	35.50	27.89	54.00	26.11
226.66	42.07	QP	H	11.80	1.11	27.61	27.37	46.00	18.63
859.59	42.34	QP	H	22.32	2.32	28.30	38.68	46.00	7.32
Middle Channel: 2441 MHz									
2441	60.49	PK	H	28.18	3.11	0.00	91.78	N/A	N/A
2441	49.68	AV	H	28.18	3.11	0.00	80.97	N/A	N/A
2441	58.84	PK	V	28.18	3.11	0.00	90.13	N/A	N/A
2441	48.37	AV	V	28.18	3.11	0.00	79.66	N/A	N/A
4882	53.64	PK	H	33.06	4.40	35.54	55.56	74.00	18.44
4882	36.17	AV	H	33.06	4.40	35.54	38.09	54.00	15.91
7323	56.67	PK	H	36.04	5.53	35.98	62.26	74.00	11.74
7323	44.38	AV	H	36.04	5.53	35.98	49.97	54.00	4.03
9764	49.68	PK	H	38.01	6.34	36.29	57.74	74.00	16.26
9764	34.53	AV	H	38.01	6.34	36.29	42.59	54.00	11.41
5965	46.59	PK	H	34.29	4.65	35.85	49.68	74.00	24.32
5965	32.42	AV	H	34.29	4.65	35.85	35.51	54.00	18.49
226.66	42.91	QP	H	11.80	1.11	27.61	28.21	46.00	17.79
859.59	42.76	QP	H	22.32	2.32	28.30	39.10	46.00	6.90
High Channel: 2480 MHz									
2480	60.75	PK	H	28.26	3.10	0.00	92.11	N/A	N/A
2480	49.67	AV	H	28.26	3.10	0.00	81.03	N/A	N/A
2480	58.79	PK	V	28.26	3.10	0.00	90.15	N/A	N/A
2480	48.65	AV	V	28.26	3.10	0.00	80.01	N/A	N/A
2483.5	31.76	PK	V	28.27	3.10	0.00	63.13	74.00	10.87
2483.5	13.95	AV	V	28.27	3.10	0.00	45.32	54.00	8.68
4960	50.26	PK	H	33.22	4.42	35.60	52.30	74.00	21.70
4960	34.79	AV	H	33.22	4.42	35.60	36.83	54.00	17.17
7440	56.43	PK	H	36.34	5.60	35.99	62.38	74.00	11.62
7440	44.38	AV	H	36.34	5.60	35.99	50.33	54.00	3.67
9920	49.51	PK	H	38.07	6.42	36.32	57.68	74.00	16.32
9920	34.35	AV	H	38.07	6.42	36.32	42.52	54.00	11.48
6358	46.68	PK	H	34.23	5.10	35.77	50.24	74.00	23.76
6358	32.25	AV	H	34.23	5.10	35.77	35.81	54.00	18.19
226.66	42.44	QP	H	11.80	1.11	27.61	27.74	46.00	18.26
859.59	43.2	QP	H	22.32	2.32	28.30	39.54	46.00	6.46

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Attenuator	3dB	3dB-1	Each Time	/
Unknown	RF Cable	Unknown	C-2	Each Time	/

*** Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	32.6 °C
Relative Humidity:	37.7 %
ATM Pressure:	100.1 kPa

** The testing was performed by Kevin Hu on 2017-07-27.*

Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
BDR (GFSK)	Low	2402	1.000	0.63
	Middle	2441	1.000	0.62
	High	2480	1.004	0.62
EDR (π/4-DQPSK)	Low	2402	1.000	0.84
	Middle	2441	1.004	0.84
	High	2480	1.008	0.84
EDR (8DPSK)	Low	2402	1.000	0.84
	Middle	2441	1.004	0.85
	High	2480	1.004	0.85

Note: Limit= (2/3) × 20dB bandwidth


BDR Mode (GFSK):

Low Channel




Date: 27.JUL.2017 00:25:05

Middle Channel



Date: 27.JUL.2017 00:24:00


High Channel



Date: 27.JUL.2017 00:23:04


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 27.JUL.2017 00:18:37

Middle Channel



Date: 27.JUL.2017 00:20:42


High Channel



Date: 27.JUL.2017 00:21:54


EDR Mode (8-DPSK):

Low Channel




Date: 27.JUL.2017 00:17:26

Middle Channel



Date: 27.JUL.2017 00:16:28

High Channel



Date: 27.JUL.2017 00:15:00

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Attenuator	3dB	3dB-1	Each Time	/
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data

Environmental Conditions

Temperature:	32.6 °C
Relative Humidity:	37.7 %
ATM Pressure:	100.1 kPa

* The testing was performed by Kevin Hu on 2017-07-27.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.94
	Middle	2441	0.93
	High	2480	0.93
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.26
	Middle	2441	1.26
	High	2480	1.26
EDR Mode (8-DPSK)	Low	2402	1.26
	Middle	2441	1.27
	High	2480	1.27


BDR Mode (GFSK):

Low Channel




Date: 27.JUL.2017 00:03:06

Middle Channel



Date: 27.JUL.2017 00:02:01


High Channel



Date: 27.JUL.2017 00:00:39


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 27.JUL.2017 00:04:43

Middle Channel



Date: 27.JUL.2017 00:06:20


High Channel



Date: 27.JUL.2017 00:07:51


EDR Mode (8-DPSK):

Low Channel




Date: 27.JUL.2017 00:09:45

Middle Channel



Date: 27.JUL.2017 00:11:56

High Channel



Date: 27.JUL.2017 00:13:04

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Attenuator	3dB	3dB-1	Each Time	/
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data

Environmental Conditions

Temperature:	32.6 °C
Relative Humidity:	37.7 %
ATM Pressure:	100.1 kPa

* The testing was performed by Kevin Hu on 2017-07-27.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15




Date: 27.JUL.2017 00:28:15

EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15

Number of Hopping Channels




Date: 27.JUL.2017 00:34:45

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels



Date: 27.JUL.2017 00:49:45

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Attenuator	3dB	3dB-1	Each Time	/
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	32.6 °C
Relative Humidity:	37.7 %
ATM Pressure:	100.1 kPa

* The testing was performed by Kevin Hu on 2017-07-27.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.380	0.122	0.4	Compliance
	Middle	0.380	0.122	0.4	Compliance
	High	0.382	0.122	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
DH3	Low	1.650	0.264	0.4	Compliance
	Middle	1.650	0.264	0.4	Compliance
	High	1.650	0.264	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
DH5	Low	2.910	0.310	0.4	Compliance
	Middle	2.910	0.310	0.4	Compliance
	High	2.910	0.310	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

DH1: Low Channel




Date: 27.JUL.2017 00:51:33

DH1: Middle Channel




Date: 27.JUL.2017 00:51:42

DH1: High Channel




Date: 27.JUL.2017 00:51:51

DH3: Low Channel




Date: 27.JUL.2017 01:29:21

DH3: Middle Channel




Date: 27.JUL.2017 01:29:30

DH3: High Channel




Date: 27.JUL.2017 00:54:12

DH5: Low Channel




Date: 27.JUL.2017 01:02:08

DH5: Middle Channel



Date: 27.JUL.2017 01:02:29

DH5: High Channel




Date: 27.JUL.2017 00:58:16

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.388	0.124	0.4	Compliance
	Middle	0.388	0.124	0.4	Compliance
	High	0.388	0.124	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
2DH3	Low	1.650	0.265	0.4	Compliance
	Middle	1.650	0.265	0.4	Compliance
	High	1.650	0.265	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
2DH5	Low	2.910	0.311	0.4	Compliance
	Middle	2.910	0.310	0.4	Compliance
	High	2.910	0.310	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

2DH1: Low Channel




Date: 27.JUL.2017 01:03:42

2DH1: Middle Channel




Date: 27.JUL.2017 01:04:20

2DH1: High Channel




Date: 27.JUL.2017 01:04:30

2DH3: Low Channel




Date: 27.JUL.2017 01:41:32

2DH3: Middle Channel




Date: 27.JUL.2017 01:46:10

2DH3: High Channel




Date: 27.JUL.2017 01:42:34

2DH5: Low Channel




Date: 27.JUL.2017 01:10:36

2DH5: Middle Channel



Date: 27.JUL.2017 01:09:57

2DH5: High Channel




Date: 27.JUL.2017 01:11:51

EDR Mode (8-DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.388	0.124	0.4	Compliance
	Middle	0.388	0.124	0.4	Compliance
	High	0.390	0.125	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
3DH3	Low	1.650	0.264	0.4	Compliance
	Middle	1.650	0.264	0.4	Compliance
	High	1.650	0.264	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
3DH5	Low	2.910	0.310	0.4	Compliance
	Middle	2.910	0.310	0.4	Compliance
	High	2.910	0.310	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

3DH1: Low Channel




Date: 27.JUL.2017 01:13:51

3DH1: Middle Channel




Date: 27.JUL.2017 01:14:00

3DH1: High Channel




Date: 27.JUL.2017 01:14:09

3DH3: Low Channel




Date: 27.JUL.2017 01:21:00

3DH3: Middle Channel




Date: 27.JUL.2017 01:16:30

3DH3: High Channel




Date: 27.JUL.2017 01:16:39

3DH5: Low Channel




Date: 27.JUL.2017 01:25:31

3DH5: Middle Channel



Date: 27.JUL.2017 01:25:40

3DH5: High Channel



Date: 27.JUL.2017 01:25:04

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Attenuator	3dB	3dB-1	Each Time	/
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data

Environmental Conditions

Temperature:	32.6 °C
Relative Humidity:	37.7 %
ATM Pressure:	100.1 kPa

* The testing was performed by Kevin Hu on 2017-07-27.

Test Result: Compliance.


Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	4.00	30
	2441	4.70	30
	2480	5.07	30
EDR Mode ($\pi/4$ -DQPSK)	2402	3.85	30
	2441	4.58	30
	2480	4.92	30
EDR Mode (8-DPSK)	2402	3.94	30
	2441	4.58	30
	2480	5.01	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):

Low Channel




Date: 27.JUL.2017 00:03:35

Middle Channel



Date: 27.JUL.2017 00:02:33


High Channel



Date: 27.JUL.2017 00:01:05


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 27.JUL.2017 00:05:16

Middle Channel



Date: 27.JUL.2017 00:06:46


High Channel



Date: 27.JUL.2017 00:08:17


EDR Mode (8-DPSK):

Low Channel




Date: 27.JUL.2017 00:10:11

Middle Channel



Date: 27.JUL.2017 00:12:24

High Channel



Date: 27.JUL.2017 00:13:31

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Attenuator	3dB	3dB-1	Each Time	/
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions


Temperature:	32.6 °C
Relative Humidity:	37.7 %
ATM Pressure:	100.1 kPa

* The testing was performed by Kevin Hu on 2017-07-27.

Test Result: Compliance


BDR Mode (GFSK):

Band Edge, Left Side



Date: 27.JUL.2017 00:03:58


Band Edge, Right Side



Date: 27.JUL.2017 00:01:22


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side



Date: 27.JUL.2017 00:05:34


Band Edge, Right Side



Date: 27.JUL.2017 00:08:41


EDR Mode (8-DPSK):

Band Edge, Left Side



Date: 27.JUL.2017 00:10:37

Band Edge, Right Side



Date: 27.JUL.2017 00:14:04

***** **END OF REPORT** *****