



# FCC RF Test Report

**APPLICANT** : Planet Avvio LLC  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : Mint  
**MODEL NAME** : M340, M341, MINT M340, MINT M341  
**FCC ID** : 2ALTAM340X  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was completed on Jul. 27, 2017. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

***Sporton International (Shenzhen) Inc.***

***1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City  
Guangdong Province 518055 China***



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT .....	6
1.6 Testing Location .....	7
1.7 Applicable Standards.....	8
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>9</b>
2.1 Carrier Frequency and Channel .....	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system .....	12
2.5 EUT Operation Test Setup .....	12
2.6 Measurement Results Explanation Example.....	13
<b>3 TEST RESULT .....</b>	<b>14</b>
3.1 6dB Bandwidth Measurement .....	14
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement .....	17
3.4 Conducted Band Edges and Spurious Emission Measurement .....	19
3.5 Radiated Band Edges and Spurious Emission Measurement .....	29
3.6 AC Conducted Emission Measurement.....	33
3.7 Antenna Requirements.....	37
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>38</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>39</b>
<b>APPENDIX A. CONDUCTED TEST RESULTS</b>	
<b>APPENDIX B. RADIATED SPURIOUS EMISSION</b>	
<b>APPENDIX C. DUTY CYCLE PLOTS</b>	
<b>APPENDIX D. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR770507B	Rev. 01	Initial issue of report	Aug. 18, 2017

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.11 dB at 2483.64 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.86 dB at 0.15 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**Planet Avvio LLC**

9725 NW 117th Ave., Medley, FL 33178, United States

## 1.2 Manufacturer

**Heng Da Chuang Xin Technology Limited**

Rm 1301 Block D, Tianan Cloud Pack Building 3th, Bantian Street, Longgang District, Shenzhen City, Guangdong Province, P. R. C. 518000

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Mint
Model Name	M340, M341, MINT M340, MINT M341
FCC ID	2ALTAM340X
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+ WLAN2.4G 802.11b/g/n HT20 Bluetooth v2.1+EDR
HW Version	1611_V2
SW Version	Avvio776_Claro_V1.00
EUT Stage	Production Unit

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This project is FCC change ID application and changed single SIM card slot to dual SIM card slots, Brand Name, Model Name and SW Version that comply with FCC C1PC rule. Based on the similarity between two products, only the worst cases of RSE were verified; all test cases were performed on original report which can be referred to Sporton Report Number FR770404B, FCC ID: 2ALTA400X.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 18.40 dBm (0.0692 W) 802.11g : 20.10 dBm (0.1023 W) 802.11n HT20 : 19.82 dBm (0.0959 W)
Antenna Type / Gain	Monopole Antenna type with gain -0.6 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No are CN5018 and CN5019

<b>Test Site</b>	Sporton International (Shenzhen) Inc.		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Test Firm Registration No.</b>
	TH01-SZ	CO01-SZ	251365

<b>Test Site</b>	Sporton International (Shenzhen) Inc.		
<b>Test Site Location</b>	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Test Firm Registration No.</b>
	03CH01-SZ		577730

**Note:** The test site complies with ANSI C63.4 2014 requirement.



## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



## 2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : GSM1900 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + Adapter + GPS RX

## 2.3 Connection Diagram of Test System

### <WLAN Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8m
4.	NOTE BOOK	lenovo	E450	FCC DoC	N/A	AC I/P : Unshielded, 1.2m
5.	Bluetooth Earphone	NOKIA	BH-108	N/A	N/A	N/A
6.	Labsat	RACELOGIC	18645	N/A	N/A	Unshielded, 1.8m
7.	SD Card	N/A	MicroSD HC	FCC DoC	N/A	N/A

## 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.



## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5 + 10 = 15 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 6dB Bandwidth Measurement

##### 3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


##### 3.1.4 Test Setup





### 3.1.5 Test Result of 6dB Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


#### 3.3.4 Test Setup





### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



### 3.4 Conducted Band Edges and Spurious Emission Measurement

#### 3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


#### 3.4.4 Test Setup








## 3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sum Zheng





Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sum Zheng


**WLAN 802.11b Channel 06****100kHz PSD reference Level****Mid Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sum Zheng

## WLAN 802.11b Channel 11


## 100kHz PSD reference Level




## High Channel Plot



## Spurious Emission 30MHz~3GHz




## Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sum Zheng

**WLAN 802.11g Channel 01****100kHz PSD reference Level**


Date: 25 JUL 2017 05:16:03

**Low Channel Plot**

Date: 25 JUL 2017 05:16:36

**Spurious Emission 30MHz~3GHz**

Date: 25 JUL 2017 05:16:48

**Spurious Emission 2GHz~25GHz**


Date: 25 JUL 2017 05:16:56



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sum Zheng


## WLAN 802.11g Channel 06

## 100kHz PSD reference Level




## Mid Channel Plot

## Spurious Emission 30MHz~3GHz



## Spurious Emission 2GHz~25GHz









Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sum Zheng

## WLAN 802.11g Channel 11


## 100kHz PSD reference Level




## High Channel Plot



## Spurious Emission 30MHz~3GHz



## Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sum Zheng


## WLAN 802.11n HT20 Channel 01

## 100kHz PSD reference Level




Date: 25 JUL 2017 05:32:57

## Low Channel Plot




Date: 25 JUL 2017 05:34:37

## Spurious Emission 30MHz~3GHz



Date: 25 JUL 2017 05:54:57

## Spurious Emission 2GHz~25GHz




Date: 25 JUL 2017 05:45:56



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sum Zheng


## WLAN 802.11n HT20 Channel 06

## 100kHz PSD reference Level




## Mid Channel Plot

## Spurious Emission 30MHz~3GHz




## Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sum Zheng



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.

For average measurement:


    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

### 3.5.7 Duty Cycle

Please refer to Appendix C.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix B .



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


### 3.6.4 Test Setup





## 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	24~25℃
Test Engineer :	HaoHai Ye	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + Adapter + GPS RX		




Site : CO01-SZ  
Condition: FCC 15C\_QP LISN\_20170301\_L LINE

IMEI : 867400020316612/86740020316620

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	49.14	-6.86	56.00	38.70	0.03	10.41	Average
2	0.15	52.84	-13.16	66.00	42.40	0.03	10.41	QP
3	0.20	39.25	-14.33	53.58	29.00	0.03	10.22	Average
4	0.20	41.25	-22.33	63.58	31.00	0.03	10.22	QP
5	0.39	28.82	-19.30	48.12	18.60	0.03	10.19	Average
6	0.39	40.22	-17.90	58.12	30.00	0.03	10.19	QP
7	0.47	21.61	-24.88	46.49	11.41	0.02	10.18	Average
8	0.47	37.91	-18.58	56.49	27.71	0.02	10.18	QP
9	0.61	23.09	-22.91	46.00	12.90	0.02	10.17	Average
10	0.61	34.79	-21.21	56.00	24.60	0.02	10.17	QP
11	0.72	25.59	-20.41	46.00	15.41	0.02	10.16	Average
12	0.72	36.39	-19.61	56.00	26.21	0.02	10.16	QP



Test Mode :	Mode 1	Temperature :	24~25°C
Test Engineer :	HaoHai Ye	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + Adapter + GPS RX		



Site : C001-SZ  
Condition: FCC 15C QP LISN\_20170301\_N NEUTRAL

IMEI : 867400020316612/86740020316620

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	48.04	-7.92	55.96	37.60	0.03	10.41	Average
2	0.15	51.64	-14.32	65.96	41.20	0.03	10.41	QP
3	0.20	37.95	-15.63	53.58	27.70	0.03	10.22	Average
4	0.20	40.55	-23.03	63.58	30.30	0.03	10.22	QP
5	0.39	30.22	-17.95	48.17	20.01	0.02	10.19	Average
6	0.39	38.92	-19.25	58.17	28.71	0.02	10.19	QP
7	0.47	26.50	-20.08	46.58	16.30	0.02	10.18	Average
8	0.47	38.10	-18.48	56.58	27.90	0.02	10.18	QP
9	0.67	23.39	-22.61	46.00	13.20	0.02	10.17	Average
10	0.67	32.99	-23.01	56.00	22.80	0.02	10.17	QP
11	0.78	25.69	-20.31	46.00	15.50	0.03	10.16	Average
12	0.78	33.29	-22.71	56.00	23.10	0.03	10.16	QP



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~40GHz	Jan. 06, 2017	Jul. 25, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 20, 2017	Jul. 25, 2017	Apr. 19, 2018	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 06, 2017	Jul. 25, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 06, 2017	Jul. 25, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Apr. 20, 2017	Jul. 17, 2017~ Jul. 27, 2017	Apr.19, 2018	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May.14, 2017	Jul. 17, 2017~ Jul. 27, 2017	May.13, 2018	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Apr. 25, 2017	Jul. 17, 2017~ Jul. 27, 2017	Apr. 24, 2018	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Nov. 19, 2016	Jul. 17, 2017~ Jul. 27, 2017	Nov. 18, 2017	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug.10, 2016	Jul. 17, 2017~ Jul. 27, 2017	Aug. 09, 2017	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 20, 2017	Jul. 17, 2017~ Jul. 27, 2017	Apr.19, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-001018 00-30-10P-R	1707137	1GHz~18GHz	Oct. 11, 2016	Jul. 17, 2017~ Jul. 27, 2017	Oct 10, 2017	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5GHz	Oct. 11, 2016	Jul. 17, 2017~ Jul. 27, 2017	Oct 10, 2017	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jul. 17, 2017~ Jul. 27, 2017	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 17, 2017~ Jul. 27, 2017	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 17, 2017~ Jul. 27, 2017	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2017	Jul. 20, 2017	Jan. 05, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2017	Jul. 20, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2017	Jul. 20, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 19, 2017	Jul. 20, 2017	Jul. 18, 2018	Conduction (CO01-SZ)

NCR: No Calibration Required

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.5dB
-----------------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	5.1dB
-----------------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	5.2dB
-----------------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	5.1dB
-----------------------------------------------------------------------------	-------



## **Appendix A. Conducted Test Results**



**A1 - DTS Part**

Test Engineer:	Sam Zheng	Temperature:	24~26	°C
Test Date:	2017/7/25	Relative Humidity:	50~53	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

2.4GHz Band								
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.89	10.05	0.50	Pass
11b	1Mbps	1	6	2437	12.89	10.05	0.50	Pass
11b	1Mbps	1	11	2462	12.99	10.03	0.50	Pass
11g	6Mbps	1	1	2412	18.18	16.00	0.50	Pass
11g	6Mbps	1	6	2437	18.43	16.24	0.50	Pass
11g	6Mbps	1	11	2462	19.83	16.02	0.50	Pass
HT20	MCS0	1	1	2412	19.08	17.22	0.50	Pass
HT20	MCS0	1	6	2437	19.30	17.36	0.50	Pass
HT20	MCS0	1	11	2462	19.73	17.10	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

2.4GHz Band										
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	17.88	30.00	-0.60	17.28	36.00	Pass
11b	1Mbps	1	6	2437	18.17	30.00	-0.60	17.57	36.00	Pass
11b	1Mbps	1	11	2462	18.40	30.00	-0.60	17.80	36.00	Pass
11g	6Mbps	1	1	2412	20.01	30.00	-0.60	19.41	36.00	Pass
11g	6Mbps	1	6	2437	20.02	30.00	-0.60	19.42	36.00	Pass
11g	6Mbps	1	11	2462	20.10	30.00	-0.60	19.50	36.00	Pass
HT20	MCS0	1	1	2412	19.54	30.00	-0.60	18.94	36.00	Pass
HT20	MCS0	1	6	2437	19.37	30.00	-0.60	18.77	36.00	Pass
HT20	MCS0	1	11	2462	19.82	30.00	-0.60	19.22	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**  
**(Reporting Only)**

2.4GHz Band						
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	14.75
11b	1Mbps	1	6	2437	0.00	15.03
11b	1Mbps	1	11	2462	0.00	15.30
11g	6Mbps	1	1	2412	0.09	12.39
11g	6Mbps	1	6	2437	0.09	12.72
11g	6Mbps	1	11	2462	0.09	13.02
HT20	MCS0	1	1	2412	0.11	11.55
HT20	MCS0	1	6	2437	0.11	11.44
HT20	MCS0	1	11	2462	0.11	12.16

**TEST RESULTS DATA**  
**Peak Power Density**

2.4GHz Band								
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-7.00	-0.60	8.00	Pass
11b	1Mbps	1	6	2437	-7.48	-0.60	8.00	Pass
11b	1Mbps	1	11	2462	-6.29	-0.60	8.00	Pass
11g	6Mbps	1	1	2412	-11.91	-0.60	8.00	Pass
11g	6Mbps	1	6	2437	-11.77	-0.60	8.00	Pass
11g	6Mbps	1	11	2462	-11.34	-0.60	8.00	Pass
HT20	MCS0	1	1	2412	-13.60	-0.60	8.00	Pass
HT20	MCS0	1	6	2437	-11.40	-0.60	8.00	Pass
HT20	MCS0	1	11	2462	-11.74	-0.60	8.00	Pass



## Appendix B. Radiated Spurious Emission

### For single SIM card mobile

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b CH 01 2412MHz		2386.125	40.31	-33.69	74	39.48	27.23	6.81	33.21	-	-	P	H
		2386.23	30.99	-23.01	54	30.16	27.23	6.81	33.21	-	-	A	H
	*	2412	93.96	-	-	93.06	27.28	6.81	33.19	-	-	P	H
	*	2412	92.29	-	-	91.39	27.28	6.81	33.19	-	-	A	H
		2383.5	41.42	-32.58	74	40.73	27.19	6.73	33.23	-	-	P	V
		2382.45	30.14	-23.86	54	29.45	27.19	6.73	33.23	-	-	A	V
	*	2412	86.29	-	-	85.39	27.28	6.81	33.19	-	-	P	V
	*	2412	84.68	-	-	83.78	27.28	6.81	33.19	-	-	A	V
802.11b CH 06 2437MHz		2349.62	40.29	-33.71	74	39.72	27.1	6.73	33.26	-	-	P	H
		2382.1	30.32	-23.68	54	29.63	27.19	6.73	33.23	-	-	A	H
	*	2437	95.02	-	-	93.94	27.37	6.86	33.15	-	-	P	H
	*	2437	93.24	-	-	92.16	27.37	6.86	33.15	-	-	A	H
		2486.7	40.87	-33.13	74	39.62	27.46	6.91	33.12	-	-	P	H
		2496.15	30.49	-23.51	54	29.18	27.5	6.91	33.1	-	-	A	H
		2344.02	40.59	-33.41	74	40.1	27.1	6.65	33.26	-	-	P	V
		2382.66	30.14	-23.86	54	29.45	27.19	6.73	33.23	-	-	A	V
	*	2437	90.83	-	-	89.75	27.37	6.86	33.15	-	-	P	V
	*	2437	89.15	-	-	88.07	27.37	6.86	33.15	-	-	A	V
		2496.92	40.31	-33.69	74	39	27.5	6.91	33.1	-	-	P	V
		2495.03	30.35	-23.65	54	29.04	27.5	6.91	33.1	-	-	A	V



<b>802.11b</b> <b>CH 11</b> <b>2462MHz</b>	*	2462	95.63	-	-	94.5	27.41	6.86	33.14	173	226	P	H
	*	2462	93.98	-	-	92.85	27.41	6.86	33.14	173	226	A	H
		2483.56	46.48	-27.52	74	45.23	27.46	6.91	33.12	173	226	P	H
		2483.52	41.1	-12.9	54	39.85	27.46	6.91	33.12	173	226	A	H
	*	2462	89.02	-	-	87.89	27.41	6.86	33.14	181	324	P	V
	*	2462	87.34	-	-	86.21	27.41	6.86	33.14	181	324	A	V
		2484.64	42.47	-31.53	74	41.22	27.46	6.91	33.12	181	324	P	V
		2483.52	34.91	-19.09	54	33.66	27.46	6.91	33.12	181	324	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11b (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
<b>802.11b CH 01 2412MHz</b>		4824	54.64	-19.36	74	68.62	31.73	10.89	56.6	163	360	P	H
		4824	53.62	-0.38	54	67.6	31.73	10.89	56.6	163	360	A	H
		4824	52.52	-21.48	74	66.5	31.73	10.89	56.6	185	255	P	V
		4824	51.12	-2.88	54	65.1	31.73	10.89	56.6	185	255	A	V
<b>802.11b CH 06 2437MHz</b>		4874	55.99	-18.01	74	70.2	31.78	10.92	56.91	165	106	P	H
		4874	53.57	-0.43	54	67.78	31.78	10.92	56.91	165	106	A	H
		7311	49.81	-24.19	74	58.86	35.66	13.29	58	174	100	P	H
		4874	52.46	-21.54	74	66.67	31.78	10.92	56.91	165	106	P	V
		4874	49.68	-4.32	54	63.89	31.78	10.92	56.91	165	106	A	V
		7311	48.85	-25.15	74	57.9	35.66	13.29	58	174	100	P	V
<b>802.11b CH 11 2462MHz</b>		4924	56.12	-17.88	74	69.38	31.83	10.99	56.08	150	360	P	H
		4924	53.54	-0.46	54	66.8	31.83	10.99	56.08	150	360	A	H
		7386	48.99	-25.01	74	58.07	35.81	13.12	58.01	165	335	P	H
		4924	50.05	-23.95	74	63.31	31.83	10.99	56.08	150	285	P	V
		7386	48.62	-25.38	74	57.7	35.81	13.12	58.01	155	274	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11g (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11g CH 01 2412MHz		2390	54.41	-19.59	74	53.58	27.23	6.81	33.21	119	66	P	H
		2389.905	42.47	-11.53	54	41.64	27.23	6.81	33.21	119	66	A	H
	*	2412	96.99	-	-	96.09	27.28	6.81	33.19	119	66	P	H
	*	2412	90	-	-	89.1	27.28	6.81	33.19	119	66	A	H
		2389.8	50.81	-23.19	74	49.98	27.23	6.81	33.21	355	280	P	V
		2390	38.37	-15.63	54	37.54	27.23	6.81	33.21	355	280	A	V
	*	2412	91.93	-	-	91.03	27.28	6.81	33.19	355	280	P	V
	*	2412	85.89	-	-	84.99	27.28	6.81	33.19	355	280	A	V
802.11g CH 06 2437MHz		2385.32	41.78	-32.22	74	41.01	27.19	6.81	33.23	119	50	P	H
		2387.7	31.12	-22.88	54	30.29	27.23	6.81	33.21	119	50	A	H
	*	2437	98.46	-	-	97.38	27.37	6.86	33.15	119	50	P	H
	*	2437	90.46	-	-	89.38	27.37	6.86	33.15	119	50	A	H
		2483.62	48.58	-25.42	74	47.33	27.46	6.91	33.12	119	50	P	H
		2484.11	32.66	-21.34	54	31.41	27.46	6.91	33.12	119	50	A	H
		2385.46	40.75	-33.25	74	39.98	27.19	6.81	33.23	380	306	P	V
		2384.62	31.01	-22.99	54	30.24	27.19	6.81	33.23	380	306	A	V
	*	2437	92.13	-	-	91.05	27.37	6.86	33.15	380	306	P	V
	*	2437	85.88	-	-	84.8	27.37	6.86	33.15	380	306	A	V
		2484.04	44.5	-29.5	74	43.25	27.46	6.91	33.12	380	306	P	V
		2483.62	31.43	-22.57	54	30.18	27.46	6.91	33.12	380	306	A	V



<b>802.11g CH 11 2462MHz</b>		2484.12	66.44	-7.56	74	65.19	27.46	6.91	33.12	119	69	P	H
		2483.72	53.29	-0.71	54	52.04	27.46	6.91	33.12	119	69	A	H
	*	2462	96.9	-	-	95.77	27.41	6.86	33.14	119	69	P	H
	*	2462	89.64	-	-	88.51	27.41	6.86	33.14	119	69	A	H
		2483.52	63.53	-10.47	74	62.28	27.46	6.91	33.12	380	286	P	V
		2483.52	49.11	-4.89	54	47.86	27.46	6.91	33.12	380	286	A	V
	*	2462	92.26	-	-	91.13	27.41	6.86	33.14	380	286	P	V
	*	2462	85.5	-	-	84.37	27.41	6.86	33.14	380	286	A	V
<b>Remark</b>	<ol style="list-style-type: none"><li>1. No other spurious found.</li><li>2. All results are PASS against Peak and Average limit line.</li></ol>												



## 2.4GHz 2400~2483.5MHz

## WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	44.23	-29.77	74	58.21	31.73	10.89	56.6	185	255	P	H
		4824	44.34	-29.66	74	58.32	31.73	10.89	56.6	185	255	P	V
802.11g CH 06 2437MHz		4874	44.53	-29.47	74	58.74	31.78	10.92	56.91	165	106	P	H
		7311	48.97	-25.03	74	58.02	35.66	13.29	58	174	100	P	H
		4874	45.33	-28.67	74	59.54	31.78	10.92	56.91	165	106	P	V
		7311	49.09	-24.91	74	58.14	35.66	13.29	58	174	100	P	V
802.11g CH 11 2462MHz		4924	46.67	-27.33	74	59.93	31.83	10.99	56.08	150	285	P	H
		7386	49.04	-24.96	74	58.12	35.81	13.12	58.01	155	274	P	H
		4924	44.53	-29.47	74	57.79	31.83	10.99	56.08	150	285	P	V
		7386	48.58	-25.42	74	57.66	35.81	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 01 2412MHz		2388.855	60.28	-13.72	74	59.45	27.23	6.81	33.21	119	65	P	H
		2389.905	43.92	-10.08	54	43.09	27.23	6.81	33.21	119	65	A	H
	*	2412	96.62	-	-	95.72	27.28	6.81	33.19	119	65	P	H
	*	2412	89.1	-	-	88.2	27.28	6.81	33.19	119	65	A	H
		2390	54.38	-19.62	74	53.55	27.23	6.81	33.21	355	280	P	V
		2389.695	39.94	-14.06	54	39.11	27.23	6.81	33.21	355	280	A	V
	*	2412	92.61	-	-	91.71	27.28	6.81	33.19	355	280	P	V
	*	2412	85.17	-	-	84.27	27.28	6.81	33.19	355	280	A	V
802.11n HT20 CH 06 2437MHz		2387.84	56.68	-17.32	74	55.85	27.23	6.81	33.21	119	65	P	H
		2385.32	34.77	-19.23	54	34	27.19	6.81	33.23	119	65	A	H
	*	2437	96.93	-	-	95.85	27.37	6.86	33.15	119	65	P	H
	*	2437	89.41	-	-	88.33	27.37	6.86	33.15	119	65	A	H
		2493.98	56.48	-17.52	74	55.17	27.5	6.91	33.1	119	65	P	H
		2488.17	35.95	-18.05	54	34.64	27.5	6.91	33.1	119	65	A	H
		2387.84	48.59	-25.41	74	47.76	27.23	6.81	33.21	348	299	P	V
		2380.84	32.16	-21.84	54	31.47	27.19	6.73	33.23	348	299	A	V
	*	2437	92.63	-	-	91.55	27.37	6.86	33.15	348	299	P	V
	*	2437	85.28	-	-	84.2	27.37	6.86	33.15	348	299	A	V
		2492.79	50.21	-23.79	74	48.9	27.5	6.91	33.1	348	299	P	V
		2484.04	33.14	-20.86	54	31.89	27.46	6.91	33.12	348	299	A	V



<b>802.11n</b> <b>HT20</b> <b>CH 11</b> <b>2462MHz</b>	*	2462	95.2	-	-	94.07	27.41	6.86	33.14	119	65	P	H
	*	2462	88.97	-	-	87.84	27.41	6.86	33.14	119	65	A	H
		2484.8	68.48	-5.52	74	67.23	27.46	6.91	33.12	119	65	P	H
		2483.64	53.89	-0.11	54	52.64	27.46	6.91	33.12	119	65	A	H
	*	2462	93.51	-	-	92.38	27.41	6.86	33.14	343	303	P	V
	*	2462	86.02	-	-	84.89	27.41	6.86	33.14	343	303	A	V
		2484.8	64.07	-9.93	74	62.82	27.46	6.91	33.12	343	303	P	V
		2483.56	49.46	-4.54	54	48.21	27.46	6.91	33.12	343	303	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	44.23	-29.77	74	58.21	31.73	10.89	56.6	185	255	P	H
		4824	44.34	-29.66	74	58.32	31.73	10.89	56.6	185	255	P	V
802.11n HT20 CH 06 2437MHz		4874	44.53	-29.47	74	58.74	31.78	10.92	56.91	165	106	P	H
		7311	48.97	-25.03	74	58.02	35.66	13.29	58	174	100	P	H
		4874	45.33	-28.67	74	59.54	31.78	10.92	56.91	165	106	P	V
		7311	49.09	-24.91	74	58.14	35.66	13.29	58	174	100	P	V
802.11n HT20 CH 11 2462MHz		4924	45.3	-28.7	74	58.56	31.83	10.99	56.08	150	285	P	H
		7386	48.45	-25.55	74	57.53	35.81	13.12	58.01	155	274	P	H
		4924	44.55	-29.45	74	57.81	31.83	10.99	56.08	150	285	P	V
		7386	47.93	-26.07	74	57.01	35.81	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## Emission below 1GHz

## 2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz 802.11n HT20 LF		31.94	24.34	-15.66	40	30.44	25.28	0.27	31.65	100	254	P	H
		165.8	17.24	-26.26	43.5	30.58	16.58	1.41	31.33	-	-	P	H
		350.1	20.45	-25.55	46	29.73	19.8	2.22	31.3	-	-	P	H
		614.91	25.86	-20.14	46	29.47	24.84	3.05	31.5	-	-	P	H
		800.18	30.19	-15.81	46	31.08	27	3.61	31.5	-	-	P	H
		1000	31.41	-22.59	54	29.7	29	4.21	31.5	-	-	P	H
		30.97	24.07	-15.93	40	30.08	25.44	0.25	31.7	100	145	P	V
		164.83	17.97	-25.53	43.5	31.32	16.59	1.4	31.34	-	-	P	V
		415.09	22.81	-23.19	46	29.92	21.74	2.45	31.3	-	-	P	V
		638.19	29.24	-16.76	46	32.41	25.21	3.12	31.5	-	-	P	V
		834.13	29.46	-16.54	46	29.82	27.48	3.66	31.5	-	-	P	V
		986.42	30.89	-23.11	54	29.36	28.89	4.14	31.5	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



## For dual SIM card mobile

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11n HT20 CH 11 2462MHz		2462	95.16	-	-	94.03	27.41	6.86	33.14	119	65	P	H
		2462	87.94	-	-	86.81	27.41	6.86	33.14	119	65	A	H
		2483.8	67.65	-6.35	74	66.4	27.46	6.91	33.12	119	65	P	H
		2483.56	53.48	-0.52	54	52.23	27.46	6.91	33.12	119	65	A	H
		2462	92.63	-	-	91.5	27.41	6.86	33.14	343	303	P	V
		2462	85.13	-	-	84	27.41	6.86	33.14	343	303	A	V
		2484.8	63.15	-10.85	74	61.9	27.46	6.91	33.12	343	303	P	V
		2483.56	48.57	-5.43	54	47.32	27.46	6.91	33.12	343	303	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												




**15C 2.4GHz 2400~2483.5MHz**
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11n		4924	45.62	-28.38	74	58.88	31.83	10.99	56.08	165	106	P	H
HT20		7386	49.25	-24.75	74	58.33	35.81	13.12	58.01	174	100	P	H
CH 11		4924	46.28	-27.72	74	59.54	31.83	10.99	56.08	165	106	P	V
2462MHz		7386	49.29	-24.71	74	58.37	35.81	13.12	58.01	174	100	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**




## Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(KHz)	VBW Setting
802.11b	100.00	-	-	10Hz
802.11g	97.92	1.362	0.734	1KHz
802.11n HT20	97.55	1.152	0.868	1KHz




802.11b



Date: 17.JUL.2017 11:43:57




802.11g



Date: 17.JUL.2017 12:30:12



## 802.11n HT20



Date: 17.JUL.2017 12:38:50