CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970   Fax: +82-31-624-9501
www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant	: CLABSYS Co., Ltd.
Applicant Address	: A-Dong, 2floor., 895-20, Sicheong-ro, Platan-myeon, Hwaseong-si, Gyeonggi-do, Republic of Korea
Kind of Product	: Android Module
Equipment model name	: SO7
FCC ID	: 2ALVHSO7
Antenna type	: PCB Antenna
Antenna Gain	: 2.0 dBi

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970   Fax: +82-31-624-9501
www.e-ctk.com

** MPE Calculations **

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.   The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$G = Log^{-1}$ (dB antenna gain / 10)

Power density at the specific separation:

$S = PG/(4R^2\pi)$	Where, S = Maximum power density (mW/cm^2) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm^2 .
The power density at 20cm does not exceed the 1 mW/cm^2 limit.

Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where, P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970   Fax: +82-31-624-9501
www.e-ctk.com

Mode	P (dBm)	P (mW)	G (dBi)	S (mW/cm^2)	R (cm)
802.11b	11.500	14.13		**0.0045**	
802.11g	14.730	29.72	2.0	**0.0094**	**20**
802.11n HT20	14.290	26.85		**0.0085**	
BLE	5.307	3.39		**0.0011**	