

**FCC§15.247 (i), §1.1307 (b) (1) & §2.1091 –MAXIMUM PERMISSIBLE****EXPOSURE (MPE)****Applicable Standard**

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

**Limits for General Population/Uncontrolled Exposure**

<b>Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (Minutes)</b>
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

**MPE Calculated :**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**MPE Results**

Tune-Up Power Including Tolerance:

mode	Frequency band (MHz)	Antenna Gain		Cable loss (dB)	Max Tune-up Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)		(dBm)	(mW)			
uplink	698-716	9	7.94	5.21	16.79	47.75	20	0.075	0.465
	776-787	9	7.94	5.21	16.79	47.75	20	0.075	0.517
	824-849	9	7.94	5.49	16.51	44.77	20	0.071	0.549
	1710-1755	10.5	11.22	5.89	16.11	40.83	20	0.091	1.0
	1850-1910	10.5	11.22	6.25	15.75	37.58	20	0.084	1.0
downlink	728-746	7	5.01	2.19	7.81	6.04	20	0.006	0.485
	746-757	7	5.01	2.19	7.81	6.04	20	0.006	0.497
	869-894	7	5.01	2.29	7.71	5.90	20	0.006	0.579
	2110-2155	8.5	7.08	2.86	7.14	5.18	20	0.007	1.0
	1930-1990	8.5	7.08	2.55	7.45	5.56	20	0.008	1.0

Note: The rated max output power is 22dBm for uplink, 10dBm for downlink.

Max Tune-up power= rated max output power- cable loss

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliance**