

## RF Exposure Requirements

---

Product Description: wireless Bluetooth microphone

Model No.: Q9S+, Q10S, I6, Q9S, Q9, M6, M7, Shoulder 3.0, Baymax, ELF

FCC ID: 2AM3FQ9S

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range: 2402-2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: -4.909dBm

Tune-Up output power: -4.5dBm

RF channel transmit frequency: 2480MHz

Result: 0.111

Limit: 3.0

The exclusion thresholds is  $0.111 < 3$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.