



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

# TEST REPORT

FCC Part 22 Subpart H / Part 24 Subpart E

Report Reference No. .... : CTL1706302041-WF01

Compiled by:  
( position+printed name+signature)

Allen Wang  
(File administrators)

*Allen Wang*

Tested by:  
( position+printed name+signature)

Nice Nong  
(Test Engineer)

*Nice Nong*

Approved by:  
( position+printed name+signature)

Ivan Xie  
(Manager)

*Ivan Xie*

Product Name ..... : Android All Mode Wireless Module

Model/Type reference ..... : M100-QVCX-2G16G

List Model(s)..... : See next page

Trade Mark..... : Temolin

FCC ID..... : 2AM5I-TML-M100

Applicant's name ..... : Temolin Technology Co., Ltd

Address of applicant..... : Room 311, Building B, No.125 TianShan Road West, ChangNing  
District, Shanghai City, China

Test Firm..... : Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm ..... : Floor 1-A, Baisha Technology Park, No.3011, ShaheXi Road,  
Nanshan District, Shenzhen, China 518055

Test specification ..... :

Standard ..... : FCC CFR Title 47 Part 2, Part 22H and Part 24E  
EIA/TIA 603-D: 2010  
KDB 971168 D01

TRF Originator ..... : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF ..... : Dated 2011-01

Date of Receipt..... : Jun. 23, 2017

Date of Test Date..... : Jun. 24, 2017–Jul. 11, 2017

Data of Issue..... : Jul. 12, 2017

Result..... : Pass

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

<b>Test Report No. :</b>	<b>CTL1706302041-WF01</b>	Jul. 12, 2017
		Date of issue

Equipment under Test : Android All Mode Wireless Module

Model /Type : M100-QVCX-2G16G

Listed Models : M100-OVCX-1G8G, M100-OVCX-2G16G,  
M100-OVWX-1G8G, M100-OVWX-2G16G,  
M100-OVTX-1G8G, M100-OVTX-2G16G,  
M100-QVCX-1G8G, M100-QVCX-2G16G,  
M100-QVWX-1G8G, M100-QVWX-2G16G,  
M100-QVTX-1G8G, M100-QVTX-2G16G,  
M100-OWNX-1G8G, M100-OWNX-2G16G,  
M100-QWNX-1G8G, M100-QWNX-2G16G

Applicant : Temolin Technology Co., Ltd

Address : Room 311, Building B, No.125 TianShan Road West,  
ChangNing District, Shanghai City, China

Manufacturer : Temolin Technology Co., Ltd

Address : Room 311, Building B, No.125 TianShan Road West,  
ChangNing District, Shanghai City, China

<b>Test result</b>	<b>Pass *</b>
--------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.


**\*\* Modified History \*\***

Revisions	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2017-07-12	CTL1706302041-WF01	Tracy Qi



# Contents

<b>1</b>	<b>SUMMARY.....</b>	<b>5</b>
1.1	TEST STANDARDS .....	5
1.2	TEST DESCRIPTION.....	5
1.3	TEST FACILITY .....	6
1.4	STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>7</b>
2.1	ENVIRONMENTAL CONDITIONS .....	7
2.2	GENERAL DESCRIPTION OF EUT .....	7
2.3	DESCRIPTION OF TEST MODES AND TEST FREQUENCY .....	8
2.4	EQUIPMENTS USED DURING THE TEST .....	9
2.5	RELATED SUBMITTAL(S) / GRANT (S) .....	9
2.6	MODIFICATIONS.....	9
<b>3</b>	<b>TEST CONDITIONS AND RESULTS .....</b>	<b>10</b>
3.1	OUTPUT POWER .....	10
3.2	OCCUPIED BANDWIDTH .....	14
3.3	BAND EDGE COMPLIANCE .....	18
3.4	SPURIOUS EMISSION .....	22
3.5	FREQUENCY STABILITY UNDER TEMPERATURE & VOLTAGE VARIATIONS .....	35
<b>4</b>	<b>TEST SETUP PHOTOS OF THE EUT .....</b>	<b>38</b>
<b>5</b>	<b>EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....</b>	<b>39</b>



# 1 SUMMARY

## 1.1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22](#): PRIVATE LAND MOBILE RADIO SERVICES.

[FCC Part 24](#): [PUBLIC](#) MOBILE SERVICES

[TIA/EIA 603 D June 2010](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[FCC Part 2](#): FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[KDB971168 D01:v02r02](#) MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

[ANSI C63.26-2015](#) American National Standard for Compliance Testing of Transmitters Used in Licensed Radio

## 1.2 Test Description

Test Item	Section in CFR 47	Result
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 ©	Pass
Peak-to-Average Ratio	Part 24.232 (d)	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability	Part 2.1055 Part 22.355 Part 24.235	Pass



## 1.3 Test Facility

### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

#### FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

## 1.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. Quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2 GENERAL INFORMATION

### 2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2 General Description of EUT

Product Name:	Android All Mode Wireless Module
Model/Type reference:	M100-QVCX-2G16G
Power supply:	DC 3.3V from host device
<b>2G</b>	
Operation Band:	GSM850, GSM900, DCS1800, PCS1900
Supported type:	GSM, GPRS, EGPRS
Power Class:	GSM850,GSM900:Power Class 4 DCS1800, PCS1900:Power Class 1
Modulation Type:	GMSK for GSM, GPRS, 8-PSK for EGPRS
GSM Release Version	R99
GPRS Multisport Class	12
EGPRS Multisport Class	12
Antenna type:	FPC antenna
<b>WCDMA</b>	
Operation Band:	FDD Band I , FDD Band II, FDD Band V, FDD Band VIII
Power Class:	Power Class 3
Modulation Type:	QPSK for HSUPA/HSDPA
WCDMA Release Version:	R8
HSDPA Release Version:	Release 7, CAT14
HSUPA Release Version:	Release 6, CAT6
DC-HSUPA Release Version:	Not Supported
Antenna type:	FPC antenna

Note: For more details, refer to the user's manual of the EUT.

Remark: The GPRS/ EGPRS frequency band includes GSM850, GSM900, DCS1800 and PCS1900, but only GSM850 and PCS1900 bands test data included in this report. The HSPA frequency band support Band I, FDD Band II, FDD Band V, and FDD Band VIII but only Band II and Band V bands test data included in this report.

## 2.3 Description of Test Modes and Test Frequency

The EUT has been tested under typical operating condition. The CUM200 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

### Test Frequency:

GSM 850		PCS1900	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20
190	836.60	661	1880.00
251	848.80	810	1909.80

FDD Band II		FDD Band V	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
9262	1852.4	4132	826.40
9400	1880.0	4182	836.60
9538	1907.6	4233	846.60

### Test Modes:

The test mode(s) are selected according to relevant radio technology specifications.

Test Mode	Test Modes Description
Mode 1	GSM system, GSM, GMSK modulation
Mode 2	GSM system, GPRS, GMSK modulation
Mode 3	GSM system, EDGE, GMSK modulation
Mode 4	WCDMA system, QPSK modulation
Mode 5	HSDPA system, QPSK modulation
Mode 6	HSUPA system, QPSK modulation

Note:

1. As GSM and GPRS with the same emission designator, test result recorded in this report at the worst case Mode 1 only after exploratory scan.
2. As WCDMA, HSDPA and HSUPA with the same emission designator, test result recorded in this report at the worst case Mode 4 only after exploratory scan.



## 2.4 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2017/06/02	2018/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061714	2017/06/02	2018/06/01
EMI Test Receiver	R&S	ESCI	103710	2017/06/02	2018/06/01
Spectrum Analyzer	Agilent	E4407B	MY45108355	2017/06/02	2018/06/01
Controller	EM Electronics	Controller EM 1000	N/A	2017/05/21	2018/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2017/05/19	2018/05/18
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062014	2017/05/19	2018/05/18
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2017/05/19	2018/05/18
Amplifier	Agilent	8349B	3008A02306	2017/05/19	2018/05/18
Amplifier	Agilent	8447D	2944A10176	2017/05/19	2018/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2017/05/20	2018/05/19
Radio Communication Tester	R&S	CMU200	115419	2017/05/22	2018/05/21
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2017/05/20	2018/05/19
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2017/05/20	2018/05/19
RF Cable	HUBER+SUHNER	RG214	N/A	2017/05/20	2018/05/19
Climate Chamber	ESPEC	EL-10KA	A20120523	2017/05/20	2018/05/19
SIGNAL GENERATOR	Agilent	E4421B	US40051744	2017/05/20	2018/05/19
Directional Coupler	Agilent	87300B	3116A03638	2017/05/20	2018/05/19

## 2.5 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AM5I-TML-M100 filing to comply with of the FCC Part 22 and Part 24 Rules.

## 2.6 Modifications

No modifications were implemented to meet testing criteria.

### 3 TEST CONDITIONS AND RESULTS

#### 3.1 Output Power


##### LIMIT

GSM850/WCDMA Band V: 7W

PCS1900/WCDMA Band II: 2W

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

##### TEST CONFIGURATION



##### TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

##### **Conducted Power Measurement:**

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- EUT Communicate with CMU200 then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

##### **Radiated Power Measurement:**

- The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter

- c) The output of the test antenna shall be connected to the measuring receiver.
- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- l) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.

**TEST RESULTS****Conducted Measurement:**

EUT Mode	Channel	Frequency (MHz)	Avg.Burst Power (dBm)	Peak-to-Average Ratio (dB)	Limit (dBm)	Result
GSM850 (GMSK,1Slot)	128	824.20	32.25	/	38.45	Pass
	190	836.60	32.62	/		
	251	848.80	32.34	/		
EGPRS850 (8PSK,1Slot)	128	824.20	27.25	/	38.45	Pass
	190	836.60	27.44	/		
	251	848.80	27.36	/		
GSM1900 (GMSK,1Slot)	512	1850.20	29.87	0.42	33.01	Pass
	661	1880.00	29.85	0.23		
	810	1909.80	29.74	0.52		
EGPRS1900 (8PSK,1Slot)	512	1850.20	24.22	3.13	33.01	Pass
	661	1880.00	24.36	3.15		
	810	1909.80	24.21	3.42		
WCDMA Band II (QPSK)	9262	1852.40	22.25	3.23	33.01	Pass
	9400	1880.00	22.36	3.55		
	9538	1907.60	22.28	3.41		
WCDMA Band V (QPSK)	4132	826.40	22.20	/	38.45	Pass
	4183	836.60	22.23	/		
	4233	846.60	22.19	/		

Note: 1. Peak-to-Average Ratio= maximum PK burst power-maximum Avg. burst power.



**Radiated Measurement:**

Note: 1. The field strength of radiation emission was measured in the following position: EUT stand-up position (Zaxis), lie-down position (X, Y axis). The data show in this report only with the worst case setup. After exploratory measurement the worst case of Z axis was reported.

Note: 2 We test the H direction and V direction and V direction is worse.

**GSM850**

Channel	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	P <sub>Ag</sub> (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
128	-10.12	2.42	8.45	2.15	36.82	30.58	38.45	7.87	V
190	-9.03	2.46	8.45	2.15	36.82	31.63	38.45	6.82	V
251	-9.73	2.53	8.36	2.15	36.82	30.77	38.45	7.68	V

**EGPRS850**

Channel	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	P <sub>Ag</sub> (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
128	-15.47	2.42	8.45	2.15	36.82	25.23	38.45	13.22	V
190	-14.68	2.46	8.45	2.15	36.82	25.98	38.45	12.47	V
251	-15.09	2.53	8.36	2.15	36.82	25.41	38.45	13.04	V

**GSM1900**

Channel	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	P <sub>Ag</sub> (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
512	-11.65	3.41	10.24	33.6	28.78	33.01	4.23	V
661	-11.79	3.49	10.24	33.6	28.56	33.01	4.45	V
810	-12.16	3.55	10.23	33.6	28.12	33.01	4.89	V

**EGPRS1900**

Channel	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	P <sub>Ag</sub> (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
512	-17.28	3.41	10.24	33.6	23.15	33.01	9.86	V
661	-17.12	3.49	10.24	33.6	23.23	33.01	9.78	V
810	-16.74	3.55	10.23	33.6	23.54	33.01	9.47	V

**WCDMA BAND II**

Channel	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	P <sub>Ag</sub> (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
9262	-18.55	3.42	10.24	33.6	21.87	33.01	11.14	V
9400	-19.12	3.49	10.24	33.6	21.23	33.01	11.78	V
9538	-18.75	3.54	10.23	33.6	21.54	33.01	11.47	V

**WCDMA BAND V**

Channel	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	P <sub>Ag</sub> (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
4132	-19.27	2.43	8.45	2.15	36.82	21.42	38.45	17.03	V
4183	-19.03	2.46	8.45	2.15	36.82	21.63	38.45	16.82	V
4233	-19.06	2.52	8.36	2.15	36.82	21.45	38.45	17.00	V

Remark:

1.  $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + P_{Ag}(dB) + G_a(dBi)$
2.  $ERP = EIRP - 2.15dBi$  as  $EIRP$  by subtracting the gain of the dipole.




## 3.2 Occupied Bandwidth

### LIMIT

N/A

### TEST CONFIGURATION




### TEST PROCEDURE


1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer
2. RBW was set to about 1% of emission BW, VBW $\geq$ 3 times RBW.
3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.


### TEST RESULTS

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
GPRS850 (GMSK,1Slot)	128	824.20	244.0710	316.821
	190	836.60	249.0342	313.584
	251	848.80	243.4334	311.480
EGPRS850 (8PSK,1Slot)	128	824.20	245.6784	312.489
	190	836.60	246.4616	311.814
	251	848.80	244.3043	307.447
GPRS1900 (GMSK,1Slot)	512	1850.20	244.6666	311.366
	661	1880.00	245.4150	317.659
	810	1909.80	246.0917	314.888
EGPRS1900 (8PSK,1Slot)	512	1850.20	244.4712	307.782
	661	1880.00	244.3720	306.991
	810	1909.80	240.7238	308.122
WCDMA Band II (QPSK)	9262	1852.4	4213.800	4861.000
	9400	1880.0	4179.900	4826.000
	9538	1907.6	4196.700	4855.000
WCDMA Band V (QPSK)	4132	826.4	4204.600	4856.000
	4183	836.6	4166.000	4827.000
	4233	846.6	4209.000	4848.000

## Test plots as follow:








### 3.3 Band Edge compliance

#### LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.


#### TEST CONFIGURATION





#### TEST PROCEDURE



In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.


#### TEST RESULTS












### 3.4 Spurious Emission

#### LIMIT


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.

#### TEST CONFIGURATION

Conducted Spurious Measurement:



Radiated Spurious Measurement:



#### TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

##### **Conducted Spurious Measurement:**


- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- EUT Communicate with CMU200 then selects a channel for testing.

- d) Add a correction factor to the display of spectrum, and then test.
- e) The resolution bandwidth of the spectrum analyzer was set at 1MHz for Part 22 and 1MHz for Part 24, sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.


**Radiated Spurious Measurement:**


- a) The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b) The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c) The output of the test antenna shall be connected to the measuring receiver.
- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- l) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q) The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.







## EGPRS850





**GSM1900**




**EGPRS1900**






**WCDMA Band II**



## WCDMA Band V



**Radiated Measurement:****GSM850**

Channel	Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Distance	G <sub>a</sub> Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
128	1648.40	-31.83	3.00	3.00	9.58	-25.25	-13.00	12.25	H
	2472.60	-35.38	3.47	3.00	10.72	-28.13	-13.00	15.13	H
	1648.40	-30.20	3.00	3.00	9.68	-23.52	-13.00	10.52	V
	2472.60	-32.71	3.47	3.00	10.72	-25.46	-13.00	12.46	V
190	1673.20	-30.79	3.14	3.00	9.61	-24.32	-13.00	11.32	H
	2509.80	-36.63	3.59	3.00	10.77	-29.45	-13.00	16.45	H
	1673.20	-30.95	3.14	3.00	9.61	-24.48	-13.00	11.48	V
	2509.80	-33.44	3.59	3.00	10.77	-26.26	-13.00	13.26	V
251	1697.60	-32.13	3.26	3.00	9.77	-25.62	-13.00	12.62	H
	2546.40	-34.61	3.69	3.00	10.89	-27.41	-13.00	14.41	H
	1697.60	-30.74	3.26	3.00	9.77	-24.23	-13.00	11.23	V
	2546.40	-32.85	3.69	3.00	10.89	-25.65	-13.00	12.65	V

**EGPRS850**

Channel	Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Distance	G <sub>a</sub> Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
128	1648.40	-35.32	3.00	3.00	-28.74	-28.65	-13.00	15.74	H
	2472.60	-38.89	3.47	3.00	-31.64	-31.26	-13.00	18.64	H
	1648.40	-33.91	3.00	3.00	-27.23	-27.54	-13.00	14.23	V
	2472.60	-37.71	3.47	3.00	-30.46	-30.21	-13.00	17.46	V
190	1673.20	-36.05	3.14	3.00	-29.58	-29.33	-13.00	16.58	H
	2509.80	-39.84	3.59	3.00	-32.66	-32.41	-13.00	19.66	H
	1673.20	-32.61	3.14	3.00	-26.14	-26.58	-13.00	13.14	V
	2509.80	-36.41	3.59	3.00	-29.23	-29.28	-13.00	16.23	V
251	1697.60	-35.03	3.26	3.00	-28.52	-28.35	-13.00	15.52	H
	2546.40	-37.52	3.69	3.00	-30.32	-30.25	-13.00	17.32	H
	1697.60	-32.92	3.26	3.00	-26.41	-26.33	-13.00	13.41	V
	2546.40	-34.77	3.69	3.00	-27.57	-27.58	-13.00	14.57	V

**GSM1900**

Channel	Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Distance	G <sub>a</sub> Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
512	3700.40	-34.32	4.25	3.00	12.34	-26.23	-13.00	13.23	H
	5550.60	-35.76	4.97	3.00	13.52	-27.21	-13.00	14.21	H
	3700.40	-32.61	4.25	3.00	12.34	-24.52	-13.00	11.52	V
	5550.60	-33.91	4.97	3.00	13.52	-25.36	-13.00	12.36	V
661	3760.00	-34.50	4.38	3.00	12.34	-26.54	-13.00	13.54	H
	5640.00	-36.02	5.01	3.00	13.58	-27.45	-13.00	14.45	H
	3760.00	-32.08	4.38	3.00	12.34	-24.12	-13.00	11.12	V
	5640.00	-33.80	5.01	3.00	13.58	-25.23	-13.00	12.23	V
810	3819.60	-34.25	4.49	3.00	12.45	-26.29	-13.00	13.29	H
	5729.40	-35.82	5.26	3.00	13.66	-27.42	-13.00	14.42	H
	3819.60	-32.58	4.49	3.00	12.45	-24.62	-13.00	11.62	V
	5729.40	-33.88	5.26	3.00	13.66	-25.48	-13.00	12.48	V

**EGPRS1900**

Channel	Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Distance	G <sub>a</sub> Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
512	3700.40	-38.83	4.25	3.00	12.34	-30.74	-13.00	17.74	H
	5550.60	-45.07	4.97	3.00	13.52	-36.52	-13.00	23.52	H
	3700.40	-37.72	4.25	3.00	12.34	-29.63	-13.00	16.63	V
	5550.60	-41.88	4.97	3.00	13.52	-33.33	-13.00	20.33	V
661	3760.00	-38.41	4.38	3.00	12.34	-30.45	-13.00	17.45	H
	5640.00	-44.98	5.01	3.00	13.58	-36.41	-13.00	23.41	H
	3760.00	-36.21	4.38	3.00	12.34	-28.25	-13.00	15.25	V
	5640.00	-43.35	5.01	3.00	13.58	-34.78	-13.00	21.78	V
810	3819.60	-39.22	4.49	3.00	12.45	-31.26	-13.00	18.26	H
	5729.40	-44.11	5.26	3.00	13.66	-35.71	-13.00	22.71	H
	3819.60	-36.32	4.49	3.00	12.45	-28.36	-13.00	15.36	V
	5729.40	-39.92	5.26	3.00	13.66	-31.52	-13.00	18.52	V

**WCDMA Band II**

Channel	Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Distance	G <sub>a</sub> Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
9262	3704.80	-40.81	4.27	3.00	12.34	-32.74	-13.00	19.74	H
	5557.20	-43.06	4.99	3.00	13.52	-34.53	-13.00	21.53	H
	3704.80	-43.73	4.27	3.00	12.34	-35.66	-13.00	22.66	V
	5557.20	-41.95	4.99	3.00	13.52	-33.42	-13.00	20.42	V
9400	3760.00	-40.81	4.38	3.00	12.34	-32.85	-13.00	19.85	H
	5640.00	-42.93	5.01	3.00	13.58	-34.36	-13.00	21.36	H
	3760.00	-41.54	4.38	3.00	12.34	-33.58	-13.00	20.58	V
	5640.00	-42.83	5.01	3.00	13.58	-34.26	-13.00	21.26	V
9538	3815.20	-42.34	4.47	3.00	12.45	-34.36	-13.00	21.36	H
	5722.80	-44.32	5.23	3.00	13.66	-35.89	-13.00	22.89	H
	3815.20	-40.73	4.47	3.00	12.45	-32.75	-13.00	19.75	V
	5722.80	-41.76	5.23	3.00	13.66	-33.33	-13.00	20.33	V

**WCDMA Band V**

Channel	Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Distance	G <sub>a</sub> Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
9262	1652.80	-39.10	3.02	3.00	9.58	-32.54	-13.00	19.54	H
	2479.20	-43.57	3.51	3.00	10.72	-36.36	-13.00	23.36	H
	1652.80	-36.91	3.02	3.00	9.68	-30.25	-13.00	17.25	V
	2479.20	-40.75	3.51	3.00	10.72	-33.54	-13.00	20.54	V
9400	1673.20	-39.83	3.14	3.00	9.61	-33.36	-13.00	20.36	H
	2509.80	-42.66	3.59	3.00	10.77	-35.48	-13.00	22.48	H
	1673.20	-37.72	3.14	3.00	9.61	-31.25	-13.00	18.25	V
	2509.80	-39.63	3.59	3.00	10.77	-32.45	-13.00	19.45	V
9538	1693.20	-40.18	3.24	3.00	9.77	-33.65	-13.00	20.65	H
	2539.80	-42.79	3.65	3.00	10.89	-35.55	-13.00	22.55	H
	1693.20	-37.77	3.24	3.00	9.77	-31.24	-13.00	18.24	V
	2539.80	-39.45	3.65	3.00	10.89	-32.21	-13.00	19.21	V

Remark:

1.  $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
2. We were not recorded other points as values lower than limits.
3.  $Margin = Limit - EIRP$




### 3.5 Frequency Stability under Temperature & Voltage Variations

#### LIMIT

Cellular Band:  $\pm 2.5$ ppm PCS Band: Within the authorized frequency block

#### TEST CONFIGURATION



#### TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

##### **Frequency Stability under Temperature Variations:**

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

##### **Frequency Stability under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

#### TEST RESULTS

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Voltage ( V )	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	40.32	0.048	2.5	Pass
	-20	45.48	0.054		
	-10	44.77	0.054		
	0	64.02	0.077		
	10	30.53	0.036		
	20	35.23	0.042		
	30	78.93	0.094		
	40	45.01	0.054		
	50	55.24	0.066		
4.26	25	46.46	0.056	2.5	Pass
End point 3.15	25	57.40	0.069		


Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Voltage ( V )	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	56.27	0.030	Within the authorized frequency block	Pass
	-20	96.63	0.051		
	-10	44.91	0.024		
	0	90.10	0.048		
	10	74.15	0.039		
	20	30.03	0.016		
	30	72.26	0.038		
	40	93.11	0.050		
	50	85.28	0.045		
4.26	25	78.90	0.042	Within the authorized frequency block	Pass
End point 3.15	25	37.00	0.020		

Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880MHz					
Voltage ( V )	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	38.52	0.020	Within the authorized frequency block	Pass
	-20	55.10	0.029		
	-10	50.40	0.027		
	0	83.67	0.045		
	10	81.95	0.044		
	20	37.05	0.020		
	30	68.86	0.037		
	40	45.66	0.024		
	50	62.98	0.034		
4.26	25	91.24	0.049	Within the authorized frequency block	Pass
End point 3.15	25	71.25	0.038		

Reference Frequency: WCDMA Band V Middle channel=4182 channel=836.6MHz					
Voltage ( V )	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	96.99	0.116	2.5	Pass
	-20	40.17	0.048		
	-10	71.97	0.086		
	0	94.41	0.113		
	10	94.74	0.113		
	20	88.02	0.105		
	30	73.99	0.088		
	40	45.11	0.054		
	50	53.53	0.064		
4.26	25	68.97	0.082	2.5	Pass
End point 3.15	25	87.04	0.104		






## 4 Test Setup Photos of the EUT







## 5 Photos of the EUT

### External Photos of EUT





\*\*\*\*\* End of Report \*\*\*\*\*

