

APPLICATION CERTIFICATION
On Behalf of
Lovehoney Ltd.

Tracey Cox Rechargeable Love Egg Black

Model No.: LH-79243

FCC ID: 2AM7I-79243

Prepared for : Lovehoney Ltd.
Address : 100 Locksbrook Road, Bath, BA13EN, UK

Prepared by : Shenzhen Accurate Technology Co., Ltd.
Address : 1/F., Building A, Changyuan New Material Port, Science
& Industry Park, Nanshan District, Shenzhen, Guangdong,
P.R. China.

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20191415
Date of Test : Oct. 21, 2019-Nov. 01, 2019
Date of Report : Nov. 02, 2019

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Accessory and Auxiliary Equipment	4
1.3. Description of Test Facility	5
1.4. Measurement Uncertainty	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
2.1. For Radiated Emission Measurement	6
3. SUMMARY OF TEST RESULTS.....	7
4. THE FIELD STRENGTH OF RADIATION EMISSION	8
4.1. Block Diagram of Test Setup.....	8
4.2. The Field Strength of Radiation Emission Measurement Limits.....	10
4.3. Configuration of EUT on Measurement	10
4.4. Operating Condition of EUT	10
4.5. Test Procedure	11
4.6. DATA SAMPLE	11
4.7. The Field Strength of Radiation Emission Measurement Results	12
5. -20DB BANDWIDTH	14
5.1. Block Diagram of Test Setup.....	14
5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section 15.231(c).....	14
5.3. EUT Configuration on Measurement	14
5.4. Operating Condition of EUT	14
5.5. Test Procedure	15
5.6. Measurement Result	15
6. RELEASE TIME MEASUREMENT.....	16
6.1. Block Diagram of Test Setup.....	16
6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)	16
6.3. EUT Configuration on Measurement	16
6.4. Operating Condition of EUT	17
6.5. Test Procedure	17
6.6. Measurement Result	17
7. AVERAGE FACTOR MEASUREMENT	18
7.1. Block Diagram of Test Setup.....	18
7.2. Average factor Measurement according to ANSI C63.10-2013	18
7.3. EUT Configuration on Measurement	18
7.4. Operating Condition of EUT	19
7.5. Test Procedure	19
7.6. Measurement Result	19
8. ANTENNA REQUIREMENT.....	20
8.1. The Requirement	20
8.2. Antenna Construction	20

Test Report Certification

Applicant : Lovehoney Ltd.
Address : 100 Locksbrook Road, Bath, BA13EN, UK
Manufacturer : TOPARC Technology (Shenzhen) Co., Ltd.
Address : 1/2F, 12 Building, Lianchuang Park, Bulan Road, Buji Town,
Longgang District, Shenzhen City, Guangdong Province, P.R. China
518114
Product : Tracey Cox Rechargeable Love Egg Black
Model No. : LH-79243
Trade name : N/A

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.231a ANSI C63.10-2013

The device described above is tested by SHENZHEN ACCURATE TECHNOLOGY CO., LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.231a. The measurement results are contained in this test report and SHENZHEN ACCURATE TECHNOLOGY CO., LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of SHENZHEN ACCURATE TECHNOLOGY CO., LTD.

Date of Test :

Oct. 21, 2019-Nov. 01, 2019

Date of Report:

Nov. 02, 2019

Prepared by :

Tim Zhang

(Tim Zhang, Engineer)

Approved & Authorized Signer :


(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Tracey Cox Rechargeable Love Egg Black

Model Number : LH-79243

Power Supply : DC 3V (powered by battery)

Modulation: : ASK

Operation Frequency : 433.92MHz

Antenna type : PCB antenna

Antenna gain : 1dBi

Applicant : Lovehoney Ltd.
Address : 100 Locksbrook Road, Bath, BA13EN, UK

Manufacturer : TOPARC Technology(Shenzhen) Co., Ltd.
Address : 1/2F, 12 Building, Lianchuang Park, Bulan Road,
Buji Town, Longgang District, Shenzhen City,
Guangdong Province, P.R. China 518114

Date of sample : Sep. 30, 2019
received

Date of Test : Oct. 21, 2019-Nov. 01, 2019

1.2. Accessory and Auxiliary Equipment

N/A

1.3. Description of Test Facility

EMC Lab	:	Recognition of accreditation by Federal Communications Commission (FCC) The Designation Number is CN1189 The Registration Number is 708358 Listed by Innovation, Science and Economic Development Canada (ISED) The Registration Number is 5077A-2 Accredited by China National Accreditation Service for Conformity Assessment (CNAS) The Registration Number is CNAS L3193 Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01
Name of Firm	:	Shenzhen Accurate Technology Co., Ltd.
Site Location	:	1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty (Mains ports, 9kHz-30MHz)	=	2.72dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	2.66dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.28dB, k=2
Radiated emission expanded uncertainty (1G-18GHz)	=	4.98dB, k=2
Radiated emission expanded uncertainty (18G-26.5GHz)	=	5.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

2.1.For Radiated Emission Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan.05, 2019	1 Year
2.	Spectrum Analyzer	Rohde&Schwarz	FSV40	101495	Jan.05, 2019	1 Year
3.	Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan.05, 2019	1 Year
4.	Test Receiver	Rohde& Schwarz	ESPI	100396/003	Jan.05, 2019	1 Year
5.	Test Receiver	Rohde& Schwarz	ESPI	101526/003	Jan.05, 2019	1 Year
6.	Test Receiver	Rohde& Schwarz	ESR	101817	Jan.05, 2019	1 Year
7.	Bilog Antenna	Schwarzbeck	VULB9163	9163-194	Jan.05, 2019	1 Year
8.	Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan.05, 2019	1 Year
9.	Log.-Per.Antenna	Schwarzbeck	VUSLP 9111B	9111B-074	Jan.05, 2019	1 Year
10.	Biconical Broad Band Antenna	Schwarzbeck	VHBB 9124+BBA 9106	9124-617	Jan.05, 2019	1 Year
11.	Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan.05, 2019	1 Year
12.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan.05, 2019	1 Year
13.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan.05, 2019	1 Year
14.	Vertical Active Monopole Antenna	Schwarzbeck	VAMP 9243	9243-370	Jan.05, 2019	1 Year
15.	RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	Jan.05, 2019	1 Year
16.	Pre-Amplifier	Agilent	8447D	294A10619	Jan.05, 2019	1 Year
17.	Pre-Amplifier	Rohde&Schwarz	CBLU11835 40-01	3791	Jan.05, 2019	1 Year
18.	50 Coaxial Switch	Anritsu Corp	MP59B	6200237248	Jan.05, 2019	1 Year
19.	50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	Jan.05, 2019	1 Year
20.	RF Coaxial Cable	Schwarzbeck	N-5m	No.1	Jan.05, 2019	1 Year
21.	RF Coaxial Cable	Schwarzbeck	N-1m	No.6	Jan.05, 2019	1 Year
22.	RF Coaxial Cable	Schwarzbeck	N-1m	No.7	Jan.05, 2019	1 Year
23.	RF Coaxial Cable	SUHNER	N-3m	No.8	Jan.05, 2019	1 Year
24.	RF Coaxial Cable	RESENBERGER	N-3.5m	No.9	Jan.05, 2019	1 Year
25.	RF Coaxial Cable	SUHNER	N-6m	No.10	Jan.05, 2019	1 Year
26.	RF Coaxial Cable	RESENBERGER	N-12m	No.11	Jan.05, 2019	1 Year
27.	RF Coaxial Cable	RESENBERGER	N-0.5m	No.12	Jan.05, 2019	1 Year
28.	RF Coaxial Cable	SUHNER	N-2m	No.13	Jan.05, 2019	1 Year
29.	RF Coaxial Cable	SUHNER	N-0.5m	No.15	Jan.05, 2019	1 Year
30.	RF Coaxial Cable	SUHNER	N-2m	No.16	Jan.05, 2019	1 Year
31.	RF Coaxial Cable	RESENBERGER	N-6m	No.17	Jan.05, 2019	1 Year
Radiated Emission Measurement Software: EZ EMC V1.1.4.2						

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.231(b)	Radiated Emission	Compliant
Section 15.231(c)	20dB Bandwidth	Compliant
Section 15.231(a)(1)	Release Time Measurement	Compliant
Section 15.203	Antenna Requirement	Compliant

The product is a manually operated transmitter.

Section 15.231 (a) (2), (3), (4) and (5) are not applicable.

Note: The power supply mode of the EUT is DC 3V, According to the FCC standard requirements, conducted emission is not applicable

All normal using modes of the normal function were tested but only the worst test data of the worst mode is recorded by this report.

4. THE FIELD STRENGTH OF RADIATION EMISSION

4.1. Block Diagram of Test Setup


4.1.1. Block diagram of connection between the EUT and simulators




(EUT: Tracey Cox Rechargeable Love Egg Black)

4.1.2. Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1GHz



(C) Radiated Emission Test Set-Up, Frequency Above 1GHz



4.2.The Field Strength of Radiation Emission Measurement Limits

4.2.1.Radiation Emission Measurement Limits According to FCC Part 15 Section 15.231(b)

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Average] [μV/m]	Field Strength of Spurious Emission [Average] [μV/m]
40.66-40.70	2250	225
70-130	1250	125
130-174	1250-3750	125-375
174-260	3750	375
260-470	3750-12500	375-1250
Above 470	12500	1250

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, uV/m at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

4.2.2.Restricted Band Radiation Emission Measurement Limits According to FCC part 15 Section 15.205 and Section15.209.

4.3.Configuration of EUT on Measurement

The following equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. Tracey Cox Rechargeable Love Egg Black (EUT)

Model Number : LH-79243
Serial Number : 1901192
Manufacturer : TOPARC Technology(Shenzhen) Co., Ltd.

4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

4.4.3. Let the EUT work in TX mode measure it.

4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground(Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 120 kHz in 30-1000 MHz, and 1 MHz in 1000-5000 MHz.

The frequency range from 9kHz to 5000MHz is checked.

4.6. DATA SAMPLE

Frequency (MHz)	Reading (dB μ v)	Factor (dB/m)	Result (dB μ v/m)	Limit (dB μ v/m)	Margin (dB)	Remark
X.XX	49.83	-22.03	27.80	43.50	-15.70	QP

Frequency(MHz) = Emission frequency in MHz

Reading(dB μ v) = Uncorrected Analyzer/Receiver reading

Factor (dB/m)= Antenna factor + Cable Loss – Amplifier gain

Result(dB μ v/m) = Reading + Factor

Limit (dB μ v/m)= Limit stated in standard

Margin (dB) = Result(dB μ v/m) - Limit (dB μ v/m)

Calculation Formula:

Margin(dB) = Result (dB μ v/m)–Limit(dB μ v/m)

Result(dB μ v/m)= Reading(dB μ v)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

4.7.The Field Strength of Radiation Emission Measurement Results

PASS.

Note: The radiation emissions from 9KHz-30MHz are not reported, because the test values lower than the limits of 20dB.

EUT:	Tracey Cox Rechargeable Love Egg Black		
Model No.:	LH-79243	Power Supply:	DC 3V
Test Mode:	433.92MHz TX	Test Engineer:	Frank

Frequency (MHz)	Reading (dBμV/m)	Factor Corr.	Average Factor	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	PEAK	(dB)	(dB)	AV	PEAK	AV	PEAK	AV	PEAK	
433.92	88.84	-6.95	-8.23	73.66	81.89	80.83	100.83	-7.17	-18.94	Horizontal
325.60	52.83	-9.51	/	43.32(QP)		46.50		-3.18		
867.84	55.58	0.03	-8.23	47.38	55.61	60.83	80.83	-13.45	-25.22	
1735.68	53.42	-9.28	-8.23	35.91	44.14	60.83	80.83	-24.92	-36.69	
2603.52	49.55	-5.46	-8.23	35.86	44.09	60.83	80.83	-24.97	-36.64	
433.92	84.78	-6.95	-8.23	69.60	77.83	80.83	100.83	-11.23	-23.00	Vertical
35.87	41.82	-10.62	/	31.20(QP)		40.00		-8.80		
867.84	50.88	0.03	-8.23	42.68	50.91	60.83	80.83	-18.15	-29.92	
1735.68	49.51	-9.28	-8.23	32.00	40.23	60.83	80.83	-28.83	-40.60	

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain
3. FCC Limit for Average Measurement = $41.6667(433.92)-7083.3333 = 10996.681164 \mu\text{V/m} = 80.83 \mu\text{V/m}$
4. The spectral diagrams in appendix I display the measurement of peak values.
5. Average value= PK value + Average Factor (duty factor)
6. If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.
7. The EUT is tested radiation emission in three axes(X,Y,Z). The worst emissions are reported in three axes.

8. Pulse Desensitization Correction Factor

Pulse Width (PW) = 1.26ms


$2/PW = 2/1.26\text{ms} = 1.587\text{kHz}$

RBW (100 kHz) > 2/PW (1.587kHz)

Therefore PDCF is not needed

5. -20DB BANDWIDTH

5.1. Block Diagram of Test Setup



(EUT: Tracey Cox Rechargeable Love Egg Black)

5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section

15.231(c)

The bandwidth of emission shall be no wider than 0.25% of the center frequency. Therefore, the bandwidth of the emission limit is $433.92 \text{ MHz} \times 0.25\% = 1084.8 \text{ kHz}$. Bandwidth is determined at the two points 20 dB down from the top of modulated carrier.

5.3. EUT Configuration on Measurement

The following equipment are installed on the bandwidth of emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1. Tracey Cox Rechargeable Love Egg Black (EUT)

Model Number : LH-79243
Serial Number : 1901192
Manufacturer : TOPARC Technology(Shenzhen) Co., Ltd.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX mode measure it.

5.5. Test Procedure

5.5.1. Set SPA Center Frequency = Fundamental frequency, RBW = 10 kHz, VBW = 30 kHz, Span = 500 kHz.


5.5.2. Set SPA Max hold, Mark peak, -20 dB.

5.6. Measurement Result

The EUT does meet the FCC requirement.

-20 dB bandwidth = 43 kHz < 1084.8 kHz.


The test chart of -20 dB bandwidth:



Date: 1.NOV.2019 15:32:42

6. RELEASE TIME MEASUREMENT

6.1. Block Diagram of Test Setup



(EUT: Tracey Cox Rechargeable Love Egg Black)

6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)

Section 15.231(a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

6.3. EUT Configuration on Measurement

The following equipment are installed on Release Time Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.3.1. Tracey Cox Rechargeable Love Egg Black (EUT)

Model Number	:	LH-79243
Serial Number	:	1901192
Manufacturer	:	TOPARC Technology(Shenzhen) Co., Ltd.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX mode measure it.

6.5. Test Procedure

6.5.1. Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 300 kHz, Span = 0 Hz. Sweep time = 8 s.

6.5.2. Set EUT as normal operation and press Transmitter button.

6.5.3. Set SPA View. Delta Mark time.

6.6. Measurement Result


The release time less than 5 seconds.

Release Time = 0.72s

The spectral diagrams in appendix I.

7. AVERAGE FACTOR MEASUREMENT

7.1. Block Diagram of Test Setup



(EUT: Wireless remote control vibrator)

7.2. Average factor Measurement according to ANSI C63.10-2013

ANSI C63.10-2013 Section 7.5 Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 s (100 ms). In cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined during a 0.1 s interval.⁶⁴ The following procedure is an example of how the average value may be determined. The average field strength may be found by measuring the peak pulse amplitude (in log equivalent units) and determining the duty cycle correction factor (in dB) associated with the pulse modulation as shown in Equation (10):

Average factor in dB = 20 log (duty cycle)

7.3. EUT Configuration on Measurement

The following equipment are installed on average factor Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.3.1. Tracey Cox Rechargeable Love Egg Black

Model Number	: LH-79243
Serial Number	: 1901192
Manufacturer	: TOPARC Technology(Shenzhen) Co., Ltd.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX mode measure it.

7.5. Test Procedure

7.5.1. The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation.

7.5.2. Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 300 kHz, Span = 0 Hz.

7.5.3. Set EUT as normal operation.

7.5.4. Set SPA View. Delta Mark time.

7.6. Measurement Result

The duty cycle is simply the on time divided by the period:

The duration of one cycle = 100.0ms

Effective period of the cycle = $(1.26 \times 23) + (4.90 \times 2)$ ms = 38.78 ms

DC = $38.78 \text{ ms} / 100.0 \text{ ms} = 0.3878$

Therefore, the average factor is found by $20 \log 0.3878 = -8.23 \text{ dB}$

The spectral diagrams in appendix I.


8. ANTENNA REQUIREMENT

8.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2.Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Antenna gain of EUT is 1dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna

APPENDIX I

(Test Curves)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: jpzdb #21
Standard: FCC 15.231a 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Tracey Cox Rechargeable Love Egg Black
Mode: TX 433.92MHz
Model: LH-79243
Manufacturer: TOPARC Technology (Shenzhen) Co., Ltd.

Polarization: Horizontal
Power Source: DC 3V
Date: 2019/10/21
Time: 14:04:14
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20191415



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	108.2667	43.51	-14.91	28.60	43.50	-14.90	QP	100	103	
2	216.7828	45.31	-12.81	32.50	46.50	-14.00	QP	100	156	
3	325.5957	52.83	-9.51	43.32	46.50	-3.18	QP	100	196	
4	379.9141	32.34	-8.34	24.00	46.50	-22.50	QP	100	216	
5	433.9249	88.84	-6.95	81.89	100.83	-18.94	peak	100	263	
6	867.8401	55.58	0.03	55.61	80.83	-25.22	peak	100	302	

Note: the peak limit for fundamental frequency is 100.83 dBuV/m.

Fundamental frequency



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: jpzdb #22
Standard: FCC 15.231a 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Tracey Cox Rechargeable Love Egg Black
Mode: TX 433.92MHz
Model: LH-79243
Manufacturer: TOPARC Technology (Shenzhen) Co., Ltd.

Polarization: Vertical
Power Source: DC 3V
Date: 2019/10/21
Time: 14:05:27
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20191417



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg)	Remark
1	35.8746	41.82	-10.62	31.20	40.00	-8.80	QP	100	106	
2	59.6492	40.57	-14.87	25.70	40.00	-14.30	QP	100	165	
3	97.4560	45.38	-14.98	30.40	43.50	-13.10	QP	100	195	
4	325.5957	42.71	-9.51	33.20	46.50	-13.30	QP	100	215	
5	433.9249	84.78	-6.95	77.83	100.83	-23.00	peak	100	263	
6	867.8401	50.88	0.03	50.91	80.83	-29.92	peak	100	315	

Note: the peak limit for fundamental frequency is 100.83 dBuV/m.

Fundamental frequency



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: zdb_tmp #8

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Tracey Cox Rechargeable Love Egg Black

Mode: TX 433.92MHz

Model: LH-79243

Manufacturer: TOPARC Technology (Shenzhen) Co., Ltd.

Polarization: Horizontal

Power Source: DC 3V

Date: 2019/10/21

Time: 17:11:24

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20191417



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1735.681	53.42	-9.28	44.14	80.83	-36.69	peak	150	23	
2	2603.523	49.55	-5.46	44.09	80.83	-36.64	peak	150	137	



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396


Job No.: zdb_tmp #7
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Tracey Cox Rechargeable Love Egg Black
Mode: TX 433.92MHz
Model: LH-79243
Manufacturer: TOPARC Technology (Shenzhen) Co., Ltd.

Polarization: Vertical
Power Source: DC 3V
Date: 2019/10/21
Time: 17:10:27
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20191417




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1735.681	49.51	-9.28	40.23	80.83	-40.60	peak	150	311	




Date: 2.NOV.2019 14:23:22

Release Time = 0.72s

The graph shows the pattern of coding during the signal transmission.
The duration of one cycle = 100.0ms.




Date: 2.NOV.2019 14:23:59



Date: 2.NOV.2019 14:11:25

The graph shows the duration of 'on' signal. From marker 1 to delta 1, duration is 1.26ms.



Date: 2.NOV.2019 14:25:22

The graph shows the duration of 'on' signal. From marker 1 to delta 1, duration is 4.90ms.