

DGD International Limited

TEST REPORT

SCOPE OF WORK

EMC TESTING-2046010

REPORT NUMBER

190905013GZU-002

ISSUE DATE

30-December-2019

[REVISED DATE]

[-----]

PAGES

9

DOCUMENT CONTROL NUMBER

© 2017 INTERTEK



TEST REPORT

Telephone: 86-20-8213 9688
Facsimile: 86-20-3205 7538
www.intertek.com

Applicant Name & : DGD International Limited.
Address : Unit B-D, 5/F, Kimley Commercial Building, 142-146 Queen's Road,
Central, HONG KONG, CHINA
Manufacturing Site : Same as applicant
Intertek Report No: 190905013GZU-002
FCC ID: 2AMHH-2046010

Test standards

47 CFR PART 1, Subpart I, Section 1.1310
KDB 680106 D01 RF Exposure Wireless Charging Apps v03

Sample Description

Product : HY-VS-VSOP-XO KIT DE CHARGE PAD LUMINOUS
Model No. : 2046010
Electrical Rating : Input: 4.96Vdc, 0.3A (Powered by adaptor) for single charge pad
Total Input: 8.94W for 6 Pic charge pad
Wireless output: 3.7Vdc, 0.14A, 0.52W max.
Adaptor: Model: AK 18WG-0500200DP
Input: 100-240V, 50/60Hz 0.5A
Power cord: 1.8m x 2 wires unscreened DC cable
Serial No. : Not Labeled
Date Received : 05 September 2019
Date Test : 05 September 2019-05 December 2019
Conducted

Prepared and Checked By

Approved By:



Daniel He

Project Engineer

Intertek Guangzhou



Helen Ma

Team Leader

Intertek Guangzhou

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

CONTENT

TEST REPORT	1
CONTENT	3
1.0 TEST RESULT SUMMARY	4
2.0 GENERAL DESCRIPTION	5
2.1 PRODUCT DESCRIPTION	5
2.2 TEST FACILITY	5
2.3 EUT EXERCISING SOFTWARE	5
2.4 SPECIAL ACCESSORIES	5
2.5 EQUIPMENT MODIFICATION	5
2.6 SUPPORT EQUIPMENT LIST AND DESCRIPTION	6
3.0 EMF TEST	7
3.1 STANDARD REQUIREMENT	7
3.2 TEST DATA	8
4.0 TEST EQUIPMENT LIST	9

TEST REPORT

1.0 TEST RESULT SUMMARY

Classification of EUT: Class B

Test Item	Standard	Result
EMF	47 CFR PART 1, Subpart I, Section 1.1310	PASS

Remark:

When determining the test results, measurement uncertainty of tests has been considered.

TEST REPORT

2.0 General Description

2.1 Product Description

Operating Frequency	542KHz
Type of Modulation:	MSK
Antenna Type	Inductive loop coil antenna
Antenna gain:	0 dBi
Power Supply:	Input: 5Vdc, 2A (Powered by adaptor) Wireless output: 3.7Vdc, 0.14A, 0.52W max.
Power cord:	1.8m x 2 wires unscreened DC cable

2.2 Test Facility

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City,
GETDD Guangzhou, China

A2LA Certificate Number 0078.10

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

2.3 EUT Exercising Software

N/A

2.4 Special Accessories

N/A

2.5 Equipment Modification

Any modifications installed previous to testing by DGD International Limited will be incorporated in each production model sold / leased in the United States.
No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

TEST REPORT

2.6 Support Equipment List and Description

This product was tested with corresponding support equipment as below:

Support Equipment:

Equipment	Model No.	Rating	Supplier
Lighting pads	2045958	--	Client

Remark: the Lighting pads was one of typical client devices, it's selected such that the EUT was fully exercised at maximum power from its transmitter.

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above evaluated respectively

Pre-test mode	Description
Charging Mode	Lighting pads is charging at 1% battery power, 50% and 99% battery power respectively, keep transmitting continuously.

TEST REPORT

3.0 EMF TEST

3.1 Standard Requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.1m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

TEST REPORT

3.2 Test Data

Input Voltage: 120V/60Hz

Ambient Condition: 24°C, 50%RH

Test distance: 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils

H-Filed Strength:

Test Position	Probe Measure Result (A/m)			50% Limit (A/m)	Limit (A/m)
	Mobile in 1% battery power	Mobile in 50% battery power	Mobile in 99% battery power		
Side 1	0.0015	0.0014	0.0012	0.815	1.63
Side 2	0.0013	0.0014	0.0013	0.815	1.63
Side 3	0.0014	0.0012	0.0012	0.815	1.63
Side 4	0.0015	0.0013	0.0013	0.815	1.63
Top	0.0016	0.0014	0.0013	0.815	1.63

TEST REPORT

4.0 Test Equipment List

Equip. No.	Equipment	Model	Manufacturer	Cal. date	Due date
EM007-03	Exposure Level Tester	ELT-400	NARDA	2018/12/11	2019/12/11

*****End of the test report*****