

Report Number: F690501/RF-RTL014491

TEST REPORT

Page:

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: 2AMKA-R13A

Equipment Under Test : InforTab

Model Name : R13A

Applicant : RainUs Co., Ltd.

: RainUs Co., Ltd. Manufacturer

Date of Receipt : 2019.09.26

: 2018.09.26 ~2019.10.18 Date of Test(s)

Jungmin Yang

Date of Issue : 2019.11.04

In the configuration tested, the EUT complied with the standards specified above.

2019.11.04 Tested By: Date: **Murphy Kim Technical** Date: 2019.11.04 Manager:

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014491 Page: 5 of

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	4



Report Number: F690501/RF-RTL014491 Page: 3 of 5

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on

request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Telephone : +82 31 688 0901 FAX : +82 31 688 0921

1.2. Details of Applicant

Applicant : RainUs Co., Ltd.

Address : 3rd-Floor, 173-36, Saneop-ro, Gwonseon-gu, Gyeonggi-do, South Korea

Contact Person : Do, Gi-tae Phone No. : +82 31 548 0782

1.3. Details of Manufacturer

Company : Same as applicant Address : Same as applicant

1.4. Description of EUT

Kind of Product	nd of Product InforTab	
Model Name	R13A	
Power Supply	DC 3.0 V	
Frequency Range	2 405 Mb ~ 2 480 Mb (Zigbee)	
Modulation Technique	DSSS	
Number of Channels	16 channels (Zigbee)	
Antenna Type	PCB antenna	
Antenna Gain	-2.37 dBi	

1.5. Test Report Revision

Revision Report Number		Date of Issue	Description	
	0	F690501/RF-RTL014491	2019.11.04	Initial

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014491 Page: 4 of 5

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm)	Average Time	
	(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6	
3.0-30	1842/f	4.89/f	*900/f ²	6	
30-300	61.4	0.163	1.0	6	
300-1 500	-	-	f/300	6	
1 500-100 000	-	-	5	6	
	(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30	
1.34-30	824/f	2.19/f	*180/f ²	30	
30-300	27.5	0.073	0.2	30	
300-1 500	-	-	f/1500	30	
1 500-100 000	-	-	1.0	<u>30</u>	

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014491 Page: 5

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

- Maximum tune up tolerance

Frequency (Mb)		Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm)	Limits (mW/cm²)
	2 402 ~ 2 480	5.5	-2.37	0.000 409	1

Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your
- The antenna gain of this transmitter is less than 6 dBi and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

- End of the Test Report -