

FCC PART 22H, PART 24E  
MEASUREMENT AND TEST REPORT

For

**K2KONNECT LLC**

2323 NW 82ND AVE, DORAL, FL 33122, USA

**FCC ID: 2AMVG5E4**

|   |   |
|---|---|
| <b>Report Type:</b><br>Original Report  | <b>Product Type:</b><br>3G Mobile Phone |
| <b>Report Number:</b> RSZ170804008-00D  |   |
| <b>Report Date:</b> 2017-08-25  |   |
| <b>Reviewed By:</b> RF Engineer   | Rocky Kang<br><i>Rocky Kang</i>         |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F., West Wing, Third Phase of Wanli Industrial<br>Building, Shihua Road, Futian Free Trade Zone,<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |   |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★". This report may contain data were produced under the subcontractor and shall be marked with an asterisk "△".

## **TABLE OF CONTENTS**

|   |           |
|---|-----------|
| <b>GENERAL INFORMATION.....</b>   | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                  | 3         |
| OBJECTIVE .....   | 3         |
| RELATED SUBMITTAL(S)/GRANT(S).....  | 3         |
| TEST METHODOLOGY .....  | 3         |
| MEASUREMENT UNCERTAINTY.....  | 4         |
| TEST FACILITY .....   | 4         |
| <b>SYSTEM TEST CONFIGURATION.....</b>   | <b>5</b>  |
| JUSTIFICATION .....   | 5         |
| EQUIPMENT MODIFICATIONS .....   | 5         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....  | 5         |
| BLOCK DIAGRAM OF TEST SETUP .....   | 5         |
| <b>SUMMARY OF TEST RESULTS .....</b>  | <b>6</b>  |
| <b>TEST EQUIPMENT LIST .....</b>  | <b>7</b>  |
| <b>FCC §1.1307(B) &amp; §2.1093 - RF EXPOSURE INFORMATION.....</b>                        | <b>8</b>  |
| APPLICABLE STANDARD .....   | 8         |
| TEST RESULT .....   | 8         |
| <b>FCC §2.1047 - MODULATION CHARACTERISTIC .....</b>                                      | <b>9</b>  |
| <b>§2.1046; § 22.913 (A); § 24.232 (C) - RF OUTPUT POWER.....</b>                         | <b>10</b> |
| APPLICABLE STANDARDS.....   | 10        |
| TEST PROCEDURE .....  | 10        |
| TEST DATA .....   | 10        |
| <b>FCC §2.1049, §22.917, §22.905 &amp; §24.238 - OCCUPIED BANDWIDTH .....</b>             | <b>16</b> |
| APPLICABLE STANDARDS.....   | 16        |
| TEST PROCEDURE .....  | 16        |
| TEST DATA .....   | 16        |
| <b>§ 2.1051; § 22.917 (A); § 24.238 (A) SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....</b> | <b>24</b> |
| APPLICABLE STANDARDS.....   | 24        |
| TEST PROCEDURE .....  | 24        |
| TEST DATA .....   | 24        |
| <b>FCC § 2.1053; § 22.917 (A); § 24.238 (A) SPURIOUS RADIATED EMISSIONS .....</b>         | <b>30</b> |
| APPLICABLE STANDARDS.....   | 30        |
| TEST PROCEDURE .....  | 30        |
| TEST DATA .....   | 30        |
| <b>FCC § 22.917 (A);§ 24.238 (A) - BAND EDGES.....</b>                                    | <b>33</b> |
| APPLICABLE STANDARDS.....   | 33        |
| TEST PROCEDURE .....  | 33        |
| TEST DATA .....   | 33        |
| <b>FCC § 2.1055; § 22.355; § 24.235; - FREQUENCY STABILITY .....</b>                      | <b>44</b> |
| APPLICABLE STANDARDS.....   | 44        |
| TEST PROCEDURE .....  | 44        |
| TEST DATA .....   | 45        |

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *K2KONNECT LLC*'s product, model number: *5E (FCC ID: 2AMVG5E4)* or the "EUT" in this report was a *3G Mobile Phone*, which was measured approximately: 14.59 cm (L) × 7.48 cm (W) × 0.95 cm (H), rated with input voltage: DC 3.7 V battery or DC 5V from adapter.

Adapter Information:

Model: C5E4

Input: AC 100-240V, 50/60Hz, 0.2A

Output: DC 5.0V, 1.0A

*Notes: This series products model: AM5E4L056, AM5E4L043 and 5E are electrically identical, only named differently. Model 5E was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.*

*\*All measurement and test data in this report was gathered from production sample serial number: 1701857 (Assigned by applicant). The EUT supplied by the applicant was received on 2017-08-04.*

### Objective

This type approval report is prepared on behalf of *K2KONNECT LLC* in accordance with Part 2, Part 22-Subpart H, Part 24-Subpart E of the Federal Communication Commission's rules.

The objective is to determine the compliance of EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, and band edge.

### Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DTS&DSS submissions with FCC ID: 2AMVG5E4.

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-Part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

| Parameter                    |            | uncertainty |
|------------------------------|------------|-------------|
| Occupied Channel Bandwidth   |            | ±5%         |
| RF output power, conducted   |            | ±1.5dB      |
| Unwanted Emission, conducted |            | ±1.5dB      |
| emissions,<br>radiated       | Below 1GHz | ±4.70dB     |
|                              | Above 1GHz | ±4.80dB     |
| Temperature                  |            | ±1 °C       |
| Supply voltages              |            | ±0.4%       |

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP(Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D.  
The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modifications were made to the EUT.

Support Equipment List and Details

| Manufacturer    | Description                          | Model  | Serial Number |
|-----------------|--------------------------------------|--------|---------------|
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 106891        |

Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules                                  | Description of Test                    | Result         |
|--|--|----------------|
| §1.1307 (b)(1), §2.1093                    | RF Exposure Information                | Compliance*    |
| §2.1046; § 22.913 (a);<br>§ 24.232 (c);    | RF Output Power                        | Compliance     |
| § 2.1047                                   | Modulation Characteristics             | Not Applicable |
| § 2.1049; § 22.905;<br>§ 22.917; § 24.238; | Occupied Bandwidth                     | Compliance     |
| § 2.1051; § 22.917 (a);<br>§ 24.238 (a);   | Spurious Emissions at Antenna Terminal | Compliance     |
| § 2.1053; § 22.917 (a);<br>§ 24.238 (a);   | Spurious Radiated Emissions            | Compliance     |
| § 22.917 (a);<br>§ 24.238 (a);             | Band Edge                              | Compliance     |
| § 2.1055; § 22.355;<br>§ 24.235;           | Frequency stability                    | Compliance     |

Compliance\*: Please refer to SAR report released by BACL, report number: RSZ170804008-20.

## TEST EQUIPMENT LIST

| Manufacturer                  | Description                         | Model                 | Serial Number         | Calibration Date | Calibration Due Date |
|-------------------------------|-------------------------------------|-----------------------|-----------------------|------------------|----------------------|
| <b>Radiated Emission Test</b> |                                     |                       |                       |                  |                      |
| Sunol Sciences                | Horn Antenna                        | DRH-118               | A052604               | 2014-12-29       | 2017-12-28           |
| Rohde & Schwarz               | Signal Generator                    | FSIQ26                | 8386001028            | 2017-04-24       | 2018-04-24           |
| Sunol Sciences                | Bi-log Antenna                      | JB1                   | A040904-2             | 2014-12-17       | 2017-12-16           |
| Mini                          | Pre-amplifier                       | ZVA-183-S+            | 5969001149            | 2017-02-14       | 2018-02-14           |
| HP                            | Amplifier                           | HP8447E               | 1937A01046            | 2017-05-21       | 2017-11-19           |
| Anritsu                       | Signal Generator                    | 68369B                | 004114                | 2016-12-05       | 2017-12-05           |
| Rohde & Schwarz               | EMI Test Receiver                   | ESCI                  | 101120                | 2016-12-07       | 2017-12-07           |
| COM POWER                     | Dipole Antenna                      | AD-100                | 041000                | NCR              | NCR                  |
| A.H. System                   | Horn Antenna                        | SAS-200/571           | 135                   | 2015-08-18       | 2018-08-17           |
| R & S                         | Wideband Radio Communication Tester | CMW500                | 146520                | 2017-02-14       | 2018-02-14           |
| Ducommun technologies         | RF Cable                            | UFA210A-1-4724-30050U | MFR64369223410-001    | 2017-05-21       | 2017-11-19           |
| Ducommun technologies         | RF Cable                            | 104PEA                | 218124002             | 2017-05-21       | 2017-11-19           |
| Ducommun technologies         | RF Cable                            | RG-214                | 1                     | 2017-05-21       | 2017-11-19           |
| Ducommun technologies         | RF Cable                            | RG-214                | 2                     | 2017-05-22       | 2017-11-22           |
| <b>RF Conducted Test</b>      |                                     |                       |                       |                  |                      |
| Rohde & Schwarz               | Signal Analyzer                     | FSIQ26                | 837405/023            | 2017-04-24       | 2018-04-24           |
| ESPEC                         | Temperature & Humidity Chamber      | EL-10KA               | 09107726              | 2016-11-22       | 2017-11-22           |
| Long Wei                      | DC Power Supply                     | TPR-6420D             | 398363                | NCR              | NCR                  |
| Aglient                       | ESG Vector Signal Generator         | E4438C                | MY42080875            | 2017-05-09       | 2018-05-09           |
| Rohde & Schwarz               | Wideband Radio Communication Tester | CMW500                | 1201.002K50-146520-wh | 2017-04-24       | 2018-04-24           |
| Rohde & Schwarz               | Wideband Radio Communication Tester | CMU200                | 106891                | 2016-10-18       | 2017-10-18           |
| Ducommun technologies         | RF Cable                            | RG-214                | 3                     | 2017-05-22       | 2017-11-22           |
| WEINSCHL                      | 10dB Attenuator                     | 5324                  | AU0709                | 2017-06-15       | 2018-06-15           |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION**

---

### **Applicable Standard**

FCC§1.1307, §2.1093.

### **Test Result**

Compliance, please refer to the SAR report: RSZ170804008-20.



---

## **FCC §2.1047 - MODULATION CHARACTERISTIC**

---

According to FCC § 2.1047(d) , Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

**§2.1046; § 22.913 (a); § 24.232 (c) - RF OUTPUT POWER****Applicable Standards**

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.


According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

**Test Procedure**

*Conducted method:*

The RF output of the transmitter was connected to the CMU200 through sufficient attenuation.



*Radiated method:*

TIA603-D section 2.2.17

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 26 °C     |
| <b>Relative Humidity:</b> | 56 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Kiki Kong on 2017-08-18.*

**Conducted Power****Cellular Band (Part 22H)**

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) | Limit (dBm) |
|------|---------|-----------------|----------------------------|-------------|
| GSM  | 128     | 824.2           | 32.50                      | 38.45       |
|      | 190     | 836.6           | 32.30                      | 38.45       |
|      | 251     | 848.8           | 31.80                      | 38.45       |

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) |         |         |         | Limit (dBm) |
|------|---------|-----------------|----------------------------|---------|---------|---------|-------------|
|      |         |                 | 1 slot                     | 2 slots | 3 slots | 4 slots |             |
| GPRS | 128     | 824.2           | 32.41                      | 31.30   | 29.18   | 27.95   | 38.45       |
|      | 190     | 836.6           | 32.27                      | 31.31   | 29.21   | 27.92   | 38.45       |
|      | 251     | 848.8           | 31.70                      | 31.00   | 29.31   | 28.31   | 38.45       |

| Mode  | Channel | Frequency (MHz) | Average Output Power (dBm) |         |         |         | Limit (dBm) |
|-------|---------|-----------------|----------------------------|---------|---------|---------|-------------|
|       |         |                 | 1 slot                     | 2 slots | 3 slots | 4 slots |             |
| EGPRS | 128     | 824.2           | 27.25                      | 25.70   | 23.21   | 22.54   | 38.45       |
|       | 190     | 836.6           | 27.49                      | 26.10   | 23.63   | 22.00   | 38.45       |
|       | 251     | 848.8           | 28.10                      | 26.64   | 24.20   | 22.53   | 38.45       |

| Mode           | Test Condition | Test Mode | 3GPP Sub Test | Average Output Power (dBm) |                  |                |
|----------------|----------------|-----------|---------------|----------------------------|------------------|----------------|
|                |                |           |               | Low Frequency              | Middle Frequency | High Frequency |
| WCDMA (Band V) | Normal         | RMC12.2   |               | 22.33                      | 22.23            | 22.05          |
|                |                | HSDPA     | 1             | 21.22                      | 21.18            | 21.04          |
|                |                |           | 2             | 21.60                      | 21.52            | 21.47          |
|                |                |           | 3             | 21.78                      | 21.66            | 21.63          |
|                |                |           | 4             | 21.53                      | 21.58            | 21.57          |
|                |                | HSUPA     | 1             | 21.28                      | 21.22            | 21.07          |
|                |                |           | 2             | 21.68                      | 21.54            | 21.52          |
|                |                |           | 3             | 21.79                      | 21.61            | 21.76          |
|                |                |           | 4             | 21.54                      | 21.58            | 21.51          |
|                |                |           | 5             | 21.78                      | 21.69            | 21.75          |
|                |                | HSPA+     | 1             | 21.32                      | 21.41            | 21.33          |

**PCS Band (Part 24E)**

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) | Limit (dBm) |
|------|---------|-----------------|----------------------------|-------------|
| GSM  | 512     | 1850.2          | 28.50                      | 33          |
|      | 661     | 1880.0          | 28.62                      | 33          |
|      | 810     | 1909.8          | 29.10                      | 33          |

| Mode | Channel | Frequency (MHz) | Average Output Power (dBm) |         |         |         | Limit (dBm) |
|------|---------|-----------------|----------------------------|---------|---------|---------|-------------|
|      |         |                 | 1 slot                     | 2 slots | 3 slots | 4 slots |             |
| GPRS | 512     | 1850.2          | 28.38                      | 27.28   | 25.26   | 23.91   | 33          |
|      | 661     | 1880.0          | 28.43                      | 27.42   | 25.48   | 24.16   | 33          |
|      | 810     | 1909.8          | 29.08                      | 28.17   | 26.36   | 25.17   | 33          |

| Mode  | Channel | Frequency (MHz) | Average Output Power (dBm) |         |         |         | Limit (dBm) |
|-------|---------|-----------------|----------------------------|---------|---------|---------|-------------|
|       |         |                 | 1 slot                     | 2 slots | 3 slots | 4 slots |             |
| EGPRS | 512     | 1850.2          | 26.37                      | 25.64   | 23.27   | 21.60   | 33          |
|       | 661     | 1880.0          | 26.17                      | 25.37   | 22.90   | 21.23   | 33          |
|       | 810     | 1909.8          | 25.82                      | 24.94   | 23.97   | 20.79   | 33          |

| Mode            | Test Condition | Test Mode | 3GPP Sub Test | Average Output Power (dBm) |                  |                |
|-----------------|----------------|-----------|---------------|----------------------------|------------------|----------------|
|                 |                |           |               | Low Frequency              | Middle Frequency | High Frequency |
| WCDMA (Band II) | Normal         | RMC12.2   |               | 22.53                      | 22.23            | 22.05          |
|                 |                | HSDPA     | 1             | 21.22                      | 21.18            | 21.04          |
|                 |                |           | 2             | 21.58                      | 21.54            | 21.39          |
|                 |                |           | 3             | 21.65                      | 21.64            | 21.53          |
|                 |                |           | 4             | 21.42                      | 21.41            | 21.38          |
|                 |                | HSUPA     | 1             | 21.28                      | 21.22            | 21.07          |
|                 |                |           | 2             | 21.52                      | 21.54            | 21.32          |
|                 |                |           | 3             | 21.55                      | 21.64            | 21.58          |
|                 |                |           | 4             | 21.59                      | 21.41            | 21.36          |
|                 |                |           | 5             | 21.58                      | 21.62            | 21.54          |
|                 |                | HSPA+     | 1             | 21.15                      | 21.28            | 21.17          |

**Peak-to-average ratio (PAR)****Cellular Band**

| Mode | Channel | PAR (dB) | Limit (dB) |
|------|---------|----------|------------|
| GSM  | Low     | 0.55     | 13         |
|      | Middle  | 0.64     | 13         |
|      | High    | 0.37     | 13         |

| Mode  | Channel | PAR (dB) | Limit (dB) |
|-------|---------|----------|------------|
| EGPRS | Low     | 0.85     | 13         |
|       | Middle  | 0.74     | 13         |
|       | High    | 0.61     | 13         |

| Mode          | Channel | PAR (dB) | Limit (dB) |
|---------------|---------|----------|------------|
| RMC (BPSK)    | Low     | 3.73     | 13         |
|               | Middle  | 3.42     | 13         |
|               | High    | 3.87     | 13         |
| HSDPA (16QAM) | Low     | 3.14     | 13         |
|               | Middle  | 3.28     | 13         |
|               | High    | 2.64     | 13         |
| HSUPA (BPSK)  | Low     | 3.82     | 13         |
|               | Middle  | 3.24     | 13         |
|               | High    | 3.33     | 13         |
| HSPA+         | Low     | 3.88     | 13         |
|               | Middle  | 3.15     | 13         |
|               | High    | 3.84     | 13         |

**PCS Band**

| Mode | Channel | PAR (dB) | Limit (dB) |
|------|---------|----------|------------|
| GSM  | Low     | 0.34     | 13         |
|      | Middle  | 0.41     | 13         |
|      | High    | 0.32     | 13         |

| Mode  | Channel | PAR (dB) | Limit (dB) |
|-------|---------|----------|------------|
| EGPRS | Low     | 0.45     | 13         |
|       | Middle  | 0.25     | 13         |
|       | High    | 0.28     | 13         |

| Mode          | Channel | PAR (dB) | Limit (dB) |
|---------------|---------|----------|------------|
| RMC (BPSK)    | Low     | 2.95     | 13         |
|               | Middle  | 2.84     | 13         |
|               | High    | 2.64     | 13         |
| HSDPA (16QAM) | Low     | 2.91     | 13         |
|               | Middle  | 3.15     | 13         |
|               | High    | 3.08     | 13         |
| HSUPA (BPSK)  | Low     | 3.45     | 13         |
|               | Middle  | 3.85     | 13         |
|               | High    | 3.25     | 13         |
| HSPA+         | Low     | 3.33     | 13         |
|               | Middle  | 3.12     | 13         |
|               | High    | 3.27     | 13         |

**Radiated Power****GSM Mode:**

| Frequency<br>(MHz)                            | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                         | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|-------------------------|----------------------------|----------------|----------------|
|   |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>loss<br>(dB) | Antenna<br>Gain<br>(dB) |                            |                |                |
| ERP, Cellular Band (Part 22H), Middle Channel |                               |                              |               |                |                |                       |                         |                            |                |                |
| 836.6   | 79.60                         | 248                          | 2.0           | H              | 19.6           | 0.6                   | 0.0                     | 19.0                       | 38.45          | 19.45          |
| 836.6   | 92.71                         | 207                          | 1.3           | V              | 33.4           | 0.6                   | 0.0                     | 32.8                       | 38.45          | 5.65           |
| EIRP, PCS Band (Part 24E), Middle Channel     |                               |                              |               |                |                |                       |                         |                            |                |                |
| 1880.00                                       | 87.71                         | 335                          | 1.9           | H              | 17.7           | 1.30                  | 8.50                    | 24.90                      | 33             | 8.1            |
| 1880.00                                       | 91.33                         | 356                          | 2.1           | V              | 21.1           | 1.30                  | 8.50                    | 28.30                      | 33             | 4.7            |

**EDGE Mode:**

| Frequency<br>(MHz)                            | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                         | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|-------------------------|----------------------------|----------------|----------------|
|   |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>loss<br>(dB) | Antenna<br>Gain<br>(dB) |                            |                |                |
| ERP, Cellular Band (Part 22H), Middle Channel |                               |                              |               |                |                |                       |                         |                            |                |                |
| 836.6   | 79.94                         | 191                          | 1.5           | H              | 19.9           | 0.6                   | 0.0                     | 19.3                       | 38.45          | 19.15          |
| 836.6   | 87.37                         | 146                          | 2.0           | V              | 28.1           | 0.6                   | 0.0                     | 27.5                       | 38.45          | 10.95          |
| EIRP, PCS Band (Part 24E), Middle Channel     |                               |                              |               |                |                |                       |                         |                            |                |                |
| 1880.00                                       | 84.33                         | 356                          | 2.1           | H              | 14.1           | 1.30                  | 8.50                    | 21.30                      | 33             | 11.70          |
| 1880.00                                       | 88.71                         | 335                          | 1.9           | V              | 18.7           | 1.30                  | 8.50                    | 25.90                      | 33             | 7.10           |

**WCDMA Mode:**

| Frequency<br>(MHz)                             | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                         | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|--|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|-------------------------|----------------------------|----------------|----------------|
|  |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>loss<br>(dB) | Antenna<br>Gain<br>(dB) |                            |                |                |
| ERP, WCDMA Band V (Part 22H), Middle Channel   |                               |                              |               |                |                |                       |                         |                            |                |                |
| 836.6  | 75.76                         | 46                           | 1.6           | H              | 15.7           | 0.6                   | 0.0                     | 15.1                       | 38.45          | 23.35          |
| 836.6  | 82.64                         | 74                           | 1.6           | V              | 23.4           | 0.6                   | 0.0                     | 22.8                       | 38.45          | 15.65          |
| EIRP, WCDMA Band II (Part 24E), Middle Channel |                               |                              |               |                |                |                       |                         |                            |                |                |
| 1880.00  | 81.60                         | 265                          | 1.8           | H              | 11.3           | 1.30                  | 8.50                    | 18.50                      | 33             | 14.50          |
| 1880.00  | 83.30                         | 150                          | 1.3           | V              | 13.3           | 1.30                  | 8.50                    | 20.50                      | 33             | 12.50          |

**Note:**

All above data were tested with no amplifier.

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit - Absolute Level


**FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH****Applicable Standards**

FCC 47 §2.1049, §22.917, §22.905, §24.238.

**Test Procedure**

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.

**Test Data****Environmental Conditions**

|                    |                 |
|--------------------|-----------------|
| Temperature:       | 23~25 °C        |
| Relative Humidity: | 52~56 %         |
| ATM Pressure:      | 100.0~101.0 kPa |

The testing was performed by Kiki Kong from 2017-08-14 to 2017-08-18.

*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to the following tables and plots.*



**Cellular Band (Part 22H)**

| Mode      | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Emission Bandwidth (kHz) |
|-----------|-----------------|------------------------------|--------------------------------|
| GSM(GMSK) | 836.6           | 243.6                        | 314.1                          |

| Mode  | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Emission Bandwidth (kHz) |
|-------|-----------------|------------------------------|--------------------------------|
| EGPRS | 836.6           | 251.6                        | 320.5                          |

| Mode          | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 26 dB Emission Bandwidth (MHz) |
|---------------|-----------------|------------------------------|--------------------------------|
| RMC (BPSK)    | 836.6           | 4.15                         | 4.68                           |
| HSUPA (BPSK)  | 836.6           | 4.15                         | 4.70                           |
| HSDPA (16QAM) | 836.6           | 4.15                         | 4.71                           |

**PCS Band (Part 24E)**


| Mode      | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Emission Bandwidth (kHz) |
|-----------|-----------------|------------------------------|--------------------------------|
| GSM(GMSK) | 1880.0          | 246.8                        | 318.9                          |

| Mode  | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Emission Bandwidth (kHz) |
|-------|-----------------|------------------------------|--------------------------------|
| EGPRS | 1880.0          | 256.4                        | 338.1                          |

| Mode          | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 26 dB Emission Bandwidth (MHz) |
|---------------|-----------------|------------------------------|--------------------------------|
| RMC (BPSK)    | 1880.0          | 4.17                         | 4.71                           |
| HSUPA (BPSK)  | 1880.0          | 4.18                         | 4.70                           |
| HSDPA (16QAM) | 1880.0          | 4.17                         | 4.68                           |


## Cellular Band (Part 22H)

## 26 dB Emissions &amp; 99% Occupied Bandwidth for GSM (GMSK) Mode




Date: 14.AUG.2017 14:32:19

## 26 dB Emissions &amp; 99% Occupied Bandwidth for EGPRS (EDGE) Mode




Date: 14.AUG.2017 14:21:43

## 26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode




Date: 18.AUG.2017 18:52:59

## 26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode




Date: 18.AUG.2017 18:50:31


## 26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode



Date: 18.AUG.2017 18:51:47


**PCS Band (Part 24E)****26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode**

Date: 14.AUG.2017 14:09:13

**26 dB Emissions & 99% Occupied Bandwidth for EGPRS (EDGE) Mode**


Date: 14.AUG.2017 14:17:43

## 26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode




Date: 18.AUG.2017 18:46:06

## 26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode



Date: 18.AUG.2017 18:48:44

## 26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode



Date: 18.AUG.2017 18:47:25

## § 2.1051; § 22.917 (a); § 24.238 (a) SPURIOUS EMISSIONS AT ANTENNA TERMINALS


### Applicable Standards

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

### Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100kHz for below 1GHz and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10<sup>th</sup> harmonic.



### Test Data

#### Environmental Conditions


|                    |                 |
|--------------------|-----------------|
| Temperature:       | 23~26 °C        |
| Relative Humidity: | 52~56 %         |
| ATM Pressure:      | 100.0~101.0 kPa |

The testing was performed by Kiki Kong from 2017-08-14 to 2017-08-23.




Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




Date: 14.AUG.2017 17:56:09

1 GHz – 10 GHz (GSM Mode)



Date: 23.AUG.2017 15:33:58


### 30 MHz – 1 GHz (WCDMA Mode)



Fundamental test

Date: 18.AUG.2017 19:07:53


### 1 GHz – 10 GHz (WCDMA Mode)



Date: 23.AUG.2017 18:30:52


PCS Band (Part 24E)

30 MHz – 1 GHz (GSM Mode)



Date: 23.AUG.2017 15:08:04


1 GHz – 2 GHz (GSM Mode)



Fundamental test


Date: 14.AUG.2017 18:54:47

### 2 GHz – 20 GHz (GSM Mode)




Date: 23.AUG.2017 15:04:25

### 30 MHz – 1 GHz (WCDMA Mode)




Date: 23.AUG.2017 18:34:05

### 1 GHz – 2 GHz (WCDMA Mode)



Date: 18.AUG.2017 19:03:02

### 2 GHz – 20 GHz (WCDMA Mode)



Date: 23.AUG.2017 18:32:39

**FCC § 2.1053; § 22.917 (a); § 24.238 (a) SPURIOUS RADIATED EMISSIONS****Applicable Standards**

FCC § 2.1053, §22.917(a) and § 24.238(a)

**Test Procedure**

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB =  $10 \lg (\text{TX pwr in Watts}/0.001)$  – the absolute level

Spurious attenuation limit in dB =  $43 + 10 \log_{10} (\text{power out in Watts})$  or,

Spurious attenuation limit in dB =  $55 + 10 \log_{10} (\text{power out in Watts})$

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 26 °C     |
| <b>Relative Humidity:</b> | 56 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Kiki Kong on 2017-08-09.*

*Test mode: Transmitting*

Test mode: Transmitting (Pre-scan with Low, Middle, High channel, and the worse case data as below)

30 MHz ~ 10 GHz:

**Cellular Band (Part 22H)**

| Frequency<br>(MHz) | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                         | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|-------------------------|----------------------------|----------------|----------------|
|                    |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>Loss<br>(dB) | Antenna<br>Gain<br>(dB) |                            |                |                |
| GSM 850 Mode       |                               |                              |               |                |                |                       |                         |                            |                |                |
| 241.25             | 33.47                         | 180                          | 1.3           | H              | -61.5          | 0.3                   | 0.0                     | -61.9                      | -13            | 48.9           |
| 241.25             | 32.86                         | 184                          | 1.0           | V              | -62.1          | 0.3                   | 0.0                     | -62.4                      | -13            | 49.4           |
| 1673.20            | 55.28                         | 156                          | 2.5           | H              | -51.8          | 1.30                  | 9.10                    | -44.00                     | -13            | 31.00          |
| 1673.20            | 58.57                         | 10                           | 1.9           | V              | -47.9          | 1.30                  | 9.10                    | -40.10                     | -13            | 27.10          |
| 2509.80            | 50.64                         | 72                           | 2.2           | H              | -52.9          | 2.60                  | 9.30                    | -46.20                     | -13            | 33.20          |
| 2509.80            | 46.69                         | 90                           | 1.5           | V              | -56.2          | 2.60                  | 9.30                    | -49.50                     | -13            | 36.50          |
| 3346.40            | 45.87                         | 257                          | 2.3           | H              | -54.5          | 1.50                  | 9.60                    | -46.40                     | -13            | 33.40          |
| 3346.40            | 43.66                         | 231                          | 1.8           | V              | -56.7          | 1.50                  | 9.60                    | -48.60                     | -13            | 35.60          |
| WCDMA 850 Mode     |                               |                              |               |                |                |                       |                         |                            |                |                |
| 251.35             | 33.47                         | 359                          | 1.1           | H              | -61.5          | 0.3                   | 0.0                     | -61.9                      | -13            | 48.90          |
| 251.35             | 32.86                         | 238                          | 1.5           | V              | -62.1          | 0.3                   | 0.0                     | -62.4                      | -13            | 49.40          |
| 1673.20            | 64.55                         | 106                          | 1.2           | H              | -42.5          | 1.30                  | 9.10                    | -34.70                     | -13            | 21.70          |
| 1673.20            | 64.81                         | 31                           | 1.5           | V              | -41.7          | 1.30                  | 9.10                    | -33.90                     | -13            | 20.90          |
| 2509.80            | 76.6                          | 283                          | 2.4           | H              | -26.9          | 2.60                  | 9.30                    | -20.20                     | -13            | 7.20           |
| 2509.80            | 77.26                         | 239                          | 1.7           | V              | -25.7          | 2.60                  | 9.30                    | -19.00                     | -13            | 6.00           |

**30 MHz ~ 20 GHz:****PCS Band (Part 24E)**

| Frequency<br>(MHz) | Receiver<br>Reading<br>(dBμV) | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Substituted    |                       |                         | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|-------------------------------|------------------------------|---------------|----------------|----------------|-----------------------|-------------------------|----------------------------|----------------|----------------|
|                    |                               |                              | Height<br>(m) | Polar<br>(H/V) | Level<br>(dBm) | Cable<br>Loss<br>(dB) | Antenna<br>Gain<br>(dB) |                            |                |                |
| GSM 1900 Mode      |                               |                              |               |                |                |                       |                         |                            |                |                |
| 241.25             | 31.89                         | 240                          | 1.1           | H              | -65.10         | 0.31                  | 0                       | -65.41                     | -13            | 52.41          |
| 241.25             | 31.94                         | 45                           | 1.3           | V              | -65.10         | 0.31                  | 0                       | -65.41                     | -13            | 52.41          |
| 3760.00            | 44.8                          | 121                          | 1.2           | H              | -56.4          | 1.50                  | 9.70                    | -48.20                     | -13            | 35.20          |
| 3760.00            | 42.76                         | 14                           | 2.3           | V              | -58.0          | 1.50                  | 9.70                    | -49.80                     | -13            | 36.80          |
| WCDMA 1900 Mode    |                               |                              |               |                |                |                       |                         |                            |                |                |
| 251.35             | 31.55                         | 333                          | 1.6           | H              | -65.40         | 0.32                  | 0                       | -65.72                     | -13            | 52.72          |
| 251.35             | 31.11                         | 159                          | 1.6           | V              | -65.90         | 0.32                  | 0                       | -66.22                     | -13            | 53.22          |
| 3760.00            | 45.94                         | 302                          | 1.9           | H              | -55.3          | 1.50                  | 9.70                    | -47.10                     | -13            | 34.10          |
| 3760.00            | 45.31                         | 303                          | 2.1           | V              | -55.4          | 1.50                  | 9.70                    | -47.20                     | -13            | 34.20          |

**Note:**

- 1) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level



## FCC § 22.917 (a);§ 24.238 (a) - BAND EDGES

### Applicable Standards


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



### Test Data

#### Environmental Conditions


|                    |                 |
|--------------------|-----------------|
| Temperature:       | 23~25 °C        |
| Relative Humidity: | 52~56 %         |
| ATM Pressure:      | 100.0~101.0 kPa |

The testing was performed by Kiki Kong from 2017-08-14 to 2017-08-18.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to the following plots.

### Cellular Band, Left Band Edge for GSM (GMSK) Mode




Date: 14.AUG.2017 18:34:39

### Cellular Band, Right Band Edge for GSM (GMSK) Mode




Date: 14.AUG.2017 18:32:51

### Cellular Band, Left Band Edge for EGPRS (EDGE) Mode




Date: 14.AUG.2017 18:37:02

### Cellular Band, Right Band Edge for EGPRS (EDGE) Mode




Date: 14.AUG.2017 18:38:25

### Cellular Band, Left Band Edge for RMC (BPSK) Mode




Date: 18.AUG.2017 18:18:07

### Cellular Band, Right Band Edge for RMC (BPSK) Mode




Date: 18.AUG.2017 18:23:03

### Cellular Band, Left Band Edge for HSDPA (16QAM) Mode




Date: 18.AUG.2017 18:20:14

### Cellular Band, Right Band Edge for HSDPA (16QAM) Mode




Date: 18.AUG.2017 18:27:05

### Cellular Band, Left Band Edge for HSUPA (BPSK) Mode




Date: 18.AUG.2017 18:21:30

### Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




Date: 18.AUG.2017 18:24:24

### PCS Band, Left Band Edge for GSM (GMSK) Mode




Date: 14.AUG.2017 13:13:50

### PCS Band, Right Band Edge for GSM (GMSK) Mode




Date: 14.AUG.2017 13:17:02

### PCS Band, Left Band Edge for EGPRS (EDGE) Mode



Date: 14.AUG.2017 13:24:20


### PCS Band, Right Band Edge for EGPRS (EDGE) Mode



Date: 14.AUG.2017 13:23:53




### PCS Band, Left Band Edge for RMC (BPSK) Mode




Date: 18.AUG.2017 18:05:26

### PCS Band, Right Band Edge for RMC (BPSK) Mode




Date: 18.AUG.2017 18:15:11

### PCS Band, Left Band Edge for HSDPA (16QAM) Mode



Date: 18.AUG.2017 18:08:25

### PCS Band, Right Band Edge for HSDPA (16QAM) Mode



Date: 18.AUG.2017 18:13:48

Ref 30 dBm \* Att 30 dB \* RBW 100 kHz \* VBW 300 kHz \* Marker 1 [T1] -19.91 dBm  
SWT 5 ms 1.849983974 GHz

30 Offset 4.5 dB

1 RM \*  
MAXH


D1 -13 dBm

A  
LVL

3DB

Center 1.85 GHz 1 MHz / Span 10 MHz

### PCS Band, Right Band Edge for HSUPA (BPSK) Mode



Page 43 of 48

**FCC § 2.1055; § 22.355; § 24.235; - FREQUENCY STABILITY****Applicable Standards**

FCC § 2.1055, §22.355, §24.235.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

**Frequency Tolerance for Transmitters in the Public Mobile Services**

| Frequency Range (MHz) | Base, fixed (ppm) | Mobile > 3 watts (ppm) | Mobile ≤ 3 watts (ppm) |
|-----------------------|-------------------|------------------------|------------------------|
| 25 to 50              | 20.0              | 20.0                   | 50.0                   |
| 50 to 450             | 5.0               | 5.0                    | 50.0                   |
| 450 to 512            | 2.5               | 5.0                    | 5.0                    |
| 821 to 896            | 1.5               | 2.5                    | 2.5                    |
| 928 to 929.           | 5.0               | N/A                    | N/A                    |
| 929 to 960.           | 1.5               | N/A                    | N/A                    |
| 2110 to 2220          | 10.0              | N/A                    | N/A                    |


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

**Test Procedure**

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 26 °C     |
| <b>Relative Humidity:</b> | 56 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

The testing was performed by Kiki Kong on 2017-08-18.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

**Cellular Band (Part 22H)****GSM Mode**

| Middle Channel, $f_0 = 836.6$ MHz |                                   |                      |                       |             |
|-----------------------------------|-----------------------------------|----------------------|-----------------------|-------------|
| Temperature (°C)                  | Power Supplied (V <sub>DC</sub> ) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| -30                               | 3.7                               | 3                    | 0.003586              | 2.5         |
| -20                               |                                   | 8                    | 0.009563              | 2.5         |
| -10                               |                                   | 12                   | 0.014344              | 2.5         |
| 0                                 |                                   | 10                   | 0.011953              | 2.5         |
| 10                                |                                   | 6                    | 0.007172              | 2.5         |
| 20                                |                                   | 3                    | 0.003586              | 2.5         |
| 30                                |                                   | 9                    | 0.010758              | 2.5         |
| 40                                |                                   | 11                   | 0.013148              | 2.5         |
| 50                                |                                   | 15                   | 0.017930              | 2.5         |
| 25                                | V min.= 3.5                       | 14                   | 0.016734              | 2.5         |
|                                   | V max.= 4.2                       | 16                   | 0.019125              | 2.5         |

**EDGE Mode**

| Middle Channel, $f_0 = 836.6$ MHz |                                   |                      |                       |             |
|-----------------------------------|-----------------------------------|----------------------|-----------------------|-------------|
| Temperature (°C)                  | Power Supplied (V <sub>DC</sub> ) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| -30                               | 3.7                               | 5                    | 0.005977              | 2.5         |
| -20                               |                                   | 4                    | 0.004781              | 2.5         |
| -10                               |                                   | 3                    | 0.003586              | 2.5         |
| 0                                 |                                   | 1                    | 0.001195              | 2.5         |
| 10                                |                                   | 7                    | 0.008367              | 2.5         |
| 20                                |                                   | 2                    | 0.002391              | 2.5         |
| 30                                |                                   | 5                    | 0.005977              | 2.5         |
| 40                                |                                   | 8                    | 0.009563              | 2.5         |
| 50                                |                                   | 9                    | 0.010758              | 2.5         |
| 25                                | V min.= 3.5                       | 10                   | 0.011953              | 2.5         |
|                                   | V max.= 4.2                       | 6                    | 0.007172              | 2.5         |

**WCDMA Mode**

| Middle Channel, $f_0 = 836.6$ MHz |                                   |                      |                       |             |
|-----------------------------------|-----------------------------------|----------------------|-----------------------|-------------|
| Temperature (°C)                  | Power Supplied (V <sub>DC</sub> ) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| -30                               | 3.7                               | -2                   | -0.0024               | 2.5         |
| -20                               |                                   | 3                    | 0.0036                | 2.5         |
| -10                               |                                   | 6                    | 0.0072                | 2.5         |
| 0                                 |                                   | 4                    | 0.0048                | 2.5         |
| 10                                |                                   | -1                   | -0.0012               | 2.5         |
| 20                                |                                   | 1                    | 0.0012                | 2.5         |
| 30                                |                                   | 5                    | 0.0060                | 2.5         |
| 40                                |                                   | -8                   | -0.0096               | 2.5         |
| 50                                |                                   | 9                    | 0.0108                | 2.5         |
| 25                                | V min.= 3.5                       | 10                   | 0.0120                | 2.5         |
|                                   | V max.= 4.2                       | 11                   | 0.0131                | 2.5         |

**PCS Band (Part 24E)****GSM Mode**

| Middle Channel, $f_0$ =1880.0 MHz |                                   |                      |                       |        |
|-----------------------------------|-----------------------------------|----------------------|-----------------------|--------|
| Temperature (°C)                  | Power Supplied (V <sub>DC</sub> ) | Frequency Error (Hz) | Frequency Error (ppm) | Result |
| -30                               | 3.7                               | 12                   | 0.006383              | pass   |
| -20                               |                                   | 18                   | 0.009574              | pass   |
| -10                               |                                   | 19                   | 0.010106              | pass   |
| 0                                 |                                   | 12                   | 0.006383              | pass   |
| 10                                |                                   | 11                   | 0.005851              | pass   |
| 20                                |                                   | 14                   | 0.007447              | pass   |
| 30                                |                                   | 20                   | 0.010638              | pass   |
| 40                                |                                   | 21                   | 0.011170              | pass   |
| 50                                |                                   | 15                   | 0.007979              | pass   |
| 25                                | V min.= 3.5                       | 29                   | 0.015426              | pass   |
|                                   | V max.= 4.2                       | 28                   | 0.014894              | pass   |

**EDGE Mode**

| Middle Channel, $f_0$ =1880.0 MHz |                                   |                      |                       |        |
|-----------------------------------|-----------------------------------|----------------------|-----------------------|--------|
| Temperature (°C)                  | Power Supplied (V <sub>DC</sub> ) | Frequency Error (Hz) | Frequency Error (ppm) | Result |
| -30                               | 3.7                               | 6                    | 0.003191              | pass   |
| -20                               |                                   | 8                    | 0.004255              | pass   |
| -10                               |                                   | 19                   | 0.010106              | pass   |
| 0                                 |                                   | 13                   | 0.006915              | pass   |
| 10                                |                                   | 16                   | 0.008511              | pass   |
| 20                                |                                   | 5                    | 0.002660              | pass   |
| 30                                |                                   | 12                   | 0.006383              | pass   |
| 40                                |                                   | 17                   | 0.009043              | pass   |
| 50                                |                                   | 6                    | 0.003191              | pass   |
| 25                                | V min.= 3.5                       | 20                   | 0.010638              | pass   |
|                                   | V max.= 4.2                       | 18                   | 0.009574              | pass   |

**WCDMA Mode**

| <b>Middle Channel, <math>f_0</math> =1880.0 MHz</b> |  |                                     |                                      |               |
|---|--|-------------------------------------|--------------------------------------|---------------|
| <b>Temperature<br/>(°C)</b>                         | <b>Power Supplied<br/>(V<sub>DC</sub>)</b> | <b>Frequency<br/>Error<br/>(Hz)</b> | <b>Frequency<br/>Error<br/>(ppm)</b> | <b>Result</b> |
| -30   | 3.7  | 6                                   | 0.0032                               | pass          |
| -20   |  | -4                                  | -0.0021                              | pass          |
| -10   |  | 3                                   | 0.0016                               | pass          |
| 0   |  | 1                                   | 0.0005                               | pass          |
| 10  |  | -5                                  | -0.0027                              | pass          |
| 20  |  | 2                                   | 0.0011                               | pass          |
| 30  |  | -1                                  | -0.0005                              | pass          |
| 40  |  | 2                                   | 0.0011                               | pass          |
| 50  |  | -4                                  | -0.0021                              | pass          |
| 25  | V min.= 3.5                                | 5                                   | 0.0027                               | pass          |
|   | V max.= 4.2                                | 8                                   | 0.0043                               | pass          |

**\*\*\*\*\* END OF REPORT \*\*\*\*\***