

FCC 47 CFR MPE REPORT

CHOICE FORTUNE HOLDINGS LIMITED

LED TV

Model Number: SC-65UK700N

FCC ID: 2AMYC-SC-65UK700N

Prepared for:	CHOICE FORTUNE HOLDINGS LIMITED
	Room 1315, 13/F, Tin King Estate, Tin Lok House,
	Tuen Mun, N.T., HongKong
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1801068
Date of Test:	Jan. 11~20, 2018
Date of Report:	Jan. 23, 2018

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5/d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2/377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result**3.1 Antenna 0**

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	14.68	29.376	14 ± 1	2.94	1.968
	2437	14.15	26.002	14 ± 1	2.94	1.968
	2462	12.14	16.368	12 ± 1	2.94	1.968
IEEE 802.11g	2412	11.48	14.060	11 ± 1	2.94	1.968
	2437	10.40	10.965	10 ± 1	2.94	1.968
	2462	9.37	8.650	9 ± 1	2.94	1.968
IEEE 802.11n HT20	2412	11.20	13.183	11 ± 1	2.94	1.968
	2437	10.26	10.617	10 ± 1	2.94	1.968
	2462	9.48	8.872	9 ± 1	2.94	1.968
IEEE 802.11n HT40	2422	8.10	6.457	8 ± 1	2.94	1.968
	2437	7.66	5.834	7 ± 1	2.94	1.968
	2452	7.72	5.916	7 ± 1	2.94	1.968

3.2 Antenna 1

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	13.22	20.989	13 ± 1	2.94	1.968
	2437	13.40	21.878	13 ± 1	2.94	1.968
	2462	11.31	13.521	11 ± 1	2.94	1.968
IEEE 802.11g	2412	9.15	8.222	9 ± 1	2.94	1.968
	2437	9.72	9.376	9 ± 1	2.94	1.968
	2462	7.51	5.636	7 ± 1	2.94	1.968
IEEE 802.11n HT20	2412	9.30	8.511	9 ± 1	2.94	1.968
	2437	9.41	8.730	9 ± 1	2.94	1.968
	2462	7.58	5.728	7 ± 1	2.94	1.968
IEEE 802.11n HT40	2422	7.07	5.093	7 ± 1	2.94	1.968
	2437	7.28	5.346	7 ± 1	2.94	1.968
	2452	7.34	5.420	7 ± 1	2.94	1.968

4、Calculated Result and Limit

4.1 Antenna 0

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
		(dBi)	(Linear)			
Wi-Fi						
IEEE 802.11b	15	2.94	1.968	0.01238	1	Compiles
IEEE 802.11g	12	2.94	1.968	0.00620	1	Compiles
IEEE 802.11n HT20	12	2.94	1.968	0.00620	1	Compiles
IEEE 802.11n HT40	9	2.94	1.968	0.00311	1	Compiles

4.2 Antenna 1

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
		(dBi)	(Linear)			
Wi-Fi						
IEEE 802.11b	14	2.94	1.968	0.00983	1	Compiles
IEEE 802.11g	10	2.94	1.968	0.00391	1	Compiles
IEEE 802.11n HT20	10	2.94	1.968	0.00391	1	Compiles
IEEE 802.11n HT40	8	2.94	1.968	0.00247	1	Compiles

4.3 Antenna 0+1

Mode	Power Density (S) (mW /cm2) Antenna 0	Power Density (S) (mW /cm2) Antenna 1	Power Density (S) (mW /cm2) Total	Limited of Power Density (S) (mW /cm2)	Test Result
Wi-Fi					
IEEE 802.11n HT20	0.00620	0.00391	0.01011	1	Compiles
IEEE 802.11n HT40	0.00311	0.00247	0.00558	1	Compiles