

# FCC TEST REPORT

## FCC ID: 2AN7N-XPACQ1

Product	:	Q1 Bluetooth Speaker
Model Name	:	XPAC Q1
Brand	:	Xpac
Report No.	:	PTCDQ06170300203E-FC02
<b>Prepared for</b>		
RESOURCES XPANDING (HK) LIMITED		
UNIT B 20/F GREATMANY CTR 109-115 QUEENS RD EAST HONGKONG		
<b>Prepared by</b>		
Dongguan Precise Testing & Certification Corp., Ltd.		
Building D, Baoding Technology Park, Guangming Road 2, Guangming Community, Dongcheng District, Dongguan, Guangdong, China		



## 1 TEST RESULT CERTIFICATION

Applicant's name : RESOURCES XPANDING (HK) LIMITED

Address : UNIT B 20/F GREATMANY CTR 109-115 QUEENS RD EAST  
HONGKONG

Manufacture's name : RESOURCES XPANDING (HK) LIMITED

Address : UNIT B 20/F GREATMANY CTR 109-115 QUEENS RD EAST  
HONGKONG

Product name : Q1 Bluetooth Speaker

Model name : XPAC Q1

Standards : FCC CFR47 Part 15 Section 15.247: 2017

Test procedure : ANSI C63.10:2013

Test Date : December 19, 2017 to January 30, 2018

Date of Issue : March 02, 2018

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

Leo Yang / Engineer

Technical Manager:

Chris Du / Manager

## Contents

	Page
<b>1 TEST RESULT CERTIFICATION.....</b>	<b>2</b>
<b>2 TEST SUMMARY.....</b>	<b>5</b>
2.1 TEST SITE.....	6
<b>3 GENERAL INFORMATION.....</b>	<b>7</b>
3.1 GENERAL DESCRIPTION OF E.U.T.....	7
3.2 CHANNEL LIST .....	8
<b>4 EQUIPMENT DURING TEST.....</b>	<b>9</b>
4.1 EQUIPMENTS LIST .....	9
4.2 MEASUREMENT UNCERTAINTY .....	11
4.3 DESCRIPTION OF SUPPORT UNITS.....	12
<b>5 CONDUCTED EMISSION.....</b>	<b>13</b>
5.1 E.U.T. OPERATION .....	13
5.2 EUT SETUP .....	13
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	14
5.4 MEASUREMENT PROCEDURE.....	14
5.5 CONDUCTED EMISSION LIMIT.....	14
5.6 MEASUREMENT DESCRIPTION .....	14
5.7 CONDUCTED EMISSION TEST RESULT.....	14
<b>6 RADIATED SPURIOUS EMISSIONS.....</b>	<b>17</b>
6.1 EUT OPERATION.....	17
6.2 TEST SETUP .....	18
6.3 SPECTRUM ANALYZER SETUP .....	19
6.4 TEST PROCEDURE.....	20
6.5 SUMMARY OF TEST RESULTS .....	21
<b>7 BAND EDGE MEASUREMENT .....</b>	<b>26</b>
7.1 TEST PROCEDURE.....	26
7.2 TEST RESULT .....	27



<b>8</b>	<b>6DB BANDWIDTH MEASUREMENT .....</b>	<b>28</b>
8.1	TEST PROCEDURE.....	28
8.2	TEST RESULT .....	28
<b>9</b>	<b>MAXIMUM PEAK OUTPUT POWER .....</b>	<b>31</b>
9.1	TEST PROCEDURE.....	31
9.2	TEST RESULT .....	31
<b>10</b>	<b>POWER SPECTRAL DENSITY.....</b>	<b>34</b>
10.1	TEST PROCEDURE.....	34
10.2	TEST RESULT .....	34
<b>11</b>	<b>ANTENNA APPLICATION .....</b>	<b>37</b>
11.1	ANTENNA REQUIREMENT .....	37
11.2	RESULT .....	37
<b>12</b>	<b>TEST SETUP .....</b>	<b>38</b>
<b>13</b>	<b>EUT PHOTOS.....</b>	<b>40</b>



## 2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS
Remark: N/A: Not Applicable		



PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02

## 2.1 Test Site

Dongguan Precise Testing & Certification Corp., Ltd.

Address: Building D, Baoding Technology Park, Guangming Road2, Dongcheng District, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1

Test Lab: Shenzhen BCTC Testing Co., Ltd.

Address: BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China

FCC Registered No.: 712850

Test items: Radiated Spurious Emission(18GHz to 25GHz)



### 3 General Information

#### 3.1 General Description of E.U.T.

Product Name	:	Q1 Bluetooth Speaker
Model Name	:	XPAC Q1
Operating frequency	:	2402-2080MHz
Number of Channels	:	40
Type of Modulation	:	GFSK
Antenna installation	:	Internal PCB Antenna
Antenna Gain	:	1.85 dBi
Power supply	:	DC 3.7V, 6000mAh Battery For Adapter: Model: GPE012A-050240-Z Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5V, 2400mA, 12W
Hardware Version	:	V9.1
Software Version	:	X200_V55_20171013



### 3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	<b>2402</b>	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	<b>19</b>	<b>2440</b>	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	<b>2480</b>
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.





## 4 Equipment During Test

### 4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
MXG Signal Analyzer	Agilent	N9020A	MY56070279	10Hz-30GHz	Apr 07, 2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Oct 09, 2018
Antenna Connector	Florida RF Labs	N/A	RF01#	N/A	Aug. 26, 2018

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions(Test Frequency from 9KHz-18GHz)

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Sep. 03, 2018
Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	Aug 31, 2018
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Aug 31, 2018
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Sep. 03, 2018
Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	Sep. 03, 2018
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-40GHz	Oct. 13, 2018
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Aug. 31, 2018
Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	Aug. 31, 2018
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Sep. 03, 2018

Radiated Emission (Test Frequency from 18GHz-25GHz)

<b>Name of Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Characteristics</b>	<b>Calibration Due</b>
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-26.5GHz	2018.08.26
Test Receiver	R&S	ESPI	101396	9KHz-7GHz	2018.08.26
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	14GHz-40GHz	2018.09.02
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	2018.08.26
RF Cable	R&S	R204	R21X	1GHz-40GHz	2018.08.26

Conducted Emissions

<b>Name of Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Characteristics</b>	<b>Calibration Due</b>
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Sep. 03, 2018
Artificial Mains Network	Rohde&Schwarz	L2-16B	000WX31025	9KHz-300MHz	Sep. 03, 2018
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Sep. 03, 2018



## 4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	



PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02

### 4.3 Description of Support Units

Equipment	Model No.	Series No.
N/A	N/A	N/A



## 5 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207  
Test Method: : ANSI C63.10: 2013  
Test Result: : PASS  
Frequency Range: : 150kHz to 30MHz  
Class/Severity: : Class B


### 5.1 E.U.T. Operation

Operating Environment :


Temperature: : 25.5 °C  
Humidity: : 51 % RH  
Atmospheric Pressure: : 101.2kPa

### 5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



### 5.3 Test SET-UP (Block Diagram of Configuration)



### 5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

### 5.5 Conducted Emission Limit

#### Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

#### Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

### 5.7 Conducted Emission Test Result


Pass.

Conducted emission at both AC 120V & 240V is assessed, and emission at AC 120V represents the worst case.

Please refer to the following test plots:




Line-AC 120V/60Hz



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBuV	Emission Level dBuV	Limit dBuV	Over Limit dB	Remark
1.	0.166	0.23	0.16	33.97	34.36	55.16	-20.80	Average
2.	0.166	0.23	0.16	48.97	49.36	65.16	-15.80	QP
3.	0.186	0.26	0.15	28.80	29.21	54.20	-24.99	Average
4.	0.186	0.26	0.15	47.80	48.21	64.20	-15.99	QP
5.	0.683	0.44	0.14	33.05	33.63	46.00	-12.37	Average
6.	0.683	0.44	0.14	43.05	43.63	56.00	-12.37	QP
7.	1.396	0.46	0.14	25.18	25.78	46.00	-20.22	Average
8.	1.396	0.46	0.14	37.18	37.78	56.00	-18.22	QP
9.	10.019	0.56	0.10	29.46	30.12	50.00	-19.88	Average
10.	10.019	0.56	0.10	39.46	40.12	60.00	-19.88	QP
11.	16.055	0.52	0.16	32.46	33.14	50.00	-16.86	Average
12.	16.055	0.52	0.16	44.46	45.14	60.00	-14.86	QP



Neutral-AC 120V/60Hz



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBuV	Emission Level dBuV	Limit dBuV	Over Limit dB	Remark
1.	0.162	0.23	0.27	28.14	28.64	55.34	-26.70	Average
2.	0.162	0.23	0.27	48.14	48.64	65.34	-16.70	QP
3.	0.679	0.44	0.33	28.81	29.58	46.00	-16.42	Average
4.	0.679	0.44	0.33	39.81	40.58	56.00	-15.42	QP
5.	1.441	0.47	0.36	27.04	27.87	46.00	-18.13	Average
6.	1.441	0.47	0.36	39.04	39.87	56.00	-16.13	QP
7.	4.070	0.47	0.31	14.14	14.92	46.00	-31.08	Average
8.	4.070	0.47	0.31	31.14	31.92	56.00	-24.08	QP
9.	9.603	0.56	0.28	21.84	22.68	50.00	-27.32	Average
10.	9.603	0.56	0.28	36.84	37.68	60.00	-22.32	QP
11.	15.066	0.56	0.32	23.87	24.75	50.00	-25.25	Average
12.	15.066	0.56	0.32	42.87	43.75	60.00	-16.25	QP





## 6 Radiated Spurious Emissions

Test Requirement: : FCC CFR47 Part 15 Section 15.209 & 15.247  
 Test Method: : ANSI C63.10:2013  
 Test Result: : PASS  
 Measurement Distance: : 3m  
 Limit: : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

### 6.1 EUT Operation


Operating Environment :

Temperature: : 23.5 °C  
 Humidity: : 51.1 % RH  
 Atmospheric Pressure: : 101.2kPa


## 6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site

The test setup for emission measurement below 30MHz




The test setup for emission measurement from 30 MHz to 1 GHz.





The test setup for emission measurement above 1 GHz



### 6.3 Spectrum Analyzer Setup

Below 30MHz			
IF Bandwidth	:	10kHz	
Resolution Bandwidth	:	10kHz	
Video Bandwidth	:	10kHz	
30MHz ~ 1GHz			
Detector	:	PK	QP
Resolution Bandwidth	:	100kHz	120kHz
Video Bandwidth	:	300kHz	300kHz
Above 1GHz			
Detector	:	PK	AV
Resolution Bandwidth	:	1MHz	1MHz
Video Bandwidth	:	3MHz	10Hz



## 6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
  - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
  - 2) Change the antenna polarization and repeat 1) with vertical polarization.
  - 3) Make a hardcopy of the spectrum.
  - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
  - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
  - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
  - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
  - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



## 6.5 Summary of Test Results

### Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

**Note:**

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance} / \text{test distance})$  (dB);  
Limit line = Specific limits (dBuV) + distance extrapolation factor.

### Test Frequency: 30MHz ~ 1GHz


Pass.

Radiated emission at both 120V & 240V is assessed, and emission at 120V represents the worst case.

Please refer to the following test plots:



Antenna Polarization: Horizontal




No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamp Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	38.078	1.27	13.56	38.23	30.05	23.01	40.00	-16.99	QP
2.	79.800	1.94	8.81	45.39	30.31	25.83	40.00	-14.17	QP
3.	197.893	2.76	10.53	42.96	30.63	25.62	43.50	-17.88	QP
4.	234.168	2.92	11.44	45.02	30.68	28.70	46.00	-17.30	QP
5.	368.112	3.33	14.59	39.54	30.84	26.62	46.00	-19.38	QP
6.	425.028	3.46	15.83	37.02	30.89	25.42	46.00	-20.58	QP

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Antenna Polarization: Vertical



Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor

**Test Frequency 1GHz-18GHz:****Low Channel (2402MHz)**

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4804	30.25	AV	V	30.18	8.01	30.42	38.02	54	-15.98
4804	31.49	AV	H	30.18	8.01	30.42	39.26	54	-14.74
4804	33.04	PK	V	30.18	8.01	30.42	40.81	74	-33.19
4804	36.22	PK	H	30.18	8.01	30.42	43.99	74	-30.01
17799	30.15	AV	V	31.45	8.52	32.69	37.43	54	-16.57
17799	29.4	AV	H	31.45	8.52	32.69	36.68	54	-17.32
17799	25.69	PK	V	31.45	8.52	32.69	32.97	74	-41.03
17799	26.43	PK	H	31.45	8.52	32.69	33.71	74	-40.29

**Middle Channel (2440MHz)**

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4880	27.15	AV	V	18.42	7.04	20.48	32.13	54	-21.87
4880	26.35	AV	H	18.42	7.04	20.48	31.33	54	-22.67
4880	28.04	PK	V	18.42	7.04	20.48	33.02	74	-40.98
4880	30.24	PK	H	18.42	7.04	20.48	35.22	74	-38.78
17796	31.08	AV	V	20.28	9.11	24.05	36.42	54	-17.58
17796	29.65	AV	H	20.28	9.11	24.05	34.99	54	-19.01
17796	28.04	PK	V	20.28	9.11	24.05	33.38	74	-40.62
17796	32.11	PK	H	20.28	9.11	24.05	37.45	74	-36.55

**High Channel (2480MHz)**

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4960	30.24	AV	V	19.72	10.48	19.48	40.96	54	-13.04
4960	32.04	AV	H	19.72	10.48	19.48	42.76	54	-11.24
4960	26.58	PK	V	19.72	10.48	19.48	37.3	74	-36.7
4960	31.06	PK	H	19.72	10.48	19.48	41.78	74	-32.22
17809	29.48	AV	V	22.04	13.05	25.06	39.51	54	-14.49
17809	28.15	AV	H	22.04	13.05	25.06	38.18	54	-15.82
17809	32.69	PK	V	22.04	13.05	25.06	42.72	74	-31.28
17809	33.24	PK	H	22.04	13.05	25.06	43.27	74	-30.73

Note: 1. The testing has been conformed to  $10 \times 2480\text{MHz} = 24800\text{MHz}$ .

2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
Emission Level = Reading + Factor  
Margin = Emission Level - Limit



**Test Frequency: From 18GHz to 25GHz**

The measurements were more than 20dB below the limit and not reported.



## 7 Band Edge Measurement

Test Requirement	: Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.1 Test Procedure



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold



PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02

## 7.2 Test Result





## 8 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013



Test Limit Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

### 8.2 Test Result


Channel number	Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)
00	2402	762	>500
19	2440	756	>500
39	2480	753	>500





PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02





## 9 Maximum Peak Output Power



Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

### 9.1 Test Procedure


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

### 9.2 Test Result

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(W)	Pass/Fail
0	2402	-1.44	0.718	1W(30dBm)	PASS
19	2440	-0.39	0.914	1W(30dBm)	PASS
39	2480	0.11	1.026	1W(30dBm)	PASS









## 10 Power Spectral density

Test Requirement	: FCC CFR47 Part 15 Section 15.247
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

### 10.2 Test Result


Channel number	Channel frequency (MHz)	Power density (dBm/3kHz)	Required Limit (dBm/3kHz)	Pass/Fail
00	2402	-17.48	8	PASS
19	2440	-15.25	8	PASS
39	2480	-14.01	8	PASS

Note:

1. Measured power density(dBm) has offset with cable loss.




Ref 10 dBm Atten 20 dB Mkr1 2.4019800 GHz  
Peak Log -17.48 dBm  
10  
dB/  
M1 S2  
S3 FC  
AA  
Center 2.402 GHz Span 1.144 MHz  
#Res BW 3 kHz #VBW 10 kHz Sweep 130.8 ms (401 pts)





PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02





## **11 Antenna Application**

### **11.1 Antenna Requirement**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **11.2 Result**

The EUT'S antenna, permanent attached antenna, is internal antenna. The antenna's gain is 1.85dBi and meets the requirement.




PRECISE TESTING


## 12 Test Setup

Report No.: PTCDQ06170300203E-FC02

### Conducted Emissions




### Radiated Spurious Emissions Test Frequency From 30MHz-1000MHz



Test frequency from 1GHz-18GHz



Test frequency from 18GHz-25GHz







PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02


## 13 EUT Photos















PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02









PRECISE TESTING



Report No.: PTCDQ06170300203E-FC02





PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02





PRECISE TESTING

Report No.: PTCDQ06170300203E-FC02



\*\*\*\*\*THE END REPORT\*\*\*\*\*