Company Name: Hangzhou Tuya Information Technology Co.,Ltd Add: Room701,Building3,More Center,No.87 GuDun Road,Hangzhou,Zhejiang,China Tel: +86-571-86581786

Fax: +86-571-86581786 E-mail: mikeshou@tuya.com

Applicant		Hangzhou Tuya Information Technology Co.,Ltd				
FCC ID:		2ANDL-WR3E				
		Section	15.212 Modu	lar Transmitters		
Request fo	r Modular	Approval	□ Request	for Limited Modular Appro	val	
		Requirement	s	EUT Conditions	Com	ply(Y/N)
		Single Mo	odular Approv	val Requirements		
tr T m	ransmitter r he physical	elements of nust have their of crystal and tunted external tooks.	own shielding.	Refer to external photos. This module does have shield cover.	Y	
b ir m re	ouffered monputs are produle wiequirements	. ,	nputs (if such sure that the ith part 15 anditions of	All inputs to the modules are buffered through logic or microprocessor inputs. Refer to Schematics.	Y	
		ar transmitte ver supply reg		The Module uses the chip W302 HBI40PI with built-in power management components, the module power is DC 3.3V. Refer to schematics.	Υ	
wrefined to the control of the contr	equirement: 5.204(c). Toermanently unique" a connections intenna, ir professiona it5.203 is n an apply to	er transmitter enna and transm s of §§15.203, he antenna m attached or entenna coup between the m ncluding the I installation" ot applicable to be limited modu eaph (b) of this s	nission system 15.204(b) and ust either be remploy a ller (at all odule and the cable). The provision of modules but ular approvals		Υ	

5 The modular transmitter must be The modular transmitter tested in a stand-alone configuration, is connected to the controlled board when i.e., the module must not be inside another device during testing for testing. compliance with Please refer to setup part requirements. Unless the transmitter photo. module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to module must not contain the ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)). 6 Refer to the label. Υ If using a permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "ContainsTransmitter Module " FCC ID: 2ANDL-WR3E"Any similarwording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included

in the application for equipment must provide authorization, or, adequate instructions along with the module which explain requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. 7 The modular transmitter must Refer to manual comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application equipment for authorization. 8 transmitter modular must The EUT comply with any applicable RF comply with any applicable RF exposure requirements exposure requirements in its final in its final configuration. configuration.

Sincerely Yours,

Signature: Xiao dong Shou

Typed or Printed Name: Xiaodong.Shou

Title: General Manager