Cover Letter-Wireless Charger Approval

FCC ID: 2ANS4-KWA-01 Date: 27 Oct, 2017

Gentlemen:

There's a KWA-01 that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below, KWA-01, with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5.2 requirements.

Company:	BOO YOUNG INDUSTRY CO.
Product Name:	Kabis Wireless Charger
Model Number:	KWA-01
FCC ID:	2ANS4-KWA-01

KDB 680106 D01 Section 5.2 Requirements:	Product Technical Specification:	Result:
a) Power transfer frequency is less that 1 MHz	0.137 ~ 0.183 MHz	Complied
b) Output power from each primary coil is less than	9 Watts	Not
5 Watts		Complied
c) The transfer system includes only single primary	The transfer system including a	Complied
and secondary coils. This includes charging systems	charging system with one primary	
that may have multiple primary coils and clients	coil is to detect and allow only	
that are able to detect and allow coupling only	between individual pairs of coils.	
between individual pairs of coils		
d) Client device is inserted in or placed directly in	Client device is placed directly in	Complied
contact with the transmitter	contact with the transmitter.	
e) The maximum coupling surface area of the	EUT coupling surface area of	Complied
transmit (charging) device is between 60 cm2 and	device is 105.84 cm2	
400 cm2.		
f) Aggregate leakage fields at 10 cm surrounding	E-Field: 18.70 V/m(max. at 10 cm)	Complied
the device from all simultaneous transmitting coils	< 184.20 V/m (30% of the limit)	
are demonstrated to be less than 30% of the MPE	H-Field: 0.360 A/m(max. at 10	
limit.	cm) $< 0.489 \text{ A/m} (30\% \text{ of the limit})$	

Sincerely, By:	MA	Harim Lee	
(Signature1)		(Print name)	
Γitle:	Technical Manager		
On behalf of:	SGS Korea Co., Ltd.	(Company Name)	
Γelephone:	+82-31-428-0903		