

RF EXPOSURE REPORT

for

Model Number: CBAR-25

FCC ID: 2ANYRCBAR-25

Prepared for : PT. Eyro Digital Teknologi

Address : Jl, Amir Mahmud IX/23 Gunung Anyar, Surabaya 60294, Indonesia

Prepared by : Shenzhen BCTC Testing Co., Ltd.

BCTC Building & 1-2F, East of B Building, Pengzhou Industrial,
Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an

Address : District, Shenzhen, China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{(min. test separation distance, mm)}} \right]$$

* $[\sqrt{f(\text{GHz})}]$

Frequency MHz	tune up power tolerance (dBm)	Maximum Tune up output power (dBm)	max. output power(mW)	Separation distance mm	RF exposure
2402	0±1	1	1.26	5	0.39

The Max RF exposure is 0.39.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.