FCC ID: 2AO2D-M055MGN

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field Power		Average Time				
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)	_				
	(A) Limits for Occupational/Control Exposures							
300-1500			F/300	6				
1500-100000			5	6				
	(B) Limits for General Population/Uncontrol Exposures							
300-1500			F/1500	6				
1500-100000		1		30				

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm², If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

WIFI and BT cannot transmit at the same time

Wifi 2.4G---Antenna 1 Antenna gain: 2.93 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
	2412	18.40	17 to 19	19	1.96	0.0310	1
11b	2437	18.06	17 to 19	19	1.96	0.0310	1
	2462	18.37	17 to 19	19	1.96	0.0310	1
	2412	19.05	18 to 20	20	1.96	0.0390	1
11g	2437	19.06	18 to 20	20	1.96	0.0390	1
	2462	19.23	18 to 20	20	1.96	0.0390	1
	2412	19.18	18 to 20	20	1.96	0.0390	1
11n HT20	2437	19.12	18 to 20	20	1.96	0.0390	1
	2462	19.39	18 to 20	20	1.96	0.0390	1

Wifi 2.4G---Antenna 2 Antenna gain: 4.77 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
	2412	18.37	17 to 19	19	3.00	0.0474	1
11b	2437	18.08	17 to 19	19	3.00	0.0474	1
	2462	18.36	17 to 19	19	3.00	0.0474	1
	2412	19.18	18 to 20	20	3.00	0.0597	1
11g	2437	19.16	18 to 20	20	3.00	0.0597	1
	2462	19.29	18 to 20	20	3.00	0.0597	1
	2412	19.05	18 to 20	20	3.00	0.0597	1
11n HT20	2437	19.01	18 to 20	20	3.00	0.0597	1
	2462	19.21	18 to 20	20	3.00	0.0597	1

Wifi 2.4G---MIMO Antenna gain: 4.77 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
	2412	22.13	21 to 23	23	3.00	0.12	1
11n HT20	2437	22.08	21 to 23	23	3.00	0.12	1
	2462	22.31	21 to 23	23	3.00	0.12	1

BT/BLE Antenna gain: 3.97 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
	2402	8.598	7 to 9	9	2.49	0.0039	1
GFSK	2441	9.838	8 to 10	10	2.49	0.0050	1
	2480	9.679	8 to 10	10	2.49	0.0050	1
	2402	8.606	7 to 9	9	2.49	0.0039	1
pi/4-DQPSK	2441	9.380	8 to 10	10	2.49	0.0050	1
	2480	9.024	8 to 10	10	2.49	0.0050	1
	2402	9.062	8 to 10	10	2.49	0.0050	1
8DPSK	2441	9.801	8 to 10	10	2.49	0.0050	1
	2480	9.551	8 to 10	10	2.49	0.0050	1
GFSK	2402	5.261	4 to 6	6	2.49	0.0020	1
(BLE)	2440	6.494	5 to 7	7	2.49	0.0025	1
(DLE)	2480	6.833	5 to 7	7	2.49	0.0025	1

Wifi 5G Antenna gain: 5.57 dBi

modulation	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
UNII-1	20.35	19 to 21	21	3.60	0.0902	1
UNII-2A	19.75	18 to 20	20	3.60	0.0716	1
UNII-2C	18.13	17 to 19	19	3.60	0.0569	1
UNII-3	17.05	16 to 18	18	3.60	0.0452	1