

## Attachment 2. – SAR Test Plots

**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.9 \text{ mho/m}$ ;  $\epsilon_r = 41.02$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Left Touch, GSM850 Ch. 190, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.15 dB  
Peak SAR (extrapolated) = 0.147 mW/g  
SAR(1 g) = 0.115 mW/g; SAR(10 g) = 0.085 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.9 \text{ mho/m}$ ;  $\epsilon_r = 41.02$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Right Touch, GSM850 Ch. 190, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 0.136 mW/g  
SAR(1 g) = 0.108 mW/g; SAR(10 g) = 0.081 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.9 \text{ mho/m}$ ;  $\epsilon_r = 41.02$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Left Tilt, GSM850 Ch. 190, Ant Internal, Standard Battery**

**Area Scan (81x131x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = -0.16 dB  
Peak SAR (extrapolated) = 0.098 mW/g  
SAR(1 g) = 0.076 mW/g; SAR(10 g) = 0.057 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.9 \text{ mho/m}$ ;  $\epsilon_r = 41.02$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Right Tilt, GSM850 Ch. 190, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = -0.17 dB  
Peak SAR (extrapolated) = 0.067 mW/g  
SAR(1 g) = 0.052 mW/g; SAR(10 g) = 0.039 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.414 \text{ mho/m}$ ;  $\epsilon_r = 40.252$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Left Touch, PCS1900 Ch. 66L, Ant Internal, Standard Battery**

**Area Scan (81x131x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.00 dB  
Peak SAR (extrapolated) = 0.216 mW/g  
SAR(1 g) = 0.143 mW/g; SAR(10 g) = 0.092 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.414 \text{ mho/m}$ ;  $\epsilon_r = 40.252$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Right Touch, PCS1900 Ch. 661, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = -0.09 dB  
Peak SAR (extrapolated) = 0.308 mW/g  
SAR(1 g) = 0.205 mW/g; SAR(10 g) = 0.128 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.414 \text{ mho/m}$ ;  $\epsilon_r = 40.252$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Left Tilt, PCS1900 Ch. 661, Ant Internal, Standard Battery**

**Area Scan (81x131x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = -0.07 dB  
Peak SAR (extrapolated) = 0.052 mW/g  
SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.020 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.414 \text{ mho/m}$ ;  $\epsilon_r = 40.252$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp: 22.5

**Right Tilt, PCS1900 Ch. 661, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.10 dB  
Peak SAR (extrapolated) = 0.061 mW/g  
SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.025 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.909 \text{ mho/m}$ ;  $\epsilon_r = 42.876$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-19; Ambient Temp: 22.4 Tissue Temp: 22.5

**Left Touch, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.03 dB  
Peak SAR (extrapolated) = 0.098 mW/g  
SAR(1 g) = 0.078 mW/g; SAR(10 g) = 0.059 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.909 \text{ mho/m}$ ;  $\epsilon_r = 42.876$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-19; Ambient Temp: 22.4 Tissue Temp: 22.5

**Right Touch, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 0.077 mW/g  
SAR(1 g) = 0.060 mW/g; SAR(10 g) = 0.045 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.909$  mho/m;  $\epsilon_r = 42.876$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-19; Ambient Temp: 22.4 Tissue Temp: 22.5

**Left Tilt, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**

**Area Scan (81x131x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 0.059 mW/g  
SAR(1 g) = 0.046 mW/g; SAR(10 g) = 0.035 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.909 \text{ mho/m}$ ;  $\epsilon_r = 42.876$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-19; Ambient Temp: 22.4 Tissue Temp: 22.5

**Right Tilt, WCDMA850 Ch. 4183, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = -0.13 dB  
Peak SAR (extrapolated) = 0.046 mW/g  
SAR(1 g) = 0.035 mW/g; SAR(10 g) = 0.026 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.411$  mho/m;  $\epsilon_r = 39.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp: 22.4

**Left Touch, WCDMA1900 Ch. 9400, Ant Internal, Standard Battery**

**Area Scan (81x131x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.07 dB  
Peak SAR (extrapolated) = 0.281 mW/g  
SAR(1 g) = 0.182 mW/g; SAR(10 g) = 0.114 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.411 \text{ mho/m}$ ;  $\epsilon_r = 39.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp: 22.4

**Right Touch, WCDMA1900 Ch. 9400, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.00 dB  
Peak SAR (extrapolated) = 0.487 mW/g  
SAR(1 g) = 0.313 mW/g; SAR(10 g) = 0.194 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.411$  mho/m;  $\epsilon_r = 39.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp: 22.4

**Left Tilt, WCDMA1900 Ch. 9400, Ant Internal, Standard Battery**

**Area Scan (81x131x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = 0.18 dB  
Peak SAR (extrapolated) = 0.050 mW/g  
SAR(1 g) = 0.032 mW/g; SAR(10 g) = 0.021 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.411$  mho/m;  $\epsilon_r = 39.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Right Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.76, 7.76, 7.76); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial: 1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp: 22.4

**Right Tilt, WCDMA1900 Ch. 9400, Ant Internal, Standard Battery**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = 0.16 dB  
Peak SAR (extrapolated) = 0.074 mW/g  
SAR(1 g) = 0.047 mW/g; SAR(10 g) = 0.030 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850\_10; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.992$  mho/m;  $\epsilon_r = 53.501$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(9.03, 9.03, 9.03); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Front, GSM850 GPRS Class 10 Ch. 190, Ant Internal****Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.297 mW/g

SAR(1 g) = 0.144 mW/g; SAR(10 g) = 0.088 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.992$  mho/m;  $\epsilon_r = 53.501$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(9.03, 9.03, 9.03); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Rear, GSM850 Ch. 190, Ant Internal****Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.216 mW/g

SAR(1 g) = 0.177 mW/g; SAR(10 g) = 0.136 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.992$  mho/m;  $\epsilon_r = 53.501$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(9.03, 9.03, 9.03); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Rear, GSM850 GPRS Class 8 Ch. 190, Ant Internal****Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.207 mW/g

SAR(1 g) = 0.170 mW/g; SAR(10 g) = 0.130 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: GSM 850\_10; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.992$  mho/m;  $\epsilon_r = 53.501$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(9.03, 9.03, 9.03); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Rear, GSM850 GPRS Class 10 Ch. 190, Ant Internal****Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.315 mW/g

SAR(1 g) = 0.183 mW/g; SAR(10 g) = 0.118 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.507 \text{ mho/m}$ ;  $\epsilon_r = 52.024$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Front, PCS1900 Ch. 661, Ant Internal****Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.096 mW/g

SAR(1 g) = 0.585 mW/g; SAR(10 g) = 0.337 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.507 \text{ mho/m}$ ;  $\epsilon_r = 52.024$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Front, PCS1900 GPRS Class 8 Ch. 661, Ant Internal****Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = -0.21 dB

Peak SAR (extrapolated) = 1.240 mW/g

SAR(1 g) = 0.644 mW/g; SAR(10 g) = 0.376 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS1900\_Class 10; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.507 \text{ mho/m}$ ;  $\epsilon_r = 52.024$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Front, PCS1900 GPRS Class 10 Ch. 661, Ant Internal****Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.271 mW/g

SAR(1 g) = 0.667 mW/g; SAR(10 g) = 0.390 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: PCS1900\_Class 10; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.507$  mho/m;  $\epsilon_r = 52.024$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-11; Ambient Temp: 22.2; Tissue Temp:22.5

**Touch from Body, Rear, PCS1900 GPRS Class 10 Ch. 661, Ant Internal****Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.434 mW/g

SAR(1 g) = 0.271 mW/g; SAR(10 g) = 0.157 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.954 \text{ mho/m}$ ;  $\epsilon_r = 53.372$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(9.03, 9.03, 9.03); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-10-19; Ambient Temp: 22.4 Tissue Temp:22.5

**Touch from Body, Front, WCDMA850 Ch. 4183, Ant Internal****Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.256 mW/g

SAR(1 g) = 0.119 mW/g; SAR(10 g) = 0.066 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 850 ; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.954 \text{ mho/m}$ ;  $\epsilon_r = 53.372$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(9.03, 9.03, 9.03); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-19; Ambient Temp: 22.4 Tissue Temp:22.5

**Touch from Body, Rear, WCDMA850 Ch. 4183, Ant Internal**

**Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Power Drift = 0.04 dB  
Peak SAR (extrapolated) = 0.223 mW/g  
SAR(1 g) = 0.125 mW/g; SAR(10 g) = 0.081 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.475$  mho/m;  $\epsilon_r = 53.066$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Front, WCDMA1900 Ch. 9262, Ant Internal**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = 0.14 dB  
Peak SAR (extrapolated) = 1.690 mW/g  
SAR(1 g) = 0.947 mW/g; SAR(10 g) = 0.563 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.513$  mho/m;  $\epsilon_r = 53.057$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Front, WCDMA1900 Ch. 9400, Ant Internal**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 1.948 mW/g  
SAR(1 g) = 1.16 mW/g; SAR(10 g) = 0.697 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.544$  mho/m;  $\epsilon_r = 52.962$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Front, WCDMA1900 Ch. 9538, Ant Internal**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.17 dB  
Peak SAR (extrapolated) = 2.346 mW/g  
SAR(1 g) = 1.34 mW/g; SAR(10 g) = 0.752 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.475$  mho/m;  $\epsilon_r = 53.066$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Rear, WCDMA1900 Ch. 9262, Ant Internal****Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (interpolated) = 1.03 mW/g

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.181 mW/g

SAR(1 g) = 0.725 mW/g; SAR(10 g) = 0.433 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1852.4 \text{ MHz}$ ;  $\sigma = 1.475 \text{ mho/m}$ ;  $\epsilon_r = 53.066$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Rear, WCDMA1900 Ch. 9262, Ant Internal****Area Scan (81x121x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.064 mW/g

SAR(1 g) = 0.676 mW/g; SAR(10 g) = 0.414 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.513$  mho/m;  $\epsilon_r = 53.057$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Rear, WCDMA1900 Ch. 9400, Ant Internal**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 1.380 mW/g  
SAR(1 g) = 0.823 mW/g; SAR(10 g) = 0.477 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.513$  mho/m;  $\epsilon_r = 53.057$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Rear, WCDMA1900 Ch. 9400, Ant Internal**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube I:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 1.190 mW/g  
SAR(1 g) = 0.697 mW/g; SAR(10 g) = 0.424 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: WCDMA 1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.544$  mho/m;  $\epsilon_r = 52.962$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section


**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(7.34, 7.34, 7.34); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335  
Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679  
Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-10-22; Ambient Temp: 22.3 Tissue Temp:22.4

**Touch from Body, Rear, WCDMA1900 Ch. 9538, Ant Internal**

**Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm  
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Power Drift = -0.19 dB  
Peak SAR (extrapolated) = 1.351 mW/g  
SAR(1 g) = 0.805 mW/g; SAR(10 g) = 0.463 mW/g



**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: W-LAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437 \text{ MHz}$ ;  $\sigma = 1.979 \text{ mho/m}$ ;  $\epsilon_r = 54.006$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(6.97, 6.97, 6.97); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)


Test Date: 2012-09-12; Ambient Temp: 22.1; Tissue Temp:22.2

**Touch from Body, Front, W-LAN(802.11b) Ch. 6, Ant Internal****Area Scan (81x141x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$ **Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.045 mW/g

SAR(1 g) = 0.00763 mW/g; SAR(10 g) = 0.00272 mW/g





**DIGITAL EMC CO., LTD****DUT: HM40; Type: Bar**

Communication System: W-LAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.979$  mho/m;  $\epsilon_r = 54.006$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

**DASY5 Configuration:**

Probe: EX3DV4 - SN3866; ConvF(6.97, 6.97, 6.97); Calibrated: 2012-06-20; ; Electronics: DAE4 Sn1335

Phantom: SAM with CRP\_20120521; Type: SAM; Serial:1679

Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Test Date: 2012-09-12; Ambient Temp: 22.1; Tissue Temp:22.2

**Touch from Body, Rear, W-LAN(802.11b) Ch. 6, Ant Internal****Area Scan (131x201x1):** Measurement grid: dx=15mm, dy=15mm**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Power Drift = -0.21 dB

Peak SAR (extrapolated) = 0.048 mW/g

SAR(1 g) = 0.008 mW/g; SAR(10 g) = 0.00293 mW/g

