



BLUEBIRD INC.

(Dogok-dong, SEI Tower 13~14), ., 39, Eonju-ro30-gil, Gangnam-gu,
Seoul, Korea

Tel. +82-70-7730-8210

Fax +82-2-548-0870

TUNE-UP PROCEDURE

Programming of this product's transmit frequencies can be performed ONLY by the manufacturer or by service or maintenance personnel. The operator can not program transmit frequencies using the equipment's external operation.

WCDMA/GSM's Max. Target PWR and Tolerance inform as following the table in next page.

GSM 850	GSM	EDGE
	(dBm)	(dBm)
Max. Target PWR (dBm)	33.00	27.00
Tolerance (± dB)	2.00	2.00
PCS 1900	GSM	EDGE
	(dBm)	(dBm)
Max. Target PWR (dBm)	30.00	25.50
Tolerance (± dB)	2.00	2.00

BAND II	PCS WCDMA	HSDPA			
		Subtest1	Subtest2	Subtest3	Subtest4
Max. Target PWR (dBm)	23.00	22.50	22.50	22.00	22.50
Tolerance (± dB)	2.00	2.00	2.00	2.00	2.00
BAND V	Cellular WCDMA	HSDPA			
		Subtest1	Subtest2	Subtest3	Subtest4
Max. Target PWR (dBm)	23.50	22.50	22.50	22.50	22.50
Tolerance (± dB)	2.00	2.00	2.00	2.00	2.00