



ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : W163R-D042

AGR No. : A161A-258

Applicant : BLUEBIRD INC.

Address : (Dogok-dong, SEI Tower13,14)39, Eonjuro30-gil, Gangnam-gu, Seoul, South Korea

Manufacturer : BLUEBIRD INC.

Address : (Dogok-dong, SEI Tower13,14)39, Eonjuro30-gil, Gangnam-gu, Seoul, South Korea

Type of Equipment : Premium Tablet

FCC ID. : SS4ST100

Model Name : ST100

Multiple Model Name: N/A

Serial number : N/A

Total page of Report: 83 pages (including this page)

Date of Incoming : February 01, 2016

Date of issue : March 16, 2016

SUMMARY

The equipment complies with the regulation; FCC PART 15 SUBPART C Section 15.247

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

ONETECH Corp.

pproved by:

Sung-ik, Han/ Managing Director

Report No.: W163R-D042

ONETECH Corp.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

EMC-002 (Rev.3)



CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	6
2. TEST SUMMARY	7
2.1 TEST ITEMS AND RESULTS	7
2.2 Additions, deviations, exclusions from standards	7
2.3 RELATED SUBMITTAL(S) / GRANT(S)	7
2.4 PURPOSE OF THE TEST	7
2.5 TEST METHODOLOGY	7
2.6 TEST FACILITY	8
3. GENERAL INFORMATION	9
3.1 PRODUCT DESCRIPTION	g
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT	9
4. EUT MODIFICATIONS	9
5. SYSTEM TEST CONFIGURATION	10
5.1 JUSTIFICATION	
5.3 MODE OF OPERATION DURING THE TEST	
5.4 CONFIGURATION OF TEST SYSTEM	
5.5 ANTENNA REQUIREMENT	
6. PRELIMINARY TEST	12
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS	12
6.2 GENERAL RADIATED EMISSIONS TESTS	12
7. MINIMUM 20 DB BANDWIDTH	13
7.1 OPERATING ENVIRONMENT	13
7.2 TEST SET-UP	13
7.3 TEST EQUIPMENT USED	13
7.4 TEST DATA FOR 1 MBPS	14
7.5 TEST DATA FOR 2 MBPS	16
7.6 TEST DATA FOR 3 MBPS	18
8. HOPPING FREQUENCY SEPARATION	20
8.1 OPERATING ENVIRONMENT	20
8.2 TEST SET-UP	20

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)

It should not be reproduced except in full, without the written approval of ONETECH Corp.



8.3 TEST EQUIPMENT USED	20
8.4 TEST DATA FOR 1 MBPS	21
8.5 TEST DATA FOR 2 MBPS	
8.6 TEST DATA FOR 3 MBPS	23
9. NUMBER OF HOPPING CHANNELS	24
9.1 OPERATING ENVIRONMENT	24
9.2 TEST SET-UP	24
9.3 TEST EQUIPMENT USED.	24
9.4 TEST DATA FOR 1 MBPS	25
9.5 TEST DATA FOR 2 MBPS	28
9.6 TEST DATA FOR 3 MBPS	31
10. TIME OF OCCUPANCY	34
10.1 OPERATING ENVIRONMENT	34
10.2 TEST SET-UP	34
10.3 TEST EQUIPMENT USED	34
10.4 TEST DATA FOR 1 MBPS	35
10.5 TEST DATA FOR 2 MBPS	38
10.6 TEST DATA FOR 3 MBPS	41
11. MAXIMUM PEAK OUTPUT POWER	44
11.1 OPERATING ENVIRONMENT	44
11.2 TEST SET-UP	44
11.3 TEST EQUIPMENT USED	44
11.4 TEST DATA FOR 1 MBPS	45
11.5 TEST DATA FOR 2 MBPS	48
11.6 TEST DATA FOR 3 MBPS	51
12. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND	54
12.1 OPERATING ENVIRONMENT	54
12.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	54
12.3 TEST SET-UP FOR RADIATED MEASUREMENT	54
12.4 TEST EQUIPMENT USED	54
12.5 TEST DATA FOR CONDUCTED EMISSION	55
12.5.1 Test data for 1 Mbps	55
12.5.2 Test data for 2 Mbps	61
12.5.3 Test data for 3 Mbps	67
12.6 TEST DATA FOR CHARGING & TRANSMITTING MODE RADIATED EMISSION	73
It should not be reproduced except in full, without the written approval of ONETECH Corp.	EMC-002 (Rev.3)





12.6.1 Radiated Emission which fall in the Restricted Band	73
12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz	76
12.6.3 Spurious Radiated Emission	79
13. CONDUCTED EMISSION TEST	81
13.1 OPERATING ENVIRONMENT	81
13.2 Test set-up	81
13.3 TEST EQUIPMENT USED	81
13.4 TEST DATA FOR CHARGING & TRANSMITTING MODE	82



Page 5 of 83 Report No.: W163R-D042

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
W163R-D042	March 16, 2016	Initial Issue	All

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea



Page 6 of 83 Report No.: W163R-D042

1. VERIFICATION OF COMPLIANCE

APPLICANT : BLUEBIRD INC.

ADDRESS : (Dogok-dong, SEI Tower13,14)39, Eonjuro30-gil, Gangnam-gu, Seoul, South Korea

CONTACT PERSON : Jae-ho, Lee / Assistant Manager

TELEPHONE NO : +82-70-7730-8210

FCC ID : SS4ST100 MODEL NAME : ST100 SERIAL NUMBER : N/A

DATE : March 16, 2016

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
KIND OF EQUIPMENT	Premium Tablet
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	None
FINAL TEST WAS CONDUCTED ON	3 m Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (1)	Carrier Frequency Separation	Met the Limit / PASS
15.247 (a) (1) (iii)	Minimum Number of Hopping Channels	Met the Limit / PASS
15.247 (a) (1) (iii)	Average Time of Occupancy	Met the Limit / PASS
15.247 (b) (1)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.209	Radiated Emission Limits, General Requirement	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 301-14, Daessangnyeong-ri, Chowol-eup, Gwangju-si, Gyeonggi-do, 464-862 Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-4617/ G-666/ T-1842

IC (Industry Canada) – Registration No. Site# 3736A-3

-. Site Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) - Designation No. KR0013

Report No.: W163R-D042





3. GENERAL INFORMATION

3.1 Product Description

The BLUEBIRD INC., Model ST100 (referred to as the EUT in this report) is a Premium Tablet. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Premium 7	Cablet
	1 Tellifulli 1	abict
OPERATING FREQUENCY	2 402 MH	z ~ 2 480 MHz
	1 Mbps	0.10 dBm
RF OUTPUT POWER	2 Mbps	-0.11 dBm
	3 Mbps	0.42 dBm
NUMBER OF CHANNEL	79 Channels	
MODULATION TYPE	GFSK for 1 Mbps, π/4-DQPSK for 2 Mbps, 8-DPSK for 3 Mbps	
ANTENNA TYPE	PIFA Antenna	
ANTENNA GAIN	0.49 dBi	
LIST OF EACH OSC. OR CRYSTAL.		
FREQ.(FREQ.>=1 MHz)	26 MHz	
RATED SUPPLY VOLTAGE	DC 3.8 V	

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

Report No.: W163R-D042





5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Display Controller Board	Kingdisplay	KD101N37-40NA-A1-REVB	
Display Panel	N/A	N/A	
Main Board	N/A	N/A	
Battery	Guandong TeamGiant New Energy Tech.Limited Liability Co.,LTD	BAT-ST100	
SUB Board	N/A	TVE1015IST-SUB-V1.1	
Sensor	N/A	CMK-TVE1013-B-V5B1.0	
Antenna	N/A	MICRO RF Rev 3.0	
Camera module	N/A	CMK-TVE1010I-F-V2B2.0	
Touch sensor controller Board	N/A	101332C-Q-00	
Wireless Module	HUAWEI TECHNOLOGIES CO.,LTD.	MU739	QISMU739

5.2 Peripheral equipment

Model	Manufacturer Description		Connected to
N/A	N/A	N/A	N/A

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea



DUELECH

5.3 Mode of operation during the test

For Bluetooth function testing, software used to control the EUT for staying in continuous transmitting and receiving mode is programmed. The EUT was set at Low Channel (2 402 MHz), Middle Channel (2 441 MHz), and High Channel (2 480 MHz) with each data transfer rate, 1 Mbps, 2 Mbps, and 3 Mbps. To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XZ" axis, but the worst data was recorded in this test report.

5.4 Configuration of Test System

Line Conducted Test: The EUT was tested in a Transmitting mode. The EUT was connected to USB and the

power of USB was connected to Adapter. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using

Report No.: W163R-D042

the procedure in ANSI C63.10: 2013 to determine the worse operating conditions.

Radiated Emission Test: The EUT was tested in a charging mode and Transmitter mode. Preliminary radiated

emissions test were conducted using the procedure in ANSI C63. 10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi

Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned

three orthogonal planes to obtain the highest reading on the field strength meter. Once

maximum reading was determined, the search antenna was raised and lowered in both

vertical and horizontal polarization.





5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The transmitter antenna of the EUT is a PIFA Antenna, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)	
Charging & Transmitting Mode	X	

6.2 General Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)	
Transmitting Mode		
Charging & Transmitting Mode	X	

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





7. MINIMUM 20 dB BANDWIDTH

7.1 Operating environment

Temperature : 23 °C

Relative humidity : 47 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 10 kHz, and peak detection was used. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.



7.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
-	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory } 223\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea$






7.4 Test data for 1 Mbps

-. Test Date : March 10, 2016

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402	923.10
Middle	2 441	923.10
High	2 480	923.10

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042




It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory } 223\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The State of Sta$





It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)






7.5 Test data for 2 Mbps

-. Test Date : March 10, 2016

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402	1 330.70
Middle	2 441	1 330.70
High	2 480	1 330.70

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042




It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE :#505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)





7.6 Test data for 3 Mbps


-. Test Date : March 10, 2016

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402	1 306.70
Middle	2 441	1 306.70
High	2 480	1 306.70



Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042




It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE :#505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)





8. HOPPING FREQUENCY SEPARATION

8.1 Operating environment

Temperature : $23 \, ^{\circ}\text{C}$

Relative humidity : 47 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 10 MHz. The analyzer is set to peak hold then a pseudo-random hopping sequence of the transmitter is captured. The mark delta function was used to measure the frequency separation between two adjacent hopping channels.



8.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
-	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory } 223\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea$






8.4 Test data for 1 Mbps


-. Test Date : March 10, 2016

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	615.40	Separated by a minimum of 25 kHz



Report No.: W163R-D042



It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





8.5 Test data for 2 Mbps


-. Test Date : March 10, 2016

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	887.13	Separated by a minimum of 25 kHz



Report No.: W163R-D042



It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE :#505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





8.6 Test data for 3 Mbps


-. Test Date : March 10, 2016

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	871.13	Separated by a minimum of 25 kHz



Report No.: W163R-D042



It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE :#505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





9. NUMBER OF HOPPING CHANNELS

9.1 Operating environment

Temperature : $23 \, ^{\circ}\text{C}$

Relative humidity : 47 % R.H.

9.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 100 MHz and the resolution bandwidth is set to 1 MHz. The analyzer is set to peak hold and then complete pseudo-random hopping sequence of the transmitter is captured.



9.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory } 223\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties of the properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties of the properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, } 123\text{-}28, Sangdaewon 1 Dong, } 123\text{-}28, Sangdaewon 2 Dong, } 123\text{-}28,$






9.4 Test data for 1 Mbps


-. Test Date : March 10, 2016

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
1 Mbps	79	Minimum of 15	64



Report No.: W163R-D042




It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)









9.5 Test data for 2 Mbps


-. Test Date : March 10, 2016

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
2 Mbps	79	Minimum of 15	64

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042




It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE :#505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-002 (Rev.3)

Report No.: W163R-D042

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea}$

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)









9.6 Test data for 3 Mbps


-. Test Date : March 10, 2016

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
3 Mbps	79	Minimum of 15	64

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042




It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE :#505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-002 (Rev.3)

Report No.: W163R-D042

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea}$

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)









10. TIME OF OCCUPANCY

10.1 Operating environment

Temperature : 23 °C

Relative humidity : 47 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The transmitter is set to operate in its normal frequency hopping mode. The center frequency of the spectrum analyzer is set to one of hopping channels near the center of the operating band and span is set to zero Hz. The sweep time is set to display one complete pulse. The mark delta function is used to measure the duration of the pulses.



10.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





10.4 Test data for 1 Mbps

-. Test Date : March 10, 2016

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 µs with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1600/2/79) for DH1, and 5.06 times (= 1600/4/79) for DH3, and 3.38 times (= 1600/6/79) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (s)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.380	10.13	31.6	121.64	400	
DH3	1.640	5.06	31.6	262.23	400	PASS
DH5	2.210	3.38	31.6	236.05	400	

Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.

Tested by: Jun-Hui, Lee / Senior Engineer


Report No.: W163R-D042

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)









10.5 Test data for 2 Mbps

-. Test Date : March 10, 2016

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 µs with 79 channels.

For 2-DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for 2-DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and 2-DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1600/2/79) for 2-DH1, and 5.06 times (= 1600/4/79) for 2-DH3, and 3.38 times (= 1600/6/79) for 2-DH5.

Packet Type	Pulse Time (ms)	me Hops per second Period Time with channels (s)		Total Dwell Time (ms)	Limit (ms)	Test Result
2-DH1	0.390	10.13	31.6	124.84	400	
2-DH3	1.190	5.06	31.6	190.28	400	PASS
2-DH5	1.190	3.38	31.6	127.10	400	


Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.

Tested by: Jun-Hui, Lee / Senior Engineer






EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)









10.6 Test data for 3 Mbps

-. Test Date : March 10, 2016

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μs with 79 channels.

For 3-DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for 3-DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and 3-DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1600/2/79) for 3-DH1, and 5.06 times (= 1600/4/79) for 3-DH3, and 3.38 times (= 1600/6/79) for 3-DH5.

Packet Type	Pulse Time (ms)	Hops per second Period Time with channels (ms)		Total Dwell Time (ms)	Limit (ms)	Test Result
3-DH1	0.390	10.13	31.6	124.84	400	
3-DH3	0.850	5.06	31.6	135.91	400	PASS
3-DH5	0.850	3.38	31.6	90.79	400	


Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.

Tested by: Jun-Hui, Lee / Senior Engineer






EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)









11. MAXIMUM PEAK OUTPUT POWER

11.1 Operating environment

Temperature : $23 \, ^{\circ}\text{C}$ Relative humidity : $47 \, \% \, \text{R.H}$

11.2 Test set-up

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The EUT was operating in transmit mode at the appropriate center frequency.



11.3 Test equipment used

	Model Number Manufacturer		Description	Serial Number	Last Cal.	
-	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)	

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory } 223\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea$



Page 45 of 83 Report No.: W163R-D042

11.4 Test data for 1 Mbps

-. Test Date : March 10, 2016


-. Test Result : Pass

CHANNEL	FREQUENCY	MEASURED VLAUE	LIMIT	MARGIN
CHANNEL	(MHz)	(dBm)	(dBm)	(dB)
LOW	LOW 2 402		21.00	21.77
MIDDLE	2 441	-0.13	21.00	21.13
HIGH	2 480	0.10	21.00	20.90

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Tested by: Jun-Hui, Lee / Senior Engineer






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)





Page 48 of 83 Report No.: W163R-D042

11.5 Test data for 2 Mbps

-. Test Date : March 10, 2016


-. Test Result : Pass

CHANNEL	FREQUENCY	MEASURED VLAUE	LIMIT	MARGIN
	(MHz)	(dBm)	(dBm)	(dB)
LOW	2 402	-1.21	21.00	22.21
MIDDLE	2 441	-0.37	21.00	21.37
HIGH	2 480	-0.11	21.00	21.11

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Tested by: Jun-Hui, Lee / Senior Engineer






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)





Page 51 of 83 Report No.: W163R-D042

11.6 Test data for 3 Mbps

-. Test Date : March 10, 2016


-. Test Result : Pass

CHANNEL	FREQUENCY	MEASURED VLAUE	LIMIT	MARGIN
CHANNEL	(MHz)	(dBm)	(dBm)	(dB)
LOW	2 402	-0.72	21.00	21.72
MIDDLE	2 441	0.14	21.00	20.86
HIGH	2 480	0.42	21.00	20.58

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Tested by: Jun-Hui, Lee / Senior Engineer






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)







12. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND

12.1 Operating environment

Temperature : 23 °C Relative humidity : 47 % R.H

12.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution and video bandwidth is set to 100 kHz, and peak detection was used.



12.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m, open-field test site. The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The frequency spectrum from 30 kHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 ms in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

12.4 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
□ -	ESCI	Rohde & Schwarz	EMI Test Receiver	101012	Nov. 02, 2015 (1Y)
-	ESU	Rohde & Schwarz	EMI Test Receiver	100261	Apr. 29, 2015 (1Y)
□ -	8564E	HP	Spectrum Analyzer	3650A00756	Apr. 28, 2015 (1Y)
□ -	FSP	Rohde & Schwarz	Spectrum Analyzer	100017	Oct. 07, 2015 (1Y)
■ -	310N	Sonoma Instrument	AMPLIFIER	312544	Apr. 29, 2015 (1Y)
■ -	FSV30	Rohde & Schwarz	Signal Analyzer	101372	Apr. 29, 2015 (1Y)
-	SCU-18	Rohde & Schwarz	PRE-AMPLIFIER	102209	Jun. 04, 2015 (1Y)
■ -	MA240	HD GmbH	Antenna Master	N/A	N/A
■ -	HD100	HD GmbH	Position Controller	N/A	N/A
-	DS420S	HD GmbH	Turn Table	N/A	N/A
■ -	HFH2-Z2	Rohde & Schwarz	Loop Antenna	879 285/26	Dec. 09, 2014 (2Y)
■ -	VULB9163	Schwarzbeck	TRILOG Broadband Antenna	9163-255	May 02, 2014 (2Y)
-	BBHA9120D	Schwarzbeck	Horn Antenna	BBHA9120D295	Aug. 31, 2015 (2Y)
-	BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178	N/A
■ -	83051A	Agilent	Microwave System Preamplifer	3950M00201	Apr. 30, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)


Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)



12.5 Test data for conducted emission



It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea







EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea










EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea (TEL: +82-31-746-8500 FAX: +82-31-746-8700)






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea








EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)







EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea










EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea (TEL: +82-31-746-8500 FAX: +82-31-746-8700)






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)








EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)






EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea

(TEL: +82-31-746-8500 FAX: +82-31-746-8700)







EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea










EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





EMC-002 (Rev.3)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





12.6 Test data for Charging & Transmitting Mode radiated emission

12.6.1 Radiated Emission which fall in the Restricted Band

12.6.1.1 Test data for 1 Mbps

-. Test Date : March 06, 2016

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode(Low Channel and High Channel)

-. Result : PASSED

Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBµV/m)	Margin (dB)	
Test Data for Low Channel										
	47.37	Peak	Н				38.97	74.00	35.03	
2 379.62	33.75	Average	Н		7.50		25.35	54.00	28.65	
	48.44	Peak	V	27.10		43.00	40.04	74.00	33.96	
2 371.43	33.81	Average	V				25.41	54.00	28.59	
			Test I	Oata for H	igh Chanr	nel				
2 490.77	47.84	Peak	Н				39.44	74.00	34.56	
2 490.78	34.04	Average	Н				25.64	54.00	28.36	
	48.20	Peak	V	27.10	7.50	43.00	39.80	74.00	34.20	
2 492.48	33.94	Average	V				25.54	54.00	28.46	

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





12.6.1.2 Test data for 2 Mbps

-. Test Date : March 06, 2016

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode(Low Channel and High Channel)

-. Result : PASSED

Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBµV/m)	Limits (dBµV/m)	Margin (dB)		
Test Data for Low Channel											
	47.67	Peak	Н				39.27	74.00	34.73		
2 378.72	33.75	Average	Н		0 7.50	43.00	25.35	54.00	28.65		
	47.93	Peak	V	27.10			39.53	74.00	34.47		
2 380.39	33.73	Average	V				25.33	54.00	28.67		
			Test I	Oata for H	igh Chanr	nel					
	48.22	Peak	Н				39.82	74.00	34.18		
2 488.72	34.02	Average	Н			43.00	25.62	54.00	28.38		
- 10- 11	48.19	Peak	V	27.10	7.50		39.79	74.00	34.21		
2 487.46	34.04	Average	V				25.64	54.00	28.36		

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Tested by: Jun-Hui, Lee / Senior Engineer





12.6.1.3 Test data for 3 Mbps

-. Test Date : March 06, 2016

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode(Low Channel and High Channel)

-. Result : PASSED

Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBµV/m)	Margin (dB)		
Test Data for Low Channel											
	48.18	Peak	Н				39.78	74.00	34.22		
2 386.81	33.71	Average	Н		7.50	43.00	25.31	54.00	28.69		
	48.01	Peak	V	27.10			39.61	74.00	34.39		
2 380.25	33.74	Average	V				25.34	54.00	28.66		
			Test I	Oata for H	igh Chanr	nel					
	47.85	Peak	Н				39.45	74.00	34.55		
2 486.23	34.02	Average	Н			43.00	25.62	54.00	28.38		
2 407 7 6	48.72	Peak	V	27.10	7.10 7.50		40.32	74.00	33.68		
2 487.76	34.03	Average	V				25.63	54.00	28.37		

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz

12.6.2.1 Test data for 1 Mbps

-. Test Date : March 06, 2016

-. Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,

100 kHz for Peak Mode for the emissions outside restricted band

-. Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode

-. Frequency range : 1 GHz ~ 26.5 GHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency (GHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBµV/m)	Margin (dB)		
	• /			Data for I	Low Chan	nel					
	51.55	Peak	Н				50.75	74.00	23.25		
4 804.00	37.95	Average	Н	• • • •			37.15	54.00	16.85		
	51.67	Peak	V	30.60	11.10	42.50	50.87	74.00	23.13		
	37.48	Average	V				36.68	54.00	17.32		
	Test Data for Middle Channel										
	52.10	Peak	Н				51.50	74.00	22.50		
	39.28	Average	Н				38.68	54.00	15.32		
4 882.00	51.75	Peak	V	30.70	11.20	42.50	51.15	74.00	22.85		
	38.39	Average	V				37.79	54.00	16.21		
			Test	Data for H	ligh Chan	nel					
	51.61	Peak	Н				51.21	74.00	22.79		
1.0.10.05	38.45	Average	Н	•			38.05	54.00	15.95		
4 960.00	51.43	Peak	V	30.80	11.30	42.50	51.03	74.00	22.97		
	38.29	Average	V				37.89	54.00	16.11		

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical, "*" Frequency fall in restricted band

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





12.6.2.2 Test data for 2 Mbps

-. Test Date : March 06, 2016

-. Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,

100 kHz for Peak Mode for the emissions outside restricted band

-. Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode

-. Frequency range : 1 GHz ~ 26.5 GHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency	Reading	Detector	Ant. Pol.	Ant.	Cable	Amp	Total	Limits	Margin		
(GHz)	(dBµV)	Mode	(H/V)	Factor	Loss	Gain	(dBµV/m)	(dBµV/m)	(dB)		
			Test	Data for I	Low Chan	nel					
	51.38	Peak	Н				50.58	74.00	23.42		
4 804.00	37.24	Average	Н	20.60	11.10	42.50	36.44	54.00	17.56		
	52.16	Peak	V	30.60	11.10	42.50	51.36	74.00	22.64		
	38.44	Average	V				37.64	54.00	16.36		
Test Data for Middle Channel											
	52.65	Peak	Н	30.70	11.20	42.50	52.05	74.00	21.95		
	37.50	Average	Н				36.90	54.00	17.10		
4 882.00	52.03	Peak	V				51.43	74.00	22.57		
	37.38	Average	V				36.78	54.00	17.22		
			Test	Data for H	ligh Chan	nel					
	52.02	Peak	Н				51.62	74.00	22.38		
	67.21	Average	Н				66.81	54.00	-12.81		
4 960.00	51.86	Peak	V	30.80	11.30	42.50	51.46	74.00	22.54		
	37.32	Average	V				36.92	54.00	17.08		

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical, "*" Frequency fall in restricted band

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory } 223\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties of the properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties of the properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea \\ \text{The properties } 123\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, } 123\text{-}28, Sangdaewon 1 Dong, } 123\text{-}28, Sangdaewon 2 Dong, } 123\text{-}28,$





12.6.2.3 Test data for 3 Mbps

-. Test Date : March 06, 2016

-. Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,

100 kHz for Peak Mode for the emissions outside restricted band

-. Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode

-. Frequency range : 1 GHz ~ 26.5 GHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency (GHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBµV/m)	Margin (dB)		
Test Data for Low Channel											
	51.97	Peak	Н		11.10		51.17	74.00	22.83		
	36.82	Average	Н				36.02	54.00	17.98		
4 804.00	51.22	Peak	V	30.60		42.50	50.42	74.00	23.58		
	37.02	Average	V				36.22	54.00	17.78		
Test Data for Middle Channel											
	51.58	Peak	Н	30.70	11.20	42.50	50.98	74.00	23.02		
	36.86	Average	Н				36.26	54.00	17.74		
4 882.00	51.29	Peak	V				50.69	74.00	23.31		
	37.00	Average	V				36.40	54.00	17.60		
	Test Data for High Channel										
	51.58	Peak	Н				51.18	74.00	22.82		
	36.17	Average	Н	30.80		42.50	35.77	54.00	18.23		
4 960.00	51.42	Peak	V		11.30		51.02	74.00	22.98		
	36.49	Average	V				36.09	54.00	17.91		

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical, "*" Frequency fall in restricted band

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea



Page 79 of 83 Report No.: W163R-D042

12.6.3 Spurious Radiated Emission

12.6.3.1 Test Data for 30 MHz ~ 1 000 MHz


Humidity Level : $(43 \sim 44)$ % R.H. Temperature: $(23 \sim 24)$ °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Premium Tablet Date: March 09, 2016

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING QP	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	[dBuV]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
Н	orizontal -									
1 2	35.820 204.600	53.2 46.7	12.3 10.9	1.8 3.8	32.8 32.8	34.5 28.6	40.0 43.5	5.5 14.9	300 100	208 359
V	ertical									
3 4 5 6	46.490 126.030 368.530 827.331	48.4 50.5 39.1 35.9	13.9 9.6 15.2 21.2	1.9 3.3 5.1 8.0	32.9 33.2 32.6 33.4	31.3 30.2 26.8 31.7	40.0 43.5 46.0 46.0	8.7 13.3 19.2 14.3	100 100 100 100	257 137 109 0

Tested by: Jun-Hui, Lee / Senior Engineer

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea



Page 80 of 83 Report No.: W163R-D042

12.6.3.2 Test Data for Below 30 MHz

-. Test Date : March 09, 2016

-. Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)

-. Frequency range : 9 kHz ~ 30 MHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency	Reading	Ant. Pol.	Ant. Factor	Cable	Amp	Emission	Limits	Margin
(MHz)	(dBµV)	(H/V)	(dB/m)	Loss	Gain	Level(dBµV/m)	$(dB\mu V/m)$	(dB)

Any emissions were not observed from the EUT.

Tested by: Jun-Hui, Lee / Senior Engineer



Page 81 of 83 Report No.: W163R-D042

13. CONDUCTED EMISSION TEST

13.1 Operating environment

Temperature : $(23 \sim 24)$ °C

Relative humidity : $(46 \sim 49) \% \text{ R.H.}$

13.2 Test set-up

The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a 50 Ω / 50 μ H + 5 Ω Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.

13.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
■, -	ESPI	Rohde & Schwarz	EMI Test Receiver	101278	Nov. 02, 2015 (1Y)
□ -	ESHS10	Rohde & Schwarz	EMI Test Receiver	834467/007	Apr. 29, 2015 (1Y)
	NSLK8128	Schwarzbeck	AMN	8128-216	Apr. 06, 2015 (1Y)
■ -	NSLK8126	Schwarzbeck	AMN	8126-404	Apr. 29, 2015 (1Y)
□ -	3825/2	EMCO	AMN	9109-1869	Apr. 29, 2015 (1Y)
■	3825/2	EMCO	AMN	9109-1867	Apr. 29, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

 $\textbf{HEAD OFFICE} \qquad : \#505 \text{ SK APT. Factory } 223\text{-}28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, } 462\text{-}121, Korea$






13.4 Test data for Charging & Transmitting Mode

-. Test Date : March 08, 2016

-. Resolution bandwidth : 9 kHz

-. Frequency range : 0.15 MHz ~ 30 MHz

-. Tested Line : HOT LINE



NO	FREQ R	EADING V		CTOR F	RESULT AV QP	LIMIT	MAR	GIN PH	ASE		
[1	MHz] [dBu∨][dBuV]	[dB] [dB]	dBu∀][dBu	uV] [dBuV][d	dBuV] [d	Bu∨][dBi	uV]			
1	0.26900	30.1		9.9	40.0		61.1		21.1		H(QP)
2	0.47200	27.4	****	9.9	37.3	****	56.5	****	19.2	****	H(QP)
3	0.53200	28.5		10.0	38.5		56.0		17.5		H(QP)
4	4.76000	19.4	****	10.1	29.5	****	56.0	****	26.5		H(QP)
5	8.90000	24.3		10.3	34.6		60.0		25.4		H(QP)
6	26.51000	24.6	****	10.5	35.1		60.0	****	24.9		H(QP)
7	0.26900		14.4	9.9		24.3		51.1		26.8	H(CAV)
8	0.47200		13.4	9.9		23.3	****	46.5	****	23.2	H(CAV)
9	0.53200	****	13.2	10.0		23.2	****	46.0		22.8	H(CAV)
10	4.76000		6.0	10.1		16.1	****	46.0		29.9	H(CAV)
11	8.90000		9.3	10.3		19.6		50.0		30.4	H(CAV)
12	26.51000		9.5	10.5		20.0		50.0		30.0	H(CAV)


It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

Report No.: W163R-D042

HEAD OFFICE :#505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea





NO FREQ READING C.FACTOR RESULT LIMIT MARGIN PHASE QP AV QP AV QP AV QP AV [MHz] [dBuV][dBuV] [dB] [dBuV][dBuV] [dBuV][dBuV] [dBuV]												
1	0.28800	31.2		9.9	41.1		60.6		19.5		N(QP)	
2	0.37200	29.7		9.9	39.6		58.5		18.9		N(QP)	
3	0.55200	32.4		10.0	42.4		56.0		13.6		N(QP)	
4	0.75600	27.8		10.0	37.8		56.0		18.2		N(QP)	
5	8.57500	23.5		10.3	33.8		60.0		26.2		N(QP)	
6	25.66000	24.7		10.5	35.2		60.0		24.8		N(QP)	
7	0.28800		15.3	9.9		25.2		50.6		25.4	N(CAV)	
8	0.37200		15.5	9.9		25.4		48.5		23.1	N(CAV)	
9	0.55200		24.9	10.0		34.9		46.0		11.1	N(CAV)	
10	0.75600		15.1	10.0		25.1		46.0		20.9	N(CAV)	
11	8.57500		19.2	10.3		29.5		50.0		20.5	N(CAV)	
12	25.66000		9.1	10.5		19.6		50.0		30.4	N(CAV)	

Remark: Margin (dB) = Limit - Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.

Tested by: Jun-Hui, Lee / Senior Engineer

Report No.: W163R-D042

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-002 (Rev.3)

HEAD OFFICE: #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Gyunggi-Do, 462-121, Korea