

TEST REPORT

OF

FCC Part 15 Subpart B&C §15.239

FCC ID : SS4BM150RE

Equipment Under Test : PDA
Model Name : BM-150R
Serial No. : N/A
Applicant : Bluebird Soft, Inc.
Manufacturer : Bluebird Soft, Inc.
Date of Test(s) : 2007-09-10 ~ 2007-11-09
Date of Issue : 2007-12-20

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date

2007-12-20

Geoffrey Do

Approved By



Date

2007-12-20

Denny Ham

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

| <u>TABLE OF CONTENTS</u> | Page |
|---|-------------|
| 1. General Information ----- | 3 |
| 2. Conducted Power Line Test ----- | 6 |
| 3. Radiated Emissions ----- | 11 |
| 4. 20 dB Bandwidth & Band Edge----- | 15 |
| Appendix A-1. Photo of Radiated Emissions | |
| Appendix A -2. Photos of Conducted Power Line Test | |
| Appendix B. Photos of the EUT | |

1. General Information

1.1. Testing Laboratory

SGS Testing Korea Co., Ltd.

- Wireless Div. 2FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040
 - 705, Dongchun-Dong Sooji-Gu, Yongin-Shi, Kyungki-Do, South Korea.

www.electrolab.kr.sgs.com

Telephone : +82 +31 428 5700

FAX : +82 +31 427 2371

1.2. Details of Applicant

Applicant : Bluebird Soft, Inc.
 Address : 558-5, Sinsa-dong, Kangnam-gu, seoul, Korea
 Contact Person : Gi-Cheol Sung
 Phone No. : 82-2-541-4002
 Fax No. : 82-2-548-0870

1.3. Description of EUT

| | |
|-----------------------------|---|
| Kind of Product | PDA |
| Model Name | BM-150R |
| Serial Number | N/A |
| Power Supply | DC 3.7 V |
| CDMA Module FCC ID | T42ICM-E600 |
| Frequency Range | 824.70 MHz ~ 848.31 MHz(CDMA - 1xRTT & EVDO Release0) 2412 MHz ~ 2462 MHz(11b/g), 2402 MHz ~ 2480 MHz(Bluetooth) 88.1 MHz ~ 107.9 MHz(FM Transmitter) |
| Modulation Technique | DSSS(11b), OFDM(11g), FHSS(Bluetooth), DQPSK(CDMA - 1xRTT & EVDO Release0), FM(FM Transmitter) |
| Number of Channels | 11 CH(11b/g), 79 CH(Bluetooth), 20 CH(CDMA - 1xRTT & EVDO Release0), 199 CH(FM Transmitter) |
| Operating Conditions | -20 °C ~ 55 °C |
| Antenna Type | Fixed Type(11b/g, Bluetooth), Inverted F Type(CDMA), Pannel ANT(FM Transmitter) |
| Antenna Gain | -3.72 dBi(WLAN), -1.93 dBi(Bluetooth), -0.48 dBi(CDMA - 1xRTT & EVDO Release0) |

1.4. Details of modification

-N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.5. Test Equipment List

| EQUIPMENT | MANUFACTURER | MODEL | CAL DUE. |
|-------------------------|-----------------|------------------------------|-----------|
| Signal Generator | Agilent | E4438C | May 2008 |
| Spectrum Analyzer | Agilent | E4440A | May 2008 |
| Spectrum Analyzer | H.P. | 8593E | Sep. 2008 |
| Two-Line V-Network | Rohde & Schwarz | NNB 41 | Sep. 2008 |
| Test Receiver | Rohde & Schwarz | ESVS10 | Apr. 2008 |
| Ultra-Broadband Antenna | Rohde & Schwarz | HL562 | Sep. 2008 |
| Anechoic Chamber | SY Corporation | L x W x H 6.5 x 3.6 x 3.6 | Aug. 2008 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.6. Summary of Test Results


The EUT has been tested according to the following specifications:

| APPLIED STANDARD:FCC Part 15, Subpart B & Subpart C | | |
|---|--|----------|
| Standard Section | Test Item | Result |
| 15.207(a) | AC Power Conducted Emission | Complied |
| 15.239(a) 15.239(b) | 20 dB Bandwidth, Band Edge and Radiated Emission | Complied |
| 15.205(a) 15.209(a) | Radiated Emission and Restricted Bands | Complied |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. Conducted Power Line Test

2.1. Test Setup



2.2. Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

| Frequency of Emission (MHz) | Conducted limit (dBμV) | |
|-----------------------------|------------------------|---------|
| | Quasi-peak | Average |
| 0.15 – 0.50 | 66-56* | 56-46* |
| 0.50 – 5.00 | 56 | 46 |
| 5.00 – 30.0 | 60 | 50 |

* Decreases with the logarithm of the frequency.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

1. The test procedure is performed in a 6.5m × 3.6m × 3.6m (L×W×H) shielded room. The EUT along with its peripherals were placed on a 1.0m(W)× 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4. Test Results

The following table shows the highest levels of conducted emissions on both phase of Hot and Neutral line.

Ambient temperature : 23 °C Relative humidity : 42 %

Frequency range : 0.15 MHz – 30 MHz

Measured Bandwidth : 9 kHz

| FREQ. (MHz) | LEVEL(dBuV) | | LINE | LIMIT(dBuV) | | MARGIN(dB) | |
|----------------|-------------|---------|------|-------------|---------|------------|---------|
| | Q-Peak | Average | | Q-Peak | Average | Q-Peak | Average |
| 0.19 | 51.90 | 32.20 | N | 64.04 | 54.04 | 12.14 | 21.84 |
| 0.20 | 58.30 | 29.60 | N | 63.61 | 53.61 | 5.31 | 24.01 |
| 0.24 | 53.00 | 24.20 | N | 62.10 | 52.10 | 9.10 | 27.90 |
| 1.31 | 32.00 | 20.90 | N | 56.00 | 46.00 | 24.00 | 25.10 |
| 1.56 | 28.70 | 18.60 | N | 56.00 | 46.00 | 27.30 | 27.40 |
| 6.70 | 38.40 | 29.30 | N | 60.00 | 50.00 | 21.60 | 20.70 |
| 0.15 | 56.20 | 30.50 | H | 66.00 | 56.00 | 9.80 | 25.50 |
| 0.20 | 49.50 | 25.80 | H | 63.61 | 53.61 | 14.11 | 27.81 |
| 0.37 | 34.10 | 18.90 | H | 58.50 | 48.50 | 24.40 | 29.60 |
| 1.31 | 39.50 | 26.30 | H | 56.00 | 46.00 | 16.50 | 19.70 |
| 1.56 | 36.60 | 24.10 | H | 56.00 | 46.00 | 19.40 | 21.90 |
| 6.70 | 40.40 | 31.80 | H | 60.00 | 50.00 | 19.60 | 18.20 |

Note ;


Line (H) : Hot

Line (N) : Neutral

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


Plot of Conducted Power line

Test mode : (Hot)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Test mode : (Neutral)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3. Radiated Emission

3.1. Test Setup for Radiated Emission.

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.2. Limit

The field strength of any emission within this band (section 15.239 frequency between 88 MHz –108 MHz) shall not exceed 250 microvolts /meter at 3 meters. (48dBuV/m at 3m)

The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

The provisions in section 15.35 for limiting peak emissions apply. The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in section 15.209(Intentional Radiators general limit), as below.

| Frequency (MHz) | Distance (Meters) | Field Strength (dBμV/m) | Field Strength (μV/m) |
|-----------------|-------------------|-------------------------|-----------------------|
| 30 - 88 | 3 | 40.0* | 100* |
| 88 – 216 | 3 | 43.5* | 150* |
| 216 – 960 | 3 | 46.0* | 200* |
| Above 960 | 3 | 54.0 | 500 |

Note:

Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

3.3.1. Test Procedures for Spurious Radiated Emissions

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.

NOTE ;

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.

3.4. Test Results

Ambient temperature : 23 °C Relative humidity : 41 %

a. Low Frequency

| Radiated Emissions | | | Ant | Correction Factors | | Total | FCC Limit | |
|--------------------|----------------|-------------|------|--------------------|-----------------|-----------------|----------------|-------------|
| Frequency (MHz) | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m) | Cable Loss (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 88.10 | 37.20 | P | V | 8.48 | 1.20 | 46.88 | 48.00 | 1.12 |
| 107.60 | 31.14 | P | H | 9.45 | 1.32 | 41.91 | 43.50 | 1.59 |
| 226.42 | 23.32 | P | H | 8.53 | 1.93 | 33.78 | 46.00 | 12.22 |
| Above 300 | Not Detected | | | | | | | |

b. Middle Frequency

| Radiated Emissions | | | Ant | Correction Factors | | Total | FCC Limit | |
|--------------------|----------------|-------------|------|--------------------|-----------------|-----------------|----------------|-------------|
| Frequency (MHz) | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m) | Cable Loss (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 98.90 | 36.1 | P | V | 9.10 | 1.26 | 46.46 | 48.00 | 1.54 |
| 107.60 | 26.44 | P | V | 9.45 | 1.32 | 37.21 | 43.50 | 6.29 |
| Above 200 | Not Detected | | | | | | | |


c. High Frequency

| Radiated Emissions | | | Ant | Correction Factors | | Total | FCC Limit | |
|--------------------|----------------|-------------|------|--------------------|-----------------|-----------------|----------------|-------------|
| Frequency (MHz) | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m) | Cable Loss (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 107.90 | 36.00 | P | V | 9.46 | 1.32 | 46.78 | 48.00 | 1.22 |
| 182.78 | 27.23 | P | H | 7.86 | 1.73 | 36.82 | 43.50 | 6.68 |
| Above 200 | Not Detected | | | | | | | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4. 20 dB Bandwidth & Band Edge

4.1. Test Setup



4.2. Limit

According to §15.239(a), emissions from the intentional radiator shall be confined within a band 200kHz wide centered on the operating frequency. The 200kHz band shall lie wholly within the frequency range of 88-108MHz.

4.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 10 kHz, VBW = RBW, Span = 500 kHz & 1 MHz, Sweep = auto.
4. Mark the peak frequency and 20 dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4.4. Test Results


Ambient temperature : 22℃ Relative humidity : 44%

| Channel | Channel Frequency (MHz) | Bandwidth (kHz) |
|---------|-------------------------|-----------------|
| Low | 88.10 | 174.6 |
| Middle | 98.9 | 164.4 |
| High | 107.9 | 156.8 |


Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.





Middle Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Appendix A-1. Photo of Field Strength & Radiated Emission Test

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Appendix B. Photos of the EUT

Appendix A -2. Photos of Conducted Power Line Test



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Appendix B. Photos of the EUT

Front View of EUT



Rear View of EUT



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


Right View of EUT**Left View of EUT**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Inner of EUT




Top View of Main-board



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Bottom View of Main-board**Top View of Keyboard**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Bottom View of Keyboard**Top View of LCD**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Bottom View of LCD



Top View of CDMA



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Bottom View of CDMA

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.