

Antenna Data Sheet

MT-484033/NH

Page 1 of 2

MT-484033/NH

5.15-5.875 GHz 16.5dBi Base Station Antenna



160 Km/h

Specifications					
MTI PART NUMBER		MT – 484033/NH			
ELECTRICAL					
FREQUENCY RANGE		5.15-5.875 GHz			
GAIN		16.5 dBi (min)			
VSWR		1.7 : 1 (max)			
13 dBi AZIMUTH BEAMWIDTH		60° ± 4°			
13.5 dBi AZIMUTH BEAMWIDTH		57° ± 4°			
POLARIZATION		Horizontal			
3 dB ELEVATION BEAMWIDTH		11° (typ)			
AZIMUTH SIDELOBES LEVEL		ETSI EN 302-085 V1.1.2 (2001-02) CS1-CS3			
		-25 dB @ ± 90°			
ELEVATION SIDELOBES LEVEL		ETSI EN 302-085 V1.1.2 (2001-02) CS1-CS3			
		-12 dB (max)			
CROSS POLARIZATION		ETSI EN 302-085 V1.1.2 (2001-02) TS1-TS3			
		-23 dB (max)			
F/B RATIO		ETSI EN 302-085 V1.1.2 (2001-02) TS1-TS3			
INDUT IMPEDANCE		-30 dB (max)			
INPUT IMPEDANCE		50 (ohm)			
INPUT POWER		6W (max)			
LIGHTNING PROTECTION MECHANICAL		DC Grounded			
DIMENSIONS (LxWxD)		250v150V20mm	(may)		
WEIGHT		350x150X30mm (max) 1.5 Kg (max)			
CONNECTOR		Two N-Type female			
RADOME		Plastic			
BASE PLATE			Aluminum with chemical conversion coating		
OUTLINE DRAWING		See page 2			
MOUNTING KIT		MT-120019			
ENVIRONMENTAL					
TEST	STANDARD	DURATION	TEMPERTURE	NOTES	
LOW TEMPERATURE	IEC 68-2-1	72 h	-45°C	-	
HIGH TEMPERATURE	IEC 68-2-2	72 h	+70°C	-	
TEMP. CYCLING	IEC 68-2-14	1 h	-45°C +70°C	3 Cycles	
VIBRATION	IEC 60721-3-4	30 min/axis	-	Random4M3	
SHOCK MECHANICAL	IEC 60721-3-4	-	-	4M3	
HUMIDITY	ETSI EN300-2-4 T4.1E	144 h	-	95%	
WATER TIGHTNESS	IEC 529	-	-	IP67	
SOLAR RADIATION	ASTM G53	1000 h	-	-	
FLAMMABILITY	UL 94	-	<u>-</u>	Class HB	
SALT SPRAY	IEC 68-2-11 Ka	500 h	-	05 D !! . !	
ICE AND SNOW	CHDVIVAL	-		25mm Radial	
WIND SPEED	SURVIVAL	-	-	220 Km/h	


OPERATION

Page 2 of 2


MT-484033/NH

5.15-5.875 GHz 16.5dBi Base Station Antenna


Azimuth Radiation Pattern



Elevation Radiation Pattern



Dimensions [mm]



Existing Antenna Versions

MT-484033/NH	With N – Type Female connector & DC grounding

MTI group is certified according to ISO 9001 and ISO 14001.

WAIVER

While the information contained in this document has been carefully compiled to the best of our present knowledge, it is not intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

MTI Wireless Edge Ltd.

11 Hamelacha St. Afek Industrial Park Rosh Ha'ayin 48091, Israel

Tel: +972-3-902-5050 Fax: +972-3-902-5051 <u>www.mtiwe.com</u>

Document No: Issued:

MT-484033/NH

Uncontrolled Copy