Wireless StatStation



LCD Display - Infocenter Specifications




General Specifications


- Font style to be Myriad Pro Condensed or Antique Olive 2 unless specified.
- Font size to be 8 or 10 unless specified.
- 2.5mm jack for 120volt wall wart.
- Receiver to have 4 AA batteries.
- Operating Temperature: 40 °F 110 °F
- After 30 seconds of no interaction, unit defaults to Idle Screen.
- Backlight on during any key touch. Off after 30 seconds on no interaction.
- Range from transmitter: ~200ft.
- Frequency of transmitter: 900mHz range with Frequency hopping
- Audible Alarm on low from factory
- Date Format : mm/dd/yyyy
- Time Format : hh:mm am/pm
- Investigate Multi-Lingual Format




System Overview










REMOTE SENDER UNIT



- Communicates with Display Unit via RF
- Communicates with Transfer Switch Control and Home Stand-By Control systems via Hardwire
- Optional: Output for Phone Dialer or Ethernet Hub
- RF: 900MHz with Frequency Hopping
- Sealed Nema-3 Housing






REMOTE DISPLAY UNIT




- Communicates with Sender Unit via RF
- Displays System Status:
 - Loss of Utility
 - Generator Operation
 - Home Power Usage
 - Exercise Mode
 - Maintenance Reminders
 - System Alarms with Audible Alert
- RF: 900MHz with Frequency Hopping
- Range: 100' from Remote Sender Unit
- Desktop Case Design



Idle Screen




Utility Power Outage Screen






Backup Power Mode Screen






Backup Power Mode Screen





Backup Power Mode Screen






Exercise Mode Screen



Should always be displayed when in exercise mode, counting down, even if other screen shows some other information



Alarm Alert Screen





Main Menu Screen





History Screen









Each will flash at "zero" time remaining, until they are reset







Note: After user has reset the interval, automatically returns to previous menu





Note: After user has reset the interval, automatically returns to previous menu





Note: After user has reset the interval, automatically returns to previous menu





Settings Screen





Alarm Settings





Alarm Settings





Alarm Settings





+ am "

INTELLI Gen



INTELLI Gen












Note: All screens should return to the previous screen after setting backlight









Confidential Property of B&S Home Power Products



Date & Time Settings





Date & Time Settings



Note: Screen should return to the "Date & Time Screen" after user presses finish



Date & Time Settings



Note: Screen should return to the "Date & Time Screen" after user presses finish



System Sync Screen

